



LOW VOLTAGE
MEDIUM VOLTAGE
HEATING CABLES

Ray
tech[®]

CABLE ACCESSORIES COMPANY

NEW

SOLARCOVER
64-65



**Ray
Tech®**
CABLE ACCESSORIES COMPANY



1 LOW VOLTAGE



- 5 FILLERS
- 6 GEL
- 18 RUBBER
- 22 RESIN



- 25 JOINTING BOXES
- 28 PRE-FILLED IP68
- 36 KIT IP68
- 42 IP55



- 45 CONNECTORS-TERMINAL BLOCKS
- GEL COVER-GEL BOX
- 46 LEVER CONNECTOR
- 48 CONNECTOR COVERS



- 63 JOINTS
- 64 PRE-FILLED FOR PHOTOVOLTAIC
- 66 PRE-FILLED IP68
- 76 PRE-FILLED IPX8 - FLAT
- 82 PRE-FILLED IPX8 - CYLINDRICAL
- 88 FOR CASTING
- 104 HEAT-SHRINK



- 111 OTHER
- 112 HEAT-SHRINK SHEATHS
- 121 INSULATION TAPES
- 126 CABLE PULLERS
- 132 FIRE STOP BARRIERS
- 138 SPECIAL



147 MEDIUM VOLTAGE



149 COLD-SHRINK

150 TERMINATIONS INDOOR

152 TERMINATIONS OUTDOOR

154 TERMINATIONS INDOOR/OUTDOOR

156 JOINTS



159 HEAT-SHRINK

162 TERMINATIONS INDOOR

165 TERMINATIONS OUTDOOR

168 TERMINATIONS INDOOR/OUTDOOR

170 TERMINATIONS ENEL CERTIFIED

172 JOINTS

178 JOINTS ENEL CERTIFIED

179 HIGH VOLTAGE



181 SEPARABLE CONNECTORS,
SHEATHS, TAPES

189 HEATING CABLES

193 INDUSTRIAL USE

194 MCA (I-PF) (I-GF) (I-FF)



199 DOMESTIC USE

PIPING

200 STOP ICE

202 ICE KILLER

203 MCA



RAMPS

205 EASY CABLE

206 EASY RAMP

207 MCA RAMP

GUTTERS

208 EASY FROST

209 MCA 8

211 COMFORT HOUSE

FLOORING

212 EASY FLOOR

MIRROR

214 EASY MIRROR

CEILING



215 WARM-UP

219 ACCESSORIES

226 Forms


SMART FACTORY OVERVIEW

CELEBRATING 30 YEARS OF EXCELLENCE

We are celebrating a significant anniversary this year: 30 years of innovation, quality and commitment to excellence. Since 1995, we have dedicated every day to improving our products and services, to meet the needs of our customers and contribute to a sustainable future.

Our Commitment to Quality, Safety and the Environment

We are proud to continue to maintain ISO certifications, which prove our continuous commitment in quality and reliability, respecting the environment and ensuring the safety of our stakeholders. These certifications are the result of rigorous controls and a systematic approach aimed at ensuring that every product dispatched from our factory meets the highest international standards.





Sustainability Award

Our focus on sustainability has been awarded the 2023 Silver Medal by EcoVadis, a leading provider of corporate social responsibility assessments. This recognition validates our efforts to reduce environmental impact, improve working conditions, and promote ethical practices throughout our supply chain.

ISO 9001:2015 Quality Management Systems.

Policies, processes and procedures for a constant improvement of our performances.

ISO 14001:2015 Environmental Management Systems.

We are committed to continuous improvement of our performances while respecting the environment.

ISO 45001:2018 Management systems for the occupational health and safety.

We protect our workers by reducing risks, improving the safety and health and well-being of workers.



Looking to the Future

While celebrating 30 years of success, we look at the future with enthusiasm and determination. We'll keep on innovating, listening to our valuable customers and investing in our people, because they are definitely the real engine of our company.

Thank you!

We must thank those who believed and still believe in us for our success: employees, customers, suppliers and partners. Without your support, this journey would not have been possible and could not continue. We invite you to browse this catalog and discover the latest news and projects that excite us for the future.


With gratitude and hope,






LOW VOLTAGE

FILLERS - JOINTING BOXES
CONNECTORS - TERMINAL BLOCKS
GEL COVER - GEL BOX
JOINTS - ACCESSORIES



OUR PRODUCTION







LOW VOLTAGE FILLERS

GEL

MAGIC GEL SPRINT
MAGIC GEL
MAGIC FLUID
MAGIC POWER GEL
RAY GEL
WONDER GEL
MONOGEL

RUBBER

GEL GUM
SKY PLAST
MAGIC RUBBER

RESIN

RAY RESIN





Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Cross linking time:

fast (about 7 min. at 23°C)

Volume resistivity:

>2 . 10¹⁵ Ω cm

Working temperature:

-60°C / +200°C

Overload temperature

for short periods:

up to 250°C

Stabilised for:

mould - UV

Degree of protection:

IP68 (in proper casings)

Magic Gel Sprint protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a IP68 system.

IP68
OFFICIALLY
TESTED | **IMQ**




MAGIC GEL SPRINT

Insulating and sealing gel with very high dielectric and thermal characteristics, ideal for POWER cables, TELECOM cables and ELECTRONICS CIRCUITS.

Magic Gel Sprint is formulated for an extra fast curing directly inside the bottle. Practical, performing, eco-sustainable, it is the ideal GEL for insulating and sealing boxes of the most commonly used dimensions.



ADVANTAGES

- ▶ Non-toxic, safe and not classified as hazardous under CLP Directive.
- ▶ Suitable for installation in salt water (sea) and in chlorinated water (pools).
- ▶ For any type of indoor / outdoor and even submerged installation.
- ▶ For installations up to 1 kV.
- ▶ Suitable for high temperatures.
- ▶ Removable.
- ▶ No shelf life.



HOW IS IP68 DEGREE OF PROTECTION OBTAINED?

The GEL protects against dusts and seals the connections from the effects of continuous immersion in water when it is poured into enclosures protected from the ingress of solid bodies, therefore contributing to create an IP68 system.

**Magic Gel 450 Sprint****Magic Gel 900 Sprint**

PRODUCT / Item	Colour	Package type	Total quantity
MAGIC GEL SPRINT 450 MAGICSPRINT450	●	1 bottle + 1 catalyst	450 ml
MAGIC GEL SPRINT 900 MAGICSPRINT900	●	2 bottles + 2 catalysts	900 ml



MAGIC GEL SPRINT is available in **2 version** which are sustainable in terms of packaging and in terms of volume, as they are specifically designed for filling boxes in the most commonly used formats.



CLASSIC



Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Cross linking time:

fast (about 10 min. at 23°C)

Volume resistivity>2 . 10¹⁵ Ω cm**Working temperature:**

-60°C / +200°C

**Overload temperature
for short periods:**

up to 250°C

Stabilised for:

mould - UV

Degree of protection:

IP68 (in proper casings)

Magic Gel protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a **IP68** system.

IP68 | **IMQ**
OFFICIALLY
TESTED


MAGIC GEL MAGIC FLUID



Two-component gel with very high dielectric and thermal characteristics, ideal for connection systems (joint shells or enclosures) for power cables.

The insulating and sealing gel, when cast in suitable casings, ensures an IP68 degree of protection and it is able to replace all types of resins. This is a self-sealing insulation polymeric type in two practical bottles or in a single use bag, with cold cross linking. Once poured, the insulation, characterized by very low viscosity, surrounds and envelopes any type of material, cross linking in less than 10 minutes. Completely non-toxic, cross linking with a very low isothermal peak that does not thermally stress the materials it comes into contact with.

ADVANTAGES

- ▶ For high temperature applications!
- ▶ The gel is not-classified as hazardous under the CLP Directive.
- ▶ Quick cross linking (only 10 minutes).
- ▶ Re-enterable also after long working periods.
- ▶ Low viscosity.
- ▶ No shelf life.





PRODUCT / Item	Colour	Package type	Total quantity
MAGIC GEL 300 MAGICGEL300	●	2 bottles	300 ml
MAGIC GEL 420 MAGICGEL-420	●	1 single, two-component bottle 1 jug - 1 spatula in wood	420 ml
MAGIC GEL 1000 MAGIC-GEL-1000	●	2 bottles - 1 jug 1 spatula in wood	1000 ml
MAGIC GEL 2000 MAGICGEL-2000	●	2 single, two-component bottles 1 jug - 1 spatula in wood	2 x 1000 ml
MAGIC GEL 10000 MAGICGEL10	●	2 tanks - 1 jug 1 spatula in wood	10 lt



PRODUCT / Item	Colour	Package type	Total quantity
MAGIC FLUID 90 100090-MAG	●	Two-component single dose bag	90 ml
MAGIC FLUID 110 100110-MAG	●	Two-component single dose bag	110 ml
MAGIC FLUID 170 100170-MAG	●	Two-component single dose bag	170 ml
MAGIC FLUID 210 100210-MAG	●	Two-component single dose bag	210 ml
MAGIC FLUID 420 100420-MAG	●	Two-component single dose bag	420 ml
MAGIC FLUID 550 100550-MAG	●	Two-component single dose bag	550 ml

Problem ENERGY

What does a gel for this type of system have to give?

INSULATION: Elevated voltages (1 kV operating, 4 kV testing)




THERMAL PERFORMANCE: Operating temperature 90°C, overload temperature 130°C, short circuit temperature 250°C

SEALING: Installations also possible in humid environments, flooded wells

DEGREE OF PROTECTION: Must also work with water between the cores of the cable

CERTIFIED SYSTEMS: The combination of insulation gel + casing must comply with current standards CEI 20-33 and EN 50393

Solution: **Magic Gel** meets all your Energy System requirements!





Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Cross linking time:

fast (about 15 min. at 25°C)

Volume resistivity:

>2 . 10¹⁵ Ω cm

Operating temperature:

-60°C / +200°C

Overload temperature for short periods:

up to 250°C

Stabilised for:

mould - UV

Degree of protection:

IP68 (in proper casings)

Magic Power Gel protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a IP68 system.

IP68 | **IMQ**
OFFICIALLY
TESTED



MAGIC POWER GEL

The unique two component gel in a single bottle, with superior dielectric, sealing and thermal characteristics, re-enterable and re-usable!

ADVANTAGES

- ▶ Very sticky.
- ▶ Strong self amalgamating characteristics.
- ▶ The gel is not-classified as hazardous under the CLP Directive.
- ▶ Single compact bottle; convenient twin compartment.
- ▶ Re-usable as well as re-enterable, even after long working periods.
- ▶ It doesn't give any waste.
- ▶ No shelf life.



INSULATING and SEALING GEL

RE-ENTERABLE

RE-USABLE



For all types of connections, even in the toughest conditions, for power, telecom and signalling!

**STICKINESS**

- Exceptional sealing properties in any condition.
- Better resistance to pressure.
- Effective even in vertical or ceiling applications.

ZERO WASTE

- Due to the nature of the product waste is eliminated; even residual product can be saved and used for the next application.
- Also any left over product maintains its high performance characteristics.

SELF-AGGLOMERATING

- Once cross linked it perfectly adheres on itself to get an homogeneous and compact mass.
- It can be therefore applied in multiple layers.

SINGLE BOTTLE

- Highly useful.
- The most compact packaging.
- Less space occupied in the toolbox.
- Both components in the same packaging.





PRODUCT / Item	Colour	Package type	Quantity
MAGIC POWER GEL 250 MAGICPOWER-250	●	1 single, two-component bottle	250 ml
MAGIC POWER GEL 500 MAGICPOWER-500	●	1 single, two-component bottle 1 jug - 1 spatula in wood	500 ml
MAGIC POWER GEL MAGICPOWER-GEL	●	1 single, two-component bottle 1 jug - 1 spatula in wood	1000 ml



PRODUCT / Item	Colour	Package type	Quantity
MAGIC POWER GEL BAG 150 MAGICPOWERBAG150	●	Two-component single dose bag	150 ml
MAGIC POWER GEL BAG 250 MAGICPOWERBAG250	●	Two-component single dose bag	250 ml

CASTING APPLICATION

HORIZONTAL installation

**AFTER CURING MANUAL APPLICATION**
CEILING or WALL application



Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Cross linking time:

about 15 min. at 23°C

Volume resistivity:

>1,5 x 10¹⁵ Ω cm

Operating temperature:

-60°C / +180°C

Thermal conductivity:

< 0,2 W/m·K

Dielectric constant:

< 7

Degree of protection:

IP68 (in proper casings)

Ray Gel protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a IP68 system.

IP68 | **IMQ**
OFFICIALLY
TESTED

RAY GEL

Insulating, sealing, re-enterable fast cross linking two-component silicone gel for telephone and intercom systems and for LED and display protection.

ADVANTAGES

- ▶ Quick cross linking.
- ▶ Antioxidant protection.
- ▶ Low temperature resistant.
- ▶ The gel is not-classified as hazardous under the CLP Directive.
- ▶ No shelf life.



**RED**

- Specially formulated for UV resistance
- Suitable for "surface" installations
- Ideal for intercom systems

**TRANSPARENT**

- Excellent transparency
- Does not opacify
- Ideal for protecting printed circuit boards, for sealing displays, for insulating and sealing LEDs

**Problem TELECOM**

What does a gel for this type of system have to give?

- SEALING:** Installations also possible in humid environments, flooded wells.
- DEGREE OF PROTECTION:** IP68 in proper casing.
- PREVENTION FROM OXIDATION:** Contacts in Telecom connections shouldn't give attenuations (low signal currents).
- HIGH INSULATION FLUIDITY:** During casting, the insulation has to fill all interstitial spaces between the cores of the cable.
- ANTICRACKING:** Insulation in the permanently cold joint should not crack at low temperatures.
- INSULATION:** The filler should be an insulating component.

Solution: Ray Gel meets all your Telecom system requirements.

PRODUCT / Item	Colour	Package type	Total quantity
BAG GEL 200-T BAGGEL200-T	○	Two-component single dose bags	200 ml
BAG GEL 400-T BAGGEL400-T	○		400 ml
BAG GEL 200-R BAGGEL200-R	●		200 ml
BAG GEL 400-R BAGGEL400-R	●		400 ml
RAY GEL 300-T RAYGEL300-T	○	2 bottles	300 ml
RAY GEL 1000-T RAYGEL1000-T	○		1000 ml
RAY GEL 300-R RAYGEL300-R	●		300 ml
RAY GEL 1000-R RAYGEL1000-R	●		1000 ml
RAY GEL 10K-T RAYGEL10K-T	○	2 tanks	10 lt
RAY GEL 20K-T RAYGEL20K-T	○		20 lt
RAY GEL 10K-R RAYGEL10K-R	●		10 lt
RAY GEL 20K-R RAYGEL20K-R	●		20 lt





Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Volume resistivity:

>2 . 10¹⁵ Ω cm

Operating temperature:

-60°C / +200°C

Overload temperature

for short periods:

up to 250°C

Stabilised for:

mould - UV

Degree of protection:

IP68 (in proper casings)

Wonder Gel protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a **IP68** system.

IP68 | IMQ
OFFICIALLY
TESTED

WONDER GEL

Single component insulating gels in cartridge to instantly protect new installations and oversee maintenance of all types of electrical connections.


Installer's best friends. Electrical connections, within empty enclosures, are exposed to the risk of short circuit, oxidation and corrosion, at times, resulting in irreparable damages. Without stress and no waiting around, **WonderGel** and **WonderGel Invisible** make your job easier, guaranteeing the protection and safety of systems in compliance to best practice rules to provide the highest quality solution, quick and perfect to get the satisfaction of both you and your clients.

ADVANTAGES

- Ready to use! No mixing required! Already cross-linked! No need to wait!
- Resolve issues connected to incorrect insulation or sealing.
- Eliminate annoying out of service instances caused by moisture.
- Protect your systems from the penetration of insects.
- Protect your electrical connections from oxidation and corrosion.
- Applicable in all climatic conditions.
- The gel is not-classified as hazardous under the CLP Directive.



Easy to apply even in areas which are difficult to access!

**WHAT IS GEL WONDER?**


- A single component gel
- Extremely sticky
- Stays soft with time
- Never dries
- Non-toxic and safe
- No shelf life

**WHAT DOES GUARANTEE?**

- Maximum insulation and sealing
- Effective and stable adhesion with the passing of time
- High resistance to water pressure
- Degree of protection IP68 when dispensed in suitable casings

**WHY IS IT IN A CARTRIDGE?**

- Always ready to use and at your fingertips
- Can be used with standard guns
- It is measurable
- No waste
- Complete with nozzle
- Extremely rapid to use even in difficult positions
- Compact



PRODUCT / Item	Colour	Package type	Total quantity
WONDER GEL WONDER	●	Cartridge with dosing nozzle	280 ml
WONDER GEL INVISIBLE WONDER-INV	○	Cartridge with dosing nozzle	280 ml



Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Operating temperature:

-60°C / +200°C


Installation temperature:

-40°C / +110°C

Degree of protection:

IP68 (in proper casings)

Wonder Gel Fluid protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a IP68 system.



WONDER FLUID

Single component insulation fluid gel cartridge.

ADVANTAGES

- The gel is not-classified as hazardous under the CLP Directive.
- Ready-to-use fluid gel.
- Suitable for box filling.
- Does not solidify when opened.
- No waste.
- No shelf life.




PRODUCT / Item	Colour	Package type	Total quantity
WONDER FLUID 280 WONDER-F280	●	Cartridge with dosing nozzle	280 ml

MONOGEL

Single component transparent insulation gel for generic use.

ADVANTAGES

- The gel is not-classified as hazardous under the CLP Directive.
- Ready to use.
- No shelf life.
- Inspectable.



PRODUCT / Item	Colour	Package type	Total quantity
MONOGEL MONOGEL	○	Cartridge with dosing nozzle	300 ml



Gel: UL 94-HB

Dielectric strength:

>20 kV/mm

Operating temperature:


-60°C / +200°C

Installation temperature:

-40°C / +110°C

Degree of protection:

IP68 (in proper casings)





TECHNO GEL GUM

Single bottle two-component insulation with very high dielectric, thermal and sealing characteristics. Waterproof and re-enterable!

TechnoGelGum is a strong hold flexible elastomer whose formula has been optimised for the protection of POWER CABLE, TELECOM CABLE and ELECTRONIC CIRCUIT connections. A new recipe that gives the product a surprising, original texture that combines the characteristics of GEL and RUBBER to emphasise its features. It's elastic and flexible like gel, but also tough and dry like rubber.

ADVANTAGES

- ▶ For installations up to 1 kV, suitable for high temperatures.
- ▶ Suitable for installation in salt water (sea) and in chlorinated water (pools).
- ▶ For any type of indoor / outdoor and even submerged installation.
- ▶ Waterproof > 1 MPa.
- ▶ Vibration resistant can act as a damper.
- ▶ Removable.
- ▶ The gel is not-classified as hazardous under the CLP Directive.
- ▶ No shelf life.

Dielectric strength:

>20 kV/mm

Specific weight:

~ 1.05

Cross linking time:

fast (about 10 min. at 25°C)

Volume resistivity:>2 . 10¹⁴ Ω cm**Operating temperature:**

-60°C / +200°C

Overload temperature for short periods:

up to 250°C

Stabilised for:

mould - UV

Degree of protection:


IP68 (in proper casings)

Techno Gel Gum protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a IP68 system.

IP68 | **IMQ**
OFFICIALLY
TESTED

Nonfood Compounds

STRONG CONSISTENCY**EXTREMELY FLEXIBLE AND WATER-REPELLENT**

FLEXIBLE like GEL**STRONG like RUBBER****SAFE****WATERPROOF****RE-ENTERABLE**

Shake before using.



Pour TechnoGelGum into the provided jug in a 1:1 ratio.

Mix for 1 min. max.



Pour within 1 min. max.



In just 10 minutes the curing is completed.

PRODUCT / Item	Colour	Package type	Total quantity
TECHNO GEL GUM 500 TEGELGUM500	●	1 single, two-component bottle 1 jug - 1 spatula in wood	500 gr
TECHNO GEL GUM TEGELGUM	●	1 single, two-component bottle 1 jug - 1 spatula in wood	1 kg





**SKY PLAST
BECOMES
RUBBER
IN 5 MINUTES**


SKY PLAST

Two-component insulating rubber, mouldable, self-extinguishing paste with high dielectric characteristics.

Sky Plast is ideal for covering, protecting, insulating, finishing and fireproofing any electrical and non-electrical component. Once the 2 components have been blended in a ratio of 1:1 (for max 2 min.) until uniform, it cross links quickly at room temperature in less than 5 minutes. After being wrapped around the component to be protected, Sky Plast quickly transforms into a layer of rubber with high dielectric and self-extinguishing characteristics.

ADVANTAGES

- Low smoke and toxic and corrosive gases emission.
- Able to replace taping, heat-shrinking, resin finishes.
- Flexible and elastic.
- Quickly ready for use.



Cable gland sealing



Creation of LV terminals



Insulation of multiple connections



Preparation on-site of expanders for inserts



Preparation of bars, washers, round wire insulators



Preparation on-site of seals



Conduit protection



Preparation on-site of small moulds for reliefs



Drop line, bar, transformer through insulation



On-site preparation of braces and supports



Preparation of deflectors, nozzles, flow deviators



PRODUCT / Item	Colour	Package type	Total quantity
SKY PLAST 250 SKYPLAST250	●	2 cans	250 gr
SKY PLAST SKYPLAST	●	2 cans	500 gr

MAGIC RUBBER

Fast cross linking two-component rubber.

Two-component insulating liquid rubber, extremely conformable and fluid, flexible, elastic and re-enterable. In just a few minutes, transforms into a rubber with very high dielectric, thermal, mechanical and elastic characteristics.

ADVANTAGES

- ▶ For installation up to 1kV.
- ▶ Low smoke, toxic and corrosive gas emissions.
- ▶ Ideal also for casts and moulds.
- ▶ No shelf life.



Mix the 2 components in a ratio of 1:1.



Mix for max 30".



Pour the product into the casing to be filled.



In just a few minutes, the product transforms into rubber.



Cross linking time:

15 minutes at 23°C

Volume resistivity:

>2 10¹⁵ Ω cm

Dielectric strength:

> 20 kV/mm

Specific weight:

1,22 approx

Degree of protection:

IP68 (in proper casings)


Magic Rubber protects against dust and seals the connections from the effects of continuous immersion in water when it is poured into casings protected from the ingress of solid bodies, thus helping to create a IP68 system.

PRODUCT / Item	Colour	Package type	Total quantity
MAGIC RUBBER 500 MAGIC-RUBBER	●	1 single two-component bottle 1 jug - 1 spatula in wood	500 gr
MAGIC RUBBER 10 MAGICRUBBER-10	●	Two-component tanks 1 jug - 1 spatula in wood	10 kg



PRODUCT / Item	Colour	Package type	Total quantity
RUBBER FLUID 200 RUBBERFLUID-200	●	Two-component single dose bags	200 gr
RUBBER FLUID 350 RUBBERFLUID350	●	Two-component single dose bags	350 gr



**Cross linking time:**

20 minutes at 20°C

Hardness:


70 Shore D

Dielectric strength:

20 kV/mm

Specific weight:1,07 kg/dm³1,7 kg/dm³ per Rayresin Tan 3,8**Water absorption:**


0,8% max



RAY RESIN

Two-component epoxy resin for installations up to 1 kV.

Resin for electrical insulation and for the protection of thermosetting LV and MV accessories. The two components, the base resin and hardener, are mixed in close contact to trigger the cross linking reaction. Excellent bonding to metal, plastic and rubber components.



Remove the separator from the Rayresin bag.

Mix the 2 components.

Pour Rayresin in the tray (1' max).

Installation completed.



PRODUCT / Item	Colour	Package type	Total quantity
RAYRESIN 170 100170-000	●	Two-component single dose bags	170 gr
RAYRESIN 210 100210-000	●	Two-component single dose bags	210 gr
RAYRESIN 420 100420-000	●	Two-component single dose bags	420 gr


FILLERS COMPARISON CHART



	MAGIC GEL SPRINT	MAGIC FLUID	MAGIC GEL	MAGIC POWER GEL	RAY GEL
PACK CONTENTS	1 bottle + 1 catalyst	1 sachet	2 bottles or one single 2 compartment bottle + jug + spatula	One single 2 compartment bottle + jug + spatula	2 bottles or sachet
MIXING RATIO	Predeterminate	Predeterminate	1:1 ratio with measuring Jug	1:1 ratio with measuring Jug	1:1 ratio
MIXING TIME	10 seconds	10 seconds	15 seconds	15 seconds	15 seconds
CURING TIME (at 23° C)	< 7 minutes	< 7 minutes	< 10 minutes	About 15 minutes	About 15 minutes
INSTALLATION TEMPERATURE	-15° / +55°C	-15° / +55°C	-15° / +55°C	-15° / +55°C -40° / +60° (cured)	-15° / +55°C
USAGE	By pouring	By pouring	By pouring	By pouring or "cure and stick"	By pouring
	 ALL IN ONE Ready in 1 bottle!	 ALL IN ONE CLASSIC	 CLASSIC	 SELF AGGLOMERATING	 INTERCOMS Led display



	WONDER GEL / FLUID	TECHNO GEL GUM	MAGIC RUBBER	RUBBER FLUID	RAY RESIN
PACK CONTENTS	1 cartridge	One single 2 compartment bottle + jug + spatula	One single 2 compartment bottle + jug + spatula	1 sachet	1 sachet
MIXING RATIO	None	1:1 ratio with measuring Jug	1:1 ratio with measuring Jug	Predeterminate	Predeterminate
MIXING TIME	-	15 seconds	15 seconds	15 seconds	30 seconds
CURING TIME (at 23° C)	Already cross-linked	About 15 minutes	About 15 minutes	About 15 minutes	About 25 minutes
INSTALLATION TEMPERATURE	-15° / +55°C	-15° / +55°C	-15° / +55°C	-15° / +55°C	+5° / +55°C
USAGE	Injection	By pouring	By pouring	By pouring	By pouring



**LOW VOLTAGE
JOINTING BOXES**

PRE-FILLED IP68


BOB
BABY BOX
READY BOX
FOX BOX

KIT IP68

MAGIC BOX
POWER KIT
MAGIC GEL SPRINT BOX 100

IP55

J-BOX




RAYTECH PRE-FILLED BOXES

**BOB 3**

1 Entrance 2 Outputs



Connector
3x 4 mm²
or free
connections

**BABY
BOX**

1 Entrance 2 Outputs



Connector
3x 6 mm²
or free
connections

**BABY
BOX 3**

1 Entrance 3 Outputs



Connector
5x 6 mm²
or free
connections

**READY
BOX 90**

1 Entrance 2 Outputs



Connector
3x 6 mm²
or free
connections

**READY
BOX 120**

1 Entrance 3 Outputs



Connector
5x 6 mm²
or free
connections

**FOX
BOX 3**

1 Entrance 2 Outputs

Free
connections

**FOX
BOX**

1 Entrance 4 Outputs


Free
connections



3 nuts

Cables Ø
mm 8-13Colours
mm
105 x 80 x h 25

4 nuts

Cables Ø
mm 8-13Colours
mm
105 x 65 x h 253 nuts
+ adaptersCables Ø
mm 8-18Colours
mm
95 x 80 x h 43Tubes Ø
mm 16/204 nuts
+ adaptersCables Ø
mm 8-18Colours
mm
95 x 110 x h 433 nuts
+ adaptersCables Ø
mm 8-18Colours
mm
90 x 90 x h 45Tubes Ø
mm 16/20/324 nuts
+ adaptersCables Ø
mm 8-18Colours
mm
120 x 100 x h 45Tubes Ø
mm 16/20/323 nuts
+ adaptersCables Ø
mm 8-18Colours
mm
180 x 135 x h 45Tubes Ø
mm 16/20/325 nuts
+ adaptersCables Ø
mm 8-18Colours
mm
210 x 155 x h 45Tubes Ø
mm 16/20/32**Electrical performance:****CEI EN 50393**

as applicable

Class 2 in accordance with **CEI 64-8**.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

IP68 | **IMQ**
OFFICIALLY
TESTED**IP69K**
OFFICIALLY
TESTED**IP68:**

- (6) protected against dust and solid objects over 1 mm.
(8) Protected from permanent immersion in water.

IP69K:

- (9K) protected against close-range high pressure, high temperature spray downs.



**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960°C according to EN60695-2-12

IP68
OFFICIALLY
TESTED

IMQ

IP69K
OFFICIALLY
TESTED

BOB

The IP68 / IP69K micro-joints, gel pre-filled, complete with connector, suitable for any type of installation, even the most extreme.


Extremely compact and space-saving, pre-filled with soft, highly conformable gel. With minimal aesthetic impact and visually pleasing. Equipped with integrated cable glands for IP68 and IP69K degree of ingress protection and cable retention.

ADVANTAGES


- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive.
- Extremely compact and ready to install.
- Ideal for connections in lighting systems for gardens, steps and stairways, pedestrian crossings, etc.
- Pre-threaded entries for the positioning of the clamping nuts.
- No shelf life.
- Always re-enterable.



BOB 3



BOB 4




Some installation possibilities for BOB 4


Parallel branch system with 3 three-core cables up to $3 \times 4 \text{ mm}^2$



Parallel branch system with 4 three-core cables up to $3 \times 2.5 \text{ mm}^2$




Parallel 5-lamp connection system



Can be installed with Mammut type connector (not included)


3-LED spotlight in-series system




3-LED RGB spotlight parallel system with four-core cables



For use in traps. The ideal accessory for branch connections from a through cable to light fittings and spotlights. Suitable in applications where there is presence of water and moisture.



BOB 3



BOB 4

PRODUCT / Item	Colour	Max cable formation (Nº x mm ²)	Through	Branch	Cables Ø min - max (mm)	Pieces Pack	(mm)
BOB 3 BOB3	●	1 cable 3×4 $3 \times 2,5$		2 cables 3×4		1 piece Blister	
BOB 3 - N BOB3-N	●			2 cables $3 \times 2,5$	8 - 13	1 piece Blister	105 x 80 x 25



PRODUCT / Item	Colour	Max cable formation (Nº x mm ²)	Through	Branch	Cables Ø min - max (mm)	Pieces Pack	(mm)
BOB 4 BOB	●	1 cables 3×4 $3 \times 2,5$		2 cables 3×4		1 piece Blister	
BOB 4 - N BOB4-N	●			3 cables $3 \times 2,5$	8 - 13	1 piece Blister	105 x 65 x 25



JOINT OR BOX? CHOOSE BABY BOX!



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB cULus

Installation temperature:
-40°C / +50°C

Working temperature: 90°

Gel operating temperature:
-60°C / +200°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:
Glow Wire Flammability Index at +960°C according to EN60695-2-12

IP68
OFFICIALLY
TESTED

IMQ

IP69K
OFFICIALLY
TESTED

BABY BOX


Pre-filled boxes (1 to 2) – (1 to 3) with integrated terminal block and clamping nuts.

BABY BOX is the range of ready to use boxes/junction boxes, complete with terminal block and a kit of components that allow its use with cables from 8 to 18 mm in diameter and ducts from 16 to 20 mm in diameter. Nothing to pour and no waiting times as it is already pre-filled with a non-toxic gel, not classified as dangerous and with no shelf life, which insulates and seals the connection thoroughly and gives to the range the maximum of reliability; the accessory is ideal for underground, submerged or aerial installations. BABY BOX, 3-entrances box with three-pole terminal block and BABY BOX 3, 4-entrances box with five-pole terminal block, are available in grey or black, they are very simple to install and equipped with external holes for wall fixing.


ADVANTAGES

- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive.
- Ready to use.
- Also suitable for wet or flooded environments.
- Always re-enterable.
- Wall or external ceiling fixing system.
- Click and hook closure, does not require screws.
- No shelf life.


BABY BOX 3





CABLES



TUBES



BABY BOX

With integrated connectors.

Also suitable for extra-flat lever connectors.

Also suitable for screw terminals.

PRODUCT / Item	Colour	Connectors	Cables Ø min - max (mm)	Tubes Ø (mm)	(mm)
BABY BOX BABYBOX	●	3	3x Max 12 mm ²	8 - 18	16 / 20
BABY BOX - N BABYBOX-N	●	3	3x Max 12 mm ²	8 - 18	16 / 20

PRODUCT / Item	Colour	Connectors	Cables Ø min - max (mm)	Tubes Ø (mm)	(mm)
BABY BOX 3 BABYBOX3	●	4	5x Max 12 mm ²	8 - 18	16 / 20
BABY BOX 3 - N BABYBOX3-N	●	4	5x Max 12 mm ²	8 - 18	16 / 20





READY BOX

3 or 4 entrances junction boxes pre-filled with gel, complete with integrated terminal block and cable glands

Ready Boxes are pre-filled with gel and ready to use; complete with terminal blocks but can also be used with the most common connection systems. Supplied with nuts for the conformation with 3 or 4 outputs, they are suitable for a very wide range of cables or ducts diameters.

ADVANTAGES

- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive.
- ▶ Ready to use.
- ▶ Also suitable for wet or flooded environments.
- ▶ Always re-enterable.
- ▶ Wall or external ceiling fixing system.
- ▶ Click and hook closure, does not require screws.
- ▶ Pre-threaded entries for cable gland mounting.
- ▶ No shelf life.



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Gel operating temperature:
-60°C / +200°C

Fully submersible

Can be used underground

Halogen-free Gel



UV resistant





Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960°C according to EN60695-2-12

IP68
OFFICIALLY
TESTED

IP69K
OFFICIALLY
TESTED



**READY
BOX 120**


Thanks to its innovative design, unlike a standard box, there is no need to break through the walls of the box to insert the cable.

Also suitable for extra-flat lever connectors.


Also suitable for screw terminals.

**READY
BOX 90**


PRODUCT / Item	Colour		Cables Ø min-max (mm)	Tubes Ø (mm)	
Ready Box IP68 90 READYBOX90	●		3	8 - 18	16 / 20 / 32
Ready Box IP68 90/N READYBOX90-N	●				90 x 90 x 45



PRODUCT / Item	Colour		Cables Ø min-max (mm)	Tubes Ø (mm)	
Ready Box IP68 120 READYBOX120	●		4	8 - 18	16 / 20 / 32
Ready Box IP68 120/N READYBOX120-N	●				120 x 100 x 45

**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Gel operating temperature:
-60°C / +200°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960°C according to EN60695-2-12

IP68
OFFICIALLY
TESTED

IMQ

IP69K
OFFICIALLY
TESTED



FOX BOX


3 or 5 entrance jointing enclosure with gel filled perimeter chamber providing lighter weight with maximum capacity.

Kit includes accessories to maximise versatility allowing the use of cables from 8 to 18 mm in diameter or with 16, 20 and 32 mm diameter cable conduits. The internal, gel-free compartment allows for dry connections or any future alterations or disconnections. The gel, contained in the perimeter chamber also surrounds, insulates and seals any armour continuity connections or cable shields.

ADVANTAGES

- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive.
- ▶ Functional, elegant design.
- ▶ Ideal for exposed and safety systems and for video camera installation.
- ▶ Ready for use.
- ▶ Click and hook closure, does not require screws.
- ▶ Ready and installable in all environmental conditions.
- ▶ Also suitable for wet or flooded environments.
- ▶ Always re-enterable.
- ▶ Wall or external ceiling fixing system.
- ▶ No shelf life.





PRODUCT / Item	Colour	Cables Ø min-max (mm)	Tubes Ø (mm)	Inner capacity (mm)	Outer dimensions (mm)
FOX BOX 3 FOXBOX3	●				
FOX BOX 3 - N FOXBOX3-N	●	8 - 18	16 / 20 / 32	79 x 60 x 32	180 x 135 x 45
FOX BOX 3 - ARM FOXBOX3-ARM	●				



PRODUCT / Item	Colour	Cables Ø min-max (mm)	Tubes Ø (mm)	Inner capacity (mm)	Outer dimensions (mm)
FOX BOX FOXBOX	●				
FOX BOX - N FOXBOX-N	●	8 - 18	16 / 20 / 32	116 x 78 x 32	210 x 155 x 45
FOX BOX - ARM FOXBOX-ARM	●				

**The Fox Box – Arm kit includes:**

- The yellow/green insulated wires.
- The roll springs to carry out the continuity of the armouring.

Armourings and their continuity are housed in the chamber with the gel, ensuring perfect sealing.



MAGIC BOX

IP68 Connection kit complete with Magic Fluid insulating gel.

Universal IP68 kit without shelf life, mechanically robust, non-toxic, suitable for installation even in the most extreme conditions, re-enterable, meeting all international standards. Protects from water, moisture, dust and accidental contact caused by small animals.

ADVANTAGES

- ▶ With pre-drilled walls for a faster installation.
- ▶ Re-enterable even after long periods of operation.
- ▶ Able to absorb external shock without fracturing.
- ▶ For installations even at high depths.
- ▶ Also suitable for vertical filling.
- ▶ No shelf life.
- ▶ The gel is not-classified as hazardous under the CLP Directive.



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Gel operating temperature:
-60°C / +200°C

Fully submersible

Can be used underground

Halogen-free Gel

Self-extinguishing and resistant to abnormal heat and fire:
Glow Wire Flammability Index at +960°C according to EN60695-2-12



PUBLIC LIGHTING



NAVAL SECTOR



OUTDOOR - GARDENS



ELECTRIC GATES

IP68
OFFICIALLY
TESTED | **IMQ**

Kit box installation sequence



Fix the box and cover the screws with the caps.



Knock out the pre prepared holes.




Install the cable glands.



Insert the cables and connect the wires.

Horizontal installation sequence



Vertical installation sequence



PRODUCT / Item	Input cables max. external Ø (mm)	N° and type of cable glands	Box dimensions (mm)
MAGIC BOX 65 MAGICBOX65	22	3 x PG16	Ø 65 x h 35
MAGIC BOX 80 MAGICBOX80	22	3 x PG16	Ø 80 x h 40
MAGIC BOX 100 MAGICBOX100	20	3 x M25 x 1.5	100 x 100 x h 50
MAGIC BOX 120 MAGICBOX120	20	3 x M25 x 1.5	120 x 80 x h 50
MAGIC BOX 150 MAGICBOX150	26	3 x M25 x 1.5	150 x 110 x h 70
MAGIC BOX 190 MAGICBOX190	26	3 x M25 x 1.5	190 x 140 x h 70
MAGIC BOX 240 MAGICBOX240	26	3 x M25 x 1.5	240 x 190 x h 90



Kit complete with cover
3 cable glands
Series of closing plugs
Insulating gel for complete filling



POWER KIT IP68

The only re-enterable and reusable IP68 kit. Can easily be used for ceiling mounted or recessed applications!

The most versatile, safe solution to fully protect connections in boxes with an IP68 degree of protection. Thanks to **Magic Power**, the newly developed, fast cross-linking, safe and reliable, extremely sticky self-agglomerating gel with very high dielectric, thermal and elastic characteristics, sealing is guaranteed in all type of installation, including submerged. The Power Kit IP68 solution is the only product of its kind! Not only because the insulation can be used in two different ways, both as a traditional "pour" in the box and as a "cross linked and sticky" product (cross linking first), but also because, thanks to its re-enterability and re-usability, it helps you save time and money!

ADVANTAGES

- ▶ Magic Power Gel is not-classified as hazardous under the CLP Directive.
- ▶ Complete Kit for a perfect connection IP68.
- ▶ Insulated with Magic Power Gel the innovative self-amalgamating gel.
- ▶ Can also be used in severe environmental conditions.
- ▶ Suitable for very high depths.
- ▶ No waste.
- ▶ No shelf life.



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Gel operating temperature:
-60°C / +200°C

Fully submersible

Can be used underground

Halogen-free Gel

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960°C according to EN60695-2-12

IP68 | **IMQ**
OFFICIALLY
TESTED

WHERE CAN YOU USE THE POWER KIT?

In pools, tanks, submerged pumps, outdoor lighting systems, underground, port piers, marinas, sewer systems, and with temporary connections such as with lights, street vendors, etc.

HOW DO YOU USE THE POWER KIT?

The insulation can be poured into the box (Pour!) or, for special applications, cross linked in the measuring jug and applied around the connection (Stick!). Mix the Magic Power gel in a 1:1 ratio in the supplied measuring jug. The gel will cross link in less than 15 minutes.

NO WASTE

The cross linked gel which remains on the bottom after mixing can be easily removed from the jug and saved for later use.

Choose the **POUR** or **STICK** method most suited for your needs

POUR



You can use the Magic Power gel supplied in the two-component bottle in a 1:1 ratio by simply pouring it after mixing into the box supplied in the kit, to protect and seal internal connections. The gel cross links in just 15 minutes, but the box can be energised immediately.

RE-ENTER AND RE-USE




Thanks to Magic Power Gel, the box can be **re-opened, inspected and re-insulated** all using the original installed product.

STICK



Pour the components in the measuring jug, mix and leave to cross link (about 15 minutes). Remove the insulation and position it in small parts around the connection so that it is fully covered. Insulation saved from previous mixes can of course be utilised.

IN A HURRY? ADVERSE WEATHER CONDITIONS? PREPARE YOUR INSULATION BEFORE INSTALLING IT!





WHAT ARE THE ADVANTAGES TO USING THE POWER KIT?

- The insulation is extremely sticky and self-amalgamating, with no shelf life, it is non-toxic and it adheres to everything while leaving your hands clean and dry.
- The kit does not cause waste: insulation left over in the measuring jug can be saved for later use.
- Re-enterable and reusable, saving time and money.
- The supplied box has pre-marked holes.

• Compatible with Magic Gel.

• A slight exothermic reaction (temperature increase of about 3°C) speeds up cross linking in cold weather conditions.

• Even protects boxes mounted on the ceiling to IP68 if using the "stick" method. Could also use left over product from previous installations.

• Insulation can be pre-prepared: at home, at work or in your car and then applying it once cross linked, saving time when you're in a hurry or in adverse weather conditions.

SOME LEFT OVER? SAVE IT!



Left over gel that has already cross linked can be easily removed from the measuring jug and saved for later use.



PRODUCT / Item	Box	Insulating filler
POWER KIT 65 POWER-65	Ø 65 x h 35 mm + 2 cable glands PG16 / caps	Single two-component bottle 1 small jug - 1 spatula in wood
POWER KIT 80 POWER-80	Ø 80 x h 40 mm + 3 cable glands PG16 / caps	Single two-component bottle 1 small jug - 1 mixing spatula
POWER KIT 100 POWER-100	100 x 100 x h 50 mm + 3 cable glands M25 x 1.5 / caps	Single two-component bottle 1 small jug - 1 mixing spatula
POWER KIT 120 POWER-120	120 x 80 x h 50 mm + 3 cable glands M25 x 1.5 / caps	Single two-component bottle 1 small jug - 1 mixing spatula

MAGIC GEL SPRINT BOX 100

Kit for IP68 connections with Magic Gel Sprint.

The kit includes a pack of Magic Gel Sprint 450, the gel formulated for an extra-rapid polymerization directly inside the bottle, and a 100 x 100 x h50 mm box: once connected the conductors in the box, the gel is prepared simply by pouring into the large bottle the content of the small one. Then shake and pour. Operation finished!

ADVANTAGES

- ▶ For POWER CABLES, TELECOM CABLES and ELECTRONIC CIRCUITS.
- ▶ Non-toxic, safe and not classified as hazardous under CLP Directive.
- ▶ Suitable for installation in salt water (sea) and in chlorinated water (pools).
- ▶ Suitable for very high depths.
- ▶ For installations up to 1 kV.
- ▶ No shelf life.
- ▶ Re-enterable.
- ▶ Suitable for high temperatures.



PRODUCT / Item	Box	Insulating filler
MAGIC GEL SPRINT BOX 100 MAGICSPRINTBOX1	100 x 100 x h 50 mm + 3 cable glands M25 x 1,5	Bottle + Catalyst



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Water resistance: UL 94-HB

Working temperature: 90°

Gel operating temperature:
-60°C / +200°C

Fully submersible

Can be used underground

Halogen-free Gel

Self-extinguishing and resistant
to abnormal heat and fire:

Glow Wire Flammability Index at +960°C
according to EN60695-2-12

IP68 | **IMQ**
OFFICIALLY
TESTED





J-BOX

Snap shut closing enclosures with perforated knockouts.

Enclosure with snap shut cover and perforated knockouts for faster mounting of cable glands. Very high mechanical and flame retardant properties. Re-enterable only by means of a tool. The screwless design prevents screws rusting over time due to moisture and always allows for easy re-entry. Screw caps are also supplied for the wall mounting screws along with 3 cable glands and a stopping plug for vertical filling.

Electrical Performance:
CEI 23-48, IEC 60670

Degree of protection:
empty IP55
filled with Gel Raytech IP68

**Self-extinguishing and
resistant to abnormal
heat and fire:**
Glow Wire Flammability Index at +960°C
according to EN60695-2-12

ADVANTAGES

- Can be insulated with *Magic Power Gel*, *Magic Gel*, *Wonder Gel* (IP68).
- Re-enterable only with the use of a tool.
- Snap-shut closing (without screws).
- Also suitable for vertical filling.
- Excellent shock-resistance.



Snap-shut closing (without screws)



Pre - drilled walls



PRODUCT Item	Max N° of cables that can be jointed	Max Ø predrilling holes (mm)	Max Ø possible drilling (mm)	Max dimension housed cable glands (pass) PG	Max dimension housed cable glands (pass) METRIC	Dimension (mm)
J-BOX 65 JBOX65	4	23	23	16	20	Ø 65 x h 35
J-BOX 80 JBOX80	4	23	23	16	20	Ø 80 x h 40
J-BOX100 JBOX100	8	29	29	21	25	100 x 100 x h 50
J-BOX120 JBOX120	6	25	29	21	25	120 x 80 x h 50
J-BOX150 JBOX150	10	29	37	29	32	150 x 110 x h 70
J-BOX190* JBOX190	10	37	37	29	32	190 x 140 x h 70
J-BOX240* JBOX240	12	37	37	29	32	240 x 190 x h 90

* Supplied with extractable hinge for opening book type.
Note: All boxes include 3 cable glands Ray Pass 16.

J-BOX ACCESSORIES

RAY-PRESS

METRIC pitch PRODUCT / Item	Metric pict	Assembly hole Ø (mm)	Cable range Ø min (mm)	Cable range Ø max (mm)	Pack of (PCS)
Ray PRESS-16 RAYPRESS16	M16 x 1.5	16	6	10	50
Ray PRESS-20 RAYPRESS20	M20 x 1.5	20	8	13	50
Ray PRESS-25 RAYPRESS25	M25 x 1.5	25	12	18	20
Ray PRESS-32 RAYPRESS32	M32 x 1.5	32	16	20	20



PG pitch PRODUCT / Item	PG pict	Assembly hole Ø (mm)	Cable range Ø min (mm)	Cable range Ø max (mm)	Pack of (PCS)
Ray PRESS-PG11 RAYPRESSPG11	11	19	6	9	50
Ray PRESS-PG13,5 RAYPRESSPG13,5	13,5	20	9	12	50
Ray PRESS-PG16 RAYPRESSPG16	16	23	11	14	50
Ray PRESS-PG21 RAYPRESSPG21	21	29	14	18	20



RAY-PASS

PRODUCT / Item	For pipe Ø max external (mm)	Assembly hole Ø (mm)	Pack of (PCS)
Ray PASS 16 RAYPASS16	20	23	50
Ray PASS 21 RAYPASS21	23,5	29	50
Ray PASS 29 RAYPASS29	32	38	50





**LOW VOLTAGE
CONNECTORS
TERMINAL BLOCKS
GEL COVER
GEL BOX**




**RAY BLOCK
SUPER BLOCK
HAPPY LINE
GEL BOX LINE
NANO LINE
BRAVO**



NEW

- MODULAR
- COMPOSABLE
- ULTRAFAST
- SELF-EXTINGUISHING



SECTION: 0.5-4 mm²
VOLTAGE: 600V
CAPACITY: 32A

LEVER CONNECTORS

LEVER CONNECTORS IN & OUT



RAY
BLOCK



x 50

COD. ART.
RAYBLOCK

MINIMUM ORDER QUANTITY
1 DISPLAY
OF 12 PACKS

RAY
BLOCK uno



x 20

COD. ART.
RAYBLOCKUNO

MINIMUM ORDER QUANTITY
1 DISPLAY
OF 20 BLISTER

RAY BLOCK B

The new range of lever connectors, quick and safe, time and cost-saving.

ADVANTAGES


- ▶ Extra compact, robust, practical, safe and very quick to install.
- ▶ They do not require the use of tools.
- ▶ They allow independent locking and release of individual conductors.
- ▶ Equipped with 2 voltage test points: on front and on back side.
- ▶ With high-quality, acid-resistant stainless steel pressure spring.



OPERATING: Max 105° C
VOLTAGE: 450V
CAPACITY: 32A




CEI/IEC 60998-1
 CEI/IEC 60998-2-2



x 40 COD. ART.
RAYBLOCKB2

MINIMUM ORDER QUANTITY
1 DISPLAY
OF 20 BLISTER



x 30 COD. ART.
RAYBLOCKB3

MINIMUM ORDER QUANTITY
1 DISPLAY
OF 20 BLISTER



x 18 COD. ART.
RAYBLOCKB5

MINIMUM ORDER QUANTITY
1 DISPLAY
OF 20 BLISTER

NEW**Electrical performance:**

- CEI EN 50393 as applicable (testing under water head of the accessory installed in a box).
- Class 2 in accordance with CEI 64-8.
- CEI EN 60998-1 - CEI EN 60998-2

Gel: UL 94-HB cULus

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

IP68 | **IMQ**
OFFICIALLY
TESTED**COVERS FOR
TERMINAL BLOCKS / CONNECTORS**


SUPERBLOCK

The new Gel Box with integrated lever connectors: ready, complete, submersible and compact.

The GEL BOX range, designed in 2015, is enriched with a new range of compact and waterproof connecting devices. For increasingly secure and high-performance connections over time.

ADVANTAGES

- For straight or branch connections of 3 or 5 rigid or flexible wires up to 4 mm².
- Tool-less.
- Can be powered immediately - Always re-enterable.
- Pre-filled with conforming viscoelastic gel, not classified as hazardous.
- Reusable.
- Without shelf-life.





SUPER BLOCK 3W

Item
SUPERBLOCK3W

Up to 3 x 4 mm²

Dimensions:
57 x 47 x 26 mm



SUPER BLOCK IN-OUT M

Item
SUPERBLOCKINOUTM

Up to 3 x 4 mm²

Dimensions:
67 x 50 x28 mm



SUPER BLOCK 3

Item
SUPERBLOCK3

Up to 3 x 4 mm²

Dimensions:
57 x 47 x 26 mm



SUPER BLOCK 5W

Item
SUPERBLOCK5W

Up to 5 x 2.5 mm²

Dimensions:
57 x 47 x 26 mm



SUPER BLOCK 5

Item
SUPERBLOCK5

Up to 5 x 4 mm²

Dimensions:
57 x 47 x 26 mm



SUPER BLOCK IN-OUT W

Item
SUPERBLOCKINOUTW

Up to 3 x 4 mm²

Dimensions:
67 x 50 x 28 mm



SUPER BLOCK IN-OUT

Item
SUPERBLOCKINOUT

Up to 3 x 4 mm²

Dimensions:
67 x 50 x 28 mm





HAPPY LINE

The revolutionary mini accessories with 3 entrances, pre-filled with gel and suitable for submersible installations (IPX8).


Designed in 3 dimensions to rapidly insulate and seal the most commonly used connectors. The 3 entrances not only guarantee the extreme flexibility in the range of these products by making possible triple configurations but also by the housing accepting a wide variety of connectors.

ADVANTAGES

- ▶ Extremely versatile - Ready to use - Re-enterable.
- ▶ For rigid or flexible insulated wires up to 6 mm².
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- ▶ Small compact and robust.



New closure safety



Electrical performance:

- CEI EN 50393 as applicable (testing under water head of the accessory installed in a box).
- Class 2 in accordance with CEI 64-8.
- CEI EN 60998-1 - CEI EN 60998-2

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index

a +650°C

a +850°C

according to EN60695-2-12

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible


Can be used underground

Halogen-free Gel

UV resistant

IPX8
OFFICIALLY
TESTED | **IMQ**

Configuration examples



HAPPY 00


PRODUCT	Item	Colour	Pack of (PCS)	Description	Dimension (mm)
HAPPY 00	HAPPY00	●	x 4	Blister	
HAPPY 00-T	HAPPY00-T	○	x 4	Blister	40 x 28 x 19
GEL BOX 00	GELBOX00	○	x 20	Blister	

IDEAL FOR (or similar):

**HAPPY 0**

PRODUCT	Item	Colour	Pack of (PCS)	Description	Dimension (mm)
HAPPY 0	HAPPY0	●	4	Blister	
HAPPY 0 BOX12	HAPPY0BOX12	○	12	Box	41 x 28 x 19
GEL BOX 0	GELBOX0	○	20	Blister	

IDEAL FOR (or similar):

**HAPPY 1**


PRODUCT	Item	Colour	Pack of (PCS)	Description	Dimension (mm)
HAPPY 1	HAPPY1	●	2	Blister	
HAPPY 1 BOX10	HAPPY1BOX10	○	10	Box	45 x 37 x 24
GEL BOX 1	GELBOX1	○	15	Blister	

IDEAL FOR (or similar):

**HAPPY 2**

PRODUCT	Item	Colour	Pack of (PCS)	Description	Dimension (mm)
HAPPY 2	HAPPY2	●	1	Blister	
HAPPY 2 BOX7	HAPPY2BOX7	○	7	Box	53 x 39 x 24
GEL BOX 2	GELBOX2	○	11	Blister	

IDEAL FOR (or similar):



Coloured casings are self-extinguishing according to the UL 94-V2 standard.

**Electrical performance:**

- CEI EN 50393 as applicable (testing under water head of the accessory installed in a box).
- Class 2 in accordance with CEI 64-8.
- CEI EN 60998-1 - CEI EN 60998-2

Gel: UL 94-HB c^{FM} us

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant


IPX8 | **IMQ**
OFFICIALLY TESTED

HAPPY JOINT LINE

The revolutionary mini accessories with 3 entrances, pre-filled with gel and suitable for submersible installations (IPX8) complete with connectors.


ADVANTAGES

- Extremely versatile - ready to use - re-enterable.
- Small, compact and robust.
- No need for tools.
- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- Can energise immediately.
- For straight and branch connections.
- For rigid or flexible insulated wires up to 6 mm².
- Up to 5 conductors on one phase or up to two conductors on two or three phases.



HAPPY JOINT 3

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Pack of	Dimension (mm)
HAPPY JOINT 3 HAPPYJOINT3	3 x 1 - 4	2 through / 1 branch	4 PCS/ Blister	41 x 28 x 19
HAPPY JOINT 36 HAPPYJOINT36	3 x 1 - 6	2 through / 1 branch	2 PCS/ Blister	45 x 37 x 24



With one connector included for each Happy

HAPPY JOINT 4

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Pack of	Dimension (mm)
HAPPY JOINT 4 HAPPYJOINT4	2+2 x 1 - 4	2 through / in/out	2 PCS/ Blister	45 x 37 x 24
HAPPY JOINT 46 HAPPYJOINT46	2+2 x 1 - 6	2 through / in/out	2 PCS/ Blister	45 x 37 x 24



With two connectors included for each Happy

HAPPY JOINT 5

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Pack of	Dimension (mm)
HAPPY JOINT 5 HAPPYJOINT5	5 x 1 - 4	2 through / 3 branch	2 PCS/ Blister	45 x 37 x 24
Happy Joint 56 HAPPYJOINT56	5 x 1 - 6	2 through / 3 branch	1 PC/ Blister	53 x 39 x 24



With one connector included for each Happy

HAPPY JOINT 6

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Pack of	Dimension (mm)
HAPPY JOINT 6 HAPPYJOINT6	6 x 1 - 4	3 through / in/out	1 PC/ Blister	53 x 39 x 24



With three connectors included for each Happy

**Electrical performance:**

- CEI EN 50393 as applicable (testing under water head of the accessory installed in a box).
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant


IPX8
OFFICIALLY
TESTED | **IMQ**

GEL BOX LINE

Gel pre-filled accessories for sealing, protecting and making safe electrical connections.

ADVANTAGES

- Designed with dimensions suitable for the most commonly used connectors.
- To put household systems in order.
- For rigid or flexible insulated wires.
- For civil and industrial connections.
- Also for submersible use.
- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- Versatile and ready to use.



ISAAC

PRODUCT	Item	Pack of	Pack type	Dimension (mm)
ISAAC 4	ISAAC4	4 PCS	Blister	
ISAAC 4 P30	ISAAC4P30	30 PCS	Box	
ISAAC 4 MP *	ISAAC4MP	50 PCS	Multipack	30 x 27 x 23

IDEAL FOR
(or similar):**PASCAL**

PRODUCT	Item	Pack of	Pack type	Dimension (mm)
PASCAL 6	PASCAL6	2 PCS	Blister	
PASCAL 6 P15	PASCAL6P15	15 PCS	Box	
PASCAL 6 MP *	PASCAL6MP	25 PCS	Multipack	36 x 37 x 26

IDEAL FOR
(or similar):**WATT**

PRODUCT	Item	Pack of	Pack type	Dimension (mm)
WATT	WATT	2 PCS	Blister	
WATT P15	WATTP15	15 PCS	Box	
WATT MP *	WATT-MP	25 PCS	Multipack	30 x 42 x 26

IDEAL FOR
(or similar):**JOULE**

PRODUCT	Item	Pack of	Pack type	Dimension (mm)
JOULE	JOULE	1 PC	Blister	
JOULE MP *	JOULEMP	20 PCS	Multipack	33 x 52 x 26

IDEAL FOR
(or similar):**KELVIN**

PRODUCT	Item	Pack of	Pack type	Dimension (mm)
KELVIN	KELVIN	1 PC	Blister	
KELVIN P9	KELVINP9	9 PCS	Box	
KELVIN MP *	KELVINMP	20 PCS	Multipack	52 x 53 x 29

IDEAL FOR
(or similar):

* Also available in the self-extinguishing version according to the **UL 94-V2** standard in the colours: yellow, orange, blue or black.

COVERS FOR
TERMINAL BLOCKS / CONNECTORS**GEL BOX LINE KIT**


Complete with connectors.

PASCAL M2,5

PRODUCT / Item	Pack content	Pack type	Dimension (mm)
PASCAL M2,5 PASCALM2.5	12 pieces + 36 terminal blocks (2.5 mm ²)	Box	36 x 37 x 26

**KELVIN M4**

PRODUCT / Item	Pack content	Pack type	Dimension (mm)
KELVIN M4 KELVINM4	6 pieces + 24 terminal blocks (4 mm ²)	Box	52 x 53 x 29

**WATT +**

PRODUCT / Item	Pack content	Pack type	Dimension (mm)
WATT + 1.5 WATT-1.5	10 pieces + 30 end connectors/terminal blocks (1.5 mm ²)	Box	30 x 42 x 26
WATT + 2.5 WATT-2.5	10 pieces + 30 end connectors/terminal blocks (2.5 mm ²)	Box	

**KELVIN +**

PRODUCT / Item	Pack content	Pack type	Dimension (mm)
KELVIN + 4 KELVIN-4	10 pieces + 30 end connectors/terminal blocks (4 mm ²)	Box	
KELVIN + 6 KELVIN-6	10 pieces + 30 end connectors/terminal blocks (6 mm ²)	Box	52 x 53 x 29
KELVIN 6+4 KELVIN6-4	6 pieces + 20 end connectors/terminal blocks (4 mm ²)	Box	
KELVIN 6+6 KELVIN6-6	6 pieces + 20 end connectors/terminal blocks (6 mm ²)	Box	



NANO JOINT LINE

Gel pre-filled accessories to seal, protect and make safe electrical connections.
Inclusive of connectors.

ADVANTAGES

- ▶ Ready to use, quick, re-enterable!
- ▶ No tools required.
- ▶ Can energise immediately.
- ▶ For straight & branch connections.
- ▶ For rigid or flexible insulated wires from 1 a 4 mm².
- ▶ For 1, 2 and 3 cores connections.
- ▶ Up to 5 conductors on one phase or up to 2 conductors on two or three phase.
- ▶ Small, compact and resistant.
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.



Electrical performance:

- CEI EN 50393 as applicable (testing under water head of the accessory installed in a box).
- Class 2 in accordance with CEI 64-8.
- CEI EN 60998-1 - CEI EN 60998-2

💧 Gel: UL 94-HB

🌡 Working temperature: 90°

🌡 Installation temperature: -40°C / +50°C

🌊 Fully submersible

⛏ Can be used underground

🌿 Halogen-free Gel

☀ UV resistant

🔥 Self-extinguishing according to UL 94-V2

IPX8
OFFICIALLY
TESTED | **IMQ**


COVERS FOR TERMINAL BLOCKS / CONNECTORS

With extra flat connectors included



NANO 3

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO 3 NANO3	3 x 1 - 4	2 through / 1 branch	4 PCS Blister	30 x 27 x 23




NANO 5

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO 5 NANO5	5 x 1 - 4	2 through / 3 branch	2 PCS Blister	30 x 42 x 26



NANO 6

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO 6 NANO6	6 x 1 - 4	3 through / In/Out	1 PC Blister	33 x 52 x 26



With one connector included



NANO MAM 2,5

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO MAM 2,5 NANOMAM-2,5	3 x 1 - 2,5	3 through	2 PCS/ Blister	36 x 37 x 26

 max 3 wires
max 2.5 mm²



NANO MAM 4

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO MAM 4 NANOMAM-4	3 x 1,5 - 4	3 through	1 PC/ Blister	52 x 53 x 29

 max 3 wires
max 4 mm²



NANO FOR 2,5

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO FOR 2,5 NANOFOR-2,5	3 x 1 - 2,5	3 connections / In/Out	1 PC/ Blister	33 x 52 x 26

 max 3 fili
max 2.5 mm²



NANO FOR 4

PRODUCT / Item	Formation and wires cross section (Max N° x mm ²)	Combination	Package	Dimension (mm)
NANO FOR 4 NANOFOR-4	3 x 1 - 4	3 connections / In/Out	1 PC/ Blister	52 x 53 x 29

 max 3 wires
max 4 mm²




COVERS FOR
TERMINAL BLOCKS / CONNECTORS

BRAVO

The first "Gel-Box" with integrated connectors!

ADVANTAGES

- ▶ Ready to use, quick, re-enterable!
- ▶ For rigid or flexible insulated wires from 1 to 6 mm².
- ▶ It can be powered immediately.
- ▶ For straight & branch connections.
- ▶ For 1 or 3 cores connections.
- ▶ Small, compact and transparent.
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.



Electrical performance:

- CEI EN 50393 as applicable (testing under water head of the accessory installed in a box).
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible


Can be used underground

Halogen-free Gel

UV resistant

IPX8 | **IMQ**
OFFICIALLY
TESTED

MINI BRAVO




**BRAVO**

PRODUCT / Item	Formation and wires cross section (N° x mm ²)	Branch (N° x mm ²)	Package	Dimension (mm)
BRAVO 1-6 BRAVO1-6	1 x 1 - 6	1 x 1 - 6	1 PC/ Blister	50 x 29 x 22
BRAVO 3-6 BRAVO3-6	2 x 1 - 6 3 x 1 - 6	2 x 1 - 6 3 x 1 - 6	1 PC/ Blister	53 x 49 x 22

**MINI BRAVO**

PRODUCT / Item	Formation and wires cross section (N° x mm ²)	Branch (N° x mm ²)	Package	Dimension (mm)
MINI BRAVO 1 MINIBRAVO1	1 x 1 - 4	1 x 1 - 4	3 PCS/ Blister	41 x 28 x 19
MINI BRAVO 2 MINIBRAVO2	2 x 1 - 4	2 x 1 - 4	1 PC/ Blister	45 x 37 x 24
MINI BRAVO 3 MINIBRAVO3	3 x 1 - 4	3 x 1 - 4	1 PC/ Blister	53 x 39 x 24







LOW VOLTAGE JOINTS

**PRE-FILLED FOR PHOTOVOLTAIC
SOLAR COVER**

PRE-FILLED IP68

LITTLE JOINT EASY
LITTLE JOINT
MINI RAPID JOINT IP68
RAPID JOINT IP68
READY CAST

PRE-FILLED IPX8 - FLAT

GEL COVER LINE
SUPERCLIK / CLIK / CLIK A2A

PRE-FILLED IPX8 - CYLINDRICAL

KING JOINT
RAPID JOINT

FOR CASTING

MAGIC POWER JOINT
MAGIC JOINT
RUBBER JOINT
RAY CAST

HEAT-SHRINK JOINTS / TERMINALS



NEW**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Casing mix: UL 94-V2

Working temperature: 125°C

Installation temperature: -40°C / +50°C

Halogen-free Gel

 Loaded with CARBON BLACK
UV resistant No flame propagation:
CEI 20-35 IEC 60332-1 HD405-1
As applicable Self-ignition temperature:
> 400°C

Operating voltage: 1500V DC

IP68 | **IMQ**
OFFICIALLY TESTED

SOLARCOVER

The extra dark cover with gel filler, for sealing connectors from 4 to 10 mm² for solar.

It prevents the deterioration of connectors, preserving their performance over time, thus avoiding malfunctions and difficult and expensive maintenance. Resistant to UV rays, corrosion and immersion in water, even if salty or chlorinated. Ready, fast and always inspectable.

ADVANTAGES

- ▶ Made of UL 94-V2 polypropylene.
- ▶ Highly resistant to water, corrosion and frost.
- ▶ Complete with sealing silicone gel filler, non-toxic and safe.
- ▶ It is the ideal accessory to protect cable connections for solar and photovoltaic systems over the seasons and consequently affected by variations in temperature and weather conditions.
- ▶ It allows the reduction of risks from electric arcs and the resulting overheating.





For connectors
from 4 to 10 mm²



PRODUCT Item	Pieces / Pack	Dimension (mm)	
SOLARCOVER-4 SOLARCOVER-4	2 pcs / Box	165 x 45 x 27	
SOLARCOVER-6 SOLARCOVER-6	2 pcs / Box	220 x 52 x 32	



**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with **CEI 64-8.**

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960° C according to EN60695-2-12

IP68
OFFICIALLY
TESTED

IMQ

IP69K
OFFICIALLY
TESTED


LITTLE JOINT EASY

The IP68/IP69K mini joints, gel pre-filled, complete with in-out lever connectors.

Thanks to the integrated cable glands, they allow the degree of protection IP68 and IP69K and at the same time the locking of the joint on the cable. Suitable for all types of installation, even the most extreme.


ADVANTAGES

- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- ▶ Extremely compact and ready to install.
- ▶ Ideal for connections in lighting systems for gardens, steps and stairways, pedestrian crossings, etc.
- ▶ Always re-enterable.




NEW IN-OUT LEVER CONNECTORS

- ▶ Modular, Composable, Ultra-fast, Self-extinguishing.



FRED EASY

2x 4 mm²





DINO EASY

3x 4 mm²



BETTY EASY


5x 4 mm²



For use in traps. The ideal accessory for connections to light fittings and spotlights. Suitable in applications where there is presence of water and moisture.



PRODUCT Item	Colour	Connector	Cable formation max (N° x mm²)	Cable Ø min - max (mm)	Pieces / Pack	(mm)
FRED EASY FRED-EASY	●		2 x 4	8 - 13	1 / Blister	80 x 36 x 23
DINO EASY DINO-EASY	●		3 x 4	10 - 16	1 / Blister	125 x 43 x 35
BETTY EASY BETTY-EASY	●		5 x 4	10 - 16	1 / Blister	145 x 46 x 35



PRODUCT Item	NEW IN-OUT LEVER CONNECTORS 0,5 - 4 mm²	Pieces / Pack	(mm)
RAYBLOCK RAYBLOCK	Modular, Composable, Ultra-fast, Self-extinguishing Sections: 0,5 - 4 mm² Voltage: 600 V Capacity: 32 A Operating temperature of the insulating material: up to 105°C	50 / Box	39 x 8 x 15

**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:

Glow Wire Flammability Index at +960°C according to EN60695-2-12

IP68
OFFICIALLY
TESTED

IMQ

IP69K
OFFICIALLY
TESTED

LITTLE JOINT

The IP68 / IP69K micro-joints, gel pre-filled, complete with connector, suitable for any type of installation, even the most extreme.

Extremely compact and space-saving, pre-filled with soft, highly conformable gel. With minimal aesthetic impact and visually pleasing. Equipped with integrated cable glands for IP68 and IP69K degree of ingress protection and cable retention.

ADVANTAGES

- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- Extremely compact and ready to install.
- Ideal for connections in lighting systems for gardens, steps and stairways, pedestrian crossings, etc.
- Always re-enterable.



LITTLE JOINT L

Barney	
Fred	
Dino	
Betty	
Tom	



LITTLE JOINT Y

Barney Y	
Fred Y	
Dino Y	



PRODUCT Item	Colour	Connector	Max cable formation (N° x mm ²)	Cable Ø min - max (mm)	Pieces / Pack	(mm)
BARNEY BARNEY	●				1 / Blister	
BARNEY - N BARNEY-N	●		2 x 2,5	6 - 10	1 / Blister	75 x 28 x 19
BARNEY MP BARNEY-MP	●				10 / Multipack	
FRED FRED	●				1 / Blister	
FRED - N FRED-N	●		3 x 2,5	8 - 13	1 / Blister	80 x 36 x 23
FRED MP FRED-MP	●				10 / Multipack	
FRED/4 FRED/4	●		3 x 4	8 - 13	1 / Blister	
FRED/4 - N FRED/4-N	●				1 / Blister	80 x 36 x 23
DINO DINO	●		4 x 4	10 - 16	1 / Blister	
DINO - N DINO-N	●				1 / Blister	125 x 43 x 35
DINO 6 DINO/6	●		3 x 6	10 - 16	1 / Blister	125 x 43 x 35
BETTY/4 BETTY/4	●		5 x 4	10 - 16	1 / Blister	
BETTY/4 - N BETTY/4-N	●				1 / Blister	145 x 46 x 35
BETTY/6 BETTY/6	●		5 x 6	14 - 19	1 / Blister	
BETTY/6 - N BETTY/6-N	●				1 / Blister	145 x 46 x 35
TOM TOM	●		5 x 16	19 - 23	1 / Blister	
TOM - N TOM-N	●				1 / Blister	180 x 53 x 42



PRODUCT Item	Colour	Connector	Max cable formation (N° x mm ²)	Cable Ø min - max (mm)	Pieces / Pack	(mm)
			Through	Branch		
BARNEY Y BARNEY-Y	●		1 x 4 1 x 2,5	1 x 1,5 1 x 2,5	1 / Blister	
BARNEY Y - N BARNEY-Y/N	●				1 / Blister	85 x 55 x 22
FRED Y FRED-Y	●		3 x 4 3 x 2,5	3 x 1,5 3 x 2,5	1 / Blister	
FRED Y - N FRED-Y/N	●				1 / Blister	110 x 72 x 25
DINO Y DINOV	●		5 x 6 5 x 4 *	5 x 1,5 5 x 2,5 *	1 / Blister	
DINO Y - N DINOV-N	●				1 / Blister	160 x 75 x 37

* section for rigid cables



MINI RAPID JOINT IP68


IP68 and IP69K joints for straight and branch connections, extremely compact and pre-filled with gel.

Extremely compact, ideal for lighting systems for gardens, steps and pedestrian crossings. Perfect for use in even small traps thanks to its very small overall dimensions. The cable glands supplied with the kit lock the joint on the cables.

ADVANTAGES

- ▶ Complete with screw connectors.
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- ▶ Extremely compact and ready to install.
- ▶ Always re-enterable.
- ▶ Ideal for straight or branch connections in lighting systems for gardens, steps and stairways, pedestrian crossings, etc.

RAPIDINO
IP68 Y



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB cULus

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible


Can be used underground

Halogen-free Gel

UV resistant

Self-extinguishing and resistant to abnormal heat and fire:
Glow Wire Flammability Index at +960° C according to EN60695-2-12

IP68 | IMQ
OFFICIALLY
TESTED **IP69K**
OFFICIALLY
TESTED

RAPIDINO
IP68 L


PRODUCT Item	Cable	Connector	Max cable formation (N° x mm ²)	Cable Ø min - max (mm)	Pieces / Pack	(mm)
RAPIDINO IP68 L2 RAPIDINOL2	●	●	2 x 2,5	6 - 10	3 PCS / Box	75 x 28 x 19
RAPIDINO IP68 L3 RAPIDINOL3	●	●	3 x 2,5	8 - 13	3 PCS / Box	80 x 36 x 23
RAPIDINO IP68 L4 RAPIDINOL4	●	●	4 x 4	10 - 16	1 PCS / Box	125 x 43 x 35



PRODUCT Item	Cable	Connector	Max cable formation (N° x mm ²)	Cable Ø min - max (mm)	Pieces / Pack	(mm)
RAPIDINO IP68 Y1 RAPIDINOVY1	●	●	1 x 4 1 x 2,5	1 x 1,5 1 x 2,5	6 - 10	2 PCS / Box
RAPIDINO IP68 Y3 RAPIDINOVY3	●	●	3 x 4 3 x 2,5	3 x 1,5 3 x 2,5	8 - 13	1 PCS / Box





RAPID JOINT IP68

Radial closing gel pre-filled joint for extruded insulation cables up to 1 kV.

Primary insulation, consisting of a cross-linked polymer gel, and the exceptionally robust insulating plastic casing render Class 2 joints in accordance with the definitions contained in standard CEI 64-8. The joint has been tested in accordance with the main international specifications, with repeated flexing and torsion tests and immersion in water, and has been declared as conforming to the mechanical, electrical and sealing specifications required for plastic cable accessories. The joint and its components have an unlimited shelf life, are chemically inert and therefore completely safe. Conductor connections are re-enterable even after long periods of operation. Made with self-extinguishing material, flame retardant, for cables at 90°C working temperature. The radial closing system facilitates joint application, making them re-enterable only by means of a tool.

Electrical performance:

- CEI EN 50393
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel


UV resistant

No flame propagation:

CEI 20-35 • IEC 60332-1 • HD405-1
(as applicable)


IP68
OFFICIALLY
TESTED


IMQ | **IP69K**
OFFICIALLY
TESTED



ADVANTAGES

- ▶ For straight connections (in line).
- ▶ For multi core cables of up to 5 cores.
- ▶ With suitable spacers.
- ▶ For all types of application, including submersible.
- ▶ Wide range of cable formations.
- ▶ Re-enterable only by means of a tool.
- ▶ Suitable for 3 core crossing.
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.





PRODUCT Item	Formation n°	Configuration IP68			Configuration IPX8		
		Section (mm²)	Cable Ø (mm)	A x B (mm)	Section (mm²)	Cable Ø (mm)	A x B (mm)
Rapid Joint L1,5-IP68 RAPIDJL1.5-IP68	•	4 - 25			1,5 - 50		
	◎	1,5 - 4			1,5 - 6		
	◎	1,5 - 2,5	8 - 13	155 x 55	1,5 - 6	20,5	105 x 55
	◎	1,5			1,5 - 6		
	◎	1,5			1,5 - 6		
Rapid Joint L6-IP68 RAPIDJL6-IP68	•	25 - 70			2,5 - 150		
	◎	2,5 - 6			2,5 - 10		
	◎	2,5 - 6	12 - 18	245 x 60	2,5 - 10	24	180 x 60
	◎	2,5 - 6			2,5 - 10		
	◎	2,5 - 6			2,5 - 10		
Rapid Joint L10-IP68 RAPIDJL10-IP68	•	70 - 95			120 - 240		
	◎	10			10 - 25		
	◎	10	16 - 20	275 x 65	10 - 25	31	210 x 65
	◎	10			10 - 25		
	◎	10			10 - 25		
Rapid Joint L25-IP68 RAPIDJL25-IP68	•	120 - 240			120 - 240		
	◎	25			10 - 50		
	◎	16 - 25	21 - 28	410 x 100	10 - 50	42	320 x 100
	◎	16 - 25			10 - 50		
	◎	16 - 25			10 - 50		

For single core cable: do not install the separator with screw connectors and connect with crimp connector.





READY CAST

The new pre-filled resin joint for extruded insulation cables up to 1 kV.

Thanks to its innovative pre-engraved and fracture-facilitated cable entry system, Ready Cast adapts itself quickly and extremely easily to any cable diameter, while respecting the minimum and maximum diameters that can be housed in the range. With the quick and safe connection block included in the pack or with commonly used connectors that can always be housed in the practical 4x separator, included in the kit. Ready Cast is equipped with an anti-traction system of the cable since it can be secured to the casing using the supplied cable ties.

**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Resin: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Resin

UV resistant

IP68
OFFICIALLY
TESTED




INNOVATIVE RESIN SOLUTIONS



EASY!
Scissors and nothing more!



MULTICONNECTION!
Ideal for many types of connection



RELIABILITY!
Range compliant with EN 50393
which consists in a test in air and of prolonged immersion for about 30 days, with repeated temperature changes, after the intentional removal of the cable sheath at the inlet and outlet with consequent infiltration of water between the cores of the cable.

INTEGRATED SOLUTIONS!

HOLE CASING technology - Anti-traction cable system using the supplied cable ties secured to the casing.

PRODUCT Item	Cable Ø (mm)	Cable formation (N° x mm ²)					(mm)
		1 x	2 x	3 x	4 x	5 x	
READY CAST L4 READYCASTL4	8-18	6-25	2,5-4	2,5-4	2,5-4	-	160x45
		-	2,5-4	2,5-4	-	-	
READY CAST L10 READYCASTL10	8-23	16-50	4-10	4-10	4-10	-	180x50
		-	2,5-6	2,5-6	2,5-6	2,5-6	
READY CAST L 16/25 READYCASTL16/25	8-30	35-150	10-25	6-25	4-25	-	215x55
		-	6-25	6-25	6-16	6-16	



Each kit contains:

- Enclosure, complete with filler
- Cable ties
- Screw connection system
- 4x separator
- Rayteam black insulating tape

PRODUCT Item	Cable Ø (mm)	Cable formation (N° x mm ²)					(mm)
		1 x	2 x	3 x	4 x	5 x	
READY CAST Y6 READYCASTY6	T 8-20 B 8-20	T 16-50 B 6-35	T 4-10 B 2,5-4	T 2,5-6 B 1,5-4	T 2,5-6 B 1,5-2,5	-	180x100
		-	T 4-6 B 2,5-4	T 2,5-6 B 1,5-4	T 2,5-6 B 1,5-2,5	T 2,5-6 B 1,5-2,5	
READY CAST Y 16/25 READYCASTY16/25	T 8-30 B 8-30	T 70-150 B 50-150	T 10-25 B 6-25	T 6-25 B 6-16	T 6-25 B 6-10	-	220x105
		-	T 10-16 B 4	T 6-16 B 2,5-4	T 6-16 B 2,5-4	T 4-16 B 2,5-4	




GEL COVER LINE

Gel pre-filled accessories for straight connections, for the protection, safety and covering of electrical connections using strip connectors or alternatives.

ADVANTAGES

- ▶ For 3 x 1 to 6 mm² cables or 3 insulated wires.
- ▶ For domestic and industrial connections.
- ▶ To put household systems in order.
- ▶ Also for underwater use.
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.
- ▶ Ready to use.



Electrical performance:

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

IPX8 | **IMQ**
OFFICIALLY
TESTED





PRODUCT Item	Colour	Housed connectors type	Nº pieces	Package type	Dimension (mm)
OHM OHM	○	2 from 4 mm ²	1	blister	61 x 35 x 28
OHM PACK 11 OHMPACK11			11	box	
BAR BAR	○	3 from 4 mm ² / 6 mm ²	1	blister	63 x 41 x 28
BAR PACK 9 BARPACK9			9	box	



PRODUCT Item	Colour	Housed connectors type	Nº pieces	Package type	Dimension (mm)
GEL COVER 4 GELCOVER4	●	2 from 4 mm ²	1	blister	61 x 35 x 28
MAMMUT GEL COVER MAMMUTGELCOVER			8	box	
GEL COVER 6 GELCOVER6	●	3 from 4 mm ² / 6 mm ²	1	blister	63 x 41 x 28
MAMMUT GEL COVER 6 MAMMUTGELCOVER6			6	box	



No flame propagation. CEI 20-35 • IEC 60332-1 • HD405-1 (as applicable). Casing mix: UL 94-V2

**Electrical performance:**

- CEI EN 50393 as applicable
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Casing mix: UL 94-V2

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel

UV resistant

 No flame propagation:
CEI 20-35 • IEC 60332-1 • HD405-1
(as applicable)**IPX8**
OFFICIALLY
TESTED | **IMQ**

SUPER CLIK

Range of fast gel pre-filled straight or branch type joints for 0.6/1 kV multi core cables of up to 5 conductors.

The combination of the primary insulation in a cross-linked polymer gel and the highly robust insulating plastic case makes this a Class 2 joint defined by CEI 64-8. The joint has been tested in accordance with the main international specifications, with repeated flexing and torsion tests and immersion in water, it has been declared as conforming to the mechanical, electrical and sealing specifications required for plastic cable accessories. The joint and its components have an unlimited shelf life, they are chemically inert and therefore completely safe; the connections are re-entrant even after long working periods. Made of self-extinguishing components the joint is flame retardant. For cables at 90°C working temperature.

ADVANTAGES

- Complete with insulated terminal blocks.
- For straight and branch connections.
- For all types of application, including submersible.
- Re-accessible.
- Flame retardant.
- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.



SUPER CLIK MINI

PRODUCT Item	Cable formation and conductor cross sections (n° x mm ²)			max cables Ø (mm)	(mm)
	In line	T	B		
SUPER CLIK MINI L SUPERCLIKMINI-L	3 x 0,5 - 1,5	-	-	10	71 x 38 x 23
SUPER CLIK MINI Y SUPERCLIKMINI-Y	-	1 x 2,5 - 6	1 x 2,5	10	71 x 38 x 23


T : Through cable - B : Branch cable



SUPER CLIK

PRODUCT Item	Cable formation and conductor cross sections (n° x mm ²)			max cables Ø (mm)	(mm)
	In line	T	B		
SUPER CLIK 0 SUPERCLIK0	3 x 1,5 - 6	3 x 1,5 - 4	3 x 1,5 - 2,5	14	95 x 43 x 28

T : Through cable - B : Branch cable



PRODUCT	In line	T		max cables Ø (mm)	(mm)
		B			
SUPER CLIK 1 SUPERCLIK1	2 x 1,5 - 6	2 x 4	2 x 2,5	20,5	150 x 56 x 30
	3 x 1,5 - 6	3 x 4	3 x 2,5		
	4 x 1,5 - 6	4 x 4	4 x 2,5		
	5 x 1,5 - 6	5 x 4	5 x 2,5		

T : Through cable - B : Branch cable



PRODUCT	In line	T		max cables Ø (mm)	(mm)
		B			
SUPER CLIK 2 SUPERCLIK2	2 x 4 - 16	2 x 10	2 x 6	30	220 x 85 x 46
	3 x 4 - 16	3 x 10	3 x 6		
	4 x 4 - 16	4 x 10	4 x 6		
	5 x 4 - 16	5 x 10	5 x 6		

T : Through cable - B : Branch cable



PRODUCT	In line	T		max cables Ø (mm)	(mm)
		B			
SUPER CLIK 3 SUPERCLIK3	-	2 x 4 - 25	2 x 1,5 - 16	30	220 x 85 x 46
		3 x 4 - 25	3 x 1,5 - 16		
		4 x 4 - 25	4 x 1,5 - 16		

T : Through cable - B : Branch cable



Electrical performance:

- CEI EN 50393
with connectors complying
with EN 61238-1
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Casing mix: UL 94-V2

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

Halogen-free Gel


UV resistant

No flame propagation:
CEI 20-35 • IEC 60332-1 • HD405-1
(as applicable)



RINA

IPX8
OFFICIALLY
TESTED



Sections based on
extruded 0,6/1 kV cable.

CLIK FIRE

Straight or branch gel pre-filled joint,
for multi core cables up to 4 cores.



► Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.

STRAIGHT OR BRANCH MULTI CORE JOINTS

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)		max cables Ø (mm) Through or straight	Branch	Dimension (mm)
	Through or straight	1 or 2 branch cables			
CLIK 0 Fire * 214663-003	1 x 2,5 - 50 2 x 2,5 - 6	1 x 1,5 - 10 2 x 1,5	16	10	95 x 43 x 28
CLIK 1 Fire * 225449-001	1 x 6 - 95 2 x 1,5 - 16 3 x 1,5 - 10 4 x 1,5 - 10	1 x 1,5 - 35 2 x 1,5 - 6 3 x 1,5 - 6 4 x 1,5 - 4	20,5	15	150 x 56 x 30
CLIK 2 Fire 301096-001	1 x 50 - 185 2 x 10 - 35 3 x 6 - 35 4 x 6 - 35	1 x 16 - 185 2 x 1,5 - 35 3 x 1,5 - 35 4 x 1,5 - 16	30	29	220 x 85 x 46

* Available in hangable BLISTER with the following Codes. Art.: CLIK0FIRE-BL and CLIK1FIRE-BL

BRANCH JOINTS WITH 30° OUTPUT

PRODUCT / Item	Through	Branch	Through	Branch	(mm)
CLIK 2000 Fire 214663-004	1 x 2,5 - 25	1 x 1,5 - 16	14	12,5	75 x 40 x 21
CLIK 2001 Fire 225448-002	1 x 6 - 95 2 x 1,5 - 16 3 x 2,5 - 16 4 x 2,5 - 10	1 x 1,5 - 70 2 x 1,5 - 10 3 x 1,5 - 10 4 x 1,5 - 6	22,5	18,5	138 x 60 x 37
CLIK 2002 Fire 301096-005	1 x 50 - 150 2 x 1,5 - 25 3 x 4 - 25 4 x 4 - 16	1 x 1,5 - 70 2 x 1,5 - 10 3 x 1,5 - 10 4 x 1,5 - 6	26	18,5	194 x 74 x 43
CLIK 2003 Fire 301097-006	1 x 150 - 240 2 x 16 - 50 3 x 16 - 50 4 x 16 - 50	1 x 50 - 120 2 x 10 - 25 3 x 10 - 25 4 x 6 - 16	36	26	290 x 105 x 51

CLIK FIRE A2A

Main line branch joint for parallel type public lighting systems.

Branch joints from main to main cable, from main to pole rise, from overhead line to pole equipment, from pre-assembled cable to pole equipment, of a type certified by Azienda Elettrica Milanese (A2A, ex AEM). Accessories are complete with mantel-type, pre-insulated Allen screw connectors and, for installations with traps, with the specific protection monitor plate. Joints are non-toxic, with no shelf life and re-enterable.



PRODUCT Item	Approval code	Branch type	Through cable (n° x mm ²)	Branch cable (n° x mm ²)
CLIK 2 Fire Dor/Palo 301009-000	E 27.012	Main / Pole	RG7R 2 x 1 x 16	FG7OR 2 x 2,5
CLIK 1 Fire Dor/Dor 302009-000	E 27.013	Main / Main	RG7R 4 x 1 x 16	RG7R 4 x 1 x 16
CLIK 1 Fire Aer/Dap 302008-000	E 27.014	Overhead line / Equipment	UG7R 2 x 1 x 16	FG7R 2 x 1 x 4
CLIK 2 Fire Prec/Dap 301008-000	E 27.015	Pre-assembled / Equipment	RE4E4X 2 x 1 x 10	FG7OR 2 x 2,5



Electrical performance:

- CEI EN 50393 • CEI 20-33 • IP 0033 (A2A)

Gel: UL 94-HB

Casing mix: UL 94-V2

Working temperature: 90°

Installation temperature: -40°C / +50°C

Fully submersible

Can be used underground

No flame propagation:
CEI 20-35 • IEC 60332-1 • HD405-1
(as applicable)

A2A Certified

IPX8
OFFICIALLY
TESTED

CLIK FIRE A2A (FUSE)

Branch joint from main to pole rise, with protection fuse.

Branch joints from main to pole rise complete with disconnectable fuse holder and fuse with signal indicating intervention. Accessories are complete with mantel-type, pre-insulated Allen screw connectors and, for installations with traps, with the specific protection monitor plate. Joints are non-toxic, with no shelf life and re-enterable and flame retardant.



PRODUCT / Item	Fuse inserted	Branch type	Through cable (n° x mm ²)	Branch cable (n° x mm ²)
CLIK 2 Fire Dor/Palo Fuse 301010-000	2 A	Main / Pole	RG7R 4 x 1 x 16	FG7OR 2 x 2,5



KING JOINT

Range of fast gel pre-filled straight or branch type joints for 0.6/1 kV multi core cables of up to 5 conductors.

The primary insulation, consisting of a cross-linked polymer gel and extremely strong plastic insulating housing, make the Class 2, in accordance with the definitions contained in CEI Regulation 64-8. The joint, tested in accordance with the most important international specifications with repeated bending and twisting cycles and immersion in water, was found to comply with the mechanical, electrical and sealing requirements necessary for accessories for plastic cables. The joint and its components have no self life, are chemically inert and therefore completely safe; the conductor connections are re-accessible even after long operating periods. Packaged with self-extinguishing material, it is flame retardant. Suitable for cables with a temperature of +90°C.

ADVANTAGES

- ▶ For multicore cables of up to 5 cores.
- ▶ 5 sector spacers for proper centring of five-core connection.
- ▶ Complete with screw connectors.
- ▶ For straight and branch connections, including armoured cable.
- ▶ For all types of application, including submersible.
- ▶ Re-accessible.
- ▶ Flame retardant.
- ▶ Non-toxic, safe and not classified as hazardous under CLP Directive.

Electrical performance:

- CEI EN 50393
- Class 2 in accordance with CEI 64-8.

💧 Gel: UL 94-HB cULus

💧 Casing mix: UL 94-V2

🌡 Working temperature: 90°

🌡 Installation temperature: -40°C / +50°C

🌊 Fully submersible


⛏ Can be used underground

🌿 Halogen-free Gel

🔥 No flame propagation:


CEI 20-35 • IEC 60332-1 • HD405-1
(as applicable)
Low smoke and toxic and
corrosive gas emissions.

● Degree of protection: IPX8




KING JOINT L

Straight joints, including armoured cable.



PRODUCT / Item	LINE CONNECTIONS Cable formation and conductor cross sections (n° x mm ²)	max cables Ø (mm)	Dimension (mm)
KING JOINT 0 blister RAYKJOINT0	2 x 1,5 - 6 3 x 1,5 - 6 4 x 1,5 - 6 5 x 1,5 - 6	20,5	105 x 55 x 55
KING JOINT L6 box RAYKJOINTL6	2 x 1,5 - 6 3 x 1,5 - 6 4 x 1,5 - 6 5 x 1,5 - 6	20,5	105 x 55 x 55



PRODUCT / Item	LINE CONNECTIONS Cable formation and conductor cross sections (n° x mm ²)	max cables Ø (mm)	Dimension (mm)
KING JOINT L10 RAYKJOINTL10	2 x 2,5 - 10 3 x 2,5 - 10 4 x 2,5 - 10 5 x 2,5 - 10	24	180 x 60 x 60
KING JOINT L10 - ARM RAYKJL10ARM			





PRODUCT / Item	LINE CONNECTIONS Cable formation and conductor cross sections (n° x mm ²)	max cables Ø (mm)	Dimension (mm)
KING JOINT L25 RAYKJOINTL25	2 x 10 - 25 3 x 10 - 25 4 x 10 - 25 5 x 10 - 25	31	210 x 65 x 65
KING JOINT L25 - ARM RAYKJL25ARM			



ARM type joints complete with continuity device
suitable for connection to **armoured wire or steel tape cables**.

KING JOINT Y

Branch joints, including armoured cable.



PRODUCT / Item	BRANCH CONNECTIONS		max cables Ø (mm)	Dimension (mm)
	T	B		
KING JOINT Y6 KINGJ-Y6	2 x 1,5 - 6	2 x 1,5 - 4	22,5	18,5
	3 x 1,5 - 6	3 x 1,5 - 4		
KING JOINT Y6 - ARM KINGJ-Y6ARM	4 x 1,5 - 6	4 x 1,5 - 4	22,5	18,5
	5 x 1,5 - 6	5 x 1,5 - 4		

T: Through cable - B: Branch cable



PRODUCT / Item	BRANCH CONNECTIONS		max cables Ø (mm)	Dimension (mm)
	T	B		
KING JOINT Y16 KINGJ-Y16	2 x 4 - 16	2 x 1,5 - 4	26	18,5
	3 x 4 - 16	3 x 1,5 - 4		
KING JOINT Y16 - ARM KINGJ-Y16ARM	4 x 4 - 16*	4 x 1,5 - 4	26	18,5
	5 x 4 - 16*	5 x 1,5 - 4		

T: Through cable - B: Branch cable

* For armoured cables max conductor cross section 10 mm².

PRODUCT / Item	BRANCH CONNECTIONS		max cables Ø (mm)	Dimension (mm)
	T	B		
KING JOINT Y35 KINGJ-Y35	2 x 10 - 35	2 x 1,5 - 6	36	26
	3 x 10 - 35	3 x 1,5 - 6		
KING JOINT Y35 - ARM KINGJ-Y35ARM	4 x 10 - 35*	4 x 1,5 - 6	36	26
	5 x 10 - 35*	5 x 1,5 - 6		

T: Through cable - B: Branch cable

* For armoured cables max conductor cross section 10 mm².

ARM type joints complete with continuity device suitable for connection to **armoured wire or steel tape cables**.


RAPID JOINT

Radial closing gel pre-filled joint for extruded insulation cables up to 1 kV.

Made with self-extinguishing material, flame retardant, for cables at 90°C working temperature. The radial closing system facilitates joint application, making them re-enterable only by means of a tool.

ADVANTAGES

- ▶ For straight connections (in line).
- ▶ With suitable spacers.
- ▶ For all types of application, including submersible.
- ▶ Wide range of cable formations.
- ▶ Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.



For **COPPER**
cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				With fiber-optic separator	Dimension (mm)
	1x	2x	3x	4x		
RAPID JOINT L6 301098-037	1,5 - 50	1,5 - 10	1,5 - 10	1,5 - 6	-	105 x 55
RAPID JOINT L10 301098-004	2,5 - 150	2,5 - 25	2,5 - 16	2,5 - 16	-	180 x 60
RAPID JOINT L25 301098-006	120 - 240	6 - 50	6 - 35	4 - 35	-	210 x 65
RAPID JOINT L95 301098-003	185 - 400	35 - 95	25 - 70	25 - 70	16 - 50	320 x 100

For **ALUMINIUM**
cables

	1x	2x	3x	4x	4x	(mm)
RAPID JOINT L25 301098-006	120 - 150	16 - 35	10 - 25	10 - 25	-	210 x 65
RAPID JOINT L95 301098-003	185 - 400	35 - 95	25 - 70	25 - 70	16 - 50	320 x 100



Electrical performance:

- CEI EN 50393 with connectors complying with EN 61238-1
- Class 2 in accordance with CEI 64-8.

Water: Gel: UL 94-HB

Water: Casing mix: UL 94-V2

Temperature: Working temperature: 90°

Temperature: Installation temperature: -40°C / +50°C

Water: Fully submersible

Tool: Can be used underground

Tool: Halogen-free Gel

Flame: No flame propagation:
CEI 20-35 • IEC 60332-1 • HD405-1
(as applicable)

Protection: Degree of protection: IPX8



Joint supplied with
armour continuity device

RAPID JOINT S/ARM

For screened or tape or wire armoured cables.

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				With fiber-optic separator 4x	Dimension (mm)
	1x	2x	3x	4x		
RAPID JOINT L 10-S 301098-035	2,5 - 120	2,5 - 10	2,5 - 10	2,5 - 10	-	180 x 60
RAPID JOINT L 25-S 301098-036	120 - 185	16 - 25	10 - 25	10 - 25	-	210 x 65
RAPID JOINT L 95-S 301098-012	240 - 400	35 - 95	25 - 70	25 - 70	16 - 50	320 x 100

For ARMOURED cables	1x	2x	3x	4x	(mm)
RAPID JOINT L 10-ARM 301098-10ARM	2,5 - 10	2,5 - 10	2,5 - 10	-	180 x 60
RAPID JOINT L 25-ARM 301098-25ARM	16 - 25	10 - 25	10 - 25	-	210 x 65
RAPID JOINT L 95-ARM 301098-016	35 - 95	25 - 70	25 - 70	16 - 50	320 x 100



RAPID JOINT LS

For signalling and control cables.


PRODUCT Item	Conductors (mm ²)	Cable formation (n° conduttori)								Dimension (mm)
		5x	7x	10x	12x	16x	19x	24x	40x	
RAPID JOINT-LS1 301098-018	1,5	•	•	•	•	•	•	•	•	180 x 60
	2,5	•	•	•	•	•				
RAPID JOINT-LS2 301098-019	1,5				•	•	•	•	•	210 x 65
	2,5			•	•	•	•	•	•	
RAPID JOINT-LS3 301098-020	1,5					•	•	•	•	320 x 100
	2,5					•	•	•	•	




RAPID JOINT T

Straight joints for telephone cables.


UNscreened PRODUCT / Item	SCREENED PRODUCT / Item	N° pairs for conductor cross sections (n° x mm ²)	Dimension (mm)
RAPID JOINT-T26 301098-021	RAPID JOINT-TS26 301098-024	(1 - 26) x (0,5 - 0,6)	180 x 60
RAPID JOINT-T61 301098-022	RAPID JOINT-TS61 301098-025	(30 + 1 - 64 + 1) x (0,5 - 0,6)	210 x 65
RAPID JOINT-T101 301098-023	RAPID JOINT-TS101 301098-026	(60 + 1 - 100 + 1) x (0,5 - 0,6)	320 x 100



Dimension (mm)





Dimension (mm)



Dimension (mm)


RAPID JOINT SYSTEM FAST RP

Straight joint + Shear bolt connectors.



PRODUCT / Item	Cable formation from 2x a 4x (n° x mm ²)	Dimension (mm)
RAPID JOINT L 10 RP RAPIDJL10RP	1,5 - 10	180 x 60
RAPID JOINT L 25 RP RAPIDJL25RP	10 - 25	210 x 65
RAPID JOINT L 95 RP RAPIDJL95RP	35 - 95	320 x 100

Shear bolt connectors



PRODUCT / Item	Aluminium cross sections* (mm ²)	Copper cross sections (mm ²)	Breakaway torque (Nm)	L	D	d (mm)
RAY-TTF 1,5/16 RAY-TTF1,5/16	10 - 16	1,5 - 16	4	30	12	6,1
RAY-TTF 10/35 RAY-TTF10/35	10 - 35	10 - 35	10	36	16	9,0
RAY-TTF 25/50 RAY-TTF25/50	25 - 50	25 - 50	12	36	18	10,0
RAY-TTF 35/150 RAY-TTF35/150	35 - 150	35 - 150	30	70	28	17,0

* For round conductors.

**Electrical performance:**

- CEI EN 50393 with connectors complying with EN 61238-1
- Class 2 in accordance with CEI 64-8.

Gel: UL 94-HB

Working temperature: 90°

Installation temperature: -15°C / +55°C

Fully submersible

Can be used underground

Halogen-free Gel

IP68
OFFICIALLY
TESTEDIn 15 minutes, the gel is cross-linked and **Magic Power Joint** is ready!

MAGIC POWER JOINT

Straight or branch joint with Magic Power Gel, for extruded insulation cables up to 1 kV.

Joints for extruded cables F(R)G7OR 0.6/1 kV. Easy installation, composed of two anti-fracture plastic shells, to be filled with non-toxic quick cross linking two-component insulation such as Magic Power Gel. Suitable for installation in traps, channels or directly underground or under water. Non-toxic, safe, light and re-enterable. Thanks to the softness of the insulation, they are able to absorb external shock without cracking or fracturing. The extreme stickiness of the insulation together with its softness allow it to transmit water pressure for installation even at high depths.

ADVANTAGES

- Re-enterable and inspectable joint.
- Insulated with Magic Power Gel, the innovative self-amalgamating gel.
- For installations even in harsh conditions and high depths!
- Extremely adherent and tight sealing.
- The gel is not-classified as hazardous under the CLP Directive and it has no shelf life.

RE-ENTERABLE**REMOVABLE****INSPECTIONABLE****REUSABLE**

MAGIC POWER JOINT L

Straight joint for 0.6/1 kV extruded cables.



For **COPPER** cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cable Ø (mm)	Dimension (mm)
	1x	2x	3x	4x		
MAGIC P JOINT L10 MPOWERJOINT-L10	2,5 - 50	1,5 - 10	1,5 - 10	1,5 - 10 *	8 - 16	180 x 50
MAGIC P JOINT L25 MPOWERJOINT-L25	16 - 150	4 - 25	4 - 25	2,5 - 25	8 - 32	215 x 55
MAGIC P JOINT L35 MPOWERJOINT-L35	16 - 185	16 - 35	16 - 35	16 - 35	12 - 33	232 x 70
MAGIC P JOINT L50 MPOWERJOINT-L50	50 - 300	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
MAGIC P JOINT L95 MPOWERJOINT-L95	120 - 400	25 - 95	25 - 95	25 - 95	15 - 42	330 x 95
MAGIC P JOINT L120 MPOWERJOINT-L120	240 - 500	70 - 120	70 - 120	50 - 120	25 - 50	365 x 95
MAGIC P JOINT L240 MPOWERJOINT-L240	400 - 1000	120 - 300	120 - 240	120 - 240	30 - 75	510 x 120
MAGIC P JOINT L300 MPOWERJOINT-L300	630 - 2000	240 - 400	240 - 300	240 - 300	41 - 78	760 x 180

For **ALUMINIUM** cables

PRODUCT / Item	1x	2x	3x	4x	(mm)	(mm)
	16 - 150	16 - 25	16 - 25	16 - 25	14 - 34	266 x 72
MAGIC P JOINT L120 MPOWERJOINT-L120	185 - 400	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
MAGIC P JOINT L240 MPOWERJOINT-L240	400 - 630	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120
MAGIC P JOINT L300 MPOWERJOINT-L300	630 - 2000	185 - 300	185 - 300	185 - 300	41 - 78	760 x 180

* Magic Power Joint 10 suggested for cable diameters smaller than 16 mm.

MAGIC POWER JOINT Y

Branch joint for 0.6/1 kV extruded cables.



For **COPPER** cables


PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm)	Dimension (mm)		
	T	1x	B	T	2x	B	T	3x	B	T	4x	B
MAGIC P JOINT Y6 MPOWERJOINT-Y6	4 - 50	4 - 50		4 - 10	4 - 10		2,5 - 6	2,5 - 6		2,5 - 6	2,5 - 6	
MAGIC P JOINT Y25 MPOWERJOINT-Y25	50 - 150	50 - 150		10 - 25	10 - 25		6 - 25	6 - 16		6 - 25	6 - 10	
MAGIC P JOINT Y95 MPOWERJOINT-Y95	120 - 400	95 - 240		25 - 95	16 - 50		25 - 95	16 - 50		25 - 95	10 - 50	
MAGIC P JOINT Y240* MPOWERJOINT-Y240	240 - 630	240 - 630		95 - 240	50 - 240		95 - 240	50 - 240		95 - 240	50 - 240	
										65 max		600 x 285

* also for aluminium cables. **T**: Through - **B**: Branch



MAGIC POWER JOINT L-S

Straight joint for 0.6/1 kV screened extruded cables.



For **COPPER** cables

PRODUCT / Item	1x	2x	3x	4x	max cable Ø (mm)	Dimension (mm)
MAGIC P JOINT L10-S MPOWERJOINT-L10S	2,5 - 50	1,5 - 10	1,5 - 6	1,5 - 6	8 - 16	180 x 50
MAGIC P JOINT L25-S MPOWERJOINT-L25S	16 - 120	4 - 25	4 - 16	2,5 - 16	8 - 32	215 x 55
MAGIC P JOINT L35-S MPOWERJOINT-L35S	16 - 185	16 - 35	16 - 25	16 - 25	12 - 33	232 x 70
MAGIC P JOINT L50-S MPOWERJOINT-L50S	50 - 240	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
MAGIC P JOINT L120-S MPOWERJOINTL120S	240 - 500	70 - 120	70 - 120	50 - 95	25 - 50	365 x 95
MAGIC P JOINT L240-S MPOWERJOINTL240S	400 - 1000	120 - 300	120 - 185	120 - 185	30 - 75	510 x 120
MAGIC P JOINT L300-S MPOWERJOINTL300S	630 - 2000	240 - 400	240 - 300	240 - 300	41 - 78	760 x 180


For **ALUMINIUM** cables

	1x	2x	3x	4x	(mm)	(mm)
MAGIC P JOINT L50-S MPOWERJOINT-L50S	16 - 150	16 - 25	16 - 25	16 - 25	14 - 34	266 x 72
MAGIC P JOINT L120-S MPOWERJOINTL120S	185 - 400	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
MAGIC P JOINT L240-S MPOWERJOINTL240S	400 - 630	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120
MAGIC P JOINT L300-S MPOWERJOINTL300S	630 - 2000	185 - 300	185 - 300	185 - 300	41 - 78	760 x 180



MAGIC POWER JOINT Y-S

Branch joint for 0.6/1 kV screened extruded cables.



For **COPPER** cables

PRODUCT	Item
MAGIC P JOINT Y6-S	MPOWERJOINT-Y6S
MAGIC P JOINT Y25-S	MPOWERJOINT-Y25S
MAGIC P JOINT Y95-S	MPOWERJOINT-Y95S
MAGIC P JOINT Y240-S*	MPOWERJOINTY240S

	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm)	Dimension (mm)		
	1x		2x		3x		4x					
	T	B	T	B	T	B	T	B	T	B	T	B
MAGIC P JOINT Y6-S	4 - 35	4 - 35	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90	
MAGIC P JOINT Y25-S	35 - 120	35 - 120	10 - 25	10 - 25	6 - 16	6 - 16	6 - 16	6 - 10	8 - 32	8 - 32	220 x 105	
MAGIC P JOINT Y95-S	95 - 300	70 - 150	25 - 95	16 - 50	16 - 70	16 - 35	16 - 50	10 - 35	15 - 42	8 - 32	315 x 115	
MAGIC P JOINT Y240-S*	240 - 630	150 - 630	95 - 240	50 - 240	70 - 240	35 - 240	50 - 240	35 - 240	65 max		600 x 285	

* also for aluminium cables. **T**: Through - **B**: Branch

MAGIC POWER JOINT L-ARM

Straight joint for 0,6/1 kV extruded cables with tape, wire or plate armouring.



For **COPPER** cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm²)			max cables Ø (mm)	Dimension (mm)
	2x	3x	4x		
MAGIC P JOINT L10-ARM MPJOINTL10-ARM	1,5 - 10	1,5 - 6	1,5 - 6	8 - 16	180 x 50
MAGIC P JOINT L25-ARM MPJOINTL25-ARM	4 - 25	4 - 16	2,5 - 16	8 - 32	215 x 55
MAGIC P JOINT L35-ARM MPJOINTL35-ARM	16 - 35	16 - 25	16 - 25	12 - 33	232 x 70
MAGIC P JOINT L50-ARM MPJOINTL50-ARM	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
MAGIC P JOINT L120-ARM MPJOINTL120-ARM	70 - 120	70 - 120	50 - 95	25 - 50	365 x 95
MAGIC P JOINT L240-ARM MPJOINTL240-ARM	120 - 300	120 - 185	120 - 185	30 - 75	510 x 120
MAGIC P JOINT L300-ARM MPJOINTL300-ARM	240 - 400	240 - 300	240 - 300	41 - 78	760 x 180



For **ALUMINIUM** cables

	2x	3x	4x	(mm)	(mm)
MAGIC P JOINT L50-ARM MPJOINTL50-ARM	16 - 25	16 - 25	16 - 25	14 - 34	266 x 72
MAGIC P JOINT L120-ARM MPJOINTL120-ARM	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
MAGIC P JOINT L240-ARM MPJOINTL240-ARM	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120
MAGIC P JOINT L300-ARM MPJOINTL300-ARM	185 - 300	185 - 300	185 - 300	41 - 78	760 x 180



MAGIC POWER JOINT Y-ARM

Branch joint for 0,6/1 kV extruded cables with tape, wire or plate armouring.



For **WIRE** armoured **COPPER** cables

PRODUCT	Item	Cable formation and conductor cross sections (n° x mm²)						max cables Ø (mm)	Dimension (mm)	
		2x		3x		4x		T	B	
MAGIC P JOINT Y6-ARM-F MPJOINTY6-ARM-F		4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90
MAGIC P JOINT Y25-ARM-F MPJOINTY25-ARM-F		10 - 25	10 - 25	6 - 16	6 - 16	6 - 16	6 - 10	8 - 32	8 - 32	220 x 105
MAGIC P JOINT Y95-ARM-F MPJOINTY95-ARM-F		25 - 70	16 - 50	25 - 70	16 - 35	25 - 50	10 - 35	15 - 42	8 - 32	315 x 115
MAGIC P JOINT Y240-ARM-F* MPJOINTY240ARM-F		70 - 240	50 - 240	70 - 240	35 - 240	50 - 240	35 - 240	65 max		600 x 285


For **TAPE, WIRE OR PLATE** armoured **COPPER** cables

PRODUCT	Item	Cable formation and conductor cross sections (n° x mm²)						max cables Ø (mm)	Dimension (mm)	
		2x		3x		4x		T	B	
MAGIC P JOINT Y6-ARM MPJOINTY6-ARM		4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90
MAGIC P JOINT Y25-ARM MPJOINTY25-ARM		10 - 25	10 - 25	6 - 16	6 - 16	6 - 16	6 - 10	8 - 32	8 - 32	220 x 105
MAGIC P JOINT Y95-ARM MPJOINTY95-ARM		25 - 70	16 - 50	25 - 70	16 - 35	25 - 50	10 - 35	15 - 42	8 - 32	315 x 115
MAGIC P JOINT Y240-ARM* MPJOINTY240ARM		70 - 240	50 - 240	70 - 240	35 - 240	50 - 240	35 - 240	65 max		600 x 285

* also for aluminium cables. T: Through - B: Branch

MAGIC POWER JOINT-SL


Straight joint for signaling and control multi core extruded 0,6/1 kV cables



PRODUCT	Item	Conductor (mm²)	5x	7x	10x	12x	16x	19x	24x	40x	75x	100x	250x	500x	max cables Ø (mm)	Dimension (mm)
MAGIC P JOINT SL11	MPOWERJOINTSL11	1,5	•	•	•	•	•								8 - 16	180 x 50
		2,5	•	•	•											
MAGIC P JOINT SL12	MPOWERJOINTSL12	1,5		•	•	•	•	•	•						8 - 32	215 x 55
		2,5		•	•	•	•	•	•							
MAGIC P JOINT SL13	MPOWERJOINTSL13	1,5				•	•	•	•	•					14 - 34	266 x 72
		2,5				•	•	•	•	•						
MAGIC P JOINT SL14	MPOWERJOINTSL14	1,5						•	•	•					15 - 42	330 x 75
		2,5						•	•	•						
MAGIC P JOINT SL15	MPOWERJOINTSL15	1,5							•	•	•				25 - 50	365 x 95
		2,5							•	•	•					
MAGIC P JOINT SL16	MPOWERJOINTSL16	1,5								•	•	•			30 - 75	510 x 120
		2,5								•	•	•				
MAGIC P JOINT SL17	MPOWERJOINTSL17	1,5									•	•	•	•	41 - 78	760 x 180
		2,5									•	•	•	•		


MAGIC POWER JOINT-SY

Branch joint for signaling and control multi core extruded 0,6/1 kV cables.



PRODUCT	Item	Conductor (mm²)	5x	7x	10x	12x	16x	19x	24x	40x	75x	100x	250x	500x	max cables Ø (mm) T	max cables Ø (mm) B	Dimension (mm)
MAGIC P JOINT SY1	MPOWERJOINTSY1	1,5	•	•	•	•	•	•	•						8 - 27	8 - 27	180 x 90
		2,5	•	•	•	•	•	•	•								
MAGIC P JOINT SY2	MPOWERJOINTSY2	1,5				•	•	•	•						8 - 32	8 - 32	220 x 105
		2,5				•	•	•	•	•							
MAGIC P JOINT SY3	MPOWERJOINTSY3	1,5				•	•	•	•	•					15 - 42	8 - 32	315 x 115
		2,5				•	•	•	•	•							
MAGIC P JOINT SY4	MPOWERJOINTSY4	1,5					•	•	•	•	•	•	•	•	65 max		600 x 285
		2,5					•	•	•	•	•	•	•	•			

T: Through - B: Branch

**MAGIC POWER JOINT-T e TS**


Straight joint for Telecom cables.

UNSCREENED PRODUCT	Item	SCREENED PRODUCT	Item	N° pairs per conductor cross sections (n° x mm²)	max cables Ø (mm)	Dimension (mm)
MAGIC P JOINT T16	MPOWERJOINT-T16	MAGIC P JOINT TS16	MPOWERJOINT-TS16	1 - 16 x 0,5 - 0,6	8 - 16	180 x 50
MAGIC P JOINT T25	MPOWERJOINT-T25	MAGIC P JOINT TS25	MPOWERJOINT-TS25	16 - 25 x 0,5 - 0,6	8 - 32	215 x 55
MAGIC P JOINT T35	MPOWERJOINT-T35	MAGIC P JOINT TS35	MPOWERJOINT-TS35	25 - 35 x 0,5 - 0,6	12 - 33	266 x 72
MAGIC P JOINT T40	MPOWERJOINT-T40	MAGIC P JOINT TS40	MPOWERJOINT-TS40	35 - 40 x 0,5 - 0,6	15 - 42	330 x 75
MAGIC P JOINT T64	MPOWERJOINT-T64	MAGIC P JOINT TS64	MPOWERJOINT-TS64	40 - 64 x 0,5 - 0,6	25 - 50	365 x 95
MAGIC P JOINT T500	MPOWERJOINT-T500	MAGIC P JOINT TS500	MPOWERJOINTTS500	60 - 500 x 0,5 - 0,6	30 - 75	510 x 120
MAGIC P JOINT T1000	MPOWERJOINTT1000	MAGIC P JOINT TS1000	MPOWERJ-TS1000	450 - 1000 x 0,5 - 0,6	41 - 78	760 x 180

MAGIC POWER JOINT SYSTEM PLUS L

Straight joint + Five-core spacer + Screw connectors.


For COPPER cables PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	2x	3x	4x	5x		
MAGIC P JOINT SP L6 MPOWERJSPL6	1,5 - 6	1,5 - 6	1,5 - 6	1,5 - 6	8 - 16	180 x 50
MAGIC P JOINT SP L16 MPOWERJSPL16	4 - 16	4 - 16	4 - 16	4 - 16	8 - 32	215 x 55
MAGIC P JOINT SP L25 MPOWERJSPL25	4 - 25	4 - 25	4 - 25	4 - 25	8 - 32	215 x 65



MAGIC POWER JOINT SYSTEM PLUS Y

Y Branch joint + Five-core spacer + Screw connectors.


For COPPER cables PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)	
	T	B	T	B	T	B	
MAGIC P JOINT SP Y6 MPOWERJSPY6	1,5-6	1,5-4	1,5-6	1,5-4	1,5-6	1,5-4	T 8 - 27 B 8 - 27 180 x 90
MAGIC P JOINT SP Y16 MPOWERJSPY16	4-16	1,5-4	4-16	1,5-4	4-16	1,5-4	T 8 - 32 B 8 - 32 220 x 105



MAGIC POWER JOINT SYSTEM PLUS T

T Branch joint + Four-core spacer + Screw connectors.


For COPPER cables PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)	
	T	B	T	B	T	B	
MAGIC P JOINT SP T35 MPOWERJSPT35	6 - 35	1,5 - 10	6 - 35	1,5 - 10	6 - 35	1,5 - 10	P 22 - 42 D 22 - 42 305 x 155



MAGIC POWER JOINT SYSTEM FAST RP

Straight joint + Shear bolt connectors.

PRODUCT / Item	Cable formation from 2x to 4x (n° x mm ²)		max cables Ø (mm)	Dimension (mm)
MAGIC P JOINT L 35- RP/16 MPOWERJL35RP16	Cu 1,5 - 16	Al 10 - 16	12 - 33	232 x 70
MAGIC P JOINT L 35- RP/35 MPOWERJL35RP35		10 - 35	12 - 33	232 x 70
MAGIC P JOINT L 50- RP/50 MPOWERJL50RP50		25 - 50	14 - 34	266 x 72
MAGIC P JOINT L 120- RP/120 MPOWERJL120RP120		35 - 120	25 - 50	365 x 95
MAGIC P JOINT L 240- RP/150 MPOWERJL240RP150		35 - 150	30 - 75	510 x 120



MAGIC JOINT

Straight or branch joint with Magic Gel filling gel for extruded insulation cables up to 1 kV.

Joints for extruded cables F(R)G7OR 0.6/1 kV. Easy installation, composed of two anti-fracture plastic shells, to be filled with non-toxic quick cross linking two-component insulation with no shelf life, Magic Gel type. Suitable for installation in traps, channels or directly underground or under water. Non-toxic, safe, light and re-enterable. Thanks to the softness of the insulation, they are able to absorb external shock without cracking or fracturing. The extreme stickiness of the insulation, together with its softness allow it to transmit water pressure for installation even at high depths. Thanks to the materials used, joints are completely non-toxic, safe, re-enterable even after long periods of operation.

ADVANTAGES

- ▶ Quick cross linking gel, (only 10 minutes at 23°C) .
- ▶ Extremely adherent and tight sealing.
- ▶ The gel is not-classified as hazardous under the CLP Directive and it has no shelf life.

IP68




Slip off the separator.



Mix for a minute.



Pour within a minute.



After 10 minutes,
Magic joint is ready.

MAGIC JOINT

Straight joint for 0.6/1 kV extruded cables.

For COPPER cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	1x	2x	3x	4x		
MAGIC JOINT 4 100004-002	1,5 - 25	1,5 - 4	1,5 - 4	1,5 - 4	10 - 18	160 x 45
MAGIC JOINT 10 100001-MAG	2,5 - 50	1,5 - 10	1,5 - 10	1,5 - 10 *	8 - 16	180 x 50
MAGIC JOINT 25 100002-MAG	16 - 150	4 - 25	4 - 25	2,5 - 25	8 - 32	215 x 55
MAGIC JOINT 35 100035-002	16 - 185	16 - 35	16 - 35	16 - 35	12 - 33	232 x 70
MAGIC JOINT 50 100005-MAG	50 - 300	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
MAGIC JOINT 95 100003-MAG	120 - 400	25 - 95	25 - 95	25 - 95	15 - 42	330 x 75
MAGIC JOINT 120 100007-MAG	240 - 500	70 - 120	70 - 120	50 - 120	25 - 50	365 x 95
MAGIC JOINT 240 100004-MAG	400 - 1000	120 - 300	120 - 240	120 - 240	30 - 75	510 x 120
MAGIC JOINT 300 100009-000	630 - 2000	240 - 400	240 - 300	240 - 300	41 - 78	760 x 180



For ALUMINIUM cables

PRODUCT	1x	2x	3x	4x	(mm)	(mm)
	T	B	T	B	T	B
MAGIC JOINT 50 100005-MAG	16 - 150	16 - 25	16 - 25	16 - 25	14 - 34	266 x 72
MAGIC JOINT 120 100007-MAG	185 - 400	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
MAGIC JOINT 240 100004-MAG	400 - 630	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120
MAGIC JOINT 300 100009-000	630 - 2000	185 - 300	185 - 300	185 - 300	41 - 78	760 x 180

* Magic Joint 10 suggested for cable diameters smaller than 16 mm.

MAGIC JOINT Y

Branch joint for 0.6/1 kV extruded cables.

For COPPER cables

PRODUCT	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm) T	Dimension (mm) B	
	1x	2x	3x	4x	T	B	T	B			
MAGIC JOINT Y6 100006-MAG	4 - 50	4 - 50	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90
MAGIC JOINT Y25 100025-MAG	50 - 150	50 - 150	10 - 25	10 - 25	6 - 25	6 - 16	6 - 25	6 - 10	8 - 32	8 - 32	220 x 105
MAGIC JOINT Y95 100095-MAG	120 - 400	95 - 240	25 - 95	16 - 50	25 - 95	16 - 50	25 - 95	10 - 50	15 - 42	8 - 32	315 x 115
MAGIC JOINT Y240* 100240-MAG	240 - 630	240 - 630	95 - 240	50 - 240	95 - 240	50 - 240	95 - 240	50 - 240	65 max		600 x 285




* also for aluminium cables. T: Through - B: Branch



MAGIC JOINT SYSTEM PLUS L

Straight joint + Five-core spacer + Screw connectors.




For COPPER cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	2x	3x	4x	5x		
Magic Joint SP L6 MAGICJSPL6	1,5 - 6	1,5 - 6	1,5 - 6	1,5 - 6	8 - 16	180 x 50
Magic Joint SP L16 MAGICJSPL16	4 - 16	4 - 16	4 - 16	4 - 16	8 - 32	215 x 55
Magic Joint SP L25 MAGICJSPL25	4 - 25	4 - 25	4 - 25	4 - 25	8 - 32	215 x 65



MAGIC JOINT SYSTEM PLUS Y

Y branch joint with cast gel + Five-core spacer + Screw connectors.



For COPPER cables


PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm)	(mm)
	2x		3x		4x		5x			
T	B	T	B	T	B	T	B			
MAGIC JOINT SP Y6 MAGICJSPY6	1,5-6	1,5-4	1,5-6	1,5-4	1,5-6	1,5-4	1,5-6	1,5-4	T 8 - 27 B 8 - 27	180 x 90
MAGIC JOINT SP Y16 MAGICJSPY16	4-16	1,5-4	4-16	1,5-4	4-16	1,5-4	4-16	1,5-4	T 8 - 32 B 8 - 32	220 x 105

T: Through - B: Branch



MAGIC JOINT SYSTEM PLUS T

T Branch joint + Four-core spacer + Screw connectors.



For COPPER cables


PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm)	(mm)
	2x		3x		4x					
T	B	T	B	T	B	T	B			
MAGIC JOINT SP T35 MAGICJSPT35	6 - 35	1,5 - 10	6 - 35	1,5 - 10	6 - 35	1,5 - 10			T 22 - 42 B 22 - 42	305 x 155

T: Through - B: Branch



MAGIC JOINT SYSTEM FAST RP

Straight joint + Shear bolt connectors.



PRODUCT / Item	Cable formation from 2x a 4x (n° x mm ²)	Max cables Ø (mm)	Dimension (mm)
MAGIC JOINT L 35- RP/16 MAGICJL35RP16	1,5 - 16	12 - 33	232 x 70
MAGIC JOINT L 35- RP/35 MAGICJL35RP35	10 - 35	12 - 33	232 x 70
MAGIC JOINT L 50- RP/50 MAGICJL50RP50	25 - 50	14 - 34	266 x 72
MAGIC JOINT L 120- RP/120 MAGICJL120RP120	35 - 120	25 - 50	365 x 95
MAGIC JOINT L 240- RP/150 MAGICJL240RP150	35 - 150	30 - 75	510 x 120

RUBBER JOINT


Straight or branch joint with two-component cast quick cross linking rubber insulation for 0.6/1 kW cables.

With Magic Rubber insulation, designed and developed by Raytech for 0.6/1 kV cables. A range of accessories with extremely high mechanical characteristics, as well as dielectric and thermal properties. The range is re-enterable even after long periods of operation, is free of exotherm during cross linking, is extremely fast-acting and has no shelf life. Significant also for its very low emission of toxic and corrosive gases and fumes. Thanks to its exceptional mechanical characteristics, these joints are especially suitable for placement in traps or channels where there is the possibility of handling even after the laying of cables or, however, in cases of heavy abrasion, or mechanical stress within the normal parameters of installation and operation.



ADVANTAGES

- ▶ Quick cross linking rubber (only 15 minutes).
- ▶ Very high mechanical and elastic characteristics.
- ▶ For 0.6/1 kV extruded cables.
- ▶ No shelf life.



Electrical performance:

- CEI EN 50393
with connectors complying
with EN 61238-1
- Class 2 in accordance with CEI 64-8.

Working temperature: 90°

Installation temperature: -15°C / +55°C

Can be used underground

IP68




RUBBER JOINT

Straight joint for 0.6/1 kV extruded cables.

For **COPPER** cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	1x	2x	3x	4x		
RUBBER JOINT 4 RUBBERJOINT4	1,5 - 25	1,5 - 4	1,5 - 4	1,5 - 4	10 - 18	160 x 45
RUBBER JOINT 10 RUBBERJOINT10	2,5 - 50	1,5 - 10	1,5 - 10	1,5 - 10 *	8 - 16	180 x 50
RUBBER JOINT 25 RUBBERJOINT25	16 - 150	4 - 25	4 - 25	2,5 - 25	8 - 32	215 x 55
RUBBER JOINT 35 RUBBERJOINT35	16 - 185	16 - 35	16 - 35	16 - 35	12 - 33	232 x 70
RUBBER JOINT 50 RUBBERJOINT50	50 - 300	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
RUBBER JOINT 95 RUBBERJOINT95	120 - 400	25 - 95	25 - 95	25 - 95	15 - 42	330 x 75
RUBBER JOINT 120 RUBBERJOINT120	240 - 500	70 - 120	70 - 120	50 - 120	25 - 50	365 x 95
RUBBER JOINT 240 RUBBERJOINT240	400 - 1000	120 - 300	120 - 240	120 - 240	30 - 75	510 x 120
RUBBER JOINT 300 RUBBERJOINT300	630 - 2000	240 - 400	240 - 300	240 - 300	41 - 78	760 x 180



* Rubber Joint 10 suggested for cable diameters smaller than 16 mm.




RUBBER JOINT Y

Branch joint for 0.6/1 kV extruded cables.

For **COPPER** cables

PRODUCT	Item
RUBBER JOINT Y6	RUBBERJOINTY6
RUBBER JOINT Y25	RUBBERJOINTY25
RUBBER JOINT Y95	RUBBERJOINTY95
RUBBER JOINT Y240*	RUBBERJOINTY240

T	B	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	T	B	Dimension (mm)	
		1x	2x	3x	4x					
4 - 50	4 - 50	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90
50 - 150	50 - 150	10 - 25	10 - 25	6 - 25	6 - 16	6 - 25	6 - 10	8 - 32	8 - 32	220 x 105
120 - 400	95 - 240	25 - 95	16 - 50	25 - 95	16 - 50	25 - 95	10 - 50	15 - 42	8 - 32	315 x 115
240 - 630	240 - 630	95 - 240	50 - 240	95 - 240	50 - 240	95 - 240	50 - 240	65 max		600 x 285



* also for aluminium cables. **T**: Through - **B**: Branch

RAY CAST

Straight or branch joint with two-component epoxy resin insulation for 0.6/1 kV cables.

Straight or branch joints for 0.6/1 kV extruded cables: easily installed, composed of two anti-fracture plastic shells, to be filled with two-component epoxy resin such as Rayresin. For installation in traps, channels or directly underground.

RAYCAST L

Straight joint.



For COPPER cables PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	1x	2x	3x	4x		
RAYCAST L10 100001-000	2,5 - 50	1,5 - 10	1,5 - 10	1,5 - 10 *	8 - 16	180 x 50
RAYCAST L16/25 100002-000	16 - 150	4 - 25	4 - 25	2,5 - 25	8 - 32	215 x 55
RAYCAST L35 100035-001	16 - 185	16 - 35	16 - 35	16 - 35	12 - 33	232 x 70
RAYCAST L50 100500-000	50 - 300	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
RAYCAST L95 100095-000	120 - 400	25 - 95	25 - 95	25 - 95	15 - 42	330 x 75
RAYCAST L120 100120-000	240 - 500	70 - 120	70 - 120	50 - 120	25 - 50	365 x 95
RAYCAST L240 100240-000	400 - 1000	120 - 300	120 - 240	120 - 240	30 - 75	510 x 120
For ALUMINIUM cables PRODUCT	1x	2x	3x	4x	(mm)	(mm)
	16 - 150	16 - 25	16 - 25	16 - 25	14 - 34	266 x 72
RAYCAST L120 100120-000	185 - 400	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
RAYCAST L240 100240-000	400 - 630	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120

* Raycast L10 is suggested for cable diameters not exceeding 16 mm.



RAYCAST D

Branch joint.

For COPPER cables PRODUCT	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm) T	max cables Ø (mm) B	Dimension (mm)	
	1x		2x		3x		4x					
	T	B		T	B		T	B		T	B	
RAYCAST D6 100006-000	4 - 50	4 - 50	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90	
RAYCAST D16/D25 100016-000	50 - 150	50 - 150	10 - 25	10 - 25	6 - 25	6 - 16	6 - 25	6 - 10	8 - 32	8 - 32	220 x 105	
RAYCAST D95 100095-001	120 - 400	95 - 240	25 - 95	16 - 50	25 - 95	16 - 50	25 - 95	10 - 50	15 - 42	8 - 32	315 x 115	




T: Through - **B**: Branch



RAYCAST L-S

Screened joint.




PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	1x	2x	3x	4x		
RAYCAST L10-S 100001-00S	2,5 - 50	1,5 - 10	1,5 - 6	1,5 - 6	8 - 16	180 x 50
RAYCAST L25-S 100025-00S	16 - 120	4 - 25	4 - 16	2,5 - 16	8 - 32	215 x 55
RAYCAST L35-S 100035-00S	16 - 185	16 - 35	16 - 25	16 - 25	12 - 33	232 x 70
RAYCAST L50-S 100050-00S	50 - 240	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
RAYCAST L120-S 100120-00S	240 - 500	70 - 120	70 - 120	50 - 95	25 - 50	365 x 95
RAYCAST L240-S 100240-055	400 - 1000	120 - 300	120 - 185	120 - 185	30 - 75	510 x 120

PRODUCT / Item	1x	2x	3x	4x	(mm)	(mm)
	RAYCAST L50-S 100050-00S	16 - 150	16 - 25	16 - 25	16 - 25	14 - 34
RAYCAST L120-S 100120-00S	185 - 400	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
RAYCAST L240-S 100240-055	400 - 630	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120



RAYCAST D-S

Screened joint.



For COPPER cables

PRODUCT	Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)		
		T	B	T	B	T	B	T	B
RAYCAST D6-S 100006-00S		4 - 35	4 - 35	4 - 10	4 - 10	2,5 - 6	1,5 - 6	2,5 - 6	2,5 - 6
RAYCAST D25-S 100017-00S		35 - 120	35 - 120	10 - 25	10 - 25	6 - 16	6 - 16	6 - 16	6 - 10
RAYCAST D95-S 100950-00S		95 - 300	70 - 150	25 - 95	16 - 50	16 - 70	16 - 35	16 - 50	10 - 35

T : Through - B : Branch

RAYCAST L-ARM

Joint for tape, wire or plate armoured cables.



For **COPPER** cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm²)			max cables Ø (mm)	Dimension (mm)
	2x	3x	4x		
RAYCAST L10-ARM 100001-001	1,5 - 10	1,5 - 6	1,5 - 6	8 - 16	180 x 50
RAYCAST L25-ARM 100002-002	4 - 25	4 - 16	2,5 - 16	8 - 32	215 x 55
RAYCAST L35-ARM 100035-ARM	16 - 35	16 - 25	16 - 25	12 - 33	232 x 70
RAYCAST L50-ARM 100003-001	16 - 50	16 - 50	16 - 50	14 - 34	266 x 72
RAYCAST L120-ARM 100120-002	70 - 120	70 - 120	50 - 95	25 - 50	365 x 95
RAYCAST L240-ARM 100240-LARM	120 - 300	120 - 185	120 - 185	30 - 75	510 x 120

For ALUMINIUM cables	2x	3x	4x	(mm)	(mm)
RAYCAST L50-ARM 100003-001	16 - 25	16 - 25	16 - 25	14 - 34	266 x 72
RAYCAST L120-ARM 100120-002	25 - 95	25 - 95	25 - 95	25 - 50	365 x 95
RAYCAST L240-ARM 100240-LARM	95 - 185	95 - 185	95 - 185	30 - 75	510 x 120

RAYCAST D-ARM

Joint for tape, wire or plate armoured cables.



For **COPPER** cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm²)			max cables Ø (mm)	(mm)	
	T	B	T	B	T	B
RAYCAST D6-ARM-F 100006-002	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6
RAYCAST D16-ARM-F 100016-002	10 - 25	10 - 25	6 - 16	6 - 16	6 - 16	6 - 10
RAYCAST D95-ARM-F 100095-003	25 - 70	16 - 50	25 - 70	16 - 35	25 - 50	10 - 35


For TAPE OR PLATE armoured

PRODUCT / Item	2x			3x			4x			(mm)	(mm)
	T	B	T	B	T	B	T	B	T		
RAYCAST D6-ARM 100006-001	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	8 - 27	180 x 90	
RAYCAST D16-ARM 100016-001	10 - 25	10 - 25	6 - 16	6 - 16	6 - 16	6 - 10	8 - 32	8 - 32	8 - 32	220 x 105	
RAYCAST D95-ARM 100095-004	25 - 70	16 - 50	25 - 70	16 - 35	25 - 50	10 - 35	15 - 42	8 - 32	8 - 32	315 x 115	

T: Through - B: Branch

RAYCAST LPS / DPS

Joint for very deep submersible pumps.

For **COPPER** cables

PRODUCT	Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	(mm)
		1x	2x	3x	4x		
RAYCAST LPS10	100010-LPS	2,5 - 50	1,5 - 10	1,5 - 10	1,5 - 10	8 - 16	180 x 50
RAYCAST LPS25	100025-LPS	16 - 150	4 - 25	4 - 25	2,5 - 25	8 - 32	215 x 55
RAYCAST LPS95	100095-LPS	120 - 400	25 - 95	25 - 95	25 - 95	15 - 42	330 x 75
RAYCAST LPS240	100240-LPS	400 - 1000	120 - 300	120 - 240	120 - 240	30 - 75	510 x 120

For **COPPER** cables

PRODUCT	Item	Cable formation and conductor cross sections (n° x mm ²)								Ø max cables (mm)	(mm)	
		T	B	T	B	T	B	T	B			
RAYCAST DPS6	100006-DPS	4 - 50	4 - 50	4 - 10	4 - 10	2,5 - 6	2,5 - 6	2,5 - 6	2,5 - 6	8 - 27	8 - 27	180 x 90
RAYCAST DPS25	100025-DPS	50 - 150	50 - 150	10 - 25	10 - 25	6 - 25	6 - 16	6 - 16	6 - 10	8 - 32	8 - 32	220 x 105
RAYCAST DPS95	100095-DPS	120 - 400	95 - 240	25 - 95	16 - 50	25 - 95	16 - 50	25 - 95	10 - 50	15 - 42	8 - 32	315 x 115

T: Through - B: Branch

RAYCAST SL / SD

Joint for signalling and control.

PRODUCT	Item	Conductor (mm ²)	Cable formation (n° conductors)										max cables Ø (mm)	(mm)	
			5x	7x	10x	12x	16x	19x	24x	40x	75x	100x	250x		
RAYCAST SL11	100011-OSL	1,5	•	•	•	•	•	•						8 - 16	180 x 50
		2,5	•	•	•	•									
RAYCAST SL12	100012-OSL	1,5		•	•	•	•	•	•					8 - 32	215 x 55
		2,5		•	•	•	•	•	•						
RAYCAST SL13	100013-OSL	1,5			•	•	•	•	•	•				14 - 34	266 x 72
		2,5			•	•	•	•	•	•					
RAYCAST SL14	100014-OSL	1,5				•	•	•	•					15 - 42	330 x 75
		2,5				•	•	•	•						
RAYCAST SL15	100015-OSL	1,5					•	•	•	•				25 - 50	365 x 95
		2,5					•	•	•	•					
RAYCAST SL16	100016-OSL	1,5						•	•	•	•			30 - 75	510 x 120
		2,5						•	•	•	•				

PRODUCT	Item	Conductor (mm ²)	Cable formation (n° conductors)									max cables Ø (mm)	T (mm)	B (mm)
			5x	7x	10x	12x	16x	19x	24x	40x	75x			
RAYCAST SD1	100001-OSD	1,5	•	•	•	•	•	•	•			8 - 27	8 - 27	180 x 90
		2,5	•	•	•	•	•	•	•					
RAYCAST SD2	100002-OSD	1,5			•	•	•	•	•			8 - 32	8 - 32	220 x 105
		2,5			•	•	•	•	•					
RAYCAST SD3	100003-OSD	1,5				•	•	•	•	•	•	15 - 42	8 - 32	315 x 115
		2,5				•	•	•	•	•	•			

T: Through - B: Branch

RAYCAST TL AND TSL

Straight joint for telephone cable.

UNSCREENED		SCREENED		N° pairs per conductor cross sections (n° x mm ²)	max cables Ø (mm)	Dimension (mm)
PRODUCT	Item	PRODUCT	Item			
RAYCAST TL16	100016-OTL	RAYCAST TSL16	100016-TSL	1 - 16 x 0,5 - 0,6	8 - 16	180 x 50
RAYCAST TL25	100025-OTL	RAYCAST TSL25	100025-TSL	16 - 25 x 0,5 - 0,6	8 - 32	215 x 55
RAYCAST TL35	100035-OTL	RAYCAST TSL35	100035-TSL	25 - 35 x 0,5 - 0,6	12 - 33	266 x 72
RAYCAST TL40	100040-OTL	RAYCAST TSL40	100040-TSL	35 - 40 x 0,5 - 0,6	15 - 42	330 x 75
RAYCAST TL64	100064-OTL	RAYCAST TSL64	100064-TSL	40 - 64 x 0,5 - 0,6	25 - 50	365 x 95
RAYCAST TL500	100500-OTL	RAYCAST TSL500	100500-TSL	60 - 500 x 0,5 - 0,6	30 - 75	510 x 120

RAYCAST SYSTEM PLUS L

Straight joint + Five-core spacer + Screw connectors.

For COPPER cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)				max cables Ø (mm)	Dimension (mm)
	2x	3x	4x	5x		
RAYCAST SP L6 RAYCASTSPL6	1,5 - 6	1,5 - 6	1,5 - 6	1,5 - 6	8 - 16	180 x 50
RAYCAST SP L16 RAYCASTSPL16	4 - 16	4 - 16	4 - 16	4 - 16	8 - 32	215 x 55
RAYCAST SP L25 RAYCASTSPL25	4 - 25	4 - 25	4 - 25	4 - 25	8 - 32	215 x 65




RAYCAST SYSTEM PLUS Y

Y Branch joint + Five-core spacer + Screw connectors.

For COPPER cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)								max cables Ø (mm)	(mm)
	2x		3x		4x		5x			
T	B	T	B	T	B	T	B			
RAYCAST SP D6 RAYCASTSPD6	1,5-6	1,5-4	1,5-6	1,5-4	1,5-6	1,5-4	1,5-6	1,5-4	T 8-27 B 8-27	180 x 90
RAYCAST SP D16 RAYCASTSPD16	4-16	1,5-4	4-16	1,5-4	4-16	1,5-4	4-16	1,5-4	T 8-32 B 8-32	220 x 105

T: Through - B: Branch



RAYCAST SYSTEM PLUS T

T Branch joint + Four-core spacer + Screw connectors.

For COPPER cables

PRODUCT / Item	Cable formation and conductor cross sections (n° x mm ²)						max cables Ø (mm)	(mm)
	2x		3x		4x			
T	B	T	B	T	B			
RAYCAST SP T 35 RAYCASTSPT35	6 - 35	1,5 - 10	6 - 35	1,5 - 10	6 - 35	1,5 - 10	T 22-42 B 22-42	305 x 155

T: Through - B: Branch




RAYCAST

SYSTEM FAST RP

Straight joint + Shear bolt connectors.

PRODUCT / Item

PRODUCT / Item	Cable formation from 2x a 4x (n° x mm ²)		max cables Ø (mm)	Dimension (mm)
	2x	4x		
RAYCAST L 35- RP/16 RAYCASTL35RP16	1,5 - 16		12 - 33	232 x 70
RAYCAST L 35- RP/35 RAYCASTL35RP35	10 - 35		12 - 33	232 x 70
RAYCAST L 50- RP/50 RAYCASTL50RP50	25 - 50		14 - 34	266 x 72
RAYCAST L 120- RP/120 RAYCASTL120RP120	35 - 120		25 - 50	365 x 95
RAYCAST L 240- RP/150 RAYCASTL240RP150	35 - 150		30 - 75	510 x 120



HEAT-SHRINK



Straight or branch heat-shrinkable joints for extruded insulation cables up to a 1 kV.

Electrical performance:

- CEI EN 50393 with connectors complying with EN 61238-1
- Class 2 in accordance with CEI 64-8.

 **Working temperature:** 90°


 **Installation temperature:** -15°C / +45°C



GDL


Joint for single core cables including concentric neutral.

PRODUCT / Item	Conductor cross section mm ² from to		Dimension L (mm)
GDL 92 A1 224578-TEC	4	10	300
GDL 92 A2 945252-TEC	16	150	300
GDL 92 A3 935251-000	185	400	300
GDL 92 PA 210254-TEC	10	50	300

**GLV**

Joint for multi core cables (also for submersible pumps).

PRODUCT / Item	Conductor cross section mm ² from to		Number of phases	Dimension L (mm)	D (mm)
GLV 0306 254656-TEC	1,5	6	3	250	18
GLV 0316 224477-TEC	10	16	3	400	37
GLV 0335 554268-TEC	25	35	3	550	43
GLV 0370 457896-TEC	50	70	3	650	52
GLV 3150 789992-000	95	150	3	800	65
GLV 3300 789994-000	185	300	3	900	82
GLV 0406 336598-TEC	1,5	6	4	250	20
GLV 0416 789890-000	10	16	4	400	40
GLV 0435 789891-000	25	35	4	650	45
GLV 0470 234477-TEC	50	70	4	650	54
GLV 4150 482979-000	95	150	4	800	67
GLV 4300 609695-000	185	300	4	900	84
GLV 2,5 - CP 411124-TEC	2,5 complete with connectors		4	300	15




For both copper and aluminium cables. For aerial, underground, submerged installation.


GLV-N

Joint for multi core cables with concentric neutral.

PRODUCT / Item	Conductor cross section mm ² from to		Number of phases	Dimension L (mm)	D (mm)
GLV 0306 - N 788459-000	1,5	6	3	250	18
GLV 0316 - N 788429-000	10	16	3	400	37
GLV 0335 - N 788460-000	25	35	3	550	43
GLV 0370 - N 788461-000	50	70	3	650	52
GLV 3150 - N 788462-000	95	150	3	800	65
GLV 3300 - N 210054-TEC	185	300	3	900	82
GLV 0406 - N 789995-000	1,5	6	4	250	20
GLV 0416 - N 789996-000	10	16	4	400	40
GLV 0435 - N 789997-000	25	35	4	650	45
GLV 0470 - N 789998-000	50	70	4	650	54
GLV 4150 - N 405718-000	95	150	4	800	67
GLV 4300 - N 788463-000	185	300	4	900	84




These kits include components for the phase insulation, metallic braiding to replace the neutral and external self-sealing heat-shrinkable tube.

**GLV-ARM**


Joint for armoured multi core cables.

For armoured tape cables	Conductor cross section (mm ²) from	to	Dimension L (mm)	D (mm)
PRODUCT / Item				
GLV 0406-ARM	788969-000	1,5	6	300 25
GLV 0416-ARM	307689-000	6	16	400 40
GLV 0450-ARM	630855-000	25	50	800 60
GLV 4150-ARM	378703-000	70	150	1000 100
GLV 4300-ARM	152410-000	185	300	1000 120


**BOPA**

Joint for MV cables for public lighting.

PRODUCT / Item	Operating voltage kV	Number of phases	Section (mm ²)	Dimension L (mm)	D (mm)
BOPA 3 BOPA3-TEC	3	1	1x10	300	50
BOPA 4 BOPA4-TEC	3	2	2x10	450	60
BOPA 5 BOPA5-TEC	3	3	3x10	450	70
BOPA 3/2 BOPA3/2-TEC	3,6	1 + concentric neutral	1 x 6 + 6 concentric	700	35
BOPA 4/T transition 784472-TEC	3	2	2,5 - 10 paper / 10 - 50 extruded	750	40

**DJ**

LV branch joint.



PRODUCT / Item	Single core cables cross section (mm ²)		Multi core cables cross section (mm ²)		Dimension L (mm)	D (mm)
	Through	Branch	Through	Branch		
DJ01 416127-000	1 x 4 - 50	1 x 2,5 - 50	4 x 1,5 - 10	2 x 1,5	200	25
DJ02 396633-000	1 x 50 - 120	1 x 6 - 120	4 x 16 - 25 2 single core cables 1 x 6 - 50	2 x 1,5 1 two core cable 2 x 2,5	250	40
DJ03 396634-000	1 x 150 - 300	1 x 6 - 300	4 x 25 - 3,5 x 50	4 x 2,5 - 25	400	70

**GLV SYSTEM FAST RP**

Straight joint + Shear bolt connectors.

PRODUCT / Item	Cable formation 4x (n° x mm ²)	Dimension L x D (mm)
GLV 0435- RP/16 GLV0435RP16	6 - 16	650 x 50
GLV 0470- RP/35 GLV0470RP35	25 - 35	650 x 70
GLV 0470- RP/50 GLV0470RP50	25 - 50	650 x 75
GLV 4150- RP/150 GLV4150RP150	50 - 150	800 x 80

GLV F/R - GMP F/R

Joint for flame resistant cables (0,6/1 kV).



For NAVAL TYPE POWER cables

UNARMOURED	Cable formation (n° x mm²)	L (mm)	ARMoured	Cable formation (n° x mm²)	L (mm)
PRODUCT / Item			PRODUCT / Item		
GLV 4004-F/R GLV4004-F/R	4 x 1,5 - 4	300	GLV 4004-ARM-F/R GLV4004-ARM-F/R	4 x 1,5 - 4	400
GLV 4016-F/R GLV4016-F/R	4 x 6 - 16	300	GLV 4016-ARM-F/R GLV4016-ARM-F/R	4 x 6 - 16	400
GLV 4050-F/R GLV4050-F/R	4 x 25 - 50	400	GLV 4050-ARM-F/R GLV4050-ARM-F/R	4 x 25 - 50	500
GLV 4150-F/R GLV4150-F/R	4 x 70 - 150	500	GLV 4150-ARM-F/R GLV4150-ARM-F/R	4 x 70 - 150	750

For NAVAL TYPE signalling and control cables


UNARMOURED	Cable formation (n° x mm²)	L (mm)	ARMoured	Cable formation (n° x mm²)	L (mm)
PRODUCT / Item			PRODUCT / Item		
GMP 007-F/R GMP007-F/R	4 - 7 x 1,5 - 2,5	300	GMP 007-ARM-F/R GMP007-ARM-F/R	4 - 7 x 1,5 - 2,5	300
GMP 014-F/R GMP014-F/R	10 - 14 x 1,5 - 2,5	300	GMP 014-ARM-F/R GMP014-ARM-F/R	10 - 14 x 1,5 - 2,5	300
GMP 030-F/R GMP030-F/R	16 - 30 x 1,5 - 2,5	400	GMP 030-ARM-F/R GMP030-ARM-F/R	16 - 30 x 1,5 - 2,5	400

For UNDERGROUND POWER cables

UNARMOURED	Cable formation (n° x mm²)	L (mm)	ARMoured	Cable formation (n° x mm²)	L (mm)
PRODUCT / Item			PRODUCT / Item		
GLV 4006-F/R-G7 GLV4006-F/R-G7	4 x 1,5 - 6	300	GLV 4006-ARM-F/R-G7 GLV4006-ARM-F/R-G7	4 x 1,5 - 6	400
GLV 4016-F/R-G7 GLV4016-F/R-G7	4 x 6 - 16	300	GLV 4016-ARM-F/R-G7 GLV4016-ARM-F/R-G7	4 x 6 - 16	400
GLV 4050-F/R-G7 GLV4050-F/R-G7	4 x 25 - 50	400	GLV 4050-ARM-F/R-G7 GLV4050-ARM-F/R-G7	4 x 25 - 50	500
GLV 4150-F/R-G7 GLV4150-F/R-G7	4 x 70 - 150	500	GLV 4150-ARM-F/R-G7 GLV4150-ARM-F/R-G7	4 x 70 - 150	750

For UNDERGROUND signalling and control cables

UNARMOURED	Cable formation (n° x mm²)	L (mm)	ARMoured	Cable formation (n° x mm²)	L (mm)
PRODUCT / Item			PRODUCT / Item		
GMP 014-F/R-G7 GMP014-F/R-G7	Up to 14 x 1,5 - 2,5	300	GMP 014-ARM-F/R-G7 GMP014-ARM-F/R-G7	Up to 14 x 1,5 - 2,5	400
GMP 019-F/R-G7 GMP019-F/R-G7	Up to 19 x 1,5 - 2,5	400	GMP 019-ARM-F/R-G7 GMP019-ARM-F/R-G7	Up to 19 x 1,5 - 2,5	500

**DJ F/R**

Branch joint for flame resistant cables (0,6/1 kV).

For POWER cables

UNARMOURED**PRODUCT / Item**
DJ 4016 - F/R
DJ4016FR
ARMoured**PRODUCT / Item**
DJ 4016 - ARM-F/R
DJ4016-ARM-FR
Cable formation (n° x mm²)

Through

Branch


L

(mm)

x 1,5 - 16

x 1,5 - 16

300

**GMP**Jointing kits for multi conductor cables
for signalling, command and control.**NON ARMoured cable****PRODUCT / Item**

	Nº of conductors from	to	Section mm ² from	to	External Ø of cable min (mm)	max (mm)
GMP 007	786768-000	4	7	1,0	2,5	8 19
GMP 014	666635-TEC	8	14	1,0	2,5	12 22
GMP 021	786272-000	15	21	1,0	2,5	15 27
GMP 040	786684-000	22	40	1,0	2,5	20 35
GMP 075	786683-000	41	75	1,0	2,5	26 44
GMP 100	786688-000	76	100	1,0	2,5	26 60

ARMoured cable**PRODUCT / Item**

	Nº of conductors from	to	Section mm ² from	to	External Ø of cable min (mm)	max (mm)
GMP 007-A	786686-000	4	7	1,0	2,5	14 23
GMP 014-A	786687-000	8	14	1,0	2,5	15 26
GMP 021-A	786785-000	15	21	1,0	2,5	24 35
GMP 040-A	786356-000	22	40	1,0	2,5	30 45
GMP 075-A	786689-000	41	75	1,0	2,5	39 55

GMCJointing kits for multi pair cables
for communication, command and control.**NON ARMoured cable****PRODUCT / Item**

	Nº of pairs from	to	Section mm ² from	to	External Ø of cable min (mm)	max (mm)
GMC 010	939629-000	5	10	2 x 0,6	2 x 1,0	9 14
GMC 020	786828-000	11	20	2 x 0,6	2 x 1,0	13 20
GMC 030	946619-000	21	30	2 x 0,6	2 x 1,0	16 24
GMC 050	934676-000	31	50	2 x 0,6	2 x 1,0	22 29
GMC 100	156732-000	51	100	2 x 0,6	2 x 1,0	30 40

ARMoured cable**PRODUCT / Item**

	Nº of pairs from	to	Section mm ² from	to	External Ø of cable min (mm)	max (mm)
GMC 004-A	802965-000	1	4	2 x 0,6	2 x 1,0	15 23
GMC 007-A	786769-000	5	7	2 x 0,6	2 x 1,0	15 26
GMC 019-A	803162-000	8	19	2 x 0,6	2 x 1,0	24 35
GMC 037-A	786412-000	20	37	2 x 0,6	2 x 1,0	30 45
GMC 061-A	786355-000	38	61	2 x 0,6	2 x 1,0	39 55


TERMINATIONS HEAT-SHRINK

TLV

Terminations for armoured and non armoured extruded cables up to 1 kV.

NON ARMoured extruded cables	
PRODUCT / Item	
TLV 0216	946613-000
TLV 0316	496973-000
TLV 0416	288775-000
TLV 0250	101526-000
TLV 0350	786134-000
TLV 0450	786200-000
TLV 3150	786220-000
TLV 4150	597107-000
TLV 3300	208159-000
TLV 4300	063097-000

Extruded cables with WIRE ARMOUR		Conductor section mm ²		Number of phases
from	to			
TLV 0216 - AF	106391-000	4	16	2
TLV 0316 - AF	178316-000	4	16	3
TLV 0416 - AF	121775-000	4	16	4
TLV 0250 - AF	024865-000	25	50	2
TLV 0350 - AF	179335-000	25	50	3
TLV 0450 - AF	868777-000	25	50	4
TLV 3150 - AF	181196-000	70	150	3
TLV 4150 - AF	223409-000	70	150	4
TLV 3300 - AF	181097-000	185	300	3
TLV 4300 - AF	803719-000	185	300	4
TLV 4500 - AF	915556-000		500	4




Include sheath to cover phases, sealing of the point of divergence of phases and sealing between phase and cable terminal.

TLV 500

Terminations for concentric neutral extruded cables up to 1 kV.

PRODUCT / Item	Conductor section mm ²	Number of phases
from	to	
TLV 0116 - 500	181198-000	4
TLV 0216 - 500	181198-001	16
TLV 0316 - 500	816659-000	4
TLV 0150 - 500	181198-002	16
TLV 0250 - 500	181198-003	25
TLV 0350 - 500	828617-000	50
TLV 2150 - 500	179925-000	25
TLV 3150 - 500	181198-004	50
TLV 2300 - 500	181198-005	70
TLV 3300 - 500	909765-000	150



Include sheath to cover the concentric conductor.



**LOW VOLTAGE
OTHERS**

**HEAT-SHRINK SHEATHS
INSULATION TAPES
CABLE PULLERS
FIRE STOP BARRIERS
SPECIALS**





Operating temperature: -55°C / +125°C

Tensile resistance	10,4 Min
Elongation	200 % Min
Tensile resistance after ageing	7,3 Min
Elongation after ageing	100 % Min
Dielectric strength	20 kV/mm
Flammability	VW1*
Minimum shrinkage temperature	110°C

* except transparent sheath.



THIN-WALL SHEATHS

Flexible heat-shrink modified polyolefin sheaths, cross linked by means of radiation. Longitudinal shortening up to 15%. Suitable for insulation and covering of conductors and their connections, bars. etc. Replace self-adhesive, self-amalgamating insulating tapes.

- Black
- Red
- Blue
- Yellow
- White
- ① Transparent
- Yellow Green



D = min. Ø before shrinkage

d = max. Ø after free shrinkage

S = min. rated thickness after free shrinkage (+/- 20%)

LST-TEC

Heat-shrink sheaths in dispensers for commercial use.

PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Lenght (m)
LST-TEC 1,6 *	6635996003	●	1,6	0,8	0,50	10
LST-TEC 2,4 *	7284836003	●	2,4	1,2	0,55	10
LST-TEC 3,2 *	0316676003	●	3,2	1,6	0,55	10
LST-TEC 4,8 *	3876656003	●	4,8	2,4	0,55	9
LST-TEC 6,4 *	3363736003	●	6,4	3,2	0,65	8
LST-TEC 9,5 *	0915756003	●	9,5	4,8	0,65	6
LST-TEC 12,7 *	1963796004	●	12,7	6,4	0,65	6
LST-TEC 19,0 *	9601076004	●	19,0	9,5	0,80	5
LST-TEC 25,4 *	2348536003	●	25,4	12,7	0,95	3
LST-TEC-GV 3/1,5	5038106035	●	3	1,5	0,51	7
LST-TEC-GV 4,8/2,4	5038815824	●	4,8	2,4	0,55	10
LST-TEC-GV 6/3	5038606049	●	6	3	0,58	5
LST-TEC-GV 10/5	5038816019	●	10	5	0,64	4
LST-TEC-GV 12/6	5038812764	●	12	6	0,65	7
LST-TEC-GV 19/9	5038496027	●	19	9	0,74	3
LST-TEC-GV 26/13	5038186026	●	26	16	0,89	2,5

* Also available in blue colour ● in red colour ● - See codes on page 120



RAY ROLL

Heat-shrink sheaths in dispensers for industrial use.

PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Lenght (m)
RAY ROLL 1,6	RAYROLL-1.6	●	1,6	0,8	0,50	20
RAY ROLL 2,4	RAYROLL-2.4	●	2,4	1,2	0,55	20
RAY ROLL 3,2	RAYROLL-3.2	●	3,2	1,6	0,55	10
RAY ROLL 4,8	RAYROLL-4.8	●	4,8	2,4	0,55	10
RAY ROLL 6,4	RAYROLL-6.4	●	6,4	3,2	0,65	10
RAY ROLL 9,5	RAYROLL-9.5	●	9,5	4,8	0,65	10
RAY ROLL 12,7	RAYROLL-12.7	●	12,7	6,4	0,65	10
RAY ROLL 19,0	RAYROLL-19.0	●	19,0	9,5	0,80	5
RAY ROLL 25,4	RAYROLL-25.4	●	25,4	12,7	0,95	5

MAXI ROLL

Heat-shrink sheaths in maxi dispensers for industrial use.


PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Spool (m)
MAXI ROLL 1,6	MAXIROLL-1.6	●	1,6	0,8	0,50	300
MAXI ROLL 2,4	MAXIROLL-2.4	●	2,4	1,2	0,55	300
MAXI ROLL 3,2	MAXIROLL-3.2	●	3,2	1,6	0,55	300
MAXI ROLL 4,8	MAXIROLL-4.8	●	4,8	2,4	0,55	150
MAXI ROLL 6,4	MAXIROLL-6.4	●	6,4	3,2	0,65	75
MAXI ROLL 9,5	MAXIROLL-9.5	●	9,5	4,8	0,65	150
MAXI ROLL 12,7	MAXIROLL-12.7	●	12,7	6,4	0,65	150
MAXI ROLL 19,0	MAXIROLL-19.0	●	19,0	9,5	0,80	75
MAXI ROLL 25,4	MAXIROLL-25.4	●	25,4	12,7	0,95	60



CGP-TEC

Heat-shrink sheaths for commercial use.

PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Spool (m)
CGP-TEC 1,2/0,6	5069794007	●	1,2	0,6	0,45	600
CGP-TEC 1,6/0,8	5069804009	●	1,6	0,8	0,45	300
CGP-TEC 2,4/1,2	5069814012	●	2,4	1,2	0,50	300
CGP-TEC 3,2/1,6	5069824023	●	3,2	1,6	0,50	300
CGP-TEC 4,8/2,4	5069834023	●	4,8	2,4	0,50	150
CGP-TEC 6,4/3,2	5069844021	●	6,4	3,2	0,65	75
CGP-TEC 9,5/4,8	5069854021	●	9,5	4,8	0,65	150
CGP-TEC 12,7/6,4	5069864018	●	12,7	6,4	0,65	150
CGP-TEC 19/9,5	5069874011	●	19,0	9,5	0,75	75
CGP-TEC 25,4/12,7	5069884015	●	25,4	12,7	0,90	60
CGP-TEC 38/19	5069894005	●	38,0	19,0	1,00	60
CGP-TEC 51/26	5069904003	●	51,0	26	1,15	30
CGP-TEC 76/38	5067104003	●	76,0	38,0	1,27	15
CGP-TEC 102/51	5067164001	●	102,0	51,0	1,40	15




Also available in Red, Blue, Yellow, White, Transparent colours ● ○ □ ⊖ ⊕ ⊖ ⊖ - See codes on page 116

DCP-TEC

Heat-shrink sheaths suitable for coating grounding cables.

PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Spool (m)
DCP-TEC 3/1,5	5038104002	●	3,0	1,5	0,51	300
DCP-TEC 6/3	5038604008	●	6,0	3,0	0,58	75
DCP-TEC 10/5	5038814001	●	10,0	5,0	0,64	75
DCP-TEC 12/6	5038114002	●	12,0	6,0	0,64	75
DCP-TEC 19/9	5038494001	●	19,0	9,0	0,74	75
DCP-TEC 26/13	5038184001	●	26,0	13,0	0,89	30
DCP-TEC 38/19	5673904001	●	38,0	19,0	1,00	60





Operating temperature: -55°C / +125°C

Tensile resistance	10,4 Min
Elongation	200 % Min
Tensile resistance after ageing	7,3 Min
Elongation after ageing	100 % Min
Dielectric strength	20 kV/mm
Flammability	VW1*
Minimum shrinkage temperature	110°C

* except transparent sheath.

SHEATHS IN BARS

Flexible heat-shrink modified polyolefin sheaths, cross linked by means of radiation. Longitudinal shortening up to 15%. Suitable for insulation and covering of conductors and their connections, bars. etc. Replace self-adhesive, self-amalgamating insulating tapes.

- Black
- Red
- Blue
- Yellow
- White
- Transparent
- Yellow Green



D = min. Ø before shrinkage
d = max. Ø. after free shrinkage
S = min. rated thickness after free shrinkage (+/- 20%)

Minimum shrinkage temperature: 125°C

Operating temperature: -55°C / +120°C



RDCT-B

Yellow green tube for general use in bars.

Shrinkage ratio 2:1

PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Bars (m)
RDCT-B 3/1,5	315002-BAR	○	3,0	1,5	0,51	1,2
RDCT-B 6/3	630045-BAR	○	6,0	3,0	0,58	1,2
RDCT-B 10/5	105004-BAR	○	10,0	5,0	0,64	1,2
RDCT-B 12/6	126040-BAR	○	12,0	6,0	0,64	1,2
RDCT-B 19/9	199550-BAR	○	19,0	9,0	0,74	1,2
RDCT-B 26/13	261345-BAR	○	26,0	13,0	0,89	1,2



RGPO-B

Tube for general use in bars.

Shrinkage ratio 2:1

PRODUCT	Item	Colour	D (mm)	d (mm)	S (mm)	Lenght (m)
RGPO-B 2,4/1,2	241200-BAR	●	2,4	1,2	0,50	1,2
RGPO-B 3,2/1,6	321600-BAR	●	3,2	1,6	0,50	1,2
RGPO-B 4,8/2,4	482400-BAR	●	4,8	2,4	0,50	1,2
RGPO-B 6,4/3,2	643200-BAR	●	6,4	3,2	0,65	1,2
RGPO-B 9,5/4,8	954800-BAR	●	9,5	4,8	0,65	1,2
RGPO-B 12,7/6,4	127640-BAR	●	12,7	6,4	0,65	1,2
RGPO-B 19/9,5	199500-BAR	●	19,0	9,5	0,75	1,2
RGPO-B 25,4/12,7	254120-BAR	●	25,4	12,7	0,90	1,2
RGPO-B 38/19	381900-BAR	●	38,0	19,0	1,00	1,2
RGPO-B 51/26	512600-BAR	●	51,0	26	1,15	1,2

Also available in Red, Blue, White, Transparent colours ● ○ ⊖ ⊕ ⊖ ⊕ ⊖ ⊕ - See codes on page 116

RAY-TUM

Sheaths in bars with adhesive.

Shrinkage ratio 3:1

PRODUCT	Item	Colour	D (mm)	d (mm)	S ₂ (mm)	S ₁ (mm)	Bars (m)
RAY-TUM-3/1-0	5504062059	●	3	1	1,00	0,5	1,2
RAY-TUM-6/2-0	5509092033	●	6	2	1,00	0,5	1,2
RAY-TUM-9/3-0	5507832055	●	9	3	1,40	0,6	1,2
RAY-TUM-12/4-0	5509102048	●	12	4	1,75	0,7	1,2
RAY-TUM-19/6-0	5067452035	●	19	6	2,25	0,8	1,2
RAY-TUM-24/8-0	5509112040	●	24	8	2,50	1,0	1,2
RAY-TUM-40/13-0	5509122053	●	40	13	2,50	1,0	1,2

Shrinkage ratio 4:1

PRODUCT	Item	Colour	(mm)	(mm)	(mm)	(mm)	(m)
RAY-TUM-4/1-0	550406260	●	4	1	1,00	0,5	1,2
RAY-TUM-8/2-0	5110554007	●	8	2	1,00	0,5	1,2
RAY-TUM-12/3-0	5634732003	●	12	3	1,40	0,6	1,2
RAY-TUM-16/4-0	8014642003	●	16	4	1,75	0,7	1,2
RAY-TUM-24/6-0	4177512003	●	24	6	2,25	0,8	1,2
RAY-TUM-32/8-0	4951522003	●	32	8	2,50	1,0	1,2
RAY-TUM-52/13-0	7024702003	●	52	13	2,50	1,0	1,2



D = min. Ø before shrinkage

d = max. Ø after free shrinkage

S1 = rated thickness as supplied

S2 = min. rated thickness after free shrinkage

Operating temperature: -55°C / +125°C

Tensile resistance	10,4 MPa min
Elongation	200 % min
Tensile resistance after ageing	7,3 MPa min
Elongation after ageing	100 % min
Thermal shock 4h a 250°C	No-drip No breaking
Flexibility at low temperature (1h a -30°C)	No breaking
Dielectric strength	Min 15,8 kV/mm
Resistance to fluids (lubricant oil, hydraulic fluid, diesel)	

THERMO MINI MIX

Pre-cut heat-shrink sheaths kit.

Ready-for-installation heat-shrink sheaths in a practical, multi-compartment box divided by diameter. Indispensable for Electrical systems, as a replacement for taped insulation, wiring of all types, switchboards, Hi-Fi, hobbies, DIY.

ADVANTAGES

- Wide range of diameters and colours.
- Always ready, quick application.
- Flexible.

BLACK COLOUR PRODUCT	MIXED COLOURS PRODUCT	Ø before and after shrinkage (mm)	Length of sheath (mm)	Pieces for box
THERMO MINI MIX-N THERMOMIN-N	THERMO MINI MIX-MC THERMOMIN-MC	1,0 / 0,5	97	60
		2,0 / 1,0	97	40
		3,0 / 1,5	97	30
		4,5 / 2,25	97	20
		6,0 / 3,0	97	10
		9,0 / 4,5	97	10





D = min. Ø before shrinkage

d = max. Ø after free shrinkage

S1 = rated thickness as supplied

S2 = min. rated thickness after
free shrinkage

Operating temperature: -55°C / +125°C

Tensile resistance	12 MPa min
Elongation	350% min
Tensile resistance after ageing	12 MPa
Elongation after ageing	300% min
Dielectric strength	12 kV/mm min
Minimum shrinkage temperature	125°C

HF Halogen Free

MEDIUM-WALL SHEATHS

Heat-shrink modified polyolefin sheaths, cross linked by means of radiation for insulation, sealing and LV component protection. It is in fact used for restoring insulation and for the outer covering of LV cables and wherever optimal mechanical characteristics are required for resistance to impact, abrasion, general weathering including UV radiation, or for use in under water environments. Used for the insulation of bars or naked LV connections with optimal mechanical resistance for sealing, especially if used with hot-melt adhesive, and for anti-corrosion protection. Also replaces self-adhesive and self-amalgamating tapes.

MTR PRODUCT	WITH ADHESIVE	WITHOUT ADHESIVE	Applications by Ø from (mm) to (mm)	D (mm)	d (mm)	S ₁ (mm)	S ₂ (mm)
	Item	Item					
MTR 10/3*	488809-000	854745-000	3,5	9,0	10	3	0,3
MTR 16/5*	925679-000	411365-000	5,5	14,0	16	5	0,3
MTR 25/8*	717783-000	082743-000	8,5	22,0	25	8	0,4
MTR 35/12*	064641-000	089407-000	13,0	32,0	35	12	0,4
MTR 50/16*	046911-000	738765-000	17,5	45,0	50	16	0,5
MTR 63/19*	223993-000	644113-000	21,0	57,0	63	19	0,6
MTR 75/22*	237137-000	605711-000	24,0	68,0	75	22	0,6
MTR 85/25*	727282-000	917867-000	28,0	77,0	85	25	0,6
MTR 95/29*	498559-000	355919-000	32,0	86,0	95	29	0,7
MTR 115/34*	827835-000	036893-000	37,0	104,0	115	34	0,7
MTR 140/42*	891939-000	149759-000	46,0	126,0	140	42	0,7
MTR 160/55*	474381-000	938745-000	55,0	144,0	160	55	0,7
MTR 180/60*	323497-000	827643-000	66,0	162,0	180	60	0,7

* Complete the item code adding the length (in mm), adhesive (/172) or without adhesive (/U).

MTN

Suitable for submersible pumps

WITH ADHESIVE PRODUCT	Item	Applications by Ø from (mm) to (mm)	D (mm)	d (mm)	S ₁ (mm)	S ₂ (mm)
MTN 10/3*	MTN1031000172	3,5	9,0	10	3	0,3
MTN 16/5*	MTN1651000172	5,5	14,0	16	5	0,3
MTN 25/8*	MTN2581000172	8,5	22,0	25	8	0,4
MTN 35/12*	MTN35121000172	13,0	32,0	35	12	0,4
MTN 50/16*	MTN50161000172	17,5	45,0	50	16	0,5
MTN 63/19*	MTN63191000172	21,0	57,0	63	19	0,6
MTN 75/22*	MTN75221000172	24,0	68,0	75	22	0,6
MTN 85/25*	MTN85251000172	28,0	77,0	85	25	0,6
MTN 95/29*	MTN95291000172	32,0	86,0	95	29	0,7
MTN 115/34*	MTN115341000172	37,0	104,0	115	34	0,7

* Complete the item code adding the length (in mm).

HEAVY-WALL SHEATHS

RAY-CSM heat-shrink tubular sheath is very thick and has been designed for uses requiring exceptional mechanical characteristics. Its ideal field of application is in underwater or directly underground environments, or where exceptional resistance to abrasion and impact is required, but also outstanding resistance to weathering, including UV radiation, for sealing, especially if used with hot-melt adhesive, and for anti-corrosion protection.

RAY-CSM

PRODUCT	Item	Applications by Ø from (mm) to (mm)		D (mm)	d (mm)	S ₁ (mm)	S ₂ (mm)
Ray-CSM 12/3*	672693-000	3,5	10	12	3	0,8	2,0
Ray-CSM 16/4*	542973-000	4,5	14	16	4	0,9	2,4
Ray-CSM 24/6*	050119-000	6,5	22	24	6	1,0	2,7
Ray-CSM 34/8*	453083-000	9	31	34	8	1,3	4,0
Ray-CSM 48/12*	582237-000	13	44	48	12	1,5	4,5
Ray-CSM 56/16*	898079-000	17,5	50	56	16	1,5	4,4
Ray-CSM 70/21*	862223-000	22	63	70	21	1,4	4,4
Ray-CSM 90/25*	862225-000	27	81	90	25	1,3	4,3
Ray-CSM 110/30*	934589-000	33	100	110	30	1,2	4,3
Ray-CSM 130/36*	833598-000	38	118	130	36	1,2	4,3
Ray-CSM 160/50*	430277-000	55	144	160	50	1,0	4,3
Ray-CSM 180/50*	237977-000	55	162	180	50	1,0	4,3

* Complete the item code adding the length (mm), adhesive (/172).

WRAP AROUND

Wrap around heat-shrink sheath for repairing plastic or metal cable sheaths. It combines the previously seen mechanical, protective and sealing properties of tubular junctions with easy of application and closing. Indispensable when cable cutting is not possible. Does not require pre-insertion, reducing the space necessary for its application.

RAY-RSM

PRODUCT	1000 Item	1500 Item	Ø Cable (mm) from	to	D (mm)	d (mm)
Ray-RSM 34/10*	406345-000	240699-000	12	21	34	10
Ray-RSM 53/13*	279727-000	505955-000	15	32	53	13
Ray-RSM 84/20*	953639-000	219483-000	23	50	84	20
Ray-RSM 107/29*	395359-000	546145-000	34	65	107	29
Ray-RSM 143/36*	002611-000	091525-000	42	86	143	36
Ray-RSM 198/55*	318575-000	247637-000	62	120	198	55
Ray-RSM 250/98*	595947-000	247698-000	111	150	250	98

* Complete the item code adding the length (mm) and adhesive (/232).




S₁ = rated thickness as supplied
S₂ = min. rated thickness after free shrinkage
D = min. Ø before shrinkage
d = max. Ø after free shrinkage

Operating temperature: -55°C / +125°C

Tensile resistance	12 MPa min
Elongation	350% min
Tensile resistance after ageing	12 MPa
Elongation after ageing	300% min
Dielectric strength	12 kV/mm min
Minimum shrinkage temperature	125°C

HF Halogen Free


WRAP AROUND



D = min. Ø before shrinkage
d = max. Ø after free shrinkage

Tensile resistance	17 MPa (min)
Elongation	350 % (min)
Density	1,0-1,2 g/cm³
Hardness	50-70 Shore D
Thermal duration	120°C
Flexibility at low temperature	4h a -40°C Non-crackin
Dielectric strength	Wall 1 mm 180 kV/cm Wall 3,5 mm 120 kV/cm

HF Halogen Free



ANTI-CORROSION POLE PROTECTION

On installed poles, the most section vulnerable to corrosion is right above and below ground. This section is attacked by corrosive agents that cause a rapid decay of the metal with a significant reduction of the operating life of the pole. Special heat-shrinking sheaths are suitable for the rust protection of public lighting and electric traction poles, traffic lights and traffic signs. They are composed of very thick cross linked polyolefin. The inside of the tubes and the ends are covered in a suitable thermal fuse adhesive that ensures perfect sealing without allowing moisture to enter.

ADVANTAGES

- ▶ Ultra adhesive.
- ▶ Excellent electrical properties.
- ▶ Good chemical resistance.
- ▶ Resistant to mould and micro-organisms.
- ▶ Constant protection against stray electrical currents.
- ▶ Easy application.
- ▶ Long-term stability of all properties.



WPCT

Open ends complete with closing pieces for already installed poles.

PRODUCT / Item	End height (mm)	Package roll (m)	Code for closing piece for pole diameter	
			Up to 450 mm	Over 450 mm
WPCT-17X100-RL WPCT17X100-RL	450	30	WPCP-IV-4X17 WPCP-IV-4X17	WPCP-IV-6X17 WPCP-IV-6X17
WPCT-24X100-RL WPCT24X100-RL	600	30	WPCP-IV-4X24 WPCP-IV-4X24	WPCP-IV-6X24 WPCP-IV-6X24

Closing pieces sold separately



LTPSM


Tubular sleeve for poles for installation.

PRODUCT / Item	Diameter before/after shrinkage (mm)	Sleeve length (mm)		
			180/58	245/80
LTPSM 180/58-500 LTPSM180/58-500	180/58	500		
LTPSM 245/80-500 LTPSM245/80-500	245/80			500

SELF-SEALING CAP

Self-sealing heat-shrink cap with adhesive for sealing cable heads.

D=Ø min. before shrinkage
d=Ø max. after free shrinkage
S / L1=min. rated size after free shrinkage



PRODUCT	Item	Ø Cable from (mm)	to (mm)	D (mm)	d (mm)	S (±20% mm)	L1 (±10% mm)
RAYL011	334969-000	4	8	12	4,0	2,0	40
RAYL022	821617-000	8	17	20	6	2,3	55
RAYL033	692333-000	17	30	35	16	3,0	83
RAYL044	547889-000	30	45	55	26	3,3	103
RAYL048	068743-000	45	65	75	36	3,3	120
RAYL055	190805-000	65	95	100	52	3,8	140
RAYL066	855203-000	95	115	120	60	3,8	150



HF Halogen Free


Tensile resistance	12 MPa (min)
Elongation	200 % (min)
Density	0,9-1,2 g/cm³
Hardness	50-70 Shore D
Accelerated ageing (7 days at 150°C)	Tensile resistance 12 Mpa (min) Ultimate elongation 200% (min)
Flexibility at low temperature	4h a -40°C Non-cracking
Water absorption	0,5% max after 24h a 23°C

SELF-SEALING TERMINATION

PRODUCT	LV cable conductor (mm²) from to	D1 (mm)	d1 (mm)	S1 ±20% (mm)	D2 (mm)	d2 (mm)	S2 ±20% (mm)	L1 ±10% (mm)	L2 ±10% (mm)
RayK33 324253-000	4 16	22	8	2	9	3,5	2	55	18
RayK24 522347-000	25 70	40	16	2	15	7,5	2	125	35
RayK46 556514-001	95 185	60	23	2,5	25	7,5	2,5	155	45



HF Halogen Free



D= min. Ø before shrinkage
d= max. Ø after free shrinkage
S1 / S2= min. rated size after free shrinkage
L1 / L2= min. rated size after free shrinkage

Tensile resistance	10,5 MPa (min)
Elongation	300 % (min)
Density	1,0-1,3 g/cm³
Hardness	50-70 Shore D
Accelerated ageing (7 days at 150°C)	Tensile resistance 8,5 Mpa (min) Ultimate elongation 100% (min)
Flexibility at low temperature	4h a -40°C Nessuna cricca
Water absorption	0,5% max after 14 days at 23°C

PRODUCT	LV cable conductor (mm²) from to	D1 (mm)	d1 (mm)	S1 ±20% (mm)	D2 (mm)	d2 (mm)	S2 ±20% (mm)	L1 ±10% (mm)	L2 ±10% (mm)
RayK033 645763-000	4 35	42	15	2,3	14	3,5	1,9	105	26
RayK046 747267-000	50 70	55	21	3,1	20	5	2,5	150	40
RayK016 119983-000	95 150	65	26	3,5	26	7	2,9	175	45
RayK026 017847-000	185 300	102	47	3,9	38	12	3	198	58

OTHER AVAILABLE COLOURS




LST-TEC

 Blue

 Red

PRODUCT	Item	Item
LST-TEC 1,6	5068276019	LSTTEC16-ROS
LST-TEC 2,4	5068286021	LSTTEC24-ROS
LST-TEC 3,2	5068296023	LSTTEC32-ROS
LST-TEC 4,8	5068306020	LSTTEC48-ROS
LST-TEC 6,4	5068316033	LSTTEC64-ROS
LST-TEC 9,5	5068326022	LSTTEC95-ROS
LST-TEC 12,7	5068336020	LSTTEC127-ROS
LST-TEC 19,0	5068346012	LSTTEC190-ROS
LST-TEC 25,4	5068356017	LSTTEC254-ROS



CGP-TEC

 Red

 Blue

 Yellow

 White

T Transparent

PRODUCT	Item	Item	Item	Item	Item
CGP-TEC 1,2/0,6	5069674009	5069674010	5069674011	5069914004	5069674008
CGP-TEC 1,6/0,8	5068034005	5068274004	5068154005	5069924005	5069684005
CGP-TEC 2,4/1,2	5068044005	5068284006	5068164005	5069934006	5069694007
CGP-TEC 3,2/1,6	5068054008	5068294010	5068174005	5069944006	5069704005
CGP-TEC 4,8/2,4	5068064006	5068304007	5068184005	5069954004	5069714007
CGP-TEC 6,4/3,2	5068074011	5068314009	5068194012	5069964007	5069724010
CGP-TEC 9,5/4,8	5068084007	5068324006	5068204006	5069974006	5069734006
CGP-TEC 12,7/6,4	5068094006	5068334005	5068214005	5069984005	5069744004
CGP-TEC 19/9,5	5068104006	5068344005	5068224005	5069944004	5069754005
CGP-TEC 25,4/12,7	5068114005	5068354006	5068234005	5068384005	5069764008
CGP-TEC 38/19	5068124001	5068364001	5068244001	5068004001	5068364005
CGP-TEC 51/26	5068134001	5068374001	5068254001	226598-TEC	5069784002
CGP-TEC 76/38	5067104002	889754-TEC	5067144001	230701-000	763800-TEC
CGP-TEC 102/51	5067204002	5068204003	5067204001	254199-TEC	5067214001



RGPO-B

 Red

 Blue

 White

T Transparent

PRODUCT	Item	Item	Item	Item
RGPO-B 2,4/1,2	241202-BAR	241206-BAR	241209-BAR	241201-BAR
RGPO-B 3,2/1,6	321602-BAR	321606-BAR	321609-BAR	321601-BAR
RGPO-B 4,8/2,4	482402-BAR	482806-BAR	482009-BAR	482401-BAR
RGPO-B 6,4/3,2	643202-BAR	643206-BAR	643209-BAR	643201-BAR
RGPO-B 9,5/4,8	954802-BAR	954806-BAR	954809-BAR	954801-BAR
RGPO-B 12,7/6,4	127642-BAR	127646-BAR	127649-BAR	127641-BAR
RGPO-B 19/9,5	199502-BAR	199506-BAR	199509-BAR	199501-BAR
RGPO-B 25,4/12,7	254722-BAR	254726-BAR	254129-BAR	254721-BAR
RGPO-B 38/19	381902-BAR	381906-BAR	381909-BAR	381901-BAR
RGPO-B 51/26	-	-	512609-BAR	-

TAPES



SELF-ADHESIVE TAPES IN PVC

RAYTEAM

Self-adhesive for general use



RAYTECH SUPER 3-3

Self-adhesive for low and high temperatures



SELF-AMALGAMATING

RAYTECH 2.3

Insulation tape EPR



RAYTECH 23 BT

LV insulation tape



RAYTEFILL

Heavy duty insulation tape



RAYTECH 7-0

Silicone insulation tape

SPECIAL TAPES

RAYCOPPER

Copper braid tape



MCA-FV

Fibreglass self-adhesive tape



MCA-ALL


Self-adhesive aluminium tape





VDE marking

Complies with standards CEI 60454 (EN60454)



Available colours: black, grey, white, red, blue, brown, yellow/green.
Contact Raytech for other sizes and thicknesses.

Property	Typical values
Breaking Strength (tensile)	30 N/cm min
Elongation at break	> 170 %
Adhesion to steel	1,8 N/cm
Adhesion to backing	1,8 N/cm
Self-extinguishing	Self-extinguishing
Operating temperature	-5°C / 85°C
Electric strength after exposure to damp environment	40 kV/mm min

RAYTEAM

Self-adhesive tape for general use.

PVC adhesive tape for electrical applications and mechanical protection for general use. Recommended for insulating low-voltage joints and for covering cables, accessories and products in general. It is self-extinguishing and does not propagate fire. Excellent resistance to ageing, exposure to weather conditions, hydrocarbons and chemical solvents in general.

PRODUCT	Item	Item	Thickness	Width	Length
RAYTEAM 1925/13	270913-000	270913-008	0,13 mm	19 mm	25 m
RAYTEAM 1510/13	021513-000	021513-008		15 mm	10 m
RAYTEAM 1925	012141-000	012141-004		19 mm	25 m
RAYTEAM 1510	021514-000	021514-006		15 mm	10 m
RAYTEAM 1525	270999-000	270999-008	0,15 mm	15 mm	25 m
RAYTEAM 2525	280999-000	280997-000		25 mm	25 m

RAYTEAM 1925/13	270913-005	270913-002	270913-006	270913-001	270913-045
RAYTEAM 1510/13	021513-009	021513-002	021513-006	-	021513-045
RAYTEAM 1925	012141-007	012141-001	012141-002	012141-005	012141-003
RAYTEAM 1510	021514-004	021514-001	021514-002	021514-007	021514-003
RAYTEAM 1525	270999-009	270999-002	270999-006	-	270999-045
RAYTEAM 2525	280998-000	-	-	-	-

NEW

RAYTEAM K20

20 RAYTEAM TAPES
+ 3 MT MEASURING TAPE
INCLUDED



PRODUCT / Item	Description
RAYTEAM K20 RAYTEAM-K20	20 RAYTEAM 1925 PVC adhesive tapes dimension: 0,15 mm x 19 mm x 25 m + measuring tape in ABS with retractable belt clip and lanyard.

RAYTECH SUPER 3-3

Self-adhesive tape for use at low and high temperatures.

PVC adhesive tape with excellent electrical and mechanical properties for a wide range of working temperatures. This tape is particularly suitable for use at low temperatures and in all weather conditions, including the most extreme. The tape is flame retardant and self-extinguishing. It is recommended as the primary insulation for joints up to 0.6/1 kV, and as the outer covering for joints and other products, and for all applications at low temperatures.

PRODUCT / Item	Colour	Width	Thickness	Length
RAYTECH SUPER 3-3 3-3061-00-13	●	19 mm	0,18 mm	20 m

Complies with standards
CEI 60454 (EN60454)



Property	Typical values
Breaking Strength (tensile)	35 N/cm min
Elongation at break	180 %
Adhesion to steel	> 1,8 N/cm
Adhesion to backing	> 1,8 N/cm
Self-extinguishing	Self-extinguishing
Temperatura d'esercizio	-18°C / 105°C
Electric Strength after exposure to damp environment	40 kV/mm min

RAYTECH 2.3

EPR Self-amalgamating tape low and high voltage tape.

This ethylene-propylene (EPR) self-amalgamating tape is used for insulating and sealing high voltage electrical joints for voltages up to Um 72 kV. It amalgamates rapidly, adapting itself to the product underneath, forming a solid unit without air bubbles. It is particularly resistant to partial discharges (corona), with the characteristics remaining unchanged with time. Joints must be protected with a PVC tape or similar.

PRODUCT / Item	Colour	Width	Thickness	Length
RAYTECH 2.3 3-2001-00-13	●	19 mm	0,76 mm	9 m



Property	Typical values
Breaking Strength (tensile)	2.2 MPa min
Elongation at break	800% min
Overload temperature	130°C
Operating temperature	90°C
Dielectric strength	38 kV/mm min
Volume resistivity	10 ¹⁵ Ω cm min
Resistance to ozone	Positive
Resistance to U.V.	Positive



Property	Typical values
Breaking Strength (tensile)	3 MPa min
Elongation at break	500% min
Operating temperature	80°C
Dielectric strength	20 kV/mm min

RAYTECH 23 BT

Low voltage Self-amalgamating tape.

This rubber self-amalgamating low voltage tape (0.6/1 kV) is used for insulating and sealing low voltage electrical joints. It amalgamates rapidly, adapting itself to the product underneath, forming a solid unit. The joints must be protected with a PVC tape. The characteristics remain unchanged with time.

PRODUCT / Item	Colour	Width	Thickness	Length
RAYTECH 23 BT 3-2002-96-13	●	19 mm	0,76 mm	6,7 m



RAYTEFILL

Thick low voltage Self-amalgamating tape.

This self-amalgamating thick-wall (3.2mm) has been specially designed for the rapid reconstruction of low-voltage cable insulation, to cover complex shapes (insulating and covering joints between busbars and relative bolts, clamps, etc.) and to seal against possible penetration of humidity. Once applied it becomes a solid, absolutely non-porous mass, with first class electrical qualities and ageing resistance, perfectly suited to the product it is covering.

Property	Typical values
Breaking Strength (tensile)	0,1 MPa
Operating temperature: Continuous	From -30°C to 80°C
Dielectric strength	23,0 kV/mm

PRODUCT / Item	Colour	Width	Thickness	Length
RAYTEFILL 3-2140-00-13	●	38 mm	3,2 mm	1,5 m



Complies with standards
ASTM-D-2148

RAYTECH 7-0

Self-amalgamating silicone rubber tape.

This self-amalgamating silicone rubber tape is used for covering medium and high voltage terminations on extruded cables up to Um 72 kV, because of its first-rate performance for electrical installations in damp or polluted environments, against corrosion, corona and against ageing. It is used as an insulation up to 180°C due to its excellent heat properties. It can be perfectly adapted to all the shapes to be covered.

Property	Typical values
Elongation at break	300%
Resistance to U.V.	Positive
Resistance to ozone	Positive
Working temperature maximum	180°C
Dielectric strength	24 kV/mm

PRODUCT / Item	Colour	Width	Thickness	Length
RAYTECH 7-0 3-2042-00-13	●	25 mm	0,51 mm	9,1 m

RAYCOPPER

Tinned copper mesh tape for electrical screening.

Property	Typical values
Material	Tinned copper mesh tape with high flexibility
Elongation at break	70% min
Breaking Strength (tensile)	35 N/10 mm
Volume resistivity	0,3 cm

PRODUCT	Item	Colour	Width	Thickness	Length
RAYCOPPER 1000	COPPER-100	Silver	60 mm	0,3 mm	1 m
RAYCOPPER 2000	COPPER-200	Silver	60 mm	0,3 mm	2 m
RAYCOPPER 3000	COPPER-300	Silver	60 mm	0,3 mm	3 m
RAYCOPPER 5000	COPPER-500	Silver	60 mm	0,3 mm	5 m
RAYCOPPER 6000	COPPER-600	Silver	60 mm	0,3 mm	6 m



MCA-FV

Fiberglass adhesive tape.

Self-adhesive mono-directional fibreglass tape with polypropylene support. Suitable for cable fixing on pipes (i.e.: Raytech MCA... cables for electrical tracing), and for any kind of strong fixing. Inextensible, it is suitable for temperatures up to 130°C.

Property	Typical values
Breaking Strength (tensile)	300 N/cm min
Ultimate elongation	8%
Adhesion to steel	2 N/cm min



MCA-ALL

Self-adhesive aluminium tape.

Self-adhesive adhesive aluminium tape suitable for fixing on flat surfaces (i.e.: for heating cable fixing on tanks outer surfaces); used also for holes or abrasion repairs on metallic or plastic surfaces. Strong adhesion.

Property	Typical values
Breaking Strength (tensile)	1,2 da N/cm min
Elongation at break	5% min
Adhesion to steel	4 N/cm min
Adhesion to backing	4,5 N/cm min
Flame resistance BS476-7	Class 1



PRODUCT / Item	Colour	Width	Thickness	Length
MCA-ALL 75 R42562	Aluminium	75 mm	0,06 mm	50 m

SPEEDY LINE

Raytech, leader in the field of cable accessories, has always based its research and product line on the quality. This is why Raytech offers in the field of pulling tapes and lubricants too, systems of extremely high reliability and quality, always over the conventional types offered by the market:

- These fixed head, interchangeable nylon fishtapes are constructed with very high mechanical characteristic, long-lasting materials. Speedy Sonda tapes are made of PERLON, a practically non-deformable nylon, protecting the installer from unexpected elongation or breakage of the probe in ducts.
- "Twisted" polyester tapes, self-lubricated, extremely flexible and light, with exceptional mechanical characteristics, able to be inserted into long cable ducts, avoid the need of intermediate cable boxes; allowable bending radius is very small and, once bent, they do not break and released they come back to their original shape.
- Fibreglass tapes, thanks to their "nervous" elasticity together with their strength, are easy to use in any type of conduit.
- Nylon-steel tapes, when an exceptional strength is required.
- The widest range of accessories for all the types.
- Raytech offers the widest range of high sliding, non-toxic lubricants that are easily removable from cables. Choose from lubricant oil, lubricant gel (non-drip, allowing for a savings of up to 3 times compared to conventional types) or lubricant spray (easy application directly into the cable ducts, non-drip and dramatically reducing friction and traction force).



PRODUCT	Positioning	Ease of bending	Pulling resistance
Speedy Nylon and Speedy Sonda	Good	Good	Very good
Polyester Speedy Helix	Very good	Very good	Very good
Fibreglass Speedy Glass	Excellent	Good	Good
Nylon-Steel Speedy Steel	Very good	Excellent	Excellent



Speedy Nylon
Fixed head Nylon probes



Speedy Sonda 3
Fixed head or interchangeable Nylon Perlon® Ø 3 mm



Speedy Sonda 4
Fixed head or interchangeable Nylon Perlon® Ø 4 mm



Speedy Helix 5
Polyester Ø 5 mm with eyelet and fixed flexible head

SPEEDY WIRE OIL - SPEEDY WIRE GEL SPEEDY WIRE SPRAY

Lubricants for threading any kind of cable, power, telecom and optical fibre in ducts, smooth or corrugated piping, etc. With a very high lubrication power, especially when compared to products for similar uses, these are easily removable from cables, and require very low installation strength, even in the case of bent conduits.

Speedy Wire Oil is a standard, fluid and low viscosity lubricant.

Speedy Wire Gel, thanks to its consistency, allows for savings of up to 3 times the amount used compared to other solutions.

Speedy Wire Spray, thanks to its canister and dispensing nozzle, allows for suitable guiding of the lubricant, including inside piping and ducts, greatly facilitating application.



PRODUCT / Item	Package	Wrapping	Appearance	PH	Density
SPEEDY WIRE OIL 900000-003	1 L bottle	12-piece pack	Transparent gel	6 - 8	About 1
SPEEDY WIRE GEL 900000-001	1 L bottle	12-piece pack	Milky liquid	6 - 8	About 1
SPEEDY WIRE SPRAY SPEEDYWSPRAY	400 ml can	12-piece pack	White foam	8,5 - 9	About 1,04

SPEEDY NYLON

Fixed head Nylon transparent cable pullers.

PRODUCT	Item	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY NYLON 3/5-F	SPEEDYNYLON3/5F	3	5	50
SPEEDY NYLON 3/10-F	SPEEDYNYLON3/10F	3	10	40
SPEEDY NYLON 3/15-F	SPEEDYNYLON3/15F	3	15	30
SPEEDY NYLON 3/20-F	SPEEDYNYLON3/20F	3	20	20
SPEEDY NYLON 3/25-F	SPEEDYNYLON3/25F	3	25	15
SPEEDY NYLON 4/5-F	SPEEDYNYLON4/5F	4	5	50
SPEEDY NYLON 4/10-F	SPEEDYNYLON4/10F	4	10	25
SPEEDY NYLON 4/15-F	SPEEDYNYLON4/15F	4	15	20
SPEEDY NYLON 4/20-F	SPEEDYNYLON4/20F	4	20	15
SPEEDY NYLON 4/25-F	SPEEDYNYLON4/25F	4	25	12



Speedy Helix 4
Polyester Ø 4 mm
with eyelet and fixed
flexible head



Speedy Glass
Interchangeable
head fibreglass
probe Ø 3 mm



Speedy Steel
Nylon-steel
probe Ø 6 mm



Accessories



SPEEDY SONDA 3

Nylon tape PERLON® Ø 3 mm with fixed or interchangeable head*.

FIXED head

PRODUCT	Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY SONDA 3/5-F	7139-0001		3	5	50
SPEEDY SONDA 3/10-F	7139-0002	○	3	10	40
SPEEDY SONDA 3/15-F	7139-0003	Transparent	3	15	30
SPEEDY SONDA 3/20-F	7139-0004		3	20	20

INTERC. head*

PRODUCT	Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY SONDA 3/5-I	7139-0005		3	5	50
SPEEDY SONDA 3/10-I	7139-0006	○	3	10	40
SPEEDY SONDA 3/15-I	7139-0007	Transparent	3	15	30
SPEEDY SONDA 3/20-I	7139-0008		3	20	20

Other dimensions available on request

* Supplied with flexible head curve guide and pulling eyelet.

SPEEDY SONDA 4

Nylon tape PERLON® Ø 4 mm with fixed or interchangeable head*.

FIXED head

PRODUCT	Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY SONDA 4/5-F	7139-0009		4	5	35
SPEEDY SONDA 4/10-F	7139-0010	○	4	10	25
SPEEDY SONDA 4/15-F	7139-0015	Transparent	4	15	20
SPEEDY SONDA 4/20-F	7139-0012		4	20	18
SPEEDY SONDA 4/25-F	7139-0059		4	25	15

INTERC. head*

PRODUCT	Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY SONDA 4/5-I	7139-0017		4	5	35
SPEEDY SONDA 4/10-I	7139-0018	○	4	10	25
SPEEDY SONDA 4/15-I	7139-0019	Transparent	4	15	20
SPEEDY SONDA 4/20-I	7139-0020		4	20	18
SPEEDY SONDA 4/25-I	7139-0058		4	25	15

FIXED head

PRODUCT	Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY SONDA 4/5-F-N	7139-0013		4	5	35
SPEEDY SONDA 4/10-F-N	7139-0014	●	4	10	25
SPEEDY SONDA 4/15-F-N	7139-0011	Black	4	15	20
SPEEDY SONDA 4/20-F-N	7139-0016		4	20	18
SPEEDY SONDA 4/25-F-N	7139-0065		4	25	15

INTERC. head*

PRODUCT	Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY SONDA 4/5-I-N	7139-0021		4	5	35
SPEEDY SONDA 4/10-I-N	7139-0022	●	4	10	25
SPEEDY SONDA 4/15-I-N	7139-0023	Black	4	15	20
SPEEDY SONDA 4/20-I-N	7139-0024		4	20	18
SPEEDY SONDA 4/25-I-N	7139-0066		4	25	15

Other dimensions available on request

* Supplied with flexible head curve guide and pulling eyelet.

SPEEDY HELIX 5

Polyester tape Ø 5 mm with fixed eyelet and flexible interchangeable head.

Twisted tapes, very strong, extremely flexible and light. They pass the "4 curves test" on both rigid and corrugated pipes, but they can also avoid to have an intermediate box, and even if bent on themselves they do not break.

PRODUCT / Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY HELIX 5/10 7139-0025	Yellow	5	10	1
SPEEDY HELIX 5/15 7139-0026		5	15	1
SPEEDY HELIX 5/20 7139-0027		5	20	1
SPEEDY HELIX 5/25 7139-0064		5	25	1
SPEEDY HELIX 5/30 7139-0028		5	30	1
SPEEDY HELIX 5/50 7139-0029		5	50	1
SPEEDY HELIX 5/60 7139-0030		5	60	1

Other dimensions available on request



SPEEDY HELIX 4

Polyester tape Ø 4 mm with interchangeable eyelet and head*.


Twisted tapes, very strong, extremely flexible and light. They pass the "4 curves test" on both rigid and corrugated pipes, but they can also avoid to have an intermediate box, and even if bent on themselves they do not break.

PRODUCT / Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY HELIX 4/10 7139-0031	Orange	4	10	1
SPEEDY HELIX 4/15 7139-0032		4	15	1
SPEEDY HELIX 4/20 7139-0033		4	20	1
SPEEDY HELIX 4/30 7139-0034		4	30	1

Other dimensions available on request

* Supplied with flexible head curve guide and pulling eyelet





The tape is complete of repairing kit

SPEEDY GLASS

Interchangeable head "self-starting" fibreglass Ø 3 mm cable pullers*.

Suitable for light use, even on long lengths, easy to use thanks to their "nervous" elasticity which makes easier their positioning in pipes and conduits.

INTERC. head

PRODUCT / Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY GLASS 3/10 7139-0035		3	10	10
SPEEDY GLASS 3/15 7139-0036		3	15	10
SPEEDY GLASS 3/20 7139-0037	Yellow	3	20	10
SPEEDY GLASS 3/25 7139-0060		3	25	10
SPEEDY GLASS 3/30 7139-0038		3	30	10

Other dimensions available on request

* Supplied with flexible head curve guide and pulling eyelet



SPEEDY STEEL

Nylon-steel tape Ø 6 mm complete of all accessories.

Nylon-steel tapes are extremely robust, and are made of an internal core 4 x 1,5 mm steel made, coated with a nylon layer. Particularly suitable for industrial use with heavy duty. Use in installations without voltage.




PRODUCT / Item

PRODUCT / Item	Colour	Ø (mm)	Length (m)	Pack of (PCS)
SPEEDY STEEL 6/20 7139-0039		6	20	1
SPEEDY STEEL 6/25 7139-0061		6	25	1
SPEEDY STEEL 6/30 7139-0040	Green	6	30	1
SPEEDY STEEL 6/40 7139-0041		6	40	1
SPEEDY STEEL 6/50 7139-0062		6	50	1
SPEEDY STEEL 6/60 7139-0063		6	60	1





Other dimensions available on request

ACCESSORIES




For Speedy Sonda cable pullers.

PRODUCT	Item	Description	Pack of (PCS)	
Speedy TFG	7139-0042	Flexible head curve guide	3	
Speedy TFC	7139-0043	Flexible head with sheave	3	
Speedy OTL	7139-0047	Long pulling eyelet	3	
Speedy OTC	7139-0044	Short pulling eyelet	3	
Speedy BU	7139-0045	Joint bush for fishtapes	3	
Speedy PN	7139-0050	Pin M4 (for tape Ø 4 mm)	3	
Speedy AT	7139-0048	Pulling slot	3	
Speedy CA	7139-0049	Accessories kit	1	

For Speedy Glass cable pullers.

PRODUCT	Item	Description	Pack of (PCS)	
Speedy REP	7139-0051	Repairing kit	3	
Speedy TFG	7139-0042	Flexible head curve guide	3	
Speedy TFC	7139-0043	Flexible head with sheave	3	
Speedy OTL	7139-0047	Long pulling eyelet	3	
Speedy OTC	7139-0044	Short pulling eyelet	3	
Speedy BU	7139-0045	Joint bush for fishtapes	3	
Speedy PNG	7139-0046	Pin for Speedy Glass tape	3	
Speedy AT	7139-0048	Pulling slot	3	
Speedy CA	7139-0049	Accessories kit	1	

For Speedy Steel cable pullers.

PRODUCT	Item	Description	Pack of (PCS)	
Speedy MO	7139-0072	Snap link	3	
Speedy TS	7139-0069	Flexible head curve guide	3	
Speedy OL	7139-0071	Clamping device	3	
Speedy RS	7139-0070	Sliding wheel device	3	

Accessories available upon request
for Speedy Helix and:

PRODUCT	Item	Description	Pack of (PCS)	
Speedy AS	7139-0054	Reels with support	1	(see A)
Speedy AF	7139-0053	Reels on frame	1	(see B)
Speedy AFS	7139-0055	Steel reels on frame	1	(see C)
Speedy PR Glass	7139-0052	Repairing pliers for Speedy Glass tapes	1	(see D)



(A)



(B)



(C)



(D)

**APPROVAL**

Class EI 120 Non toxic and asbestos free.
In compliance with standard EN 1366-3.

FIRE STOP BARRIERS


FIRE STOP BAG

Fire stop barrier in an intumescent bag.

Intumescent incombustible bags which stop the passage of fire through openings in walls. They are available in different sizes and they have to be placed to seal the openings, both in walls and floor slabs. At a temperature of 200°C the material starts to compact sealing the gaps thus avoiding the passage of the flames.

- ▶ Made from a fireproof fabric.
- ▶ Contains intumescent putty seal inside.

PRODUCT / Item	Bag dimensions
FSB-11 FSB-11	mm 250 x 100 x 25
FSB-12 FSB-12	mm 250 x 200 x 35
FSB-13 FSB-13	mm 250 x 300 x 35



INSTALLATION

Finish and opening then lay, the bags as bricks, staggered and overlapped.

For the application on plasterboard walls please contact Raytech.

**APPROVAL**

Class EI 120
Non toxic, asbestos and solvent free.
In compliance with standard EN 1366-3.


FIRE STOP PANEL

Fire stop barriers in panels.

Incombustible panels treated on the surface with putty to stop the passage of fire through openings in walls. This product allows for the sealing of cavities in walls safely and cost effectively.

- ▶ Manufactured from Rockwool.
- ▶ Coated with putty.
- ▶ Resistant to mould and bacteria .

PRODUCT / Item	Dimension (mm)
FSP-11 FSP-11	600 x 600 x 51



INSTALLATION

Finish and clean the opening edges then cut the panels with a cutters and position them in the opening. The edges and the jointing lines, as well as the interstices among the cables, are sealed and covered with FIRE STOP SEAL FSS sealant..

For the application on plasterboard walls please contact Raytech.


FIRE STOP COLLAR

Fire stop transit collar for plastic pipes.

Fire stop barrier transit collar for plastic pipes (minimum wall thickness 200mm). Available in a wide range of dimensions to surround pipes that pass through walls.

► Stainless steel outer band.

► Contains intumescent putty inside.



PRODUCT / Item	\varnothing (mm)
FSC 11 FSC-11	from 63 to 110
FSC 12 FSC-12	from 110 to 160
FSC 13 FSC-13	200
FSC 14 FSC-14	250

INSTALLATION

No special care is required: the collar, when opened, is positioned around the duct, closed and fastened by means of inserts.

For other dimensions and installation please contact Raytech.



APPROVAL

Class EI 120 non toxic and asbestos free.
In compliance with standard EN 1366-3.


FIRE STOP TAPE

Fire stop barrier in an intumescent tape for plastic corrugated pipes.

Fire stop barrier in an intumescent tape for the crossing closure of single corrugated pipes. Highly heat-sensitive, intumescent graphite tape with high expansion properties for the protection of corrugated electrical pipes containing cables. Applied on both sides of the pipe crossing through the wall so as to surround the pipe. The heat from a fire causes the tape to expand and fill all possible voids.

RECOMMENDATION

The solution is 10m long, and it can be cut at the required length, saving the remaining parts for a future application. Can also be used in conjunction with FSCI, FSSE, FSCE box covering protections.



INSTALLATION

Wrap the tape twice around the corrugation, on both sides of the wall, fitting it in the through hole. Seal with FIRE STOP SEAL (FSS) sealant putty. Let dry.



APPROVAL

Class EI 120 non toxic and asbestos free.
In compliance with standard EN 1366-3.

PRODUCT / Item	Application corrugated pipe diameter range (mm)	Width (mm)	Thickness (mm)	Length (m)
FST-E-25/32	da 25 a 32 *	20	2	10
FST-E-25/32				

*containing cables up to 10 mm²

**APPROVAL**


Class EI 120

Non toxic and asbestos free.

Does not emit toxic gases and dense fumes.
In compliance with standard EN 1366-3.**FIRE STOP SEAL****Fire stop barrier in intumescence sealing mastic.**

Intumescence mastic to seal and close small voids in walls, also in addition to other types of barriers. It is applied to seal a void or to provide a barrier in a cable duct.

- A polymer compound with fireproof fibres and intumescence in an aqueous solution.
- Non-hygroscopic and thixotropic.
- Can be applied with a spatula.

**INSTALLATION**

Once the edges of the opening have been finished and cleaned, the sealant putty is put in place with a spatula in the case of boxed product, or with a spatula or silicone gun for cartridge product.


For other dimensions or the application on plasterboard walls please contact Raytech.

PRODUCT / Item	Package
FSS 10 FSS-10	Spatula type, 10 kg drum

**FIRE STOP FOAM****Fire stop barriers in expanding foam.**

Single-component expandable sealant foam for filling and fire sealing of small crossing gates on cable duct channels that have been previously compartmented with FSB bags and small gaps. Each canister covers a volume of approximately 20 L.

- Made from a fire resistant polyurethane based foam.
- Graphite fortified.
- Hardens upon contact with air.
- Suitable for the protection of plasterboard walls or slabs.

**APPROVAL**

Class EI 120

Non toxic and asbestos free.

Does not emit toxic gases and dense fumes.
In compliance with standard EN 1366-3.

PRODUCT / Item	Package
FSF 700 FSF-700	Spray can of 750 ml

INSTALLATION

After the edges of the openings have been cleaned, shake the can for at least 30 seconds, then turn upside down and spray the product.

FSC-TPC

Fire stop barrier for plastic and/or corrugated pipes with cables.

Protection designed to be built into the wall after pipes have been installed. Can be installed in locations where the construction support is damaged and there is an annular space around the services. It is possible to protect mixed corrugated plastic pipes in the same crossing.

- ▶ For PE/PP, PVC, Abs pipes containing electrical cables or other services.

- ▶ Pipes can be grouped and protected in bundles.

PRODUCT / Item	For pipes with Ø (mm)
FSC-TPC 050 FSC-TPC-050	50
FSC-TPC 060 FSC-TPC-060	60
FSC-TPC 090 FSC-TPC-090	90
FSC-TPC 120 FSC-TPC-120	125

INSTALLATION

Clean the pipe. Open the sleeve longitudinally, place it around the pipe and clamp it on it using special metal tabs. Push the collar towards the centre of the wall.

Fix with FSS putty in the event of installation on a special crossover pipe.

Contact Raytech regarding through openings or installation on inclined piping.



APPROVAL

Class EI 120

Non toxic and asbestos free.

Does not emit toxic gases and dense fumes.
In compliance with standard EN 1366-3.

FSM

Fire stop barriers in incombustible plaster.

Protective coating to seal and prevent fire propagation in wall cavities; it can be applied manually or sprayed. It can be easily mixed in big quantities with suitable mixer (e.g. concrete mixer).

- ▶ Made from mineral fibres.
- ▶ Simply mix with water and with or without cement mixes.
- ▶ For gates on walls or slabs.

PRODUCT / Item	Package
FSM 20 FSM-20	20 kg bag

INSTALLATION

After the edges of the openings have been finished and cleaned, the incombustible plaster is mixed with water, than applied manually, with a trowel or a pump, and left to dry in air. Water quantity: about 0,85 lt/kg (volume 1 kg = about 2,5 dm³).

For other applications please contact Raytech.



APPROVAL

Class EI 120

Non toxic and asbestos free.

Does not emit toxic gases and dense fumes.
In compliance with standard EN 1366-3.



INSTALLATION

No special care is required. The protection must be placed on the ceiling light grid adhering to the panel.

FSCP

Fire stop barriers for ceiling lights.

Fireproof barriers for fluorescent lights in suspended ceilings. Maintains conditions of fire resistance of ceilings and suspended ceilings. Slightly reduces the temperature in the space between the ceiling and the ceiling panel.

- ▶ Made from non-toxic mineral fibres.
- ▶ Prevents propagation.
- ▶ Flexible, light and self-supporting, easy to install and to remove.

PRODUCT / Item	Dimension (mm)	Weight (kg)
FSCP 600 FSCP-600	720 x 750 x 150	1,7 circa
FSCP 1200 FSCP-1200	1330 x 720 x 140	3,5 circa

APPROVAL

Class EI 120

Non toxic and in compliance with standard EN 1365-2 • 1363-1.

**APPROVAL**

Class EI 120

Non toxic.

It expands up to 5 times.

In compliance with standard
EN 1365-2 • 1363-1**FSCF****Fire stop hoods for downlighters.**

Fireproof dome shaped hood for downlighters in suspended ceilings. Maintains conditions of fire resistance of ceilings and suspended ceilings. Prevents fire propagation and slightly reduces the temperature in the void between the ceiling and the suspended ceiling.


- Made from non-toxic mineral fibres.
- Resistant to fire and expandable compounds.
- Prevents lamp overheating.
- Flexible, light and self-supporting.
- Easy to install and to remove.

INSTALLATION

No special care is required.

The protection must be placed on the spotlight, adhering to the panel.

For other dimensions please contact Raytech.

**PRODUCT / Item****FSCF 250** FSCF-250**FSCF 350** FSCF-350**Dimension (mm)**

250 x 280

350 x 230

Type

Cone-shaped

Dome-shaped

**APPROVAL**

Class EI 120

Non toxic.


In compliance with standard
EN 1364-1**FSSE****Intumescent fire stop barrier for electrical boxes.**

Intumescent barrier for the fire protection of electrical system components built into walls.

- Inserted in electrical boxes.
- Protection with high expansion properties.
- Guarantees wall conditions in the event of a fire.

INSTALLATION

The protections are inserted inside the box before the insertion of modules. Protect corrugated pipes crossing walls with FST-E-25/32

**PRODUCT / Item****FSSE 01** FSSE01**FSSE 02** FSSE02

For electric boxes

Up to three modules (type 503)

Up to six modules (type 506)

FSCC

Fire stop barriers for covering enclosures.


Fire protection system for electrical enclosures and junction boxes. These protect plasterboard wall compartments from heat and fire propagation.

- Made from calcium silicate.

- Contains enclosure.

INSTALLATION

After the opening edges have been finished and cleaned, the protection is properly placed and fixed to the wall by means of screws and putty.



PRODUCT / Item	External dimension (mm)	Internal dimension (mm)
FSCC 150 FSCC-150	150 x 120 x 75	110 x 80 x 55

APPROVAL

Class EI 120

Non toxic and asbestos free.
Does not emit toxic gases and dense fumes.
In compliance with standard EN 1364-1.



FSCO T110

Metal pipe insulating mat protective barrier.


The FSCO T110 barrier is made up a flexible and easily conformable, highly fire resistant insulating mat. It is clad with an aluminium sheet and protects insulated or non-insulated metal piping in wall crossings. The product is cut and modelled with ease, wrapped in a single layer around the pipe, and then closed with aluminised tape. Protects metal piping crossing walls or slabs, preventing longitudinal transmission of heat and fusion of any insulating material.

- Composed of fibres free of any resins or organic binders.

- For wall thicknesses of at least 125 mm.

INSTALLATION

The product is laid in a single layer around the pipe, matching the edges and fastening them with aluminised tape. The installation is then reinforced with wrapped steel wire pulled with pliers. It is positioned letting at least 430 mm come out from each side.



APPROVAL

Class EI 120

Non toxic and asbestos free.
In compliance with standard
EN 1366-1 • EN 1366-3 • EN 1366-5



PRODUCT / Item	Colour	Width	Thickness	Length
FSCO T110 FSCO-T110	Aluminium	1 m	20 mm	5 m

SPECIALS

Kits for the connection, maintenance and protection of electrical systems.



Kit composition:

One bottle for component (A+B)

GALACTIC PROTECTION

Two-component rubber for printed circuit protection including against animal intrusion.

Protection for printed circuits which are especially exposed to dust, animal intrusion (insects, snails, snakes, etc., e.g. in automatic gate trays). Opaque but slightly translucent allows cover forming a protective film. It can be removed (adheres without sticking) even on a small area to access the underlying component. The replaced component is then covered with new filler material which adheres perfectly to the previous material. Composed of two-component rubber with no shelf life and insulating and resistant to UV rays and ageing.



PRODUCT / Item	Description	Rubber colour	Total quantity (ml)
GALACTIC PROTECTION GALACTIC-PROT	two-component rubber	●	300


GALACTIC MAMMUT SECURITY

Straight joint pre-filled with gel.

Galactic Mammut Security is an extremely compact accessory that is suitable for resolving insulation and sealing problems. Make reliable strip connector connections using the components found within the kit. Supplied with connectors for up to 3 core 4mm cables. Suitable for all types of domestic and industrial uses. Make safe temporary or uninsulated connections already in place. For quick repairs of damaged cable and extension cords. Suitable for outdoor use, in panels, within the kitchen etc. Non-toxic, no shelf life, easily re-enterable. Once closed the internal connectors are immediately protected. Galactic Mammut is essential in any area where water is present.

ADVANTAGES


- ▶ No more tangled wires or uncovered connectors!
- ▶ A safe, reliable and quick solution *Galactic Mammut Security*.





Package:
3-piece blister pack

Electrical performance:
CEI EN 50393 as applicable
(testing under water head
of the accessory installed in a box)

BEFORE



AFTER



Dimension
(mm)

61 x 35 x 28

PRODUCT / Item

GALACTIC MAMMUT SECURITY
GALACTIC-MAM

Cable formation

Cables 3 x 1 to 4 mm²
3 insulated conductors
with ground from 1 to 4 mm²



Kit composition:
1 can for component (A+B)



GALACTIC ANIMAL BARRIER

Mouldable two-component rubber paste to prevent animal intrusion.


Galactic Animal Barrier is a two-component paste with no shelf life that can be easily be moulded before cross linking is complete. It can be applied to entries to protect against intrusion (conduits, cable ducts and pipes etc). It cross links quickly to form an effective barrier against small insects however it is easily removable. Ideal for electric gate type installations.



PRODUCT / Item	Description	Rubber colour	Total quantity (g)
GALACTIC ANIMAL BARRIER GALACTIC-ANIBAR	two-component rubber	●	250



Kit composition: 2 cans, 100 g each



GALACTIC WATER STOP

Ready to use single component gel.

The Galactic Water Stop single component gel is a soft, extremely sticky product supplied in convenient, ready to use packages: just tear open the quantity needed and place it at the entry point to protect from infiltration. Thanks to its stickiness, it provides stable and effective sealing over time. Easily removable and re-enterable, allowing repeated access to the protected component without leaving traces. Non-drip so it can also be installed vertically or on the ceiling. Highly sealant, lends itself to the insulation of small connections, or for the protection of particularly exposed connections (connections to external car battery terminals, etc.). This product can be applied wherever there may be leakages from pipes, corrugated pipes, channels, etc., or where there is a need for rapid and efficient insulation.



PRODUCT / Item	Description	Gel colour	Package (g)
GALACTIC WATER STOP GALAWATERSTOP	single component gel	transparent	2 x 100

RAY RTV

Fast cross linking two-component silicone rubber with high mechanical, thermal and elastic characteristics.

Ray-RTV cross links quickly at room temperature, transforming into a rubber with high mechanical, thermal and elastic characteristics. Available in single dose bags, bottles, tanks and boxes, in standard 30 Shore A hardness for black and 15 Shore A for pink. Fast cross linking (less than 8 minutes at 30°C) and easily re-enterable.

ADVANTAGES

- Highly resistant, non-stick, insulating and sealing.
- No shelf life.

Applications Examples



Glass sealing



Pit sealing



Rubber mats



Extruded profiles




Rubber gaskets



Profile reliefs



Anti-corrosion protection



Moulds for making models and for industry



In 15 minutes
Ray RTV
is ready!



PRODUCT / Item	Colour	Shore A hardness	Weight	Package type
BAG-RTV 200-N BAGRTV200-N	●	30	200 g	Single dose bag
BAG-RTV 350-N BAGRTV350-N	●	30	350 g	
RAY-RTV 10K-N RAYRTV10K-N	●	30	10 kg	Boxes
RAY-RTV 20K-N RAYRTV20K-N	●	30	20 kg	
RAY-RTV 400K-N RAYRTV400K-N	●	30	400 kg	

Other colours, hardness and cross linking times (pot life) are available upon request for tanks of 400 Kg. Ray-RTV is available in bags up to 600 g.

Density: about 1.24 gr/cm³ (black)

1.05 gr/cm³ (pink)

Cross linking: (pot life) at + 30°C: <8 minutes

Viscosity: 4000-6000 max MPas

Elongation at break: 350 %

Tensile strength: 2,8 MPa

Operating temperature: -60°C / +200°C

Overload temperature: +250°C

Thermal conductivity: 0,2 W/m°K

Dielectric strength: >21 kV/mm

Volume resistivity: >1,5 x 10 exp 15 Ω cm

**Kit composition:**

1 mould for elastic washers, insulating gaskets and rubber profiles.
1 bottle for component (A+B).

Advantages:

Use directly on site, usable in all weather conditions, easy installation, easy separation from the moulds.

Note: max thickness: 3 mm.



Side A



Side B

**GASKET KIT****Kit to produce rubber gaskets and profiles.**

Kit for the assembly of elastic washers, insulating gaskets and rubber profiles, UV resistant and anti-aging, with working temperature up to 200°C and 30 Shore A hardness, suitable for any electrical, plumbing, or sealing work. The articles produced are suitable for the sealing of outdoor lamps, for the sealing and insulation of screwed and bolted components, for any maintenance, replacement or shimming work. Easy to use, the liquid component is poured and the pieces are ready in minutes, at room temperature and with no exothermic reaction. Easily removed from the mould. Rapid cross-linking at room temperature (<15 min). Elevated dielectric, mechanical, elastic and thermal properties.


► **Without shelf life and re-enterable.**

► **Low emission of smoke and toxic and corrosive gases.**

► **Flexible and elastic over time.**

FLAT GASKETS		RODS	PROFILES
External Ø (mm)	Internal Ø (mm)	Ø (mm)	L x L (mm)
30	22	30	130 x 6
25,5	17	25	130 x 5
24	18	20	130 x 4
22	16,5	15	130 x 3
21	15	10	130 x 2
18	12		
14	8		
11	6		
10	7		
8	4		

GASKETS FOR TAPS		ANTISLIP	CORRUGATED
External Ø (mm)	Internal Ø (mm)	L x L (mm)	L x L - Ø foro (mm)
22	4,5	30 x 30	30 x 30 - Ø foro 4,5
15,8	4,5	25 x 25	
14	4,5	20 x 20	
		15 x 15	
		10 x 10	

Installation sequence

Pour the 2 components in a 1:1 ratio in a jug and mix.



Pour the product into the desired mould (30 sec max).



Remove the object from the mould.



< 15 minutes at 23°C

PRODUCT / Item	Description	Rubber colour	Package (g)
Gasket Kit RAYGASKIT	Mould + Two-component liquid rubber	●	360

SHINY SOLAR

Solution for solar and photovoltaic panel maintenance.

Shiny Solar is a product for photovoltaic and solar module maintenance, for easy removal of grease, limestone and crystallised deposits, dust, smog, excrement, etc. A photovoltaic panel can reduce generated power by up to 15% for non-polluted areas and 25% for highly polluted areas. Regular use of Solar Shiny keeps systems running efficiently. Extremely effective and easy to apply, with no shelf life. To maintain system efficiency, proceed with 2-3 applications/year for medium-polluted areas. The degreasing and anti-static protection contained in the product allows excellent results even with rinsing with hard water (even higher than 30°f). Rapid application: treatment of a 6 kW system (approximately 50 m²), thanks to the fact that degreasing, cleaning and application of the anti-static protection are all part of one single operation, requires less than 20 minutes. Shiny Solar respects panel components, the aluminium frame, gaskets and protective glass. A single package of Shiny Solar can treat installed photovoltaic panel power from 10 to 15 kW, equal to a surface of about 80-120 m². The order data table shows the power and surfaces which can be treated with different packages.

► For easy removal of grease, limestone and crystallised deposits,

dust, smog, excrement, etc.

► Contains anti-static protection.



Spray the product evenly on the solar or photovoltaic panel or on the surface to be cleaned and protected.



Let stand for a few minutes, depending on the level of dirt to be cleaned, then wipe with a soft, non-abrasive, slightly damp pad or sponge.



Rinse with water or remove product with a paper towel. Repeat for especially dirty surfaces.



PRODUCT / Item	Product contents	Efficiency (kW/ surfaces treated per package)	
		Power in kW	Surfaces (m ²)
Shiny Solar SHINYSOLAR	750 ml	10 - 15	80 - 120
Shiny Solar 5 SHINYSOLARS5	5 lt	70 - 100	530 - 800
Shiny Solar 1000 SHINYSOLAR-1000	1000 lt	14.000 - 20.000	106.000 - 160.000
Shiny Brush SB4 SHINYBRUSCH4	brush microfiber		



Advantages:

The 750 ml and 5 lt kits are supplied together with a professional sprayer, with an adjustable spray jet nozzle with a range in the latter case of up to 3 m.

For proper application of the product even in hard to reach areas, a microfiber brush mounted on a telescopic arm which projects up to 4 m is available.



Shiny Brush
SB4



Self extinguishing: according to UL94.

Halogen free.

Excellent resistance to basis, oils, fats, hydrocarbons, chemicals, chlorinated solvents.

Operating temperature: -40°C / +85°C

Installation temperature: -10°C / +60°C



100-piece pack.

CABLE TIES

Tilted tip for easy insertion into clamping head. Rounded corners for greater safety. Quick sliding thanks to a low material friction coefficient. Good UV resistance thanks to its black colour.

ESSENTIAL FOR:

- ▶ **Electrical installations.**
- ▶ **Industrial applications.**
- ▶ **Panels.**
- ▶ **Special applications.**

Colour Black		Width (mm)	Length (mm)	Appl. diameter		Strength (Kg) (n)
PRODUCT	Item			min	max	
Ray-fasc N 22/75	700000-050	2,2	75	0.75	15	6.12 60
Ray-fasc N 25/98	700000-026	2,5	98	1	21	8.16 80
Ray-fasc N 25/135	700000-027	2,5	135	1	32	8.16 80
Ray-fasc N 26/160	700000-028	2,6	160	1	40	8.16 80
Ray-fasc N 26/200	700000-029	2,6	200	2	52	8.16 80
Ray-fasc N 36/140	700000-030	3,6	140	2	35	13.26 130
Ray-fasc N 36/200	700000-031	3,6	200	2	50	13.26 130
Ray-fasc N 36/290	700000-032	3,6	290	2	80	13.26 130
Ray-fasc N 36/370	700000-033	3,6	370	2	103	13.26 130
Ray-fasc N 48/178	700000-035	4,8	178	2	45	22.44 220
Ray-fasc N 48/200	700000-036	4,8	200	3	50	22.44 220
Ray-fasc N 48/250	700000-037	4,8	250	3	68	22.44 220
Ray-fasc N 48/290	700000-038	4,8	290	3,5	79	22.44 220
Ray-fasc N 48/360	700000-039	4,8	360	3,5	103	22.44 220
Ray-fasc N 48/430	700000-041	4,8	430	3,5	115	22.44 220
Ray-fasc N 78/180	700000-051	7,8	180	3,5	45	55.08 540
Ray-fasc N 78/240	700000-043	7,8	240	3,5	63	55.08 540
Ray-fasc N 78/300	700000-044	7,8	300	4	80	55.08 540
Ray-fasc N 78/365	700000-045	7,8	365	8	100	55.08 540
Ray-fasc N 78/450	700000-046	7,8	450	35	130	55.08 540
Ray-fasc N 78/540	700000-047	7,8	540	35	158	55.08 540
Ray-fasc N 78/750	700000-048	7,8	750	35	220	55.08 540



100-piece pack.


Colour White		Width (mm)	Length (mm)	Appl. diameter		Strength (Kg) (n)
PRODUCT	Item			min	max	
Ray-fasc B 22/75	700000-049	2,2	75	0.75	15	6.12 60
Ray-fasc B 25/98	700000-002	2,5	98	1	21	8.16 80
Ray-fasc B 25/135	700000-003	2,5	135	1	32	8.16 80
Ray-fasc B 26/160	700000-004	2,6	160	1	40	8.16 80
Ray-fasc B 26/200	700000-005	2,6	200	2	52	8.16 80
Ray-fasc B 36/140	700000-006	3,6	140	2	35	13.26 130
Ray-fasc B 36/200	700000-007	3,6	200	2	50	13.26 130

Ray-fasc B 36/290	700000-008	3,6	290	2	80	13.26	130
Ray-fasc B 36/370	700000-009	3,6	370	2	103	13.26	130
Ray-fasc B 48/178	700000-011	4,8	178	2	45	22.44	220
Ray-fasc B 48/200	700000-012	4,8	200	3	50	22.44	220
Ray-fasc B 48/250	700000-013	4,8	250	3	68	22.44	220
Ray-fasc B 48/290	700000-014	4,8	290	3,5	79	22.44	220
Ray-fasc B 48/360	700000-015	4,8	360	3,5	103	22.44	220
Ray-fasc B 48/430	700000-017	4,8	430	3,5	115	22.44	220
Ray-fasc B 78/180	700000-052	7,8	180	3,5	45	55.08	540
Ray-fasc B 78/240	700000-019	7,8	240	3,5	63	55.08	540
Ray-fasc B 78/300	700000-020	7,8	300	4	80	55.08	540
Ray-fasc B 78/365	700000-021	7,8	365	8	100	55.08	540
Ray-fasc B 78/450	700000-022	7,8	450	35	130	55.08	540
Ray-fasc B 78/540	700000-023	7,8	540	35	158	55.08	540
Ray-fasc B 78/750	700000-024	7,8	750	35	220	55.08	540

CABLE TIE SUPPORT

Fastening with standard inserts for cable ties with widths up to 9 mm. UV resistant.


PRODUCT / Item	A	Dimension (mm)			
		B	C	D	
Ray-fasc S 700001-000	9,4	5	23	17,6	



BI-DIRECTIONAL ADHESIVE FIXING DEVICE

Self adhesive, can be used on all materials. Suitable for cable ties up to 4.8 mm. Made from ABS with rubber based adhesive foam. UV resistant.


Colour Black	Colour White	Tie width (mm)	Dimension (mm)				
PRODUCT / Item	PRODUCT / Item		A	B	C	F	H
Ray-fasc NBA36 700003-000	Ray-fasc BBA36 700002-000	3,6	19	4,1	19	4	5
Ray-fasc NBA48 700005-000	Ray-fasc BBA48 700004-000	4,8	27	4,8	27	6	6,5



BAYONET-JOINT SUPPORT

Push fit support for cable ties up to 7.8mm. Can be used on sheet surfaces with up to 3.2 mm thick. 6.2mm O/D hole required. Polyamide 6.6.



PRODUCT / Item	A	B	C	D	E	F	Dimension (mm)	
							G	H
Ray-fasc SI 700006-000	10	10,6	8,1	3,2	8	7,1		6,2





MEDIUM VOLTAGE

HEAT-SHRINK
COLD-SHRINK
TERMINATIONS
AND JOINTS.
SEPARABLE
CONNECTORS,
SHEATHS AND TAPES.







MEDIUM VOLTAGE
COLD-SHRINK



**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

Kit composition:

Three single core terminations

RANGES OF APPLICATION

For single core cables type:

**Extruded cable
copper wire screened****Extruded cable
copper tape screened****TEMPERATURES**

105°C
Working temperature

140°C
Max overload temperature


300°C
Short circuit temperature

To select the right termination:Cable code, section in mm², nominal voltage, indoor or outdoor installation.

COLD-SHRINK TERMINATIONS FOR INDOOR USE

Silicone rubber terminations with electric field control.
For extruded cables up to **18/30 kV (Um 36 kV)**.


Cold-shrink technology is based on pre-dilated insulating sheaths on a removable spiral support, which is removed without tools during installation to allow for complete covering of the cable insulation. The Raytech silicone sheath, supplied pre-expanded, is flame retardant, is highly anti-tracking, has very high elastic characteristics, is able to maintain pressure on the cable during operation, is water-repellent and is extremely sturdy. Raytech terminations are suitable for indoor, very compact applications, with a smooth structure and complete with all components. Each kit contains 3 single core indoor terminations. The components are cold-installed without tools, unwinding the pigtail wire.

**For cables****(A)RG16H1R12 and (A)RG7H1R insulation thickness FULL**

Product	Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm ²)	L (mm)
AUTO 10/120-I	10120-I-AUTO		15,3 - 20,2	24,6 - 29,6	50 - 120	
AUTO 10/240-I	10240-I-AUTO	12	18,7 - 25,6	28,0 - 35,8	95 - 240	
AUTO 10/630-I	10630-I-AUTO		28,2 - 37,8	38,5 - 49,4	300 - 630	
AUTO 15/70-I	1570-I-AUTO		16,3 - 19,2	25,6 - 28,7	35 - 70	
AUTO 15/240-I	15240-I-AUTO	17,5	19,2 - 27,8	28,7 - 38,1	70 - 240	320
AUTO 15/630-I	15630-I-AUTO		27,8 - 40,0	38,1 - 52,1	240 - 630	
AUTO 20/50-I	2050-I-AUTO		17,3 - 19,5	27,8 - 29,0	25 - 50	
AUTO 20/185-I	20185-I-AUTO	24	19,5 - 27,4	29,0 - 37,8	50 - 185	
AUTO 20/630-I	20630-I-AUTO		29,8 - 42,0	40,2 - 54,2	240 - 630	
AUTO 30/95-I	3095-I-AUTO		22,3 - 27,9	33,5 - 38,5	22 - 95	
AUTO 30/120-I	30120-I-AUTO	36	29,4 - 31,0	37,3 - 41,2	120 - 150	410
AUTO 30/400-I	30400-I-AUTO		30,6 - 40,3	39,0 - 51,3	150 - 400	

For cables RG7H1M1 insulation thickness LOW

Product	Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm ²)	L (mm)
AUTO 20/50-I	2050-I-AUTO		17,0 - 19,0	23,3 - 25,3	25 - 70	
AUTO 20/185-I	20185-I-AUTO	24	21,0 - 28,0	26,7 - 34,5	95 - 240	320
AUTO 20/630-I	20630-I-AUTO		28,0 - 41,0	34,6 - 48,3	240 - 630	
AUTO 30/95-I	3095-I-AUTO		25,0 - 27,0	31,2 - 33,4	50 - 120	
AUTO 30/120-I	30120-I-AUTO	36	28,0 - 29,0	32,3 - 35,0	150 - 185	410
AUTO 30/400-I	30400-I-AUTO		28,0 - 40,0	34,6 - 47,9	150 - 500	



For cables CPR RG26H1M16 12/20 kV (Umax 24 kV)

Product Item	Nominal voltage Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L (mm)
AUTO 20/50-I 2050-I-AUTO	24	17	26	25	320
		17	27	35	
		18	28	50	
AUTO 20/185-I 20185-I-AUTO	24	19	29	70	320
		20,6	30	95	
		22	32	120	
		23,7	34	150	
		25	36	185	
AUTO 20/630-I 20630-I-AUTO	24	27,8	39	240	320
		30,8	43	300	
		33	46	400	
		37	49	500	
		40	51	600	

For cables CPR RG26H1M16 18/30 kV (Umax 36 kV)


Product Item	Nominal voltage Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L (mm)
AUTO 30/95-I 3095-I-AUTO	36	25,6	32	35	410
		25	35	50	
		25	36	70	
		26	37	95	
		27	38	120	
AUTO 30/120-I 30120-I-AUTO	36	28,2	39	150	410
		29,2	41	185	
AUTO 30/400-I 30400-I-AUTO	36	31,5	43	240	410
		34,5	46	300	
		37	48	400	
		41	52	500	

The accessories for cables in accordance with CPR, type RG26H1M16 (Italian designation), are suitable for

- Cables with copper conductors
- Special thermoplastic sheath
- Red copper wire screen
- High modulus rubber insulation

★ ADVANTAGES

- Rapid installation for lower labour cost
- Highly reliable and safe for operators
- Installation without heating and without tools



**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

Kit composition:

Three single core terminations

RANGES OF APPLICATION

For single core cables type:

**Extruded cable**
copper wire screened**Extruded cable**
copper tape screened**TEMPERATURES**

105°C
Working temperature

140°C
Max overload temperature


300°C
Short circuit temperature

To select the right termination:Cable code, section in mm², nominal voltage, indoor or outdoor installation.

COLD-SHRINK TERMINATIONS FOR OUTDOOR USE

Silicone rubber outdoor terminations with electric field control and bell-shaped insulators. For extruded cables up to **18/30 kV (Um 36 kV)**.


The Raytech silicone sheath, supplied pre-expanded, is flame retardant, is highly anti-tracking, has very high elastic characteristics, is able to maintain pressure on the cable during operation, is water-repellent and is extremely sturdy. With pre-dilated silicone fins on a spiral support for modular installation of the outdoor accessory for upside-down installation. Raytech terminations are suitable for external, very compact applications, complete with all components. Each kit contains 3 single core outdoor terminations. The components are cold-installed without tools, unwinding the pigtail wire.

**For cables****(A)RG16H1R12 and (A)RG7H1R insulation thickness FULL**

Product	Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm ²)	L (mm)
AUTO 10/120-E	10120-E-AUTO	12	15,3 - 20,2	24,6 - 29,6	50 - 120	410
	10240-E-AUTO		18,7 - 25,6	28,0 - 35,8	95 - 240	410
	10300-E-AUTO		28,0 - 29,0	35,5 - 39,0	300	410
	10630-E-AUTO		28,3 - 37,8	38,5 - 49,4	300 - 630	420
	1570-E-AUTO		16,3 - 19,2	25,6 - 28,7	35 - 70	410
	15240-E-AUTO		19,2 - 27,8	28,7 - 38,1	70 - 240	410
AUTO 15/300-E	15300-E-AUTO	17,5	30,0 - 31,0	38,0 - 41,0	300	410
	15630-E-AUTO		30,4 - 40,0	40,2 - 52,1	300 - 630	420
	2050-E-AUTO		17,3 - 19,5	27,8 - 29,0	25 - 50	410
	20185-E-AUTO		19,5 - 27,4	29,0 - 37,8	50 - 185	410
	20240-E-AUTO		27,5 - 31,0	35,7 - 41,0	185 - 240	410
	20630-E-AUTO		29,8 - 42,0	40,2 - 54,2	240 - 630	420
AUTO 30/95-E	3095-E-AUTO	24	22,3 - 27,9	33,5 - 38,5	25 - 95	680
	30120-E-AUTO		29,4 - 31,0	37,3 - 41,2	120 - 150	680
	30400-E-AUTO		30,6 - 40,3	39,0 - 51,3	150 - 400	680
	30120-E-AUTO		28,0 - 29,0	32,3 - 35,0	150 - 185	680
	30400-E-AUTO		28,0 - 40,0	34,6 - 47,9	150 - 500	680

For cables RG7H1M1 insulation thickness LOW

Product	Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm ²)	L (mm)
AUTO 20/50-E	2050-E-AUTO	24	17,0 - 19,0	23,3 - 25,3	25 - 70	410
	20185-E-AUTO		21,0 - 28,0	26,7 - 34,5	95 - 240	410
	20240-E-AUTO		28,0 - 31,5	34,6 - 42,0	240 - 300	410
	20630-E-AUTO		31,0 - 41,0	37,4 - 48,3	300 - 630	420
	3095-E-AUTO		25,0 - 27,0	31,2 - 33,4	50 - 120	680
	30120-E-AUTO		28,0 - 29,0	32,3 - 35,0	150 - 185	680
AUTO 30/400-E	30400-E-AUTO		28,0 - 40,0	34,6 - 47,9	150 - 500	680



For cables CPR RG26H1M16 12/20 kV (Umax 24 kV)

Product Item	Nominal voltage Umax (kV)	\varnothing on insulation (mm)	\varnothing on external sheath (mm)	Conductor cross section (mm ²)	L (mm)
AUTO 20/50-E 2050-E-AUTO	24	17	26	25	410
		17	27	35	
		18	28	50	
AUTO 20/185-E 20185-E-AUTO	24	19	29	70	410
		20,6	30	95	
		22	32	120	
		23,7	34	150	
		25	36	185	
AUTO 20/240-E 20240-E-AUTO	24	27,8	39	240	410
		30,8	43	300	
AUTO 20/630-E 20630-E-AUTO	24	33	46	400	420
		37	49	500	
		40	51	630	

For cables CPR RG26H1M16 18/30 kV (Umax 36 kV)

Product Item	Nominal voltage Umax (kV)	\varnothing on insulation (mm)	\varnothing on external sheath (mm)	Conductor cross section (mm ²)	L (mm)
AUTO 30/95-E 3095-E-AUTO	36	25,6	32	35	680
		25	35	50	
		25	36	70	
		26	37	95	
		27	38	120	
AUTO 30/120-E 30120-E-AUTO	36	28,2	39	150	680
		29,2	41	185	
AUTO 30/400-E 30400-E-AUTO	36	31,5	43	240	680
		34,4	46	300	
		37	48	400	
		41	52	500	


The accessories for cables in accordance with CPR, type RG26H1M16 (Italian designation), are suitable for

- Cables with copper conductors
- Special thermoplastic sheath
- Red copper wire screen
- High modulus rubber insulation

★ ADVANTAGES

- Rapid installation for lower labour cost
- Highly reliable and safe for operators
- Installation without heating and without tools



**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

RANGES OF APPLICATION

For single core cables type:



Three-core extruded cable, wire screened



Three-core extruded cable, tape screened, armoured

Note: for three-core cables, low thickness insulation, please contact Raytech.

★ ADVANTAGES

- Rapid installation for lower labour cost
- Highly reliable and safe for operators
- Installing without heating and without tools

THREE-CORE COLD-SHRINK TERMINATIONS FOR INDOOR/OUTDOOR USE

Termination for armoured and non armoured extruded cables up to **36 kV**

Hybrid technology that provides heat-shrink trifurcation and cold-shrink termination.

For INDOOR use

For NON ARMoured cables

Product	Item	Umax 12 kV sez. (mm ²)	Umax 17,5 kV sez. (mm ²)	Umax 24 kV sez. (mm ²)	Umax 36 kV sez. (mm ²)
AUTO 20/50-I-3	2050-I-3-AUTO	50 - 120	35 - 70	25 - 50	-
AUTO 20/185-I-3	20185-I-3-AUTO	95 - 240	70 - 240	50 - 185	-
AUTO 20/630-I-3	20630-I-3-AUTO	300 - 500	240 - 400	240 - 300	-
AUTO 30/95-I-3	3095-I-3-AUTO	-	-	-	25 - 95
AUTO 30/240-I-3	30240-I-3-AUTO	-	-	-	120 - 240

For ARMoured cables

Product	Item	Umax 12 kV sez. (mm ²)	Umax 17,5 kV sez. (mm ²)	Umax 24 kV sez. (mm ²)	Umax 36 kV sez. (mm ²)
AUTO 20/50-I-3ARM	2050-I-3ARM-AUTO	50 - 120	35 - 70	25 - 50	-
AUTO 20/185-I-3ARM	20185-I-3ARM-AUTO	95 - 240	70 - 240	50 - 185	-
AUTO 20/630-I-3ARM	20630-I-3ARM-AUTO	300 - 500	240 - 400	240 - 300	-
AUTO 30/95-I-3ARM	3095-I-3ARM-AUTO	-	-	-	25 - 95
AUTO 30/240-I-3ARM	30240-I-3ARM-AUTO	-	-	-	120 - 240

For OUTDOOR use

For NON ARMoured cables

Product	Item	Umax 12 kV sez. (mm ²)	Umax 17,5 kV sez. (mm ²)	Umax 24 kV sez. (mm ²)	Umax 36 kV sez. (mm ²)
AUTO 20/50-E-3	2050-E-3-AUTO	50 - 120	35 - 70	25 - 50	-
AUTO 20/185-E-3	20185-E-3-AUTO	95 - 240	70 - 240	50 - 185	-
AUTO 20/630-E-3	20630-E-3-AUTO	300 - 500	240 - 400	240 - 300	-
AUTO 30/95-E-3	3095-E-3-AUTO	-	-	-	25 - 95
AUTO 30/240-E-3	30240-E-3-AUTO	-	-	-	120 - 240

For ARMoured cables

Product	Item	Umax 12 kV sez. (mm ²)	Umax 17,5 kV sez. (mm ²)	Umax 24 kV sez. (mm ²)	Umax 36 kV sez. (mm ²)
AUTO 20/50-E-3ARM	2050-E-3ARM-AUTO	50 - 120	35 - 70	25 - 50	-
AUTO 20/185-E-3ARM	20185-E-3ARM-AUTO	95 - 240	70 - 240	50 - 185	-
AUTO 20/630-E-3ARM	20630-E-3ARM-AUTO	300 - 500	240 - 400	240 - 300	-
AUTO 30/95-E-3ARM	3095-E-3ARM-AUTO	-	-	-	25 - 95
AUTO 30/240-E-3ARM	30240-E-3ARM-AUTO	-	-	-	120 - 240

MEDIUM VOLTAGE TESTING DETAILS FOR TERMINALS AND JOINTS UP TO 36 KV.

TEST	TEST METHOD (VOLTAGES IN kV)	MAXIMUM VOLTAGE PER CABLE UM (kV)					RESULTS
		7,2	12	17,5	24	36	
INDUSTRIAL FREQUENCY AC	a) 1 min. (dry)	27	35	45	55	75	Neither perforations nor discharges
	b) 1 min. (in the rain)	27	35	45	55	75	
	c) 4 h.	14	24	36	48	73	
PARTIAL DISCHARGES	PE, XLPE, EPR, PVC (voltages in kV)	4,5	7,5	10,9	15	22,5	< 3 pC
		7,2	12	17,5	24	-	< 20 pC
IMPULSE	a) 10 positive 10 negative 1,2/50 µs (voltages in kV)	60	75	95	125	170	Neither perforations nor discharges
	b) 10 positive 10 negative 1,2/50 µs (voltages in kV)	70	95	110	150	200	
THERMAL CYCLES WITH APPLIED VOLTAGE	a) 63 cycles of 5 h. of heating, 3 h. of air cooling	-	-	-	-	-	Neither perforations nor discharges
	b) 63 cycles of 5 h. of heating, 3 h. of water cooling (1m of water head)	-	-	-	-	-	
	Extruded cable and non-migrant mixture paper cable	9	15	22	30	45	
	Migrant mixture paper cable	6,5	11	15	22	32	
THERMAL SHORT-CIRCUIT TEST	a) short-circuit of 1s f/f at maximum temperature specified for the cable	-	-	-	-	-	No visible damage
	b) short-circuit of 1s f/t at maximum temperature specified for the cable	-	-	-	-	-	
DIRECT CURRENT	30 min	28	48	72	96	144	Neither perforations nor discharges
HUMIDITY TEST WITH APPLIED VOLTAGE	a) 100 h. in saturated air	4,5	7,5	10,9	15	22,5	Neither perforations nor discharges, nor visible carbonisation nor erosion
	b) 1000 h. in saturated air	4,5	7,5	10,9	15	22,5	
DYNAMIC SHORT-CIRCUIT TEST	63 kA - Standard	-	-	-	-	-	No visible damage
	125 kA - High Current	-	-	-	-	-	
IMPACT	Fall from a height of 2 m at a weight of 4 kg, 6 times (only reinforced joints)	-	-	-	-	-	
SALTY FOG TEST WITH APPLIED VOLTAGE	1h of sealing salinity 224 kg/m³ (voltages in kV)	4,5	7,5	10,9	15	22,5	No discharge

TESTING SEQUENCE

Indoor terminations 1a,2,3a, 4a,2,5, 4a, 1c, 3a,6,7a, 8**Outdoor terminations** 1b, 2, 3b, 4a,2, 5,4a, 2, 1c,3b, 6,7b, 8, 10**Joints** 9, 1a,2,3b,4a,2,5, 4b,2,5, 4b,2,1c,3b, 6,8

**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

RANGES OF APPLICATION

For single core cables type:

**Extruded cable**
copper wire screened**Extruded cable**
copper tape screened**TEMPERATURES**

 **105°C**
Working temperature

 **140°C**
Max overload temperature

 **300°C**
Short circuit temperature

SINGLE CORE COLD-SHRINK JOINTS

Monoblock joints for extruded cables up to **18/30 kV (Um 36 kV)**.

Suitable for outdoor, underground and even underwater applications. Very compact and complete with all components. Each kit contains 1 single core joint. Each joint component is pre-dilated on a spiral support and is extremely easy to remove for fast, safe installation without the use of any tools or heating.

**For cables****(A)RG16H1R12 and (A)RG7H1R insulation thickness FULL**

Product	Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L (mm)
JMAUTO 20/95-1	JM-2095-1-AUTO	12	17 - 23	26 - 33	70 - 150	550
	JM-20240-1-AUTO		22 - 32	33 - 39	185 - 400	600
	JM-20400-1-AUTO		32 - 36	42 - 48	400 - 630	600
JMAUTO 20/95-1	JM-2095-1-AUTO	17,5	17 - 23	26 - 33	50 - 150	550
	JM-20240-1-AUTO		22 - 32	33 - 39	150 - 300	600
	JM-20400-1-AUTO		32 - 36	42 - 48	400 - 500	600
JMAUTO 20/95-1	JM-2095-1-AUTO	24	17 - 23	26 - 33	25 - 95	550
	JM-20240-1-AUTO		22 - 32	33 - 39	120 - 240	600
	JM-20400-1-AUTO		32 - 36	42 - 48	300 - 400	600
JMAUTO 30/95-1	JMAUTO 30/95-1	36	25 - 29	31,2 - 38,3	50 - 95	750
	JMAUTO 30/185-1		27 - 31	33,4 - 42	120 - 185	750
	JMAUTO 30/300-1		31 - 36	max 43	240 - 300	750

For cables RG7H1M1 insulation thickness LOW

Product	Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L (mm)
JMAUTO 20/95-1	JM-2095-1-AUTO	24	17 - 23	26 - 33	25 - 120	550
	JM-20240-1-AUTO		22 - 32	33 - 39	120 - 300	600
	JM-20400-1-AUTO		32 - 36	42 - 48	300 - 500	600

★ ADVANTAGES

- Rapid installation for lower labour cost
- Highly reliable and safe for operators
- Installing without heating and without tools
- Reduced size of the joint and joint bay dimensions
- Minimized possibility of error



For cables CPR RG26H1M16 12/20 kV (Umax 24 kV)

Product Item	Nominal voltage Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L (mm)
JMAUTO 20/95-1 JM-2095-1-AUTO	24	17	26	25	
		17	27	35	
		18	28	50	550
		19	29	70	
		20,6	30	95	
JMAUTO 20/240-1 JM-20240-1-AUTO	24	22	32	120	
		23,7	34	150	600
		25	36	185	
JMAUTO 20/400-1 JM-20400-1-AUTO	24	27,8	39	240	
		30,8	43	300	600



Single core cold-shrink joints (Umax 24 kV)



For cables CPR RG26H1M16 18/30 kV (Umax 36 kV)

Product Item	Nominal voltage Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L (mm)
JMAUTO 30 / 95-1 JMAUTO 30/95-1	36	25,6	32	35	
		25	35	50	750
		25	36	70	
JMAUTO 30 / 185-1 JMAUTO 30/185-1	36	26	37	95	
		27	38	120	750
		28,5	39	150	
		29,5	41	185	
JMAUTO 30 / 300-1 JMAUTO 30/300-1	36	31 - 36	max 43	240 - 300	750



Single core cold-shrink singleblock joints (Umax 36 kV)

The accessories for cables in accordance with CPR, type RG26H1M16 (Italian designation), are suitable for

- Cables with copper conductors
- Special thermoplastic sheath
- Red copper wire screen
- High modulus rubber insulation

Installation sequence



The body of the joint carries the integrated shield and outer sheath.




The joint is fitted on the connected cable.




Position at the centre of the connection and collapsed on the cable removing the inner support.



The joint is completed and can be used immediately.





MEDIUM VOLTAGE
HEAT-SHRINK





TERMINATIONS AND JOINTS HEAT-SHRINK



QUICK PREPARATION



THEY DO NOT REQUIRE A PARTICULAR MANPOWER



LOW NUMBER OF COMPONENTS



WITH NO SHELF LIFE



CAN BE INSTALLED IN ALL ENVIRONMENTAL CONDITIONS



HIGH FLEXIBILITY OF USE



EXTREMELY COMPACT



EASY CUSTOMIZATION



ACCESSORIES

HEAT-SHRINK


ELECTRIC FIELD CONTROL

The control of the electric field is achieved by means of polymers charged with metal oxides with a non-linear characteristic; in the terminations the outer sheaths, designed to get a higher resistance to UV radiation and to electrical tracking, completely cover the cable insulation.

WITHOUT FIELD CONTROL



WITH FIELD CONTROL TUBE





IDENTIFICATION OF COMPLEMENTARY ACCESSORIES

With a few complementary accessories the terminations are suitable for all types of cable:

MV Terminations how to identify and order complementary accessories

Accessory	Abbreviation to add to the product code	Example		
Grounding braid for aluminium tube shields	/H5	THVE 20/A-RC/H5		
Grounding braid with roll spring (only for single core)	/24 /25 /26 /27	For cables (mm ²) Ø on the shield (mm) up to 25 12 - 20 from 35 to 95 17 - 28 from 120 to 300 25 - 40 from 400 to 630 36 - 60	THVE 20/A-RC/24 THVE 20/B-RC/25 THVE 20/C-RC/26 THVE 20/C-RC/27	
Copper cable terminal	-C	+ Conductor cross section	THVE 20/A-RC-C50	
Aluminium cable terminal	-CA	+ Conductor cross section	THVE 20/A-RC-CA50	
Shear bolt lug	-CPR	+ Conductor cross section	THVE 20/A-RC-CPR50	
Multiple choice		With cable lug and grounding accessory, add codes	THVE 20/A-RC/24-C50	

**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

Kit composition:

Three single core terminations

RANGES OF APPLICATION

For single core cables type:

**Extruded cable, copper wire screen****Extruded cable, copper tape screen****Extruded cable, aluminium tube screen****TEMPERATURES**

105°C
Working temperature

140°C
Max overload temperature

300°C
Short circuit temperature

HEAT-SHRINK TERMINATIONS FOR INDOOR USE FOR NON ARMOURED CABLES

Terminations for **SINGLE CORE** extruded cables up to **36 kV**.**For cables****(A)RG16H1R12 and (A)RG7H1R insulation thickness FULL**

Product	Item	Voltage Umax (kV)	Conductor cross section (mm²)	L (mm)
THVE 6/A-RC	369608-000	7,2	25 - 120	210
THVE 6/B-RC	034189-000		150 - 400	
THVE 6/C-RC	882065-000		500 - 630	
THVE 15/A-RC	906848-000	12	25 - 95	320
THVE 15/B-RC	500365-000		120 - 300	
THVE 15/C-RC	068756-000		400 - 630	
THVE 15/A-RC	906848-000	17,5	25 - 50	320
THVE 15/B-RC	500365-000		70 - 300	
THVE 15/C-RC	068756-000		400 - 800	
THVE 20/A-RC	507698-000	24	25 - 50	320
THVE 20/B-RC	190360-000		70 - 240	
THVE 20/C-RC	485361-000		240 - 630	
THVE 30/A-RC	454523-000	36	35 - 95	430
THVE 30/B-RC	308359-000		120 - 185	
THVE 30/C-RC	651264-000		240 - 500	

For shielded aluminium tube cables, add terminal abbreviation **H5**.**For cables RG7H1M1 Afumex insulation thickness LOW**

Product	Item	Voltage Umax (kV)	Conductor cross section (mm²)	L (mm)
THVE 20/A-RC	507698-000	24	25 - 120	320
THVE 20/B-RC	190360-000		95 - 300	
THVE 20/C-RC	485361-000		240 - 630	
THVE 30/A-RC	454523-000	36	50 - 185	430
THVE 30/B-RC	308359-000		120 - 240	
THVE 30/C-RC	651264-000		240 - 630	



For cables CPR RG26H1M16 12/20 kV (Umax 24 kV)

Product Item	Nominal voltage Umax (kV)	\varnothing on insulation (mm)	\varnothing on external sheath (mm)	Conductor cross section (mm^2)	L (mm)
THVE 20/A-RC 507698-000	24	17	26	25	320
		17	27	35	
		18	28	50	
		19	29	70	
		20,6	30	95	
		22	32	120	
		23,7	34	150	
		25	36	185	
		27,8	39	240	
		30,8	43	300	
THVE 20/B-RC 190360-000	24	33	46	400	320
		37	49	500	
		40	51	630	
THVE 20/C-RC 485361-000	24				320

The heat shrink terminations for cables in accordance with CPR, type RG26H1M16 (Italian designation), are suitable for


- Cables with copper conductors
- Special thermoplastic sheath
- Red copper wire screen
- High modulus rubber insulation

For cables CPR RG26H1M16 18/30 kV (Umax 36 kV)

Product Item	Nominal voltage Umax (kV)	\varnothing on insulation (mm)	\varnothing on external sheath (mm)	Conductor cross section (mm^2)	L (mm)
THVE 30/B-RC 308359-000	36	25,6	32	35	430
		25	35	50	
		25	36	70	
		26	37	95	
		27	38	120	
		28,2	39	150	
		29,2	41	185	
THVE 30/C-RC 651264-000	36	31,5	43	240	430
		34,4	46	300	
		37	48	400	
THVE 30/D-RC 700320-000	36	41	52	500	430
		45	55	630	

★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life

**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

Kit composition:

Three single core terminations


RANGES OF APPLICATION

For single core cables type:

Extruded cable, wire or tape screened, aluminium wire armoured

Extruded cable, wire or tape screened, aluminium tape armoured

HEAT-SHRINK TERMINATIONS FOR INDOOR USE FOR ARMOURED CABLES

Terminations for **SINGLE CORE** extruded cables up to **36 kV**.**For cables armoured with wires or aluminium tape**

For Umax cables 7,2 kV		Voltage Umax (kV)	Conductor cross section (mm²)	L (mm)
Product	Item	7,2	25 - 70	460
THVI 6/0-ARM	THVI6/0-ARM		95 - 120	
THVI 6/A-ARM	THVI6/A-ARM		150 - 400	
THVI 6/B-ARM	THVI6/B-ARM		500 - 630	
THVI 6/C-ARM	THVI6/C-ARM			

For Umax cables from 12 to 24 kV		Umax 12 kV sect. (mm²)	Umax 17,5 kV sect. (mm²)	Thickness FULL Umax 24 kV sect. (mm²)	Thickness LOW Umax 24 kV sect. (mm²)	L (mm)
Product	Item					
THVI 20/A-ARM	507698-002	25 - 95	25 - 50	25 - 50	25 - 120	
THVI 20/B-ARM	190360-002	120 - 300	70 - 300	70 - 240	95 - 300	600
THVI 20/C-ARM	485361-002	400 - 800	400 - 800	240 - 630	240 - 630	


For Umax cables 36 kV		Voltage Umax (kV)	Conductor cross section (mm²)	L (mm)
Product	Item	36	35 - 95	730
THVI 30/A-ARM	THVI30/A-ARM		120 - 185	
THVI 30/B-ARM	THVI30/B-ARM		240 - 500	
THVI 30/C-ARM	THVI30/C-ARM			

★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life

HEAT-SHRINK TERMINATIONS FOR OUTDOOR USE FOR NON ARMOURED CABLES

Terminations for **SINGLE CORE** extruded cables up to **36 kV**.



For cables (A)RC16H1R12 and (A)RG7H1R insulation thickness **FULL**

Product	Item	Voltage Umax (kV)	Conductor cross section (mm²)	L (mm)
THVE 6/120-E	THVE6/120-E	7,2	25 - 120	340
THVE 6/400-E	164000-000		150 - 400	
THVE 6/630-E	606630-TEC		500 - 630	
THVE 15/50-E	120036-TEC	12	25 - 95	450
THVE 15/300-E	206772-000		120 - 300	
THVE 15/800-E	125336-TEC		400 - 630	
THVE 15/50-E	120036-TEC	17,5	25 - 50	450
THVE 15/300-E	206772-000		70 - 300	
THVE 15/800-E	125336-TEC		400 - 800	
THVE 20/25-E	231047-TEC	24	25 - 50	520
THVE 20/240-E	255098-TEC		70 - 240	
THVE 20/630-E	792760-000		240 - 630	
THVE 30/95-E	900926-000	36	35 - 95	720
THVE 30/185-E	120057-TEC		120 - 185	
THVE 30/500-E	372083-000		240 - 500	


For shielded aluminium tube cables, add terminal abbreviation **H5**.

For cables RG7H1M1 Afumex insulation thickness **LOW**

Product	Item	Voltage Umax (kV)	Conductor cross section (mm²)	L (mm)
THVE 20/25-E	231047-TEC	24	25 - 120	520
THVE 20/240-E	255098-TEC		95 - 300	
THVE 20/630-E	792760-000		240 - 630	
THVE 30/95-E	900926-000	36	50 - 185	720
THVE 30/185-E	120057-TEC		120 - 240	
THVE 30/500-E	372083-000		240 - 630	

★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life



Electrical performance:
CEI 20-24 • CEI 20-62/1 • HD 629-1

Kit composition:
Three single core terminations

RANGES OF APPLICATION
For single core cables type:



Extruded cable, copper wire screen



Extruded cable, copper tape screen



Extruded cable, aluminium tube screen

TEMPERATURES

105°C
Working temperature


140°C
Max overload temperature

300°C
Short circuit temperature

For complementary accessories see page 161

The heat shrink terminations for cables in accordance with CPR, type RG26H1M16 (Italian designation), are suitable for

- Cables with copper conductors
- Special thermoplastic sheath
- Red copper wire screen
- High modulus rubber insulation



For cables CPR RG26H1M16 12/20 kV (Umax 24 kV)


Product Item	Voltage Umax (kV)	\varnothing on insulation (mm)	\varnothing on external sheath (mm)	Conductor cross section (mm²)	L (mm)
THVE 20/25-E 231047-TEC	24	17	26	25	520
		17	27	35	
		18	28	50	
		19	29	70	
		20,6	30	95	
		22	32	120	
		23,7	34	150	
		25	36	185	
		27,8	39	240	
		30,8	43	300	
THVE 20/630-E 792760-000	24	33	46	400	520
		37	49	500	
		40	51	630	

For cables CPR RG26H1M16 18/30 kV (Umax 36 kV)

Product Item	Voltage Umax (kV)	\varnothing on insulation (mm)	\varnothing on external sheath (mm)	Conductor cross section (mm²)	L (mm)
THVE 30/185-E 120057-TEC	36	25,6	32	35	720
		25	35	50	
		25	36	70	
		26	37	95	
		27	38	120	
		28,2	39	150	
		29,2	41	185	
THVE 30/500-E 372083-000	36	31,5	43	240	720
		34,4	46	300	
		37	48	400	

HEAT-SHRINK TERMINATIONS FOR OUTDOOR USE FOR ARMOURED CABLES

Terminations for **SINGLE CORE** extruded cables up to **36 kV**.




For cables armoured with wires or aluminium tape

For Umax cables

7,2 kV

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)	L (mm)
THVO 6/70-ARM	THVO6/70-ARM	7,2	25 - 70	
THVO 6/120-ARM	THVO6/120-ARM		95 - 120	
THVO 6/400-ARM	THVO6/400-ARM		150 - 400	600
THVO 6/630-ARM	THVO6/630-ARM		500 - 630	



Electrical performance:

CEI 20-24 • CEI 20-62/1 • HD 629-1

Kit composition:

Three single core terminations

Extruded cable, wire or tape screened, aluminium wire armoured

Extruded cable, wire or tape screened, aluminium tape armoured

For Umax cables
from **12 to 24 kV**

Product	Item	Umax 12 kV sect. (mm ²)	Umax 17,5 kV sect. (mm ²)	Thickness FULL Umax 24 kV sect. (mm ²)	Thickness LOW Umax 24 kV sect. (mm ²)	L (mm)
THVO 20/25-ARM	231049-TEC	25 - 95	25 - 50	25 - 50	25 - 120	
THVO 20/240-ARM	255100-TEC	120 - 300	70 - 300	70 - 240	95 - 300	800
THVO 20/630-ARM	792762-000	400 - 800	400 - 800	240 - 630	240 - 630	


For Umax cables
36 kV

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)	L (mm)
THVO 30/95-ARM	THVO30/95-ARM		35 - 95	
THVO 30/185-ARM	THVO30/185-ARM		120 - 185	
THVO 30/500-ARM	THVO30/500-ARM		240 - 500	1020

★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life


For complementary accessories see page 161

**Electrical performance:**

CEI 20-24 • CEI 20-62/1 • HD 629-1

RANGES OF APPLICATION

For three-core cable cables type:

**Three-core cable extruded, unarmoured****Three-core cable extruded, wire or tape armoured**

THREE-CORE HEAT-SHRINK TERMINATIONS FOR INDOOR/OUTDOOR USE

Terminations for armoured and non armoured extruded cables up to **36 kV**.

For INDOOR USE

For NON ARMOURED cables

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVI 6/0-3	THVI6/0-3		25 - 35
THVI 6/A-3	THVI6/A-3		50 - 120
THVI 6/B-3	THVI6/B-3	7,2	150 - 400
THVI 6/C-3	THVI6/C-3		500

Product	Item	Umax 12 kV sect. (mm ²)	Umax 17,5 kV sect. (mm ²)	Umax 24 kV sect. (mm ²)
THVI 20/A-3	507698-003	25 - 95	25 - 50	25 - 50
THVI 20/B-3	190360-003	120 - 300	70 - 300	70 - 240
THVI 20/C-3	485361-003	400 - 500	400	300

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVI 30/A-3	507702-TTEC		35 - 95
THVI 30/B-3	507701-002	36	120 - 185
THVI 30/C-3	THVI30/C-3		240

★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life

For ARMoured cables

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVI 6/0-3-ARM	THVI6/0-3-ARM		25 - 35
THVI 6/A-3-ARM	THVI6/A-3-ARM		50 - 120
THVI 6/B-3-ARM	THVI6/B-3-ARM	7,2	150 - 400
THVI 6/C-3-ARM	THVI6/C-3-ARM		500

Product	Item	Umax 12 kV sect. (mm ²)	Umax 17,5 kV sect. (mm ²)	Umax 24 kV sect. (mm ²)
THVI 20/A-3-ARM	507698-004	25 - 95	25 - 50	25 - 50
THVI 20/B-3-ARM	190360-004	120 - 300	70 - 300	70 - 240
THVI 20/C-3-ARM	485361-004	400 - 500	400	300

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVI 30/A-3-ARM	THVI30/A-3-ARM		35 - 95
THVI 30/B-3-ARM	507701-001	36	120 - 185
THVI 30/C-3-ARM	THVI30/C-3-ARM		240

For OUTDOOR USE

For NON ARMOURED cables

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVO 6/35-3	THVO6/35-3		25 - 35
THVO 6/120-3	THVO6/120-3		50 - 120
THVO 6/400-3	THVO6/400-3		150 - 400
THVO 6/500-3	THVO6/500-3		500

Product	Item	Umax 12 kV sect. (mm ²)	Umax 17,5 kV sect. (mm ²)	Umax 24 kV sect. (mm ²)
THVO 20/25-3	231050-TEC	25 - 95	25 - 50	25 - 50
THVO 20/240-3	255101-TEC	120 - 300	70 - 300	70 - 240
THVO 20/630-3	792763-000	400 - 500	400	300

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVO 30/95-3	231054-TEC		35 - 95
THVO 30/185-3	THVO30/185-3		120 - 185
THVO 30/240-3	THVO30/240-3		240

For ARMoured cables

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVO 6/35-3-ARM	THVO6/35-3-ARM		25 - 35
THVO 6/120-3-ARM	THVO6/120-3-ARM		50 - 120
THVO 6/400-3-ARM	THVO6/400-3-ARM		150 - 400
THVO 6/500-3-ARM	THVO6/500-3-ARM		500

Product	Item	Umax 12 kV sect. (mm ²)	Umax 17,5 kV sect. (mm ²)	Umax 24 kV sect. (mm ²)
THVO 20/25-3-ARM	231051-TEC	25 - 95	25 - 50	25 - 50
THVO 20/240-3-ARM	255102-TEC	120 - 300	70 - 300	70 - 240
THVO 20/630-3-ARM	792764-000	400 - 500	400	300

Product	Item	Voltage Umax (kV)	Conductor cross section (mm ²)
THVO 30/95-3-ARM	THVO30/95-3-ARM		35 - 95
THVO 30/185-3-ARM	THVO30/185-3-ARM		120 - 185
THVO 30/240-3-ARM	THVO30/240-3-ARM		240

Electrical performance:
CEI 20-24 • CEI 20-62/1 • HD629-1

ENEL tables: DJ 4456/3 • DJ 4476/2
ENEL certification: DJ 4853 • DJ 4854
Single core cable AL tube screen




ENEL tables: DJ 4456
ENEL certification: DJ 4853 • DJ 4854
Single core cable extruded wires screen



■ ENEL CERTIFIED HEAT-SHRINK TERMINATIONS

For single core type indoor and outdoor use.




ELICORD TYPE EXTRUDED CABLE (ARG7H5EXY 12/20 KV)

Product Item	Type	ENEL serial number	Conductor cross section (mm ²)	L (mm)
THVE 20/150-I/U 364179-000	With 2 INTERNAL sheaths	273047	35 ÷ 150	365
IXSU-F-5131-IT02 364180-000	Single INTERNAL tube	273047	35 ÷ 150	365
THVE 20/150-E/U 123021-000	With 2 EXTERNAL sheaths	273066	35 ÷ 150	450
OXSU-F-5131-IT02 123020-000	Single EXTERNAL tube	273066	35 ÷ 150	450

EXTRUDED CABLE FOR UNDERGROUND INSTALLATION ([A] RG7H1R 12/20 KV)

Product Item	Type	ENEL serial number	Conductor cross section (mm ²)	L (mm)
IXSU-F-5121-IT01 200315-000	Single INTERNAL tube	273045	25	360
THVE 20/185-I/U 618430-000	With 2 INTERNAL sheaths	273046	50 - 185	360
IXSU-F-5131-IT01 618429-000	Single INTERNAL tube	273046	50 - 185	360
THVE 20/240-I/U 521413-000	With 2 INTERNAL sheaths	273048	240	360
IXSU-F-5151-IT01 897524-000	Single INTERNAL tube	273049	400 - 630	360
THVE 20/185-E/U 365891-000	With 2 EXTERNAL sheaths	273065	50 - 185	450
OXSU-F-5131-IT01 365890-000	Single EXTERNAL tube	273065	50 - 185	450



**INSULATED CABLE MADE OF IMPREGNATED PAPER
([A] RC1HLRX 12/20 KV)**

Product Item	Type	ENEL serial number	Conductor cross section (mm ²)	L (mm)
THVP 20/240-I/U 252214-000	INTERNAL	273042	50 - 240	370
THVP 20/240-E/U-N1 145110-000	EXTERNAL	273083	50 - 240	600

ENEL tables: DJ 4453 • DJ 4473

ENEL certification: DJ 4854 • DJ 4851

Single core cable lead sheathed



**EXTRUDED CABLE FOR UNDERGROUND INSTALLATION
WITH ALUMINIUM TUBE SHIELD (ARE4H5EX 12/20 KV)**

Product Item	Type	ENEL serial number	Conductor cross section (mm ²)	Ø (mm) insulation min max	L (mm)
IXSU-F-5131-IT04 124400-TEC	INTERNAL	273040	70 - 185	19 27	350
OXSU-F-5131-IT03 124500-TEC	EXTERNAL	273064	70 - 185	19 27	450

ENEL tables: DJ4456/6 • DJ4476/7

ENEL certification: DJ4853

Single core cable AL tube




★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life



VOLTAGE DISTRIBUTION (PERCENT)
HEAT-SHRINKABLE JOINT



HEAT-SHRINK JOINTS

The preparation of cables and the installation techniques for medium voltage joints are identical to those for terminations. Even cable made with paper impregnated with non-migrant oil up to 36 kV uses the same basic design. In this way, the heat-shrink system sets new standards regarding the effectiveness, reliability and simplicity of cable installation. The performance and ease of installation of heat-shrink materials are not affected by stocking, even if long and in adverse environmental conditions. A low number of "kits" per cable type covers the entire range of sections, allowing use with any type of connector, regardless of the type of conductor (round or sectoral) and different shields.


ELECTRICAL FIELD DISTRIBUTION

When the cable shield is cut, the electrical field is controlled by a material that has already been experimented in terminations: the electrical gradient control tube. This tube is made of non-linear impedance insulating material that is able to control the electrical field both at the end of the cable shield and on the metal connector. As with the terminations, thanks to the heat-shrink components, the range of joints includes practically all the configurations of the existing cables, as well as the joints mixed between different types of cable. The kit references that appear on the selection tables are those that are most used by national installers for cable applications up to 36 kV. In the described cases, please contact Raytech regardless of the type of cable.

HOW TO IDENTIFY AND ORDER COMPLEMENTARY ACCESSORIES

Accessory	Abbreviation to add to the product code	Example
Copper connectors	-C + Conductor cross section	GHVE 20/185-C95
Aluminium connectors	-CA + Conductor cross section	GHVE 20/185-CA95
Shear bolt connectors	-CPR + conductor cross section	GHVE 20/185-CPR95

INSTALLATION SEQUENCE



SINGLE CORE HEAT-SHRINK JOINTS


For extruded and impregnated paper insulated cables.

High reliability and superior electrical, mechanical and sealing properties make these joints the ideal solution for all types of cables and installation.

FOR EXTRUDED INSULATION CABLES WITH COPPER WIRE SHIELD

([A]RG7H1R[X], [A]RE4H1E[X], [A]RG7H1M1[X])

Product	Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)	L max (mm)	D max (mm)
GHVE 15/50-1	153003-000	7,2 - 17,5	25 50	700	75
GHVE 15/300-1	442803-000	7,2 - 17,5	70 300	700	80
GHVE 15/630-1	357174-000	7,2 - 17,5	400 630	1000	100
GHVE 20/240-1	623051-000	24	25 240	700	80
GHVE 20/630-1	GHVE20/630-1	24	240 630	1000	100
GHVE 30/240-1	GHVE30/240-1	36	35 240	1000	90
GHVE 30/500-1	GHVE30/500-1	36	300 500	1000	100



Electrical performance:

CEI 20-24 • HD 629-1 • HD 629-2



For complementary accessories see page 172


FOR SINGLE CORE EXTRUDED INSULATION CABLES ARMOURED WITH ALUMINIUM WIRES ([A]RG7H1RFR[X], [A]RE4H1EFE[X])

Product	Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)	L max (mm)	D max (mm)
GHVE 20/240-1-ARM	623052-000	24	25 240	1700	80
GHVE 20/630-1-ARM	GHVE20/630-1-ARM	24	240 630	1700	100
GHVE 30/240-1-ARM	GHVE30/240-1-ARM	36	35 240	1850	100
GHVE 30/500-1-ARM	GHVE30/500-1-ARM	36	300 500	1850	110

FOR INSULATED CABLES MADE OF PAPER IMPREGNATED WITH MIXTURE ([A]RC1HLR[X])

Product	Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)	L max (mm)	D max (mm)
GHVP 20/70-1	190901-000	24	35 70	1000	75
GHVP 20/240-1	GHVP20/240-1	24	50 240	1000	75
GHVP 20/400-1	861101-000	24	300 400	1000	80

Supplies do not include connectors which must be requested separately.




Electrical performance:
CEI 20-24 • HD 629-1 • HD 629-2

Accessories for cables in accordance with CPR, type RG26H1M16 (Italian designation), are suitable for

- Cables with copper conductors
- Special thermoplastic sheath
- Red copper wire screen
- High modulus rubber insulation

SINGLE CORE HEAT-SHRINK JOINTS



For cables CPR RG26H1M16 12/20 kV (Umax 24 kV)

Product Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L max (mm)	D max (mm)
GHVE 20/240-1 623051-000	24	17	26	25	700	80
		17	27	35	700	80
		18	28	50	700	80
		19	29	70	700	80
		20,6	30	95	700	80
		22	32	120	700	80
		23,7	34	150	700	80
		25	36	185	700	80
		27,8	39	240	1000	100
GHVE 20/630-1 GHVE20/630-1	24	30,8	43	300	1000	100
		33	46	400	1000	100
		37	49	500	1000	100

For cables CPR RG26H1M16 18/30 kV (Umax 36 kV)

Product Item	Umax (kV)	Ø on insulation (mm)	Ø on external sheath (mm)	Conductor cross section (mm²)	L max (mm)	D max (mm)
GHVE 30/240-1 GHVE30/240-1	36	25,6	32	35	1000	90
		25	35	50	1000	90
		25	36	70	1000	90
		26	37	95	1000	90
		27	38	120	1000	90
		28,2	39	150	1000	90
		29,2	41	185	1000	90
		31,5	43	240	1000	90
		34,4	46	300	1000	100
GHVE 30/500-1 GHVE30/500-1	36	37	48	400	1000	100
		41	52	500	1000	100

TEMPERATURES

105°C
Working temperature

140°C
Max overload temperature

300°C
Short circuit temperature

★ ADVANTAGES

- Immediately energizable
- Quick in installation
- Simple and reliable they do not require a special skilling
- Optimal distribution of the electric field
- Can be installed in all environmental conditions
- No shelf life

THREE CORE HEAT-SHRINK JOINTS


For extruded insulation cables and insulated cables.

High reliability and superior electrical, mechanical and sealing properties make these joints the ideal solution for all types of cables and installation.



FOR EXTRUDED INSULATION CABLES ([A]RG7H1OR, [A]RE4H1OR)

Product	Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)	L max (mm)	D max (mm)
GHVE 15/50-3	545116-000	7,2 - 17,5	25	50	1500
GHVE 15/300-3	251291-000	7,2 - 17,5	70	300	1500
GHVE 15/630-3	GHVE15/630-3	7,2 - 17,5	400	630	1600
GHVE 20/240-3	708732-000	24	25	240	1500
GHVE 20/630-3	GHVE20/630-3	24	300	630	1600
GHVE 30/240-3	GHVE30/240-3	36	50	240	1800
GHVE 30/300-3	GHVE30/300-3	36		300	1900



Electrical performance:

CEI 20-24 • CEI 20-62/2 • HD 629-1



FOR INSULATED ARMOURED CABLES WITH GALVANIC CONTINUITY OF ARMOUR


Product	Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)	L max (mm)	D max (mm)
GHVE 15/50-ARM	155000-001	7,2 - 17,5	25	50	1500
GHVE 15/300-ARM	153000-001	7,2 - 17,5	70	300	1500
GHVE 15/630-ARM	GHVE15/630-ARM	7,2 - 17,5	400	630	1600
GHVE 20/240-ARM	202400-001	24	25	240	1500
GHVE 20/630-ARM	GHVE20/630-ARM	24	300	630	1600
GHVE 30/240-ARM	GHVE30/240-ARM	36	50	240	1800
GHVE 30/300-ARM	GHVE30/300-ARM	36		300	1900



FOR INSULATED CABLES MADE OF IMPREGNATED PAPER ([A]RC1HLOR LEAD SHEATH OVER EACHCORE))

Product	Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)	L max (mm)	D max (mm)
GHVP 20/70-3	056242-000	24	35	70	1600
GHVP 20/240-3	843918-000	24	95	240	1600
GHVP 20/400-3	741685-000	24	300	400	1600



**Electrical performance:**

CEI 20-24 • CEI 20-62/2

HD 629-1 • HD 629-2

TRANSITION JOINTS BETWEEN SINGLE CORE CABLES



BETWEEN SINGLE CORE PAPER INSULATED CABLE AND EXTRUDED CABLE (RESPECTIVELY [A]RG7H1R[X] AND [A]RC1HLRX)

Product Item	Umax (kV)	Conductor cross section (mm ²) paper cable	Conductor cross section (mm ²) extruded cable	ENEL serial number
GHVE 20/25-1-T 202500-000	24		25	-
GHVE 20/240-1-T GHVE20/240-1-T	24	50 - 240	35 - 185	271074
GHVE 20/400-1-T 250499-000	24		240 - 400	-



BETWEEN SINGLE CORE PAPER INSULATED CABLE AND EXTRUDED CABLE WITH ALUMINIUM SHEET SCREEN (RESPECTIVELY [A]RC1HLRX AND ARG7H5EXY)

Product Item	Umax (kV)	Conductor cross section (mm ²) paper cable	Conductor cross section (mm ²) extruded cable	ENEL serial number
GHVE 20/240-1-TE GHVE20/240-1-TE	24	50 - 240	35 - 150	270118



BETWEEN SINGLE CORE EXTRUDED CABLE WITH WIRE SCREEN AND EXTRUDED CABLE WITH ALUMINIUM FOIL SCREEN (RESPECTIVELY [ARG7H1R[X]] OR [A]RG7H1M1 AND ARG7H5EXY)

Product Item	Umax (kV)	Conductor cross section from (mm ²)	Conductor cross section to (mm ²)	L max (mm)	D max (mm)
GHVE 20/240-1X-TE GHVE20/240-1X-TE	24	25	240	1000	75


TRANSITION JOINTS BETWEEN MULTI CORE CABLES

The three core transition joints kits are composed of one three core joint and do not contain the connectors.



BETWEEN 3-CORE PAPER INSULATED CABLE AND 3 SINGLE CORE EXTRUDED CABLES (RESPECTIVELY [A]RC1HLOR AND [A]RG7H1R[X])




Product Item	Umax (kV)	Conductor cross section (mm²)	
		paper cable	extruded cable
GHVT 20/25-1X-3H 202020-000	24	25	25
GHVT 20/240-1X-3H 202019-000	24	50 - 240	35 - 185
GHVT 20/400-1X-3H 202021-000	24	300 - 400	240 - 400



Electrical performance:

CEI 20-24 • CEI 20-62/2

HD 629-1 • HD 629-2



BETWEEN 3-CORE EXTRUDED CABLE AND 3 SINGLE CORE PAPER INSULATED CABLES (RESPECTIVELY [A]RG7H10R AND [A]RC1HLRX)


Product Item	Umax (kV)	Conductor cross section	
		from (mm²)	to (mm²)
GHVT 20/70-3X-1H on request 1	24	25	70
GHVT 20/240-3X-1H on request 2	24	95	240
GHVT 20/400-3X-1H on request 3	24	300	400

SINGLE CORE PLASTIC OR PAPER INSULATED CABLE JOINT WITH SCREEN INTERRUPTION

Single and three core joints are available, both on extruded cable and on impregnated paper insulated cable, also belted and for transition joint, which allow galvanic separation between the screens when the spliced cables are connected to two different earth networks.

Product Item	Type of cable	Umax (kV)	Conductor cross section from (mm²)	to (mm²)	L max (mm)	D max (mm)
GHVP 20/240-1-IS 159852-INT	(A)RC4HLR(X)	24	50	240	1000	75
GHVE 20/240-1-IS 20GHIS-TEC	(A)GR7H1R(X)	24	50	240	1000	75
GHVE 20/150-1-IS 080799-TEC	ARG7H5EXY	24	35	150	1000	75

For complementary accessories see page 172

**Electrical performance:**

CEI 20-24 • CEI 20-62/2

HD 629-1 • HD 629-2

ENEL CERTIFIED HEAT-SHRINK JOINTS

ENEL tables: DJ 4376

ENEL certification: DJ 4853 • DJ 4854




ENEL tables: DJ 4376

ENEL certification: DJ 4853 • DJ 4854



ENEL tables: DJ 4373

ENEL certification: DJ 4851 • DJ 4854



FOR EXTRUDED INSULATION CABLES ([A]RG7H1RX 12/20 KV COPPER WIRE SHIELD - EXTERNAL PVC SHEATH)

Product Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)		L max (mm)	ENEL serial number
GHVE 20/185 - 1/U 512605-000	24	50	185	700	271071

FOR WIRE CARRYING OVERHEAD CABLES (ARG7H5EXY 12/20 KV ALUMINIUM TUBE SHIELD - EXTERNAL PE SHEATH)


Product Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)		L max (mm)	ENEL serial number
GHVE 20/150 - 1/U 478596-000	24	35	150	700	271072

FOR INSULATED CABLES WITH IMPREGNATED PAPER (RC4HLRX WITH COPPER CONDUCTORS from 50 to 150 mm² and ARC4HLRX WITH ALUMINIUM CONDUCTORS from 95 to 240 mm²)

Product Item	Umax (kV)	Conductor cross section from (mm ²) to (mm ²)		L max (mm)	ENEL serial number
GHVP 20/150 - 1/U 085563-000	17,5 e 24	50	150	1000	-
GHVP 20/240 - 1/U 573299-000	17,5 e 24	95	240	1000	271042


HEAT-SHRINK TERMINATIONS FOR HIGH VOLTAGE (UMAX 52 KV)

Kit contains a limited number of components with unlimited shelf life at normal storage conditions. Three basic kits cover all possible cable sections, with the advantage of keeping a reduced and effective stock. The lightness and limited volume of the kits facilitate their handling and transport. No special additional training is required. Simple installation for reliable results.



FOR INDOOR		Voltage Umax (kV)	\varnothing D1 insulation (mm)	\varnothing D2 max. external (mm)
Product	Item	52	30 - 45	60
FOR OUTDOOR				
Product	Item	Voltage Umax (kV)	\varnothing D1 insulation (mm)	\varnothing D2 max. external (mm)
THVE 45/A-E	THVE45/A-E	52	30 - 45	60

In the request, always indicate the cable section, its formation and the diameter on the insulation. Contact Raytech to choose the most suitable termination.



★ ADVANTAGES

- No shelf life under normal storage conditions
- Reduced and efficient stock
- Easy handling and transport
- No special additional training required
- Easy installation with safe results



MEDIUM VOLTAGE
SEPARABLE
CONNECTORS
TAPES
SHEATHS



**Complies with standards**

CEI 20-62/1 - Cenelec HD 629.1 S2

Kit composition:

Three single core terminations


SINGLE CORE **SEPARABLE** **CONNECTORS** WITH EXTERNAL CONE WITH CONTACT PLUG In=250 A

Separable connectors for MV cables with extruded radial field for voltages up to **12/20 (24) kV**.


Single core separable connectors with contact plug In=250 A, elbow or straight for extruded cables. External coating in semi-conductive rubber protects personnel from electrocution. Each termination is factory tested before delivery with dielectric strength testing and measurements of partial discharges.



Contact Raytech for aluminium shield cables.



Kit available for tape screen. Add "A" to the end of the "Product code".




Connection kit for wire shield included.




Contact Raytech for information regarding other types of cable.




Kit available for three core cables. Order kit "TK..". See table.




Contact Raytech for different armour grounding systems available.



Different types of cable lugs available.




Contact Raytech about different shield grounding systems available.



SEPARABLE INTERFACE "A" TERMINATION 24KV - 250 A

ELBOW		Voltage Umax (kV)	Cable insulation diameter range (mm)	Copper/aluminium mechanical conductor cross section range (mm²)
Product	Item			
250 RTS-20/A-3	250RTS20/A-3		13,0 - 21,0	25 - 95
250 RTS-20/B-3	250RTS20/B-3	24	17,5 - 25,0	25 - 95
250 RTS-20/C-3	250RTS20/C-3		21,5 - 28,5	95 - 150




STRAIGHT		Voltage Umax (kV)	Cable insulation diameter range (mm)	Copper/aluminium mechanical conductor cross section range (mm²)
Product	Item			
250 RTD-20/A-3	250RTD20/A-3		13,0 - 21,0	25 - 95
250 RTD-20/B-3	250RTD20/B-3	24	17,5 - 25,0	25 - 95
250 RTD-20/C-3	250RTD20/C-3		21,5 - 28,5	95 - 150


SINGLE CORE SEPARABLE CONNECTORS WITH EXTERNAL CONE WITH CONTACT SCREW IN=630 A

Separable connectors for MV cables with extruded radial field, for voltages up to **19/33 (36) kV**.


Single core separable connectors with contact screw, for extruded cables. External coating in semi-conductive rubber protects personnel from electrocution. Each termination is factory tested before delivery with dielectric strength testing and measurements of partial discharges.



Kit available for tape screen. Add "A" to the end of the "Product code".




Connection kit for wire shield included.



Kit available for three core cables. Order kit "TK..". See table.



For use in potentially explosive areas (12kV max.) Order: -/ATEX.



Different types of cable lugs available.



Contact Raytech for different shield grounding systems available.




Complies with standards

CEI 20-62/1 - Cenelec HD 629 .1 S2

Kit composition:

Three single core terminations



SEPARABLE TEE INTERFACE "C" TERMINATION 24/36KV - 630 A

Product	Item	Voltage Umax (kV)	Cable insulation Ø range (mm)	Copper/aluminium mechanical conductor cross section range (mm²)
630 RTT-20/A-3-C95	630RTT20/A-3-C95	24	12,0 - 19,0	16 - 95
630 RTT-20/B-3-C95	630RTT20/B-3-C95		16,0 - 26,5	16 - 95
630 RTT-20/C-3-C240	630RTT20/C3-C240		19,0 - 32,6	95 - 240
630 RTT-20/D-3-C300	630RTT20/D3-C300		28,5 - 37,5	120 - 300
630 RTO-20/A-3-C400	630RTO20/A3-C400		28,5 - 37,5	185 - 400
630 RTO-20/B-3-C400	630RTO20/B3-C400		34,0 - 42,5	185 - 400
630 RTO-20/C-3-C630	630RTO20/C3-C630		39,0 - 48,5	400 - 630
630 RTO-20/D-3-C630	630RTO20/D3-C630		45,5 - 56,0	400 - 630
630 RTT-30/A-3-C95	630RTT30/A-3-C95	36	19,0 - 32,6	16 - 95
630 RTT-30/B-3-C240	630RTT30/B3-C240		22,0 - 34,6	95 - 240
630 RTT-30/C-3-C300	630RTT30/C3-C300		28,5 - 37,5	120 - 300
630 RTO-30/A-3-C400	630RTO30/A3-C400		28,5 - 37,5	185 - 400
630 RTO-30/B-3-C400	630RTO30/B3-C400		34,0 - 42,5	185 - 400
630 RTO-30/C-3-C630	630RTO30/C3-C630		39,0 - 48,5	400 - 630
630 RTO-30/D-3-C630	630RTO30/D3-C630		45,5 - 56,0	400 - 630



HEAT-SHRINK SHEATHS

Sheaths for insulating bars inside electrical cabinets or outdoors in primary or secondary cabinets.

Application

Primary (HV-MV) and secondary (MV-LV) electrical up to 36 kV today come in very compact sizes. Bars need to be insulated to prevent surface discharges and accidental short-circuits that are essentially caused by animal intrusion. Heat-shrink shrink sheaths for MV can be used on round and rectangular copper or aluminium bars. They are flexible and elastic, can be installed on previously bent bars without any risks of tearing or rippling.

Description

Sheaths utilise a special elastomer cross-linked by irradiation, with an exceptional insulating power and excellent seal over time, even in case of continuous use at high temperature. They do not contain halogens and therefore there is no risk of emission of toxic or corrosive substances in case of fire. They are resistant to solvents, UV radiation, exposure to weather, impact and tear, and therefore are fully suitable for use outdoors.

Installation

Sheaths for MV can be easily factory installed, when dealing with mass production, using an oven for heat-shrink. In situ, shrinking can be carried out with the aid of a torch or a hot air torch. Heat the sheath to over 120°C and it will shrink on the bar without risk of damage because the material is cross-linked and very resistant to high temperatures. The great elasticity of the sheaths allows, if necessary, for being of the bars during assembly of the electric cabinet with the sheath already installed.

DISTANCES ALLOWED IN BAR SYSTEMS

Phase/phase and phase/bus bars distances recommended with insulated bars with sheaths for MV. Studies and testing carried out on insulated bars have shown that it is possible to significantly reduce space with respect to those used in the case of air insulation. The minimum permitted space is defined by the absence of partial discharges at the time of testing in alternating current and by the seal upon impulse. The values shown can be applied to round or rectangular bars installed inside standard cabinets. Shapes with sharp edges or bar parallels of more than 5 m require larger spaces.

Round bus bars

Voltage Um (kV)

12	30/40 55/65	120
17,5	45/60 70/85	160
24	60/90 95/125	220
36	100/160 150/205	320

Rectangular bus bars

Voltage Um (kV)

12	35/45 65/75	120
17,5	55/65 85/105	160
24	70/100 115/150	220
36	140/190 200/285	320

Spacing in air according to IEC 71-2
phase / phase (mm)
phase / bus bars (mm)

Insulation
with BBT

Insulation with BPM or HVBT
with overlap of 2/3


For more information on different possible applications please contact Raytech.

BBT

Flexible, **heavy duty** heat-shrink sheath.

Suitable for reducing overhead distances in MV panels up to 36 kV.

Phase-to-phase distance reduced to approximately 1/3



Product Item	Size of bus bars (mm)				Heat-shrink sheath (mm)			
	A+B from	A+B to	C from	C to	D	d	S ₁	S ₂
BBT 40/16-A/U BBT40/16-AU	28	45	18	32	40	16	1,6	3,8
BBT 65/25-A/U BBT65/25-AU	44	69	28	47	65	25	1,6	3,9
BBT 100/40-A/U BBT100/40-AU	69	102	44	72	100	40	1,6	4,0
BBT 150/60-A/U BBT150/60-AU	102	148	65	105	150	60	1,6	4,0



D = Ø minimum before shrinkage

d = Ø maximum after free shrinkage


S1 = nominal thickness as supplied

S2 = minimum nominal thickness
after free shrinkage

BPM

Flexible, **medium wall** heat-shrink sheath.

Suitable for optimising space in MV panels and for protection from discharges and accidental contact for systems up to 24 kV. Phase-to-phase distance reduced to approximately 1/2



Product Item	Size of bus bars (mm)				Heat-shrink sheath (mm)			
	A+B from	A+B to	C from	C to	D	d	S ₁	S ₂
BPM 15/6-A/U BPM15/6-AU	12	20	6,5	12	15	6	1,1	2
BPM 30/12-A/U BPM30/12-AU	20	38	13,5	25	30	12	1,1	2,2
BPM 50/20-A/U BPM50/20-AU	36	65	22	43	50	20	1,1	2,4
BPM 75/30-A/U BPM75/30-AU	55	95	33	63	75	30	1,1	2,4
BPM 120/50-A/U BPM120/50-AU	90	165	55	105	120	50	1,3	2,8




D = Ø minimum before shrinkage

d = Ø maximum after free shrinkage

S1 = nominal thickness as supplied

S2 = minimum nominal thickness
after free shrinkage




D = Ø minimum before shrinkage
d = Ø maximum after free shrinkage
S₁ = nominal thickness as supplied
S₂ = minimum nominal thickness after free shrinkage

BPTM

Flexible, **medium wall** heat-shrink sheath.

Suitable for optimising space in MV panels and for protection from discharges and accidental contact for systems up to 24 kV. Phase-to-phase distance reduced to approximately 1/2

Product Item	Size of bus bars (mm)				D	Heat-shrink sheath (mm)		
	A+B from	A+B to	C from	C to		d	S ₁	S ₂
BPTM 15/6-A/U 5904284002	12	20	6,5	12	15	6	1,1	1,9
BPTM 30/12-A/U 723955-000	20	38	13,5	25	30	12	1,1	2,2
BPTM 50/20-A/U 2246244002	36	65	22	43	50	20	1,1	2,35
BPTM 75/30-A/U 6129164002	55	95	33	63	75	30	1,1	2,35
BPTM 100/40-A/U 178238-000	70	130	44	86	100	40	1,1	2,35
BPTM 120/50-A/U 412147-000	90	165	55	105	120	50	1,3	2,8
BPTM 175/70-A/U 920423-000	125	235	80	150	175	70	1,3	2,8
BPTM 205/110-A/U 499685-000	200	276	127	190	205	110	1,3	2,8



D = Ø minimum before shrinkage
d = Ø maximum after free shrinkage
S₁ = nominal thickness as supplied
S₂ = minimum nominal thickness after free shrinkage

BBIT

Flexible, **heavy duty** heat-shrink sheath.

Suitable for reducing overhead distances in MV panels up to 36 kV. Phase-to-phase distance reduced to approximately 1/3

Product Item	Size of bus bars (mm)				D	Heat-shrink sheath (mm)		
	A+B from	A+B to	C from	C to		d	S ₁	S ₂
BBIT 25/10-A/U 5609274001	17	28	11	20	25	10	1,6	3,6
BBIT 40/16-A/U 560931-000	28	45	18	32	40	16	1,6	3,6
BBIT 65/25-A/U 5609364001	44	69	28	47	65	25	1,6	3,6
BBIT 100/40-A/U 560981-000	69	102	44	72	100	40	1,6	3,6
BBIT 150/60-A/U 560982-000	102	148	65	105	150	60	1,6	3,6
BBIT 175/80-A/U 426377-000	133	196	85	125	175	80	1,6	3,6

HEAT-SHRINK TAPES

HVBT heat-shrink tape coated in hot melt adhesive for MV.

Application

HVBT tape is part of the bar insulation product range. It is a heat-shrink tape coated with a hot melt adhesive on one side.

Installation

HVBT is installed wrapping it moderately taut on the bar with overlap equal to 2/3. When heated, it shrinks and adheres to the underlying layer. At the same time, the layers of this tape amalgamate to create a continuous insulation sheath.


Insulation distance

Refer to the table on page 179 (BPM values) to determine the distances between the bars and toward grounding. HVBT tape is sold in 4 different widths and is coated with adhesive on the outer part. Fibreglass tape used to stop taping is provided with each roll.

HVBT

Self-sealing heat-shrink tape for MV bar insulation.

Product	Item	Width (mm)	Length (m)
HVBT 12-A	364471-000	25	10
HVBT 14-A	475743-000	50	10
HVBT 15-A	736143-000	75	10
HVBT 16-A	215370-000	100	10



MEDIUM VOLTAGE TESTING DETAILS FOR TERMINALS AND JOINTS UP TO 36 KV.

TEST	TEST METHOD (VOLTAGES IN kV)	MAXIMUM VOLTAGE PER CABLE UM (kV)					RESULTS
		7,2	12	17,5	24	36	
INDUSTRIAL FREQUENCY AC	a) 1 min. (dry)	27	35	45	55	75	Neither perforations nor discharges
	b) 1 min. (in the rain)	27	35	45	55	75	
	c) 4 h.	14	24	36	48	73	
PARTIAL DISCHARGES	PE, XLPE, EPR, PVC (voltages in kV)	4,5	7,5	10,9	15	22,5	< 3 pC
		7,2	12	17,5	24	-	< 20 pC
IMPULSE	a) 10 positive 10 negative 1,2/50 µs (voltages in kV)	60	75	95	125	170	Neither perforations nor discharges
	b) 10 positive 10 negative 1,2/50 µs (voltages in kV)	70	95	110	150	200	
THERMAL CYCLES WITH APPLIED VOLTAGE	a) 63 cycles of 5 h. of heating, 3 h. of air cooling	-	-	-	-	-	Neither perforations nor discharges
	b) 63 cycles of 5 h. of heating, 3 h. of water cooling (1m of water head)	-	-	-	-	-	
	Extruded cable and non-migrant mixture paper cable	9	15	22	30	45	
	Migrant mixture paper cable	6,5	11	15	22	32	
THERMAL SHORT-CIRCUIT TEST	a) short-circuit of 1s f/f at maximum temperature specified for the cable	-	-	-	-	-	No visible damage
	b) short-circuit of 1s f/t at maximum temperature specified for the cable	-	-	-	-	-	
DIRECT CURRENT	30 min	28	48	72	96	144	Neither perforations nor discharges
HUMIDITY TEST WITH APPLIED VOLTAGE	a) 100 h. in saturated air	4,5	7,5	10,9	15	22,5	Neither perforations nor discharges, nor visible carbonisation nor erosion
	b) 1000 h. in saturated air	4,5	7,5	10,9	15	22,5	
DYNAMIC SHORT-CIRCUIT TEST	63 kA - Standard	-	-	-	-	-	No visible damage
	125 kA - High Current	-	-	-	-	-	
IMPACT	Fall from a height of 2 m at a weight of 4 kg, 6 times (only reinforced joints)	-	-	-	-	-	
SALTY FOG TEST WITH APPLIED VOLTAGE	1h of sealing salinity 224 kg/m³ (voltages in kV)	4,5	7,5	10,9	15	22,5	No discharge

TESTING SEQUENCE

Indoor terminations 1a,2,3a, 4a,2,5, 4a, 1c, 3a,6,7a, 8

Outdoor terminations 1b, 2, 3b, 4a,2, 5,4a, 2, 1c,3b, 6,7b, 8, 10

Joints 9, 1a,2,3b,4a,2,5, 4b,2,5, 4b,2,1c,3b, 6,8

HEATING CABLES


INDUSTRIAL USE.
DOMESTIC USE.
COMFORT HOUSE.



Heating Cables

Heating cables are used for frost protection of pipes, tanks, ramps and walkways, gutters, etc., or for maintaining process temperatures, especially in industrial environments.

- **CONSTANT POWER CABLES**
- **SELF-REGULATING CABLES**



CONSTANT POWER CABLES

Raytech cables are composed of 2 conductors that are shielded and in the case of Stop Ice are supplied with a suitable thermostat for anti-freeze maintenance.



★ ADVANTAGES


CONSTANT POWER CABLES

- **Ready for use**, without requiring the installation of accessories.
- **Already equipped with a thermostat**, in the case of Stop Ice.
- **Completely reliable**.

SELF-REGULATING CABLES

The self-regulation technology and the parallel circuit present the following advantages:

- The heating cables can be cut at the desired length, jointed and terminated on site.
- They can be supplied at 230 V without transformers.
- They can be overlapped without over heating risks.
- They reduce automatically their power output as the required temperature is reached.
- They are easily designed and can be easily handled on site.



★ ADVANTAGES

SELF-REGULATING CABLES

- **A reduction in overall installation costs**
- **Reduction in operating cost**
- **Very easy to install**
- **Simple design**
- **Uniform temperature**
- **Complete reliability**



HEATING CABLES INDUSTRIAL USE

MCA / MCA-I-PF

CABLE POWERED

From -55°C to +65°C

CABLE NOT POWERED

From -55°C to +80°C



MCA-I-GF

CABLE POWERED

From -60°C to +120°C

CABLE NOT POWERED

From -60°C to +120°C



MCA-I-FF

CABLE POWERED

From -60°C to +110°C

CABLE NOT POWERED


From -60°C to +130°C



MCA

Self-regulating heating cables for anti-freeze or temperature maintenance use with exposure to **mild inorganic solutions**.

Suitable for anti-freeze and process temperature maintenance use **up to 65°C** on piping and tanks. Cannot be used when washing with steam or continuous exposure to strong corrosive and organic acids.



CONSTITUTION OF THE CABLE

Copper conductors

Self regulating conductive core

Modified polyolefine insulation

Copper screen

Modified polyolefine outer sheath

Cables certified for classified zones

Ex II 2G Ex 60079-30-1 IIC Gb
Ex II 2D Ex 60079-30-1 IIIC Db
In accordance: EN IEC 60079-0:2018
EN IEC 60079-30-1:2017



Type of surface to be tracked:

Steel - Painted - Stainless Steel - Plastic.

Chemical resistance:

Suitable for exposure to mild inorganic solutions.

Product	Power voltage (V)	Power at 10°C (W/m)	Minimum installation temperature (°C)	MAX Temperature Continuous with powered cable (°C)	MAX Temperature with no powered cable (°C)	Bending radius MIN (mm)	Temperature classification
MCA3		10					
MCA5		15					
MCA8	230	25	-55	65	80	25	T6
MCA10		30					
MCA13-I		40					

MAXIMUM LENGTH OF THE CIRCUITS IN THE HEATING CABLE (m)

ELECTRICAL SIZING Starting temperature (°C)	MAXIMUM LENGTH OF THE CIRCUITS IN THE HEATING CABLE (m)															
	MCA3			MCA5			MCA8			MCA10			MCA13-I			
+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°		
Switchgear protection (A), with C curve and 30mA* differential protection*	10 A	-	-	103	71	62	64	47	37	49	38	33	-	-	-	
	16 A	177	144	125	160	114	99	103	75	60	78	61	53	57	44	40
	20 A	-	149	139	-	133	124	126	94	75	97	76	66	71	55	50
	25 A	-	-	-	-	-	-	-	107	94	112	95	83	89	69	62

* Suggested where protection of people is requested; installations with no personnel admittance can be performed with 100 to 300 mA.

MCA connection accessories



MCA Universal IP68

- Connection kit integrated with the terminal box.
- Termination Kit.
- Joint Kit.



MCA-Y

Branch Kit.



MCA-BOX3 / 4

Connection boxes between heating cables or heating and power cables.



MCA-AL

Thermal insulation pass-through kit.



MCA-PRESS

Cable gland.



MCA-EA

Warning label.



MCA-FV

Glass fiber tape.



MCA-ALL

Aluminium self adhesive tape 25 or 75 mm.

For other accessories see page 219

MCA-I-PF

Self-regulating heating cables for anti-freeze or temperature maintenance use with exposure to **inorganic solutions**.

Suitable for anti-freeze and process temperature maintenance use **up to 65°C** on piping and tanks. Cannot be used when washing with steam or continuous exposure to strong corrosive and organic acids.



CONSTITUTION OF THE CABLE

Copper conductors

Self regulating conductive core

Modified polyolefine insulation

Copper screen

Fluoropolymer outer sheath

Cables certified for classified zones

Ex II 2G Ex 60079-30-1 IIC Gb

Ex II 2D Ex 60079-30-1 IIC Db

In accordance: EN IEC 60079-0:2018
EN IEC 60079-30-1:2017




Type of surface to be tracked:

Steel - Painted - Stainless Steel - Plastic.

Chemical resistance:

Suitable for exposure to mild inorganic solutions.



Product	Power voltage (V)	Power at 10°C (W/m)	Minimum installation temperature (°C)	MAX Temperature Continuous with powered cable (°C)	MAX Temperature with no powered cable (°C)	Bending radius MIN (mm)	Temperature classification
MCA3-I-PF		10					T6
MCA5-I-PF		15					T6
MCA7-I-PF	230	20	-55	65	80	25	T6
MCA8-I-PF		25					T5
MCA10-I-PF		30					T5
MCA13-I-PF		40					T6

ELECTRICAL SIZING Starting temperature (°C)	MAXIMUM LENGTH OF THE CIRCUITS IN THE HEATING CABLE (m)																	
	MCA3-I-PF			MCA5-I-PF			MCA7-I-PF			MCA8-I-PF			MCA10-I-PF			MCA13-I-PF		
+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°	
10 A	202	202	163	153	144	115	109	79	70	91	86	70	57	54	44	57	44	40
16 A	202	202	202	165	165	144	129	99	87	120	107	87	76	67	55	71	55	50
20 A	202	202	202	165	165	165	-	111	104	128	128	109	95	84	69	89	69	62
25 A	202	202	202	165	165	165	-	-	-	128	128	128	97	97	88	-	-	-

* Suggested where protection of people is requested; installations with no personnel admittance can be performed with 100 to 300 mA.

MCA-I-PF connection accessories


	MCA Universal IP68	• Connection kit integrated with the terminal box. • Termination Kit. • Joint Kit.
	MCA-Y	Branch Kit.
	MCA-BOX3 / 4	Connection boxes between heating cables or heating and power cables.
	MCA-AL	Thermal insulation pass-through kit.
	MCA-PRESS	Cable gland.
	MCA-EA	Warning label.
	MCA-FV	Glass fiber tape.
	MCA-ALL	Aluminium self adhesive tape 25 or 75 mm.

For other accessories see page 219

MCA-I-GF

Self-regulating heating cables for anti-freeze or temperature maintenance use with exposure to **corrosives and acids**.

Suitable for maintaining process temperatures **up to 120°C** on piping and tanks, even in the presence of acids and corrosives, or for anti-freeze use where acids and corrosives are present, in safe areas. Not suitable for use in the presence of steam washing.



CONSTITUTION OF THE CABLE

Copper conductors

Self regulating conductive core

Fluoropolymer insulation

Copper screen

Modified polyolefine outer sheath

Type of surface to be tracked:
Steel - Painted - Stainless Steel.

Chemical resistance:
Suitable for exposure to corrosive and organic acids.

Product	Power voltage (V)	Power at 10°C (W/m)	Minimum installation temperature (°C)	MAX Temperature Continuous with powered cable (°C)	MAX Temperature with no powered cable (°C)	Bending radius MIN (mm)
MCA3-I-GF		10				
MCA5-I-GF		15				
MCA8-I-GF	230	25	-60	120	120	25
MCA10-I-GF		30				
MCA20-I-GF		60				

MAXIMUM LENGTH OF THE CIRCUITS IN THE HEATING CABLE (m)

ELECTRICAL SIZING

Starting temperature (°C)

Switchgear protection (A), with C curve and 30mA* differential protection*

	16 A	MCA3-I-GF			MCA5-I-GF			MCA8-I-GF			MCA10-I-GF			MCA20-I-GF		
		+10°	-15°	-25°	+10°	-15°	-25°	+10°	-15°	-25°	+10°	-15°	-25°	+10°	-15°	-25°
	200	180	175	165	130	117	120	97	88	85	73	69	50	41	38	
	235	235	235	189	162	152	140	125	120	114	98	92	64	55	52	
	-	-	-	-	-	189	-	-	140	-	-	114	-	-	64	

* Suggested where protection of people is requested; installations with no personnel admittance can be performed with 100 to 300 mA.

MCA-I-GF connection accessories

	MCA Universal IP68 • Connection kit integrated with the terminal box. • Termination Kit. • Joint Kit.		MCA-Y Branch Kit.		MCA-BOX3 / 4 Connection boxes between heating cables or heating and power cables.		MCA-AL Thermal insulation pass-through kit.		MCA-PRESS Cable gland.		MCA-EA Warning label.		MCA-FV Glass fiber tape.		MCA-ALL Aluminium self adhesive tape 25 or 75 mm.
--	---	--	-----------------------------	--	---	--	---	--	----------------------------------	--	---------------------------------	--	------------------------------------	--	---

For other accessories see page 219

MCA-I-FF

Self-regulating heating cables for anti-freeze or temperature maintenance use with exposure to **corrosives and acids and high temperatures**.

Suitable for maintaining process temperatures **up to 110°C** on piping and tanks, even in the presence of acids and corrosives, or for anti-freeze use even in the presence of acids and corrosives and where high temperature thermal treatment is foreseen, like steam washing.



CONSTITUTION OF THE CABLE

- Copper conductors
- Self regulating conductive core
- Fluoropolymer insulation
- Copper screen
- Fluoropolymer outer sheath

Cables certified for classified zones

Ex II 2G Ex 60079-30-1 IIC Gb
Ex II 2D Ex 60079-30-1 IIIC Db
In accordance: EN IEC 60079-0:2018
EN IEC 60079-30-1:2017




Type of surface to be tracked:

Steel - Painted - Stainless Steel - Plastic.

Chemical resistance:

Suitable for exposure to corrosives and acids and high temperatures.



Product	Power voltage (V)	Power at 10°C (W/m)	Minimum installation temperature (°C)	MAX Temperature Continuous with powered cable (°C)	MAX Temperature with no powered cable (°C)	Bending radius MIN (mm)	Temperature classification
MCA3-I-FF		10					T4
MCA5 -I-FF		15					T4
MCA7-I-FF	230	20	-60	110	130	25	T3
MCA10-I-FF		30					T3
MCA15-I-FF		45					T3
MCA20-I-FF		60					T3

ELECTRICAL SIZING Starting temperature (°C)	MAXIMUM LENGTH OF THE CIRCUITS IN THE HEATING CABLE (m)																	
	MCA3-I-FF			MCA5-I-FF			MCA7-I-FF			MCA10-I-FF			MCA15-I-FF			MCA20-I-FF		
+10°	0°	-20°	+10°	0°	-20°	+10°	-15°	-25°	+10°	0°	-20°	+10°	-15°	-25°	+10°	0°	-20°	
16 A	230	217	195	164	155	141	122	107	102	92	87	79	55	48	36	52	49	45
20 A	231	231	231	188	188	177	136	127	124	115	109	98	68	60	57	65	61	56
25 A	231	231	231	188	188	188	-	-	-	133	133	123	-	-	-	75	75	70
32 A	231	231	231	188	188	188	-	-	-	133	133	133	91	83	82	75	75	75

* Suggested where protection of people is requested; installations with no personnel admittance can be performed with 100 to 300 mA.

MCA-I-FF connection accessories

	MCA Universal IP68 • Connection kit integrated with the terminal box. • Termination Kit. • Joint Kit.		MCA-Y Branch Kit.		MCA-BOX3 / 4 Connection boxes between heating cables or heating and power cables.		MCA-AL Thermal insulation pass-through kit.		MCA-PRESS Cable gland.		MCA-EA Warning label.		MCA-FV Glass fiber tape.		MCA-ALL Aluminium self adhesive tape 25 or 75 mm.
--	---	--	-----------------------------	--	---	--	---	--	----------------------------------	--	---------------------------------	--	------------------------------------	--	---

For other accessories see page 219



HEATING CABLES DOMESTIC USE

PIPING

CONSTANT POWER



STOP ICE

SELF-REGULATING



ICE KILLER
MCA

RAMPS

CONSTANT POWER



EASY CABLE
EASY RAMP

SELF-REGULATING



MCA RAMP

GUTTERS

CONSTANT POWER



EASY FROST

SELF-REGULATING



MCA 8



**CHARACTERISTICS****Power:** 12 W/m**Power supply:** 230 V – 50 Hz**Cable dimensions:** ~ 5x7 mm**Min. installation temperature:** +5°C**Max. working temperature:** +70°C**Heating cable type:**

2 conductors, screened cable

Insulation: XLPE**External sheath:** PVC**Min. bending radius:** 3,5 D**Protection degree:** IP X7**Marking:** CEIntegrated Bimetal Thermostat
(ON + 3°C - OFF +10°C)Complete Connections and power cord
(1,5 m - 3 x 0,75 mm²)


STOP ICE

Constant power anti-freeze kit complete with thermostat and plug.

Raytech Stop Ice is a pre-assembled kit consisting of a constant wattage heating cable of 12 W/m, complete with contact thermostat (installed on the end of the heating cable) and power cable with plug. Stop-Ice is particularly suitable for frost protection, and prevention of possible damages caused by low temperatures on pipes, valves, faucets, water meters, troughs, bowls and small tanks.

- Easy and quick to install
- No need for any external temperature control system, thanks to its built-in thermostat
- Low energy consumption

Product	Power (W/kit)	Specific power (W/m)	Length (m)
Stop Ice 2/12	24	12	2
Stop Ice 5/12	60	12	5
Stop Ice 10/12	120	12	10
Stop Ice 18/12	216	12	18



LINUS

Self-adhesive thermal insulating tape.

To offer a complete solution in the field of electrical tracking, Raytech has developed, LINUS, an insulation tape to maintain temperature. The product is a closed-cell expanded synthetic rubber, low thermal conductivity and extremely flexible tape. The rubber tape is coupled with an aluminium sheet to protect against tearing, for greater resistance to perforation and higher tensile resistance. It also protects very well against UV radiation. The tape is self-adhesive for easy application on traced pipes. The closed cells and the special material type give the tape very high insulating properties and optimal behaviour in the presence of condensation.

Product	Width (mm)	Thickness (mm)	Length (m)
LINUS	50	3	10
		pipe Ø ¾" (DN 20)	pipe Ø 1" (DN 25)
LENGTH PIPE I can insulate with 1 LINUS tape 50% overlapped	2,2 m	1,9 m	1,6 m



CHARACTERISTICS

Density: 0,7

Temperature range: -50°C -105°C

Coefficient of thermal conductivity (λ):

0,039 W/mK a 50°C

Flame resistance: Bs3-dO

(DIN EN 13501-1)

STOP ICE PLUS

Constant power anti-freeze kit complete with thermostat, connection plug and insulation tape.

STOP ICE + LINUS

- Stop Ice 12 W/m constant power cable, complete with connection plug and thermostat
- 3 mm LINUS insulation tape, for application on already traced pipe with a cable, to apply with 50% overlap

As an example, with a 10 m long LINUS tape, about 2.2 m of ¾", traced with the Stop Ice cable, can be insulated.

HEATING CABLE
BUILT-IN THERMOSTAT
BUILT-IN PLUG
 TAPE INSULATION
TO MAINTAIN TEMPERATURE



CABLE

Specific power: 12 W/m

Power supply: 230 V- 50Hz

Cold cable: 3 x 0,75 mm² - L = 1,5 m

Temperature control: integrated bimetallic thermostat

ON / OFF: +3°C / +10°C

INSULATION TAPE

Temperature range: -50 / +105°C

Coefficient of thermal conductivity (λ):

0,039 W/mK a 50°C

Dimensions: 50 mm x 3 mm x L10 m

Product	Power (W/kit)	Length cable (m)
Stop Ice Plus 2	24	2
Stop Ice Plus 5	60	5



Supply voltage: 230 V

Min installation temperature: -30°C

Cable dimensions: 7,7 x 5,3 mm

Max temperature with powered cable: 65°C

Max exposure temperature with non-powered cable: 65°C

ICE KILLER

Cut and install **self-regulating** cable kit, complete with connection side and termination kit.

The Ice Killer kit is composed of a 30 m self-regulating cable coil, complete with connection side and termination accessories. The cable can be cut to the desired length, installed on the pipe or tank, connected to the mains and terminated at the opposite end. The economic and compact Ice Killer kit is sold in an attractive, easy to carry, easy to handle on-site package, is small in size, very flexible and can be easily adapted to bends in the pipe.

The Ice Killer cable is laid linearly or wound around the pipe, depending on the specific necessary power. It is then fastened to the same by means of inextensible tape (Raytech MCA-FV or MCA-ALL75 type tapes), terminated with accessories contained in the kit and then clad with the insulation. Operating temperature is reached very quickly and is maintained almost constant even with room temperature variations.

Product	Specific power at 10°C (W/m)	Kit composition	
Ice Killer 2	10	30 m cable	Connection accessory
		Termination accessory	
Starting temperature			Maximum circuit length (m)
10 A electrical protection, characteristic C switch with differential 30 mA protection		Ice Killer 2	Ice Killer 6
		0°C -20°C	0°C -20°C
		95 77	58 41



MCA

Self-regulating cable for anti-freeze use or for maintaining temperatures for general use.

For anti-freeze use on pipes or tanks or for maintaining process temperatures under 65°C, even in hazardous areas. Maintenance-free, reliable, easy to install. Suitable even in the presence of mild inorganic solutions.

Product	Power voltage (V)	Minimum installation temperature (°C)	Power at 10°C (W/m)	TEMPERATURE MAX	
				Continuous cable powered (°C)	Intermittent cable not powered (°C)
MCA3	220-240	-30	10	65	80
MCA5	220-240	-30	15	65	80
MCA8	220-240	-30	25	65	80

ELECTRICAL SIZING	Starting temperature (°C)	MAXIMUM LENGTH OF THE CIRCUITS IN THE HEATING CABLE (m)								
		MCA3			MCA5			MCA8		
		+10°	-10°	-20°	+10°	-10°	-20°	+10°	-10°	-20°
Switchgear protection (A), with C curve and 30mA* differential protection*	10 A	-	-	-	103	71	62	64	47	37
	16 A	177	144	125	160	114	99	103	75	60
	20 A	-	149	139	-	133	124	126	94	75
	25 A	-	-	-	-	-	-	-	107	94

* Suggested where protection of people is requested; installations with no personnel admittance can be performed with 100 to 300 mA.




Pipe Ø	Thermal insulation thickness					
	10 mm		20 mm		30 mm	
Outer temperature (°C)						
inch mm	-10	-20	-10	-20	-10	-20
1/2" 15	1-3	1-3	1-3	1-3	1-3	1-3
3/4" 20	1-3	1-3	1-3	1-3	1-3	1-3
1" 25	1-3	1-8	1-3	1-3	1-3	1-3
1 1/4" 32	1-3	1-8	1-3	1-3	1-3	1-3
1 1/2" 40	1-3	1-8	1-3	1-3	1-3	1-3
2" 50	1-8	1-8	1-3	1-8	1-3	1-3
2 1/2" 65	1-8	1-8	1-3	1-8	1-3	1-3
3" 80	1-8	2-8	1-3	1-8	1-3	1-3
4" 100	1-8	2-8	1-5	1-8	1-3	1-5
6" 150	2-8	2-8	1-8	2-8	1-8	1-8
8" 200	2-8	-	1-8	2-8	1-8	1-8
10" 250	2-8	-	2-8	-	1-8	1-8

MCA connection accessories

	MCA Universal IP68 • Connection kit integrated with the terminal box. • Termination Kit. • Joint Kit.		MCA-Y Branch Kit.		MCA-BOX3 / 4 Connection boxes between heating cables or heating and power cables.		MCA-AL Thermal insulation pass-through kit.		MCA-PRESS Cable gland.		MCA-EA Warning label.		MCA-FV Glass fiber tape.		MCA-ALL Aluminium self adhesive tape 25 or 75 mm.
--	---	--	-----------------------------	--	---	--	---	--	----------------------------------	--	---------------------------------	--	------------------------------------	--	---

For other accessories see page 219



MCA

Self-regulating cable for pipe tracing for domestic hot water.

The tracing of domestic hot water systems allows you to always have the water at the ideal temperature available at each pick up point: this allows an energy saving (approximately up to 70%) also for the elimination of thermal losses in recirculation pipes. The pipes must always be insulated with suitable thermal insulation; for the choice and the project, please contact Raytech.

		MCA3	MCA5	MCA8	MCA10-I GF
TEMPERATURE (°C)	max operating	65°	65°	65°	120°
	max exposure*	80°	80°	80°	120°
	maintenance**	45°	55°	60°	80°
Available power	a 40°C (W/m)	6	8	14	25
Max length to be supplied with starting at 10°C through a switchgear	16 A	177	160	103	85
	20 A	-	-	126	114
	30 A	-	-	126	-
RECOMMENDED FOR		Small villas	Blocks of flats Buildings	Blocks of flats Buildings	Hotels Hospitals

*Circuit breakers with "C" curve, with a 30 mA differential.

**The indicated data is the limit maintenance temperature for which the cable can be used; for insulation sizing, please contact Raytech.

MCA connection accessories

	MCA Universal IP68 • Connection kit integrated with the terminal box. • Termination Kit. • Joint Kit.		MCA-Y Branch Kit.		MCA-BOX3 / 4 Connection boxes between heating cables or heating and power cables.		MCA-AL Thermal insulation pass-through kit.		MCA-PRESS Cable gland.		MCA-EA Warning label.		MCA-FV Glass fiber tape.		MCA-ALL Aluminium self adhesive tape 25 or 75 mm.
--	---	--	-----------------------------	--	---	--	---	--	----------------------------------	--	---------------------------------	--	------------------------------------	--	---


For other accessories see page 219

EASY CABLE


Constant, versatile power heating cable complete with termination accessory and power cable.

Especially suitable for solving anti-freeze problems: snow or ice accumulation on access ramps, walkways and stairs, or for frost protection of pipes or tanks, under adequate insulation. 3 standard lengths are available, with a specific power of 25 W/m, covering all possible tracking types. Complete with termination accessory and power cable, Easy cable is a shielded heating cable under a protective sheath with two conductors, with extremely simple and quick installation and connection. Please note that the cable should never be cut, spliced or overlapped.

FOR RAMPS		Specific power (W/m)	Rated power (W)	Maximum length for each individual wheel passage	
Product				40 cm (A) 4 passages	50 cm (B) 5 passages
Easy Cable 26/25 Length 26,5 m		25	655	6 m	5 m
Easy Cable 44/25 Length 44 m		25	1120	10,5 m	8,5 m
Easy Cable 92/25 Length 92 m		25	2270	22,5 m	18 m




Depth of installation about 50 mm with respect to the surface.



PER PIPING		Specific power (W/m)	Rated power (W)	Anti-freeze for pipes up to 2 1/2" (Dn 65 mm), for minimum temperatures up to -15°C, with rock wool thickness	Anti-freeze for pipes from 3" (Dn 80) up to 6" (Dn 200 mm), for minimum temperatures up to -15°C, with rock wool thickness
Product					
Easy Cable 26/25 Length 26,5 m		25	655	10 mm	20 mm
Easy Cable 44/25 Length 44 m		25	1120	10 mm	20 mm
Easy Cable 92/25 Length 92 m		25	2270	10 mm	20 mm

Anti-freeze tracking for piping, longitudinal linear installation 1 m cable/m pipe.



CHARACTERISTICS

Power supply: 230 V, 50/60 Hz
Cable dimensions: ~ 5x7 mm
Min. installation temperature: +5°C
Max. working temperature: +80°C
Heating cable type:
 2 conductors, screened cable
Specific power: 25 W/m
Insulation: XLPE
External sheath: PVC
Marking: CE

Control unit for Easy Cable for ramps.

C2000
 The C 2000 control unit, to be completed with the C2000-SR temperature, snow and humidity sensor (sensor to be placed flush with the ramp and to be ordered separately from the control unit), activating the power contactor, gives consent to start the system only when low temperature and snow or ice are present simultaneously, optimising energy consumption.

C2000-SR
 Temperature, snow and humidity sensor



ATTENTION: since it is a constant power cable, the EASY CABLE can not be cut, jointed or overlapped.

RAMPS - STEPS
WALKWAYS**CHARACTERISTICS****Mat specific power:** 300 W/m²**Power supply:** 230 V ~ 50/60 Hz**Mat thickness:** 7,5 mm**Min. installation temperature:** + 5°C**Max. working temperature:** + 80°C**Cold cable (supply):**length 4 meters - 3 x 1,5 mm² or 3x2,5 mm²**Heating cable type:**

2 conductors, screened cable

Heating cable dimensions: ~ 5 x 7 mm**Heating cable power:** 25 W/m**Insulation:** XLPE**External sheath:** PVC**Marking:** CE

EASY RAMP

Constant wattage heating mat.

Raytech Easy Ramp consists of a constant wattage heating cable assembled with tape to form a heating mat, which is easily and quickly spread on the surfaces to be protected. Easy Ramp is ideal for solving the problems caused by ice formation and the accumulation of snow on the access ramps to garages, pathways, outdoor parking areas, footpaths, etc. It can be installed in concrete, asphalt, and interlocking bricks or under porphyry paving or other paving materials blocked with cement and sand. The standard width of Easy Ramp pads is 60 cm; a sufficient width to free the track of vehicle wheels from ice and snow or to create an extremely safe pedestrian pathway.

The power density developed by Easy Ramp is 300 W/m². The mat is available in various lengths which are easily adaptable to the size of the area to track and where the size of the mat is larger than that of the ramp, the excess part of mat can be easily folded 90 degrees. The mat is supplied completely finished and ready for installation, complete with 4 meters of cold cable (3x1.5 mm² or 3x2.5 mm²) for connection to the power supply. The constant wattage heating cable, which constitutes the mat, is a 2 conductor heating cable, which is shielded; this allows one end only to be powered, making installation even faster and easier.

Product	Power (W)	Specific power (W/m ²)	Width (m)	Length (m)
Easy Ramp 4/300	670	300	0,6	4
Easy Ramp 7/300	1140	300	0,6	7
Easy Ramp 13/300	2560	300	0,6	13
Easy Ramp 21/300	3730	300	0,6	21



ATTENTION: since it is a constant power cable, the EASY RAMP can not be cut, jointed or overlapped.



MCA RAMP

Self-regulating heating cable.

The cable is used, buried in concrete, to prevent the accumulation of ice and its formation on access ramps, stairs, sidewalks, parking lots, walkways, etc. Suitable for ramps covered in concrete, interlocking brick or asphalt, both for light and heavy traffic. The cable can be installed on ramps under construction, securing the electrowelded mesh prior to pouring of the concrete, or else on already completed ramps by cutting the concrete surfaces to then fill with plastic cement after installation of the cable, or simply by laying the cable on the surface of the ramp and throwing another layer of cement. Contact Raytech for tracing designs and estimates.


Cable roofing cement or interlocking, asphalt, gneiss, and any other material

Product	Power at 0°C in concrete (W/m)	Max working temperature (°C)	Cable length Switgear*	Maximum length (m)
MCA 20-I-GF	90	120	40 A	64
MCA 10**	50	65	40 A	90

* Differential protection 30 mA

**For ramps, stairs etc. with ambient temperature not lower than -15°C; for lower temperatures use only MCA 20-I-GF cable. For draining trenches tracing MCA8 cable shall be used. For other information contact Raytech.

Notes: to trace drain outlets, use the MCA8 cable installed on the bottom of the outlets under the grate.



Control unit for Easy Ramp and MCA Ramp



C2000

The C 2000 control unit, to be completed with the C2000-SR temperature, snow and humidity sensor (sensor to be placed flush with the ramp and to be ordered separately from the control unit), activating the power contactor, gives consent to start the system only when low temperature and snow or ice are present simultaneously, optimising energy consumption.



C2000-SR

Temperature, snow and humidity sensor.

MCA Ramp connection accessories



MCA Universal IP68

- Connection kit integrated with the terminal box.
- Kit terminale lato non alimentato.
- Joint Kit.



MCA-BOX3 / 4

Connection boxes between heating cables or heating and power cables.



MCA-PRESS

Cable gland.

For other accessories see page 219

GUTTERS

**Power:** 20 W/m**Power supply:** 230 V ~ 50/60 Hz**Heating cable dimensions:** ~ 5 x 7 mm**Min. installation temperature:** + 5°C**Max. working temperature:** + 80°C**Cold cable (power supply):**length 4 meters - 3 x 1,0 mm² or 3 x 1,5 mm²**Heating cable type:**

2 conductors, screened cable

Insulation: XLPE**External sheath:** PVC**Min. bending radius:** 3,5 D**Marking:** CE

EASY FROST

Constant power heating cable for roofs, gutters and downpipes.

Raytech Easy Frost is a 20W/m constant power cable especially designed for roofs, gutters and downpipe protection from damage due to snow accumulation and ice formation. Easy Frost is supplied terminated and ready for installation, with 4 metres of cold cable (3 x 1,0 mm² o 3 x 1,5 mm²) for supply connection.


Product	Power (W)	Specific power (W/m)	Resistance (Ω)	Length (m)
Easy Frost 50/20	1000	20	52,9	50
Easy Frost 102/20	2040	20	29,9	102



Control unit for EASY FROST

**C2000**

The C 2000 control unit, to be completed with the C2000-SR temperature, snow and humidity sensor (sensor to be placed flush with the ramp and to be ordered separately from the control unit), activating the power contactor, gives consent to start the system only when low temperature and snow or ice are present simultaneously, optimising energy consumption.

**C2000-SUG**
Ice and snow sensor**C2000-STG**
Temperature sensor

Notes: control unit C2000 works only when connected to both the C2000-SUG and C2000-STG sensors.



ATTENTION: since it is a constant power cable, the *EASY FROST* can not be cut, jointed or overlapped.

MCA 8


Self-regulating cable for tracing roofs, gutters and/or downpipes.

Prevents

The formation of ice inside gutters and downspouts, snow accumulation and ice on roofs, the development of infiltrations along façades, the development of ice sticks along gutters and roof ends.

Avoiding

Gutter breaking under the weight of snow, bursting and fracturing of drainpipes due to water freezing, damaged caused by a lack of draining caused by drain clogging, damage to persons or property caused by falling ice sticks, damage to persons or property caused by possible snow slides off roofs from roof edges.



The image shows gutter installation, the input of cable in a downpipe and tracking of a roof pitch.

Product	In air 0°C Power (W/m)	In chilly water Power (W/m)	Maximum cable lenght with starting temperature of -10°C through a switchgear (*) of		
	16 A	20 A	30 A		
MCA8	24	40	40 m	50 m	90 m

*Switchgear with "C" characteristic, having a differential protection of 30 mA

Notes: the gutter cable is suspended along the down side of the drain pipes with accessory MCA-SUP. The cable is self-supporting up to 25 m vertical sections; in addition, an extra MCA-SUP accessory is provided for every 25 m, to which the cable is secured.



MCA 8 connection accessories

C2000 The C 2000 control unit, to be completed with the C2000-SR temperature, snow and humidity sensor (sensor to be placed flush with the ramp and to be ordered separately from the control unit), activating the power contactor, gives consent to start the system only when low temperature and snow or ice are present simultaneously, optimising energy consumption.	C2000-SUG Ice and snow sensor	C2000-STG Temperature sensor
---	---	--

Notes: control unit C2000 works only when connected to both the C2000-SUG and C2000-STG sensors.

MCA Universal IP68 <ul style="list-style-type: none"> • Connection kit integrated with the terminal box. • Kit terminale lato non alimentato. • Joint Kit. 	MCA-Y Branch Kit.	MCA-BOX3 / 4 Connection boxes between heating cables or heating and power cables.	MCA-SUP Support device.
---	-----------------------------	---	-----------------------------------

For other accessories see page 219



斯科亞斯

HEATING CABLES COMFORT HOUSE

FLOORING




EASY FLOOR

MIRROR



EASY MIRROR

CEILING



WARM-UP

COMFORT HOUSE

**PRIMARY, SECONDARY
OR FLOORING COMFORT HEATING SYSTEMS.**

Heating mats and intelligent timed thermostat: Raytech intelligent systems for primary, secondary and flooring heating comfort for homes, offices, kindergartens, schools and hospitals.

Combining the total reliability of the Raytech mat system with the RID microprocessor intelligent thermostat, it is possible to autonomously control all space heating parameters, as a primary means in less cold months and as a secondary means together with a more traditional system, and for comfort heating in bathrooms, kitchens, living rooms and children's bedrooms. After the first programming of the RID timed thermostat, you are free to forget about the system, which will run itself, ensuring optimal conditions.

**EASY FLOOR****The kit is composed of:**

- Heating mat complete with cold tail
- RID microprocessor intelligent room timed thermostat complete with sensor
- Corrugated pipe for positioning

Notes: -ST type kits are supplied without a RID room timed thermostat

CHARACTERISTICS

- **Mat power:** 150 W m²
- **Power supply:** 230 V ~ 50Hz
- **Thickness of the mat:** 5 mm
- **Min. temperature of installation:** + 5°C
- **Max. working temperature:** + 70°C
- **Cold cable (power supply):**

length : ~ 3,50 meters

Type of heating cable:

2 conductors, shielded

Heating cable dimensions: ~ Ø 5 mm**Heating cable power:** : ~ 10 W/m**Insulation:** XLPE**Outer sheath:** PVC**Marking:** CE

ATTENTION: since it is a constant power cable, the **EASY FLOOR** can not be cut, jointed or overlapped.

EASY FLOOR

Heating mat for the intelligent tracing of tile, marble, floors, etc.

The Easy Floor mat is laid directly on a layer of thermal insulation that coats the floor finished with concrete, and then buried in self-leveling concrete and covered with tiles. The flooring tracing mats are supplied in standard widths of 50 cm, power 150 W/m².

Product	Width (m)	Length (m)	Power (W)
Easy Floor 2	0,5	2	150
Easy Floor 3	0,5	3	225
Easy Floor 4	0,5	4	300
Easy Floor 2-ST	0,5	2	150
Easy Floor 3-ST	0,5	3	225
Easy Floor 4-ST	0,5	4	300

Other sizes available upon request.



RID RAYTECH INTELLIGENT DISPLAY

Intelligent room timed thermostat.

The RID (Raytech Intelligent Display) microprocessor room timed thermostat is simple to use, thanks to its step-by-step programming guide. The easy to read display supplies a complete explanation of set parameters after 10 seconds.

The RID autonomously controls all room functions, with no need for extra operations. Weekly programming makes it possible to take into account the set temperature to be maintained, the type and thickness of the flooring, temperature limits not to be exceeded, modes for increasing temperature, etc.

This device is equipped with an anti-freeze function when the house is not inhabited, a block for untimely interventions (for example children) and communicates any operating failures to the appropriate alarms.



Sensor	Included with the kit
Temperature range	+5 / +50°C
Temperature limit	+5 / +55°C
Start Up Programme	Automatic, self learning
Manual	0,1-10°C
Room temperature	0 / +40°C
Differential On/Off	Standard 0,4°C Adjustable 0,1-1°C
Power supply	230 V / 50-60 Hz
Self-consumption	5 W
Max output current	16 A (3400 W/220 V)

Product	(mm)
RID room thermostat	85 x 85 x 45



MIRROR




EASY MIRROR

Self-adhesive heating sheet.

No more fogged mirrors after a shower or bath! Easy Mirror, the self-adhering heating sheet to be applied on the back of the mirror and connected to the mains, eliminates this problem! Powered 230V, double insulated in accordance with safety regulations. Brings the surface of the mirror to 30°C in about 3-5 minutes, removing the film of moisture. Easy Mirror sheets are packaged with a sheet of laminated aluminium on polyester, with double insulation made with 4 more sheets of vulcanised polyester, completely sealed against water.

- Ideal for bathrooms, saunas, kitchens, private homes, Hotels, gyms and sports facilities

Product	Sheet dimensions (cm)	Power (W)
Easy Mirror 35	Ø 35	50
Easy Mirror 36/50	36 x 50	50



Installation Sequence



CEILING

HEATING CABLES
Comfort House

Ray
tech

CONSTANT POWER



Heat where you want it, when you want it



The ideal solution for all low thermal comfort environments.





WARM UP

Ceiling heating panels.

WARM-UP ceiling heating panels by Raytech can be installed invisibly and built into the ceiling of any home, office, showroom, workshop, greenhouse, camper vans etc., maximising space and freeing up wall space. Their positioning does not require any invasive procedures on the walls of the room, and their electrical connection is extremely simple. They can be installed, possibly placing them at the points where maximum thermal efficiency is required, with any mounting system: hung with chains, flush mounted, or recessed in false ceilings, always easily and quickly. The type of heating, based on infrared radiation, which makes it similar to solar radiation, is safe and unharful, quick, efficient and extremely comfortable.

Why choose the Warm-Up System?

- It is installed without requiring any invasive procedures to be carried out on the structures of the house.
- It is easily uninstalled for re-use in another context.
- Its radiated heat is safe, with no air movement, and does not dirty the walls and room.
- It is used for primary heating and for secondary heating as an integrative system, and optimises and reduces heating costs thanks to the RID-WL thermostat.

An ideally integrated invisible system that can also be decorative!



VERANDAS




PREFABRICATED BUILDINGS




EXHIBITION SPACES




GAZEBO






SUSPENDED



FIXED



ENCASED



Product	Colour	Power	Dimensions (mm)
Warm Up 1	White, Paintable	300 W	590 x 590 x 40
Warm Up 2		600 W	1190 x 590 x 40

What Are the Benefits to the System compared to others?


- Heating is immediate, in just a few minutes.
- It leaves room walls free because it is installed on the ceiling, flush mounted or recessed in false ceilings.
- It does not pollute, as it does not use gas or hydrocarbons.
- It optimises heating and reduces costs.
- Unlike other types of heating systems, it does not require maintenance!
- It uses the energy produced by photovoltaic systems, reducing heating costs.
- It can be coloured, and is therefore easily camouflaged or used as a decorative element.



STORES



OFFICES



WAREHOUSES - GARAGES



HOMES




Controlled by a timed thermostat or a power regulator, they reduce consumption to a minimum.

Class 2
degree of protection IP44

Power required for comfort heating:
about 60W/m²
(one Warm Up 1 panel every 5m²)

For primary heating with well-insulated walls:

about 150W/m²



WARM UP ACCESSORIES



Temperature accuracy: 0,1°C

Field of operation: from 0°C to +40°C

Field of temperature: from 5°C to +35°C

Power supply: 2 AAA 1.5 V batteries

Degree of protection: IP30

Frequency: 868 MHz

Powered receiver: 230 V, 50 Hz

Relay range: 8 A

Range in distance:

100 m outdoors, 30 m indoors

Programmable in 30 minute blocks
9 pre-installed programmes and
4 user-set programmes

"Self-learning" temperature control
Child lock
Low battery alarm

Unlimited programme memory
in the case of discharged batteries

RID-WL

Digital wireless timed thermostat.

Raytech has established the innovative WIRELESS RID-WL TIMED ROOM THERMOSTAT for maximum efficiency and speed and ease of installation. This system combines well-known reliability and control of environmental parameters of the system RID with a wireless connection.

The RID-WL, which operates in radio frequency, allows non-invasive installation in any environment, both for new installations and those related to renovations, or to reinforce an existing primary system.

The RID-WL is coupled with its own receiver, tuned to the frequency of its own thermostat (exclusive signal), which is able to control an ampacity of 8 A.

RID-WL, since it is not wired, it can be moved within the range of use and positioned where controlling the parameters is important.

It is equipped with an easy to read backlit LCD screen and is programmable and provided with a built-in internal sensor, but can be connected to a separate sensor, for example on the floor.

Product	Description
RID-WL	Timed thermostat including receiver



ADDITIONAL RELAY DEVICE

Additional relay device, with a maximum of 6 devices which can be controlled by the same RID-WL timed thermostat.

Product	Description
RID-WL-R	Additional receiver for loads greater than 8 A

Degree of protection: IP30

Frequency: 868 MHz

Powered receiver: 230 V, 50 Hz

Relay range: 8 A

Range in distance:

100 m outdoors, 30 m indoors

**HEATING CABLES
SELF-REGULATING
ACCESSORIES**



ACCESSORIES FOR SELF-REGULATING HEATING CABLES

(MCA, MCA-I-PF, MCA-I-GF, MCA-I-FF)


CONNECTION ACCESSORY



MCA UNIVERSAL IP68
Pre-filled gel joint



MCA BOX
Pre-filled gel boxes



MCA-PC + MCA-SG
Connection kit + Box
with terminal strip

DERIVATION ACCESSORY



MCA Y
Branch joint



MCA BOX
Pre-filled gel boxes

TERMINATION ACCESSORY



MCA UNIVERSAL IP68
Pre-filled gel joint



MCA PM
Termination kit.

AT LEAST ONE CONNECTION ACCESSORY AND ONE TERMINATION ACCESSORY ARE REQUIRED FOR EACH SECTION OF HEATING CABLE

CONNECTION
ACCESSORY

TERMINATION
ACCESSORY

L max: maximum length for each section
Refer to the ELECTRIC DIMENSIONING table on catalogue or project

IN CASE OF NEED TO MAKE DERIVATIONS, IT IS POSSIBLE TO USE THE RELEVANT ACCESSORIES;
A TERMINATION ACCESSORY IS THEN NEEDED FOR EACH BRANCH.

CONNECTION
ACCESSORY

L_1

DERIVATION
ACCESSORY

L_2

DERIVATION
ACCESSORY

L_N

TERMINATION
ACCESSORY

L_{D1}

TERMINATION
ACCESSORY

TERMINATION
ACCESSORY

The sum of the lengths of the sections under a single power supply must be less than Lmax
(please refer to the ELECTRIC DIMENSIONING table on catalogue or project)

$$L_1 + L_2 + L_{D1} + \dots + L_{DN} + L_N < L \text{ max}$$

MCA UNIVERSAL IP68

MCA-Y

Universal accessory for heating cable.

A revolutionary accessory is now available that is suitable for any type of self regulating heating cable either with or without screening. Its versatility provides a reliable unique solution unavailable elsewhere in the market. It has no shelf life and no tools are required during installation (including blow torches).



Product	Kit Composition	A x B x C (mm)
MCA Universal IP68	3 screw connectors to connect to the power cable or another heating cable	125 x 43 x 35
MCA-Y	3 screw connectors for branch connections between heating cables	160 x 75 x 37

Electrical:

CEI EN 50393 e CEI 20-33

(Notes: with testing under water head and water between the cable cores), in Class 2

Flame non propagation:


CEI 20-35, IEC 60332-1 and HD 405-1 (as applicable)

- Versatile and ready to use
- No need for tools
- Without heating
- Can be installed at any temperature
- Can be used directly underground
- Very compact
- Re-enterable
- Flame retardant
- The connections are automatically blocked when the joint is closed
- Screw connectors available with the kit
- Can be used underwater
- Pre-filled with a gel that is not-classified as hazardous under the CLP Directive and with no shelf life.


MCA-BOX

PRE-FILLED GEL CONNECTION BOXES FOR HEATING CABLES.


Boxes for single or multiple connections either between heating cables or heating and power cables. Ready to use, pre-filled with gel, complete with terminal block and screws, they allow the connection between heating cables and between heating cables and power cables, ensuring IP68 and IP69K degree of protection. They are suitable for power cables from 8 to 18 mm diameter and/or for power supplies with insulated wires in conduits of 16, 20, 25 and 32 mm diameter. MCA BOX is essential in damp environments and in areas subject to condensation or flooding. Available as either 3 or 4 entry in order to satisfy any installation requirement.



Product	Kit composition	A x B x C (mm)
MCA BOX 3	Gel-prefilled box Terminal block 3 x 6 mm ² + adaptors	90 x 90 x 45
MCA BOX 4	Gel-prefilled box Terminal block 4 x 6 mm ² + adaptors	120 x 100 x 45




MCA BOX 3




MCA BOX 4



**MCA-PC****CONNECTION KIT.**


Supply side termination allowing connections to a terminal box.
Made of cold-shrink components and also a dedicated cable gland.
One for each cable.

**MCA-AL****THERMAL INSULATION PASS-THROUGH.**


It allows the cable to pass through the metallic covering of the thermal insulation, avoiding abrasions and the moisture or water entry under the covering.
It contains cable gland and fixing plate.
One kit for each cable.

**MCA-PRESS****CABLE GLAND.**

To allow the cable to enter in boxes, to pass through walls etc.
One kit per cable.

**MCA-SG****BOX.**


Box with IP55 degree of protection, complete of terminals. It allows the entry of 1 or more heating cables, or to branch a cable from a main tracing, or to joint cable lengths. Cables inside the box shall be MCA-PC terminated.

**GUAT 26****CONNECTION KIT FOR CLASSIFIED AREA.****MCA-PM****TERMINATION KIT.**


For insulating and matching the cable ends. Made from cold-shrink components.
One kit for each termination.

**MCA-GL****JOINT KIT.**

To joint cable ends or to repair damaged cables.
It contains all the components required, including connectors.
One kit for each cable.

**MCA-SUP****SUPPORT DEVICE FOR GUTTERS AND DOWN PIPES.**

It supports and fixes the cable in gutters and downpipes. In large gutters, requiring 2 cables laid longitudinally, it maintains the cable at the right distance.

**MCA-FV****GLASS FIBER TAPE.**

To fix the cable to the pipe, 3 turns every 0,3 m of pipe.
Self adhesive, in 50 m rolls.


**MCA-ALL75****ALUMINIUM SELF ADHESIVE TAPE 75 MM WIDTH.**

For cable fixing, in 50 m rolls.

**MCA-EA****WARNING LABEL.**

To be applied for warning over traced items.

WARNING
ELECTRIC
TRACING



CONTROL UNIT C2000

C 2000 CONTROL UNIT FOR TEMPERATURE AND HUMIDITY.

The C2000 control unit and relative sensors are suitable for the tracing with both self-regulating cables and constant power cables. The unit allows you to power the system only when low temperatures and humid surfaces (snow - ice, etc.) are present simultaneously.



Segnalling lamps

- **ON** voltage
- **RELAY** cable on power
- **MOIST** humidity presence
- **TEMP** the temperature is lower than the fixed

Voltage: 230V c.a. +/- 10% 50/60Hz

Output: N° 1 relays

Switching capacity: 16A (3600 W)

Differential ON/OFF: 0,4°C

Temperature Range: 0-10°C


After run time: 1-6 hours

Protection degree: IP20

Dimensions: 85 x 42 x 48,8 mm

Weight: 252 gr

Room temperature: 0/50°C



C2000-SR

HUMIDITY AND TEMPERATURE SENSOR FOR RAMPS AND STAIRS.




Dimensions: h 32 mm - Ø 60 mm

Protection degree: IP68


Ambient temperature: -20°C / +70°C

Connecting cable: 6x1,5 mm², lenght. 10 m (possible increase up to 200 m)



C2000-SUG

ICE AND SNOW SENSOR FOR GUTTERS.



Dimensions: 105 x 30 x 10mm

Protection degree: IP68

Ambient temperature: -20°C / +70°C

Connecting cable: 4x1,5 mm², lenght 10 m (possible increase up to 200 m)

C2000-STG

TEMPERATURE SENSOR FOR GUTTERS.



Dimensions: 86 x 45 x 35 mm

Protection degree: IP55

Ambient temperature: -20°C / 70°C

Connecting cable: not included

T2000 THERMOSTAT

ON/OFF THERMOSTAT – P.I.D. 2 OUTPUTS WITH TEMPERATURE ALARM MANAGEMENT.

T2000 digital thermostats, complete with probe included in the kit, are suitable for control both in heating, maintenance and refrigeration.


Suitable for rear panel installation, on DIN guide, they are compact and they have controls and displays arranged frontally.



Characteristics T2000 thermostat

- **Measuring Range:** -40 a +105°C
- **Degree of protection:** IP40 (front)
- **2 outputs** with unipolar relay in deviation
- **Power supply:** 230 V a.c. ± 10 %
- **Contact capacity:** 240 Vac , 16 A (resistive); 4 A (inductive),
- **Self-consumption:** 3 W
- **Control:** ON/OFF or PID - Output ON or OFF depending on the incoming temperature, set point and hysteresis values set. The hysteresis is the value of the deviation from the set point that determines the reactivation of the output.
- **Alarm management:** output 2
- **Proportional control and integrative proportional**
- **Minimum or maximum set point limits**
- **Operating temperature:** -10 a +50°C
- **Dimensions:** L 71 x H 98 x W 61

CONNECTION DIAGRAM



T2000-S PROBE

(in thermostat kit included)

T2000 probe features

- **Type:** NTC10k
- **Measuring Range:** -40 a +105 °C
- **Precision** ± 1,5 K a 25 °C
- **Probe length:** 2 m
- **Connection cable:** bipolar (2 x 0.4 mm²)
- **Tip Dimensions:** Ø 6 x 34 mm
- **Degree of protection:** IP67





Data request form for the heating tracing design of
STEPS AND WALKWAYS

Company/Customer data:

Address:

E-mail:

Contact person:

Tel.:


STEPS

Number Steps _____

L step (cm) _____

H step (cm) _____

W step (cm) _____



Minimum environmental temperature -10°C -15°C -20°C


Availability of 3 phase supply Yes No

Available power (kW) _____ (Supply voltage 230V)

Notes: _____

WALKWAYS

Width Walkways (m) _____



Length Walkways (m) _____

Type of covering Concrete/Asphalt Self Locking/Porphyry

Total thickness Up to 6 cm Over 6 cm (max 10 cm)

Tracing type Complete Partial

Minimum environmental temp. -10°C -15°C -20°C Other _____ °C

Availability of 3 phase supply Yes No

Available power (kW) _____ (Supply voltage 230V)

Notes: _____

The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.



Data request form for the heating tracing design of
GUTTERS AND DOWNSPOUTS

Company/Customer data:

Address:

E-mail:

Contact person:

Tel.:

GUTTERS AND DOWNSPOUTS

Total number of gutters _____

Gutter width (cm) _____

Length of gutter n° 1 (m) _____

Length of gutter n° 2 (m) _____


Length of gutter n° 3 (m) _____

Length of gutter n° 4 (m) _____

Total number of downpipes _____

Downpipes average high (m) _____

Downpipes diameter (cm) _____



Is the gutter bitumen coated Yes No

Minimum environmental temp. -10°C -15°C -20°C Other _____ °C

Availability of 3 phase supply Yes No

Available power (kW) _____ (Supply voltage 230V)

Notes:

The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.



Data request form for the **heating tracing design** of
RAMPS

Company/Customer data:

Address:

E-mail:

Contact person:

Tel.:

TYPE OF TRACING




MCA SELF-REGULATING

- Complete
- Only wheel paths



EASY RAMP CONSTANT POWER

- Complete
- Only wheel paths



RAMP

Ramp width (m) _____

Ramp lenght (m) _____

Presence of:	Width (mm)	Length (m)	Grids distance from the upper end (m)
<input type="checkbox"/> Water collection grids			
<input type="checkbox"/> Grids			
<input type="checkbox"/> Expansion joints			
<input type="checkbox"/> Traps			

Type of covering

Concrete/Asphalt

Self Locking/Porphyry

Total thickness

Up to 6 cm

Over 6 cm (max 10 cm)

Type of traffic

One way

Two ways simultaneously

Minimum environmental temp. Up to -15°C

Severe < -15°C

Availability of 3 phase supply Yes No

Available power (kW) _____ (Supply voltage 230V)

Notes: _____

The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.



Data request form for the heating tracing design of
TERRACE/BALCONY AND ROOFS

Company/Customer data:

Address:

E-mail:

Contact person:

Tel.:

TERRACE/BALCONY

Width (m) _____

Length (m) _____


Type of covering Concrete Tarry

Minimum environmental temp. -10°C -15°C -20°C

Availability of 3 phase supply Si No

Available power (kW) _____ (Supply voltage 230V)

Notes:



ROOFS


Width (m) _____

Length (m) _____

Covering Tar/bitumen Yes No

Minimum environmental temp. -10°C -15°C -20°C

Availability of 3 phase supply Si No



Available power (kW) _____ (Supply voltage 230V)

Notes:

The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.

Data request form for the **heating tracing design** of
PIPING

Page 1/2

Company/Customer data:

Address:

E-mail:

Contact person:


Tel.:

PIPE DATA

(please send us the isometric drawing, if available)

Outer pipe diameter (cm) _____

Pipe lenght (m) _____

Material PVC/multilayer Steel or similar**TEMPERATURE DATA**Minimum environmental temp. -10°C -15°C -20°C Other _____ °CMaximum exposition temperature up to 60°C >60°CMaintenance temperature 5°C Antifreeze Other _____ °C**INSULATION**

Material

- Elastomer
- Glass fiber
- Mineral fiber
- Expanded Perlite
- Cellular polyurethane
- Rock wool
- Expanded polystyrene
- Calcium Silicate
- Other _____

**ACIDS
OR CORROSIVES** Yes NoSpecify the type
_____**Notes:**

Thickness (mm) _____

The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.

Pag. 2/2

AREA CLASSIFICATIONZone with risk of explosion: Yes No**IF THE AREA IS ATEX:****AREA CLASSIFICATION**Dangerous zone GAS zone 0 zone 1 zone 2Dangerous zone DUST zone 20 zone 21 zone 22**GAS GROUP CLASSIFICATION** I IIA IIIB IIIC**DUST GROUP CLASSIFICATION** IIIA IIIB IIIC**TEMP. CLASS CLASSIFICATION** T1 T2 T3 T4 T5 T6**CATEGORY (ATEX 94/9/Ec) Group II:** 1G 2G 3G 1D 2D 3D**EPL CLASSIFICATION** Ga Gb Gc Da Db Dc**VALVES – FLANGES – SUPPORTS – PUMPS (Number)**

Valves _____ Flanges _____ Supports _____ Pumps _____

FLUID TO BE HEATED (maintenance/heating)

- | | | |
|--|---|---|
| <input type="checkbox"/> Nitric acid | <input type="checkbox"/> Sulfur dioxide | <input type="checkbox"/> Ash (on average) |
| <input type="checkbox"/> Sulfuric Acid | <input type="checkbox"/> Air | <input type="checkbox"/> Ethane |
| <input type="checkbox"/> Water | <input type="checkbox"/> Nitrogen | <input type="checkbox"/> Hydrogen |
| <input type="checkbox"/> Water (100°) | <input type="checkbox"/> Liquid Nitrogen | <input type="checkbox"/> Methane |
| <input type="checkbox"/> Ethyl alcohol at 20°C | <input type="checkbox"/> Benzene and gasoline | <input type="checkbox"/> Olive oil (1,674 to 1,893) |
| <input type="checkbox"/> Carbon Dioxide | <input type="checkbox"/> Butane | <input type="checkbox"/> Petroleum (on average) |
| <input type="checkbox"/> Other _____ | | |

_____ Specific weight Kg/dm³

_____ Specific heat KJ/Kg °C

_____ Speed of the fluid in the pipe m/sec

Min. fluid temperature
at the heating start (°C)

_____ % of tank filling

Required final

_____ Required time to get
the final temperature (h)

temperature (°C)



Data request form for the heating tracing design of
SILOS AND TANKS

Page 1/2

Company/Customer data:

Address:

E-mail:

Contact person:

Tel.:

TYPES OF TANKS AND SILOS CYLINDRICAL


Ø cylinder (m) _____

Height (m) _____

CONICAL HOPPER (if present)


Ø coupling pipe (m) _____

Height (m) _____

 PARALLELEPIPED

W x D x H (m) _____

PYRAMIDAL HOPPER (if present)

W₂ x D₂ filler-neck x H₂ (m) _____Material PVC/multilayer Steel or similar Thickness (mm) _____**TEMPERATURE DATA**Minimum environmental temp. -10°C -15°C -20°C Other _____ °CMaximum exposition temperature Fino a 60°C >60°CMaintenance temperature 5°C Antifreeze Other _____ °C**INSULATION**

Material

- Elastomer
- Glass fiber
- Mineral fiber
- Expanded Perlite
- Cellular polyurethane
- Rock wool
- Expanded polystyrene
- Calcium Silicate
- Other _____

ACIDS OR CORROSIVES Yes No

Specify the type _____

Notes:

Thickness (mm) _____

The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.

Pag. 2/2

AREA CLASSIFICATIONZone with risk of explosion: Yes No**IF THE AREA IS ATEX:****AREA CLASSIFICATION**Dangerous zone GAS zone 0 zone 1 zone 2Dangerous zone DUST zone 20 zone 21 zone 22**GAS GROUP CLASSIFICATION** I IIA IIIB IIIC**DUST GROUP CLASSIFICATION** IIIA IIIB IIIC**TEMP. CLASS CLASSIFICATION** T1 T2 T3 T4 T5 T6**CATEGORY (ATEX 94/9/Ec) Group II:** 1G 2G 3G 1D 2D 3D**EPL CLASSIFICATION** Ga Gb Gc Da Db Dc**VALVES – FLANGES – SUPPORTS – PUMPS (Number)**

Valves _____ Flanges _____ Supports _____ Pumps _____

FLUID TO BE HEATED (maintenance/heating)

- | | | |
|--|---|---|
| <input type="checkbox"/> Nitric acid | <input type="checkbox"/> Sulfur dioxide | <input type="checkbox"/> Ash (on average) |
| <input type="checkbox"/> Sulfuric Acid | <input type="checkbox"/> Air | <input type="checkbox"/> Ethane |
| <input type="checkbox"/> Water | <input type="checkbox"/> Nitrogen | <input type="checkbox"/> Hydrogen |
| <input type="checkbox"/> Water (100°) | <input type="checkbox"/> Liquid Nitrogen | <input type="checkbox"/> Methane |
| <input type="checkbox"/> Ethyl alcohol at 20°C | <input type="checkbox"/> Benzene and gasoline | <input type="checkbox"/> Olive oil (1,674 to 1,893) |
| <input type="checkbox"/> Carbon Dioxide | <input type="checkbox"/> Butane | <input type="checkbox"/> Petroleum (on average) |
| <input type="checkbox"/> Other _____ | | |

_____ Specific weight Kg/dm³

_____ Specific heat KJ/Kg °C

_____ Speed of the fluid in the pipe m/sec

Min. fluid temperature
at the heating start (°C)

_____ % of tank filling

Required final

_____ Required time to get
the final temperature (h)

temperature (°C)



Data request form for the heating tracing design of
COMFORT - INDOOR FLOORS

Company/Customer data:

Address:

E-mail:

Contact person:

Tel.:

IMPORTANT:

Indoor floor tracings (ex. offices, homes) is usually considered as secondary/comfort heating system.
It can be considered as primary heating system, only in presence of well insulated environments.
For further information, please contact our technical office.

ROOM DATA

Is the floor well insulated?

No **Yes** Thickness (mm) _____

Are walls well insulated?

No **Yes** Thickness (mm) _____

Is the ceiling well insulated?

No **Yes** Thickness (mm) _____

Is there a primary heating system?

No **Yes**

Availability of 3 phase supply

No **Yes**

Available power (kW) _____ (Supply voltage 230V)

Room 1 Length x Width (m) _____ surface (m²) _____


Room 2 Length x Width (m) _____ surface (m²) _____

Room 3 Length x Width (m) _____ surface (m²) _____

Room 4 Length x Width (m) _____ surface (m²) _____

Room 5 Length x Width (m) _____ surface (m²) _____

**PLEASE ATTACH AT THE FORM A PLANIMETRY
OF THE TRACING AREA**



The applicant is reminded to enter in this form all data in his/her possession. The evaluation is carried out by Raytech on a free basis, to provide the customer with a rough list of Raytech Material suitable for the execution of the required tracement.

**CERTIFICATE OF CORRECT EXECUTION
OF INSULATION RESISTANCE MEASUREMENT TESTS AND
VERIFICATION OF SYSTEM FUNCTIONALITY, FOR EACH SECTION
OF SELF-REGULATING HEATING CABLE.**

To be filled in by the electrician installer

Customer:

Place of installation:

Tracing number:

Tracing type: Ramps Walkways Terrace Steps
 Gutter Roofs Piping Silos

WARNING: during cable laying and accessories installation, cable free ends must be protected against moisture ingress

Heating cable INSTALLED BY

Company: Operator: Date:

Fill in the table for each heating cable section

Heating cable section n. _____ Heating cable or mat type (code) _____

Heating cable section length (m) _____

Power connection ACCESSORY* (e.g. MCA UNIVERSAL IP68) _____

Termination ACCESSORY* (e.g. MCA UNIVERSAL IP68) _____

Straight or branch ACCESSORY* _____

*example MCA UNIVERSAL IP68

**MEASUREMENT OF INSULATION
RESISTANCE
(must exceed 20 MOhm)**

AFTER CABLE
LAYING
Measure A

AFTER APPLICATION OF THE COVERING
LAYER OR THERMAL INSULATION
Measure B

Between conductor 1 and screen (MOhm)

Between conductor 2 and screen (MOhm)

**VERIFICATION OF CABLE
FUNCTIONALITY, feeding the cable
section to the nominal voltage to
verify the suitability of the connection**

AFTER CABLE
LAYING
Measure A1
IN RUSH CURRENT **Measure A2**
In Regimen Conditions
(after 15')

AFTER APPLICATION OF THE COVERING
LAYER OR THERMAL INSULATION
Measure B1
IN RUSH CURRENT **Measure B2**
In Regimen Conditions
(after 15')

Current absorption (A)

CABLE INSTALLED AND TESTED BY:

Company

Operator

Date

Stamp end Signature

**CERTIFICATE OF CORRECT EXECUTION
OF INSULATION RESISTANCE MEASUREMENT TESTS AND
VERIFICATION OF SYSTEM FUNCTIONALITY, FOR EACH SECTION
OF CONSTANT POWER HEATING CABLE.**

To be filled in by the electrician installer

Customer:

Place of installation:

Tracing number:

Tracing type: Ramps Walkways Terrace Steps
 Gutter Roofs Piping Silos

Heating cable INSTALLED BY

Company: _____ Operator: _____ Date: _____

Fill in the table for each heating cable section

Heating cable section n. _____

Heating cable or mat type (code) _____

Heating cable / mat length (m) _____

RESISTANCE AND INSULATION TESTS (with 500 Vcc instrument)	JUST EXTRACTED THE CABLE FROM THE PACKAGE Measure A	AFTER CABLE LAYING ON THE SCREED OR PIPE Measure B	AFTER APPLICATION OF THE COVERING LAYER OR THERMAL INSULATION Measure C
Between resistance wires 1 and 2 (Ohm)			
Between wire 1 and ground (must be infinite)			
Between wire 2 and ground (must be infinite)			

VERIFICATION OF CABLE FUNCTIONALITY, feeding the cable section to the nominal voltage to verify the suitability of the connection	AFTER CABLE LAYING Measure B	AFTER APPLICATION OF THE COVERING LAYER OR THERMAL INSULATION Measure C
Current absorption (A)		

CABLE INSTALLED AND TESTED BY:

Company

Operator

Date

Stamp end Signature

ITEM CODES INDEX

Product	Item	Page
0-9		
250 RTD-20/A-3	250RTD20/A-3	182
250 RTD-20/B-3	250RTD20/B-3	182
250 RTD-20/C-3	250RTD20/C-3	182
250 RTS-20/A-3	250RTS20/A-3	182
250 RTS-20/B-3	250RTS20/B-3	182
250 RTS-20/C-3	250RTS20/C-3	182
630 RTO-20/A-3-C400	630RTO20/A3-C400	183
630 RTO-20/B-3-C400	630RTO20/B3-C400	183
630 RTO-20/C-3-C630	630RTO20/C3-C630	183
630 RTO-20/D-3-C630	630RTO20/D3-C630	183
630 RTO-30/A-3-C400	630RTO30/A3-C400	183
630 RTO-30/B-3-C400	630RTO30/B3-C400	183
630 RTO-30/C-3-C630	630RTO30/C3-C630	183
630 RTO-30/D-3-C630	630RTO30/D3-C630	183
630 RTT-20/A-3-C95	630RTT20/A-3-C95	183
630 RTT-20/B-3-C95	630RTT20/B-3-C95	183
630 RTT-20/C-3-C240	630RTT20/C3-C240	183
630 RTT-20/D-3-C300	630RTT20/D3-C300	183
630 RTT-30/A-3-C95	630RTT30/A-3-C95	183
630 RTT-30/B-3-C240	630RTT30/B3-C240	183
630 RTT-30/C-3-C300	630RTT30/C3-C300	183
A		
AUTO 10/120-E	10120-E-AUTO	152
AUTO 10/120-I	10120-I-AUTO	150
AUTO 10/240-E	10240-E-AUTO	152
AUTO 10/240-I	10240-I-AUTO	150
AUTO 10/300-E	10300-E-AUTO	152
AUTO 10/630-E	10630-E-AUTO	152
AUTO 10/630-I	10630-I-AUTO	150
AUTO 15/240-E	15240-E-AUTO	152
AUTO 15/240-I	15240-I-AUTO	150
AUTO 15/300-E	15300-E-AUTO	152
AUTO 15/630-E	15630-E-AUTO	152
AUTO 15/630-I	15630-I-AUTO	150
AUTO 15/70-E	1570-E-AUTO	152
AUTO 15/70-I	1570-I-AUTO	150
AUTO 20/185-E	20185-E-AUTO	152
AUTO 20/185-E-3	20185-E-3-AUTO	154
AUTO 20/185-E-3ARM	20185-E3ARM-AUTO	154
AUTO 20/185-I	20185-I-AUTO	150
AUTO 20/185-I-3	20185-I-3-AUTO	154
AUTO 20/185-I-3ARM	20185-I3ARM-AUTO	154
AUTO 20/240-E	20240-E-AUTO	152
AUTO 20/50-E	2050-E-AUTO	152
AUTO 20/50-E-3	2050-E-3-AUTO	154
AUTO 20/50-E-3ARM	2050-E-3ARM-AUTO	154
AUTO 20/50-I	2050-I-AUTO	150
AUTO 20/50-I-3	2050-I-3-AUTO	154
AUTO 20/50-I-3ARM	2050-I3ARM-AUTO	154
AUTO 20/630-E	20630-E-AUTO	152
AUTO 20/630-E-3	20630-E-3-AUTO	154
AUTO 20/630-E-3ARM	20630-E3ARM-AUTO	154
AUTO 20/630-I	20630-I-AUTO	150
AUTO 20/630-I-3	20630-I-3-AUTO	154
AUTO 20/630-I-3ARM	20630-I3ARM-AUTO	154
AUTO 30/120-E	30120-E-AUTO	152
AUTO 30/120-I	30120-I-AUTO	150
AUTO 30/240-E-3	30240-E-3-AUTO	154

Product	Item	Page
AUTO 30/240-E-3ARM	30240-E3ARM-AUTO	154
AUTO 30/240-I-3	30240-I-3-AUTO	154
AUTO 30/240-I-3ARM	30240-I3ARM-AUTO	154
AUTO 30/400-E	30400-E-AUTO	152
AUTO 30/400-I	30400-I-AUTO	150
AUTO 30/95-E	3095-E-AUTO	152
AUTO 30/95-E-3	3095-E-3-AUTO	154
AUTO 30/95-E-3ARM	3095-E3ARM-AUTO	154
AUTO 30/95-I	3095-I-AUTO	150
AUTO 30/95-I-3	3095-I-3-AUTO	154
AUTO 30/95-I-3ARM	3095-I3ARM-AUTO	154
B		
BABY BOX 3 IP68 Grey	BABYBOX3	30
BABY BOX 3 IP68 Black	BABYBOX3-N	30
BABY BOX IP68 Grey	BABYBOX	30
BABY BOX IP68 Black	BABYBOX-N	30
BAG GEL 200-R	BAGGEL200-R	12
BAG GEL 200-T	BAGGEL200-T	12
BAG GEL 400-R	BAGGEL400-R	12
BAG GEL 400-T	BAGGEL400-T	12
BAG RTV 200-N	BAGRTV200-N	141
BAG RTV 350-N	BAGRTV350-N	141
BAR (1 PC)	BAR	76
BAR PACK 9 (9 PCS)	BARP9	76
BARNEY (1 PC)	BARNEY	68
BARNEY Black (1 PC)	BARNEY-N	68
BARNEY Y (1 PC)	BARNEY-Y	68
BARNEY Y Black (1 PC)	BARNEY-Y/N	68
BARNEY-MP (10 PCS)	BARNEY-MP	68
BARNEY-Black - MP (10 PCS)	BARNEY-NMP	68
BBIT-100/40-A/U-4	560981-000	186
BBIT-150/60-A/U-4	560982-000	186
BBIT-175/80-A/U	426377-000	186
BBIT-25/10-A/U-4	5609274001	186
BBIT-40/16-A/U-4	560931-000	186
BBIT-65/25-A/U-4	5609364001	186
BBT 100/40-A/U	BBT100/40-AU	184
BBT 150/60-A/U	BBT150/60-AU	184
BBT 40/16-A/U	BBT40/16-AU	184
BBT 65/25-A/U	BBT65/25-AU	184
BETTY 4 (1 PC)	BETTY/4	68
BETTY 4 Black (1 PC)	BETTY/4-N	68
BETTY 6 (1 PC)	BETTY/6	68
BETTY 6 Black (1 PC)	BETTY/6-N	68
BETTY EASY (1 PC)	BETTY-EASY	66
BOB 3 (1 PC)	BOB3	28
BOB 3 Black (1 PC)	BOB3-N	28
BOB 4 (1 PC)	BOB4	28
BOB 4 Black (1 PC)	BOB4-N	28
BOPA 3	BOPA3-TEC	106
BOPA 3/2	BOPA3/2-TEC	106
BOPA 4	BOPA4-TEC	106
BOPA 4-T	784472-TEC	106
BOPA 5	BOPA5-TEC	106
BPM 120/50-A/U	BPM120/50-AU	184
BPM 15/6-A/U	BPM15/6-AU	184
BPM 30/12-A/U	BPM30/12-AU	184
BPM 50/20-A/U	BPM50/20-AU	184

Product	Item	Page
BPM 75/30-A/U	BPM75/30-AU	184
BPTM-100/40-A/U	178238-000	186
BPTM-120/50-A/U	412147-000	186
BPTM-15/6-A/U	5904284002	186
BPTM-175/70-A/U-4	920423-000	186
BPTM-205/110-A/U-4	499685-000	186
BPTM-30/12-A/U	723955-000	186
BPTM-50/20-A/U	2246244002	186
BPTM-75/30-A/U	6129164002	186
BRAVO 1-6 (1 PC)	BRAVO1-6	62
BRAVO 3-6 (1 PC)	BRAVO3-6	62
C 2000 SR Sensor	200009-000	224
C 2000	200001-000	224
C 2000-STG Sens Temp. Gutters	200005-000	224
C 2000-SUG Sens um Gutters	200004-000	224
Cable Gland Ø 20 mm	RAYPASS16	45
Cable Gland Ø 23,5 mm	RAYPASS21	45
Cable Gland Ø 32 mm	RAYPASS29	45
CGP-TEC-1.2/0.6-0 Black	5069794007	113
CGP-TEC-1.2/0.6-2 Red	5069674009	120
CGP-TEC-1.2/0.6-4 Yellow	5069674011	120
CGP-TEC-1.2/0.6-6 Blue	5069674010	120
CGP-TEC-1.2/0.6-9 White	5069914004	120
CGP-TEC-1.2/0.6-X Transparent	5069674008	120
CGP-TEC-1.6/0.8-0 Black	5069804009	113
CGP-TEC-1.6/0.8-2 Red	5068034005	120
CGP-TEC-1.6/0.8-4 Yellow	5068154005	120
CGP-TEC-1.6/0.8-6 Blue	5068274004	120
CGP-TEC-1.6/0.8 White	5069924005	120
CGP-TEC-1.6/0.8-X Transparent	5069684005	120
CGP-TEC-102/51-0 Black	5067164001	113
CGP-TEC-102/51-2 Red	5067204002	120
CGP-TEC-102/51-4 Yellow	5067204001	120
CGP-TEC-102/51-6 Blue	5068204003	120
CGP-TEC-102/51-9 White	254199-TEC	120
CGP-TEC-102/51-X Transparent	5067214001	120
CGP-TEC-12.7/6.4-0 Black	5069864018	113
CGP-TEC-12.7/6.4-2 Red	5068094006	120
CGP-TEC-12.7/6.4-4 Yellow	5068214005	120
CGP-TEC-12.7/6.4-6 Blue	5068334005	120
CGP-TEC-12.7/6.4-9 White	5069984005	120
CGP-TEC-12.7/6.4-X Transparent	5069744004	120
CGP-TEC-19/9.5-0 Black	5069874011	113
CGP-TEC-19/9.5-2 Red	5068104006	120
CGP-TEC-19/9.5-4 Yellow	5068224005	120
CGP-TEC-19/9.5-6 Blue	5068344005	120
CGP-TEC-19/9.5-9 White	5069944004	120
CGP-TEC-19/9.5-X Transparent	5069754005	120
CGP-TEC-2.4/1.2-0 Black	5069814012	113
CGP-TEC-2.4/1.2-2 Red	5068044005	120
CGP-TEC-2.4/1.2-4 Yellow	5068164005	120
CGP-TEC-2.4/1.2-6 Blue	5068284006	120
CGP-TEC-2.4/1.2-9 White	5069934006	120
CGP-TEC-2.4/1.2-X Transparent	5069694007	120
CGP-TEC-25.4/12.7-0 Black	5069884015	113
CGP-TEC-25.4/12.7-2 Red	5068114005	120
CGP-TEC-25.4/12.7-4 Yellow	5068234005	120

Product	Item	Page
CGP-TEC-25.4/12.7-6 Blue	5068354006	120
CGP-TEC-25.4/12.7-9 White	5068384005	120
CGP-TEC-25.4/12.7-X Transparent	5069764008	120
CGP-TEC-3.2/1.6-0 Black	5069824023	113
CGP-TEC-3.2/1.6-2 Red	5068054008	120
CGP-TEC-3.2/1.6-4 Yellow	5068174005	120
CGP-TEC-3.2/1.6-6 Blue	5068294010	120
CGP-TEC-3.2/1.6-9 White	5069944006	120
CGP-TEC-3.2/1.6-X Transparent	5069704005	120
CGP-TEC-38/19-0 Black	5069894005	113
CGP-TEC-38/19-2 Red	5068124001	120
CGP-TEC-38/19-4 Yellow	5068244001	120
CGP-TEC-38/19-6 Blue	5068364001	120
CGP-TEC-38/19-9 White	5068004001	120
CGP-TEC-38/19-X Transparent	5068364005	120
CGP-TEC-4.8/2.4-0 Black	5069834023	113
CGP-TEC-4.8/2.4-2 Red	5068064006	120
CGP-TEC-4.8/2.4-4 Yellow	5068184005	120
CGP-TEC-4.8/2.4-6 Blue	5068304007	120
CGP-TEC-4.8/2.4-9 White	5069954004	120
CGP-TEC-4.8/2.4-X Transparent	5069714007	120
CGP-TEC-51/26-0 Black	5069904003	113
CGP-TEC-51/26-2 Red	5068134001	120
CGP-TEC-51/26-4 Yellow	5068254001	120
CGP-TEC-51/26-6 Blue	5068374001	120
CGP-TEC-51/26-9 White	226598-TEC	120
CGP-TEC-51/26-X Transparent	5069784002	120
CGP-TEC-6.4/3.2-0 Black	5069844021	113
CGP-TEC-6.4/3.2-2 Red	5068074011	120
CGP-TEC-6.4/3.2-4 Yellow	5068194012	120
CGP-TEC-6.4/3.2-6 Blue	5068314009	120
CGP-TEC-6.4/3.2-9 White	5069964007	120
CGP-TEC-6.4/3.2-X Transparent	5069724010	120
CGP-TEC-76/38-0 Black	5067104003	113
CGP-TEC-76/38-2 Red	5067104002	120
CGP-TEC-76/38-4 Yellow	5067144001	120
CGP-TEC-76/38-6 Blue	889754-TEC	120
CGP-TEC-76/38 White	230701-000	120
CGP-TEC-76/38-X Transparent	763800-TEC	120
CGP-TEC-9.5/4.8-0 Black	5069854021	113
CGP-TEC-9.5/4.8-2 Red	5068084007	120
CGP-TEC-9.5/4.8-4 Yellow	5068204006	120
CGP-TEC-9.5/4.8-6 Blue	5068324006	120
CGP-TEC-9.5/4.8 White	5069974006	120
CGP-TEC-9.5/4.8-X Transparent	5069734006	120
CLIK 0 FIRE	214663-003	80
CLIK 0 FIRE-BL	CLIK0FIREBL	80
CLIK 1 FIRE AER/DAP	302008-000	81
CLIK 1 FIRE DOR/DOR	302009-000	81
CLIK 1 FIRE	225449-001	80
CLIK 1 FIRE-BL	CLIK1FIREBL	80
CLIK 2 FIRE DOR/PALO	301009-000	81
CLIK 2 FIRE DOR/PALO FUSE	301010-000	81
CLIK 2 FIRE	301096-001	80
CLIK 2 FIRE PREC/DAP	301008-000	81
CLIK 2000 FIRE	214663-004	80
CLIK 2001 FIRE	225448-002	80

Product	Item	Page
CLIK 2002 FIRE	301096-005	80
CLIK 2003 FIRE	301097-006	80
CHRONOTHERMOSTAT Complete with 16A receiver	RID-WL	218
D		
DCP-TEC-10/5-45	5038814001	113
DCP-TEC-12/6-45	5038114002	113
DCP-TEC-19/9-45	5038494001	113
DCP-TEC-26/13-45	5038184001	113
DCP-TEC-3/1.5-45	5038104002	113
DCP-TEC-38/19-45	5673904001	113
DCP-TEC-6/3-45	5038604008	113
DINO (1 PC)	DINO	68
DINO EASY (1 PC)	DINO-EASY	66
DINO Black (1 PC)	DINO-N	68
DINO Y (1 PC)	DINOY	68
DINO Y Black (1 PC)	DINOY-N	68
DJ 01	416127-000	106
DJ 02	396633-000	106
DJ 03	396634-000	106
DJ 4016-ARM-F/R	DJ4016ARM-FR	108
DJ 4016-F/R	DJ4016FR	108
E		
EASY CABLE 26/25	EASYCABLE2625	205
EASY CABLE 44/25	EASYCABLE4425	205
EASY CABLE 92/25	EASYCABLE9225	205
EASY FLOOR 2	EASYFLOOR2	212
EASY FLOOR 2-ST	EASYFLOOR2-ST	212
EASY FLOOR 3	EASYFLOOR3	212
EASY FLOOR 3-ST	EASYFLOOR3-ST	212
EASY FLOOR 4	EASYFLOOR4	212
EASY FLOOR 4-ST	EASYFLOOR4-ST	212
EASY FROST 102/20	EASYFROST10220	208
EASY FROST 50/20	EASYFROST5020	208
EASY MIRROR 35	EASYMIRROR35	214
EASY MIRROR 36/50	EASYMIRROR36/50	214
EASY RAMP 13/300	EASYRAMP13300	206
EASY RAMP 21/300	EASYRAMP21300	206
EASY RAMP 4/300	EASYRAMP4300	206
EASY RAMP 7/300	EASYRAMP7300	206
F		
FOX BOX	FOXBOX	34
FOX BOX - ARM	FOXBOX-ARM	34
FOX BOX 3	FOXBOX3	34
FOX BOX 3 ARM	FOXBOX3-ARM	34
FOX BOX 3 Black	FOXBOX3-N	34
FOX BOX Black	FOXBOX-N	34
FRED (1 PC)	FRED	68
FRED 4 (1 PC)	FRED/4	68
FRED 4 Black (1 PC)	FRED/4-N	68
FRED EASY (1 PC)	FRED-EASY	66
FRED Black (1 PC)	FRED-N	68
FRED Y (1 PC)	FRED-Y	68
FRED Y-Black (1 PC)	FRED-Y/N	68
FRED-MP (10 PCS)	FRED-MP	68
FSB-11	FSB-11	132
FSB-12	FSB-12	132
FSB-13	FSB-13	132
FSC 11	FSC-11	133

Product	Item	Page
FSC 12	FSC-12	133
FSC 13	FSC-13	133
FSC 14	FSC-14	133
FSC-TPC-050	FSC-TPC-050	135
FSC-TPC-060	FSC-TPC-060	135
FSC-TPC-090	FSC-TPC-090	135
FSC-TPC-120	FSC-TPC-120	135
FSCC 150	FSCC-150	137
FSCF 250	FSCF-250	136
FSCF 350	FSCF-350	136
FSCO T110	FSCO-T110	137
FSCP 1200	FSCP-1200	135
FSCP 600	FSCP-600	135
FSF 750	FSF-700	134
FSM 20	FSM-20	135
FSP-11	FSP-11	132
FSS 10	FSS-10	134
FSS-E-300	FSS-E-300	134
FSSE 01	FSSE01	136
FSSE 02	FSSE02	136
FST-E-25/32	FST-E-25/32	133
G		
GALACTIC ANIMAL BARRIER	GALACTIC-ANIBAR	140
GALACTIC MAMMUT SECURITY	GALACTIC-MAM	139
GALACTIC PROTECTION	GALACTIC-PROT	138
GALACTIC WATER STOP	GALAWATERSTOP	140
GASKET KIT	RAYGASKIT	142
GDL 92 A1	224578-TEC	104
GDL 92 A2	945252-TEC	104
GDL 92 A3	935251-000	104
GDL 92-PA	210254-TEC	104
GEL COVER 4	GELCOVER4	76
GEL COVER 6	GELCOVER6	76
GELBOX 0 (20 PCS)	GELBOX0	50
GELBOX 1 (15 PCS)	GELBOX1	50
GELBOX 2 (12 PCS)	GELBOX2	50
GHVE 15/300-1	442803-000	172
GHVE 15/300-1-H5	GHVE15/300-1-H5	172
GHVE 15/300-3	251291-000	175
GHVE 15/300-ARM	153000-001	175
GHVE 15/50-1	153003-000	172
GHVE 15/50-1-H5	GHVE15/50-1-H5	172
GHVE 15/50-3	545116-000	175
GHVE 15/50-ARM	155000-001	175
GHVE 15/630-1	357174-000	172
GHVE 15/630-1-H5	GHVE15/630-1-H5	172
GHVE 15/630-3	GHVE15/630-3	175
GHVE 15/630-ARM	GHVE15/630-ARM	175
GHVE 20/240-1	623051-000	172
GHVE 20/240-1-ARM	623052-000	172
GHVE 20/240-1-H5	GHVE20/240-1-H5	172
GHVE 20/240-1-T	GHVE20/240-1-T	176
GHVE 20/240-1-TE	GHVE20/240-1-TE	176
GHVE 20/240-1X-TE	GHVE20/240-1X-TE	176
GHVE 20/240-3	708732-000	175
GHVE 20/240-ARM	202400-001	175
GHVE 20/25-1-T	202500-000	176
GHVE 20/400-1-T	250499-000	176

Product	Item	Page
GHVE 20/630-1	GHVE20/630-1	172
GHVE 20/630-1-ARM	GHVE20/630-1-ARM	172
GHVE 20/630-1-H5	GHVE20/630-1-H5	172
GHVE 20/630-3	GHVE20/630-3	175
GHVE 20/630-ARM	GHVE20/630-ARM	175
GHVE 30/240-1	GHVE30/240-1	172
GHVE 30/240-1-ARM	GHVE30/240-1-ARM	172
GHVE 30/240-1-H5	GHVE30/240-1-H5	172
GHVE 30/240-3	GHVE30/240-3	175
GHVE 30/240-ARM	GHVE30/240-ARM	175
GHVE 30/300-3	GHVE30/300-3	175
GHVE 30/300-ARM	GHVE30/300-ARM	175
GHVE 30/500-1	GHVE30/500-1	172
GHVE 30/500-1-ARM	GHVE30/500-1-ARM	172
GHVE 30/500-1-H5	GHVE30/500-1-H5	172
GHVE-20/150-1-IS	080799-TEC	177
GHVE-20/150-1/U	478596-000	178
GHVE-20/185-1/U	512605-000	178
GHVE-20/240-1-IS	20GHIS-TEC	177
GHVP 20/240-1	GHVP20/240-1	172
GHVP 20/240-3	843918-000	175
GHVP 20/400-1	861101-000	172
GHVP 20/400-3	741685-000	175
GHVP 20/70-1	190901-000	172
GHVP 20/70-3	056242-000	175
GHVP-20/150-1/U	085563-000	178
GHVP-20/240-1-IS	159852-INT	177
GHVP-20/240-1/U	573299-000	178
GHVT 20/400-3X-1H	on request	177
GHVT-20/240-1X-3H	202019-000	177
GHVT-20/240-3X-1H	on request	177
GHVT-20/25-1X-3H	202020-000	177
GHVT-20/400-1X-3H	202021-000	177
GHVT-20/70-3X-1H	on request	177
GLV 0306	254656-TEC	104
GLV 0306-N	788459-000	104
GLV 0316	224477-TEC	104
GLV 0316-N	788429-000	104
GLV 0335	554268-TEC	104
GLV 0335-N	788460-000	104
GLV 0370	457896-TEC	104
GLV 0370-N	788461-000	104
GLV 0406	336598-TEC	104
GLV 0406-ARM	788969-000	106
GLV 0406-N	789995-000	104
GLV 0416	789890-000	104
GLV 0416-ARM	307689-000	106
GLV 0416-N	789996-000	104
GLV 0435	789891-000	104
GLV 0435-N	789997-000	104
GLV 0435-RP/16	GLV0435RP16	106
GLV 0450-ARM	630855-000	106
GLV 0470	234477-TEC	104
GLV 0470-N	789998-000	104
GLV 0470-RP/35	GLV0470RP35	106
GLV 0470-RP/50	GLV0470RP50	106
GLV 2.5-CP	411124-TEC	104

Product	Item	Page
GLV 3150	789992-000	104
GLV 3150-N	788462-000	104
GLV 3300	789994-000	104
GLV 3300-N	210054-TEC	104
GLV 4004-ARM-F/R	GLV4004-ARM-F/R	107
GLV 4004-F/R	GLV4004-F/R	107
GLV 4006-ARM-F/R-G7	GLV4006ARM-FR-G7	107
GLV 4006-F/R-G7	GLV4006-F/R-G7	107
GLV 4016-ARM-F/R	GLV4016-ARM-F/R	107
GLV 4016-ARM-F/R-G7	GLV4016ARM-FR-G7	107
GLV 4016-F/R	GLV4016-F/R	107
GLV 4016-F/R-G7	GLV4016-F/R-G7	107
GLV 4050-ARM-F/R	GLV4050-ARM-F/R	107
GLV 4050-ARM-F/R-G7	GLV4050ARM-FR-G7	107
GLV 4050-F/R	GLV4050-F/R	107
GLV 4050-F/R-G7	GLV4050-F/R-G7	107
GLV 4150	482979-000	104
GLV 4150-ARM	378703-000	106
GLV 4150-ARM-F/R	GLV4150-ARM-F/R	107
GLV 4150-ARM-F/R-G7	GLV4150ARM-FR-G7	107
GLV 4150-F/R	GLV4150-F/R	107
GLV 4150-F/R-G7	GLV4150-F/R-G7	107
GLV 4150-N	405718-000	104
GLV 4150-RP/150	GLV4150RP150	106
GLV 4300	609695-000	104
GLV 4300-ARM	152410-000	106
GLV 4300-N	788463-000	104
GMC 004-A	802965-000	108
GMC 007-A	786769-000	108
GMC 010	939629-000	108
GMC 019-A	803162-000	108
GMC 020	786828-000	108
GMC 030	946619-000	108
GMC 037-A	786412-000	108
GMC 050	934676-000	108
GMC 061-A	786355-000	108
GMC 100	156732-000	108
GMP 007 Junction Kit	786768-000	108
GMP 007-A	786686-000	108
GMP 007-ARM-F/R	GMP007-ARM-F/R	107
GMP 007-F/R	GMP007-F/R	107
GMP 014 Junction Kit	666635-TEC	108
GMP 014-A	786687-000	108
GMP 014-ARM-F/R	GMP014-ARM-F/R	107
GMP 014-ARM-F/R-G7	GMP014ARM-FR-G7	107
GMP 014-F/R	GMP014-F/R	107
GMP 014-F/R-G7	GMP014-F/R-G7	107
GMP 019-ARM-F/R-G7	GMP019ARM-FR-G7	107
GMP 019-F/R-G7	GMP019-F/R-G7	107
GMP 021 Junction Kit	786272-000	108
GMP 021-A	786785-000	108
GMP 030-ARM-F/R	GMP030-ARM-F/R	107
GMP 030-F/R	GMP030-F/R	107
GMP 040 Junction Kit	786684-000	108
GMP 040-A	786356-000	108
GMP 075 Junction Kit	786683-000	108
GMP 075-A	786689-000	108

Product	Item	Page
GMP 100 Junction Kit	786688-000	108
GUAT-26 KIT	012452-000	223
H HAPPY 0 BOX 12 (12 PCS)	HAPPY0BOX12	50
HAPPY 0 (4 PCS)	HAPPY0	50
HAPPY 1 BOX 10 (10 PCS)	HAPPY1BOX10	50
HAPPY 1 (2 PCS)	HAPPY1	50
HAPPY 2 BOX 7 (7 PCS)	HAPPY2BOX7	50
HAPPY 2 (1 PC)	HAPPY2	50
HAPPY JOINT 3 (4 PCS)	HAPPYJOINT3	52
HAPPY JOINT 36 (2 PCS)	HAPPYJOINT36	52
HAPPY JOINT 4 (2 PCS)	HAPPYJOINT4	52
HAPPY JOINT 46 (2 PCS)	HAPPYJOINT46	52
HAPPY JOINT 5 (2 PCS)	HAPPYJOINT5	52
HAPPY JOINT 56 (1 PC)	HAPPYJOINT56	52
HAPPY JOINT 6 (1 PC)	HAPPYJOINT6	52
HVBT-12-A	364471-000	187
HVBT-14-A	475743-000	187
HVBT-15-A	736143-000	187
HVBT-16-A	215370-000	187
I ICE KILLER 2	ICEKILLER2	202
ICE KILLER 6	ICEKILLER6	202
ISAAC 4 (4 PCS)	ISAAC4	54
ISAAC 4 MP (50 PCS)	ISAAC4MP	54
ISAAC 4 MP Orange (50 PCS)	ISAAC4-AMP	54
ISAAC 4 MP Blue (50 PCS)	ISAAC4-BMP	54
ISAAC 4 MP Yellow (50 PCS)	ISAAC4-GMP	54
ISAAC 4 MP Black (50 PCS)	ISAAC4-NMP	54
ISAAC 4 PACK 30 (30 PCS)	ISAAC4P30	54
IXSU-F-5121-IT01	200315-000	170
IXSU-F-5131-IT01	618429-000	170
IXSU-F-5131-IT02	364180-000	170
IXSU-F-5131-IT04	124400-TEC	171
IXSU-F-5151-IT01	897524-000	170
J JMAUTO 20/240-1	JM-20240-1-AUTO	156
JMAUTO 20/400-1	JM-20400-1-AUTO	156
JMAUTO 20/95-1	JM-2095-1-AUTO	156
JMAUTO 30/185-1	JMAUTO30/185-1	156
JMAUTO 30/300-1	JMAUTO30/300-1	156
JMAUTO 30/95-1	JMAUTO30/95-1	156
JOULE (1 PC)	JOULE	54
JOULE MP Orange (20 PCS)	JOULE-AMP	54
JOULE MP Blue (20 PCS)	JOULE-BMP	54
JOULE MP Yellow (20 PCS)	JOULE-GMP	54
JOULE MP Black (20 PCS)	JOULE-NMP	54
JOULE Multipack (20 PCS)	JOULEMP	54
K KELVIN +4	KELVIN-4	56
10 PCS+ 30 Terminals of 4 mm ²		
KELVIN +6	KELVIN-6	56
10 PCS+ 30 Terminals of 6 mm ²		
KELVIN 6+4	KELVIN6-4	56
6 PCS+ 20 Terminals of 4 mm ²		
KELVIN 6+6	KELVIN6-6	56
6 PCS+ 20 Terminals of 6 mm ²		
KELVIN M4	KELVINM4	56
6 PCS + 24 mammut da 4 mm ²		
KELVIN (1 PC)	KELVIN	54
KELVIN MP Orange (20 PCS)	KELVIN-AMP	54

Product	Item	Page
KELVIN MP Blue (20 PCS)	KELVIN-BMP	54
KELVIN MP Yellow (20 PCS)	KELVIN-GMP	54
KELVIN MP Black (20 PCS)	KELVIN-NMP	54
KELVIN Multipack (20 PCS)	KELVINMP	54
KELVIN PACK 9 (9 PCS)	KELVINP9	54
KING JOINT 0	RAYKJOINT0	82
KING JOINT 1	RAYKJOINT1	82
KING JOINT 2	RAYKJOINT2	82
KING JOINT L10	RAYKJOINTL10	82
KING JOINT L10 ARM	RAYKJL10ARM	82
KING JOINT L25	RAYKJOINTL25	82
KING JOINT L25 ARM	RAYKJL25ARM	82
KING JOINT L6	RAYKJOINTL6	82
KING JOINT Y 16	KINGJ-Y16	84
KING JOINT Y 35	KINGJ-Y35	84
KING JOINT Y 35-ARM	KINGJ-Y35ARM	84
KING JOINT Y 6	KINGJ-Y6	84
KING JOINT Y16 ARM	KINGJ-Y16ARM	84
KING JOINT Y6 ARM	KINGJ-Y6ARM	84
KIT CASSETTA 100x100x50	JBOX100	42
KIT CASSETTA 120x80x50	JBOX120	42
KIT CASSETTA 150x110x70	JBOX150	42
KIT CASSETTA 190x140x70	JBOX190	42
KIT CASSETTA 240x190x90	JBOX240	42
KIT CASSETTA 65x35	JBOX65	42
KIT CASSETTA 80x40	JBOX80	42
L LINUS	LINUS	201
LST-TEC-1.6-0 Black	6635996003	112
LST-TEC-1.6-6 Blue	5068276019	120
LST-TEC-1.6-Red	LSTTEC16-ROS	120
LST-TEC-12.7-0 Black	1963796004	112
LST-TEC-12.7-6 Blue	5068336020	120
LST-TEC-12.7-Red	LSTTEC127-ROS	120
LST-TEC-19.0-0 Black	9601076004	112
LST-TEC-19.0-6 Blue	5068346012	120
LST-TEC-19.0-Red	LSTTEC190-ROS	120
LST-TEC-2.4-0 Black	7284836003	112
LST-TEC-2.4-6 Blue	5068286021	120
LST-TEC-2.4-Red	LSTTEC24-ROS	120
LST-TEC-25.4-0 Black	2348536003	112
LST-TEC-25.4-6 Blue	5068356017	120
LST-TEC-25.4-Red	LSTTEC254-ROS	120
LST-TEC-3.2-0 Black	0316676003	112
LST-TEC-3.2-6 Blue	5068296023	120
LST-TEC-3.2-Red	LSTTEC32-ROS	120
LST-TEC-4.8-0 Black	3876656003	112
LST-TEC-4.8-6 Blue	5068306020	120
LST-TEC-4.8-Red	LSTTEC48-ROS	120
LST-TEC-6.4-0 Black	3363736003	112
LST-TEC-6.4-6 Blue	5068316033	120
LST-TEC-6.4-Red	LSTTEC64-ROS	120
LST-TEC-9.5-0 Black	0915756003	112
LST-TEC-9.5-6 Blue	5068326022	120
LST-TEC-9.5-Red	LSTTEC95-ROS	120
LST-TEC-GV-3/1.5	5038106035	112
LST-TEC-GV-6/3	5038606049	112
LST-TEC-GV-10/5	5038816019	112

Product	Item	Page
LST-TEC-GV-12/6	5038812764	112
LST-TEC-GV-19/9	5038496027	112
LST-TEC-GV-26/13	5038186026	112
LST-TEC-GV-4.8/2.4	5038814824	112
LTPSM-180/58-500/PE	LTPSM180/58-500	118
LTPSM-245/80-500/PE	LTPSM245/80-500	118
M MAGIC BOX 100	MAGICBOX100	36
MAGIC BOX 120	MAGICBOX120	36
MAGIC BOX 150	MAGICBOX150	36
MAGIC BOX 190	MAGICBOX190	36
MAGIC BOX 240	MAGICBOX240	36
MAGIC BOX 65	MAGICBOX65	36
MAGIC BOX 80	MAGICBOX80	36
MAGIC FLUID 110	100110-MAG	8
MAGIC FLUID 170	100170-MAG	8
MAGIC FLUID 210	100210-MAG	8
MAGIC FLUID 420	100420-MAG	8
MAGIC FLUID 550	100550-MAG	8
MAGIC FLUID 90	100090-MAG	8
MAGIC GEL 1000	MAGIC-GEL	8
MAGIC GEL 10000	MAGICGEL10	8
MAGIC GEL 2000	MAGICGEL-2000	8
MAGIC GEL 300	MAGICGEL-300	8
MAGIC GEL 420	MAGICGEL-420	8
MAGIC GEL SPRINT 450	MAGICSPRINT450	6
MAGIC GEL SPRINT 900	MAGICSPRINT900	6
MAGIC GEL SPRINT BOX100	MAGICSPRINTBOX1	41
MAGIC JOINT 10	100001-MAG	94
MAGIC JOINT 120	100007-MAG	94
MAGIC JOINT 240	100004-MAG	94
MAGIC JOINT 25	100002-MAG	94
MAGIC JOINT 300	100009-000	94
MAGIC JOINT 35	100035-002	94
MAGIC JOINT 4	100004-002	94
MAGIC JOINT 50	100005-MAG	94
MAGIC JOINT 95	100003-MAG	94
MAGIC JOINT L120-RP/120	MAGICJL120RP120	96
MAGIC JOINT L240-RP/150	MAGICJL240RP150	96
MAGIC JOINT L35-RP/16	MAGICJL35RP16	96
MAGIC JOINT L35-RP/35	MAGICJL35RP35	96
MAGIC JOINT L50-RP/50	MAGICJL50RP50	96
MAGIC JOINT SP L16	MAGICJSPL16	96
MAGIC JOINT SP L25	MAGICJSPL25	96
MAGIC JOINT SP L6	MAGICJSPL6	96
MAGIC JOINT SP T35	MAGICJSPT35	96
MAGIC JOINT SP Y16	MAGICJSPY16	96
MAGIC JOINT SP Y6	MAGICJSPY6	96
MAGIC JOINT Y240	100240-MAG	94
MAGIC JOINT Y25	100025-MAG	94
MAGIC JOINT Y6 O	100006-MAG	94
MAGIC JOINT Y95	100095-MAG	94
MAGIC POWER GEL 250	MAGICPOWER-250	10
MAGIC POWER GEL 500	MAGICPOWER-500	10
MAGIC POWER GEL BAG 150	MAGICPOWERB150	10
MAGIC POWER GEL BAG 250	MAGICPOWERB250	10
MAGIC POWER GEL	MAGICPOWER-GEL	10
MAGIC POWER JOINT L10	MPOWERJOINT-L10	88

Product	Item	Page
MAGIC POWER JOINT L10 - ARM	MPJOINTL10-ARM	91
MAGIC POWER JOINT L10-S	MPOWERJOINT-L10S	90
MAGIC POWER JOINT L120	MPOWERJOINT-L120	88
MAGIC POWER JOINT L120 - ARM	MPJOINTL120-ARM	91
MAGIC POWER JOINT L120-RP/120	MPOWERJL120RP120	93
MAGIC POWER JOINT L120-S	MPOWERJOINTL120S	90
MAGIC POWER JOINT L240	MPOWERJOINT-L240	88
MAGIC POWER JOINT L240 - ARM	MPJOINTL240-ARM	91
MAGIC POWER JOINT L240-RP/150	MPOWERJL240RP150	93
MAGIC POWER JOINT L240-S	MPOWERJOINTL240S	90
MAGIC POWER JOINT L25	MPOWERJOINT-L25	88
MAGIC POWER JOINT L25 - ARM	MPJOINTL25-ARM	91
MAGIC POWER JOINT L25-S	MPOWERJOINT-L25S	90
MAGIC POWER JOINT L300	MPOWERJOINT-L300	88
MAGIC POWER JOINT L300 - ARM	MPJOINTL300-ARM	91
MAGIC POWER JOINT L300-S	MPOWERJOINTL300S	90
MAGIC POWER JOINT L35	MPOWERJOINT-L35	88
MAGIC POWER JOINT L35 - ARM	MPJOINTL35-ARM	91
MAGIC POWER JOINT L35-RP/16	MPOWERJL35RP16	93
MAGIC POWER JOINT L35-RP/35	MPOWERJL35RP35	93
MAGIC POWER JOINT L35-S	MPOWERJOINT-L35S	90
MAGIC POWER JOINT L50	MPOWERJOINT-L50	88
MAGIC POWER JOINT L50 - ARM	MPJOINTL50-ARM	91
MAGIC POWER JOINT L50-RP/50	MPOWERJL50RP50	93
MAGIC POWER JOINT L50-S	MPOWERJOINT-L50S	90
MAGIC POWER JOINT L95	MPOWERJOINT-L95	88
MAGIC POWER JOINT SL11	MPOWERJOINTSL11	92
MAGIC POWER JOINT SL12	MPOWERJOINTSL12	92
MAGIC POWER JOINT SL13	MPOWERJOINTSL13	92
MAGIC POWER JOINT SL14	MPOWERJOINTSL14	92
MAGIC POWER JOINT SL15	MPOWERJOINTSL15	92
MAGIC POWER JOINT SL16	MPOWERJOINTSL16	92
MAGIC POWER JOINT SL17	MPOWERJOINTSL17	92
MAGIC POWER JOINT SP L16	MPOWERJSPL16	93
MAGIC POWER JOINT SP L25	MPOWERJSPL25	93
MAGIC POWER JOINT SP L6	MPOWERJSPL6	93
MAGIC POWER JOINT SP T35	MPOWERJSPT35	93
MAGIC POWER JOINT SP Y16	MPOWERJSPY16	93
MAGIC POWER JOINT SP Y6	MPOWERJSPY6	93
MAGIC POWER JOINT SY1	MPOWERJOINTSY1	92
MAGIC POWER JOINT SY2	MPOWERJOINTSY2	92
MAGIC POWER JOINT SY3	MPOWERJOINTSY3	92
MAGIC POWER JOINT SY4	MPOWERJOINTSY4	92
MAGIC POWER JOINT T1000	MPOWERJOINTT1000	92
MAGIC POWER JOINT T16	MPOWERJOINT-T16	92
MAGIC POWER JOINT T25	MPOWERJOINT-T25	92
MAGIC POWER JOINT T35	MPOWERJOINT-T35	92
MAGIC POWER JOINT T40	MPOWERJOINT-T40	92
MAGIC POWER JOINT T500	MPOWERJOINT-T500	92
MAGIC POWER JOINT T64	MPOWERJOINT-T64	92
MAGIC POWER JOINT TS1000	MPOWERJ-TS1000	92
MAGIC POWER JOINT TS16	MPOWERJOINT-TS16	92
MAGIC POWER JOINT TS25	MPOWERJOINT-TS25	92
MAGIC POWER JOINT TS35	MPOWERJOINT-TS35	92
MAGIC POWER JOINT TS40	MPOWERJOINT-TS40	92
MAGIC POWER JOINT TS500	MPOWERJOINTTS500	92
MAGIC POWER JOINT TS64	MPOWERJOINT-TS64	92

Product	Item	Page
MAGIC POWER JOINT Y240	MPOWERJOINT-Y240	88
MAGIC POWER JOINT Y240 - ARM	MPJOINTY240-ARM	91
MAGIC POWER JOINT Y240- ARM-F	MPJOINTY240ARM-F	91
MAGIC POWER JOINT Y240-S	MPOWERJOINTY240S	90
MAGIC POWER JOINT Y25	MPOWERJOINT-Y25	88
MAGIC POWER JOINT Y25 - ARM	MPJOINTY25-ARM	91
MAGIC POWER JOINT Y25- ARM-F	MPJOINTY25-ARM-F	91
MAGIC POWER JOINT Y25-S	MPOWERJOINT-Y25S	90
MAGIC POWER JOINT Y6	MPOWERJOINT-Y6	88
MAGIC POWER JOINT Y6 - ARM	MPJOINTY6-ARM	91
MAGIC POWER JOINT Y6 - ARM-F	MPJOINTY6-ARM-F	91
MAGIC POWER JOINT Y6-S	MPOWERJOINT-Y6S	90
MAGIC POWER JOINT Y95	MPOWERJOINT-Y95	88
MAGIC POWER JOINT Y95 - ARM	MPJOINTY95-ARM	91
MAGIC POWER JOINT Y95 - ARM-F	MPJOINTY95-ARM-F	91
MAGIC POWER JOINT Y95-S	MPOWERJOINT-Y95S	90
MAGIC RUBBER 10000	MAGICRUBBER-10	21
MAGIC RUBBER	MAGIC-RUBBER	21
MAMMUT GEL COVER	MAMMUTGELCOVER	76
MAMMUT GEL COVER 6	MAMMUTGELCOVER6	76
MAXI ROLL 1.6 Black	MAXIROLL-1.6	113
MAXI ROLL 12.7 Black	MAXIROLL-12.7	113
MAXI ROLL 19.0 Black	MAXIROLL-19.0	113
MAXI ROLL 2.4 Black	MAXIROLL-2.4	113
MAXI ROLL 25.4 Black	MAXIROLL-25.4	113
MAXI ROLL 3.2 Black	MAXIROLL-3.2	113
MAXI ROLL 4.8 Black	MAXIROLL-4.8	113
MAXI ROLL 6.4 Black	MAXIROLL-6.4	113
MAXI ROLL 9.5 Black	MAXIROLL-9.5	113
MCA 10	220799-000	194
MCA 10-I-FF	200137-000	197
MCA 10-I-GF	261098-000	196
MCA 10-I-PF	261097-000	195
MCA 13-I	MCA13-I	194
MCA 13-I-PF	MCA13-I-PF	195
MCA 15-I-FF	MCA15-I-FF	197
MCA 20-I-FF	200138-000	197
MCA 3	320102-000	194 203
MCA 3 I-PF	200129-000	195
MCA 3-I-FF	200134-000	197
MCA 3-I-GF	200131-000	196
MCA 5	320103-000	194 203
MCA 5 I-PF	261099-000	195
MCA 5-I-FF	200135-000	197
MCA 5-I-GF	200132-000	196
MCA 7-I-FF	MCA7-I-FF	197
MCA 7-I-PF	MCA7-I-PF	195
MCA 8	320104-000	194 203 209
MCA 8 I-PF	200128-000	195
MCA 8-I-GF	200133-000	196
MCA BOX 3	MCABOX3	222
MCA BOX 4	MCABOX4	222
MCA UNIVERSAL IP68	MCA-UNIVERSAL	221

Product	Item	Page
MCA-20- I-GF	320105-000	196 207
MCA-AL KIT	RK16.02-00	223
MCA-ALL.75	R42562	125
MCA-EA	014211-000	223
MCA-FV	012521-000	125
MCA-GL Junction Kit	120021-TEC	223
MCA-PC Connection kit	123110-TEC	223
MCA-PM	012511-000	223
MCA-PRESS Cable Gland Kit	014144-000	223
MCA-SG	MCASG-TEC	223
MCA-SUP	RARAKE-000	223
MCA-Y	MCA-Y	221
MINI BRAVO 1 (3 PCS)	MINIBRAVO1	60
MINI BRAVO 2 (1 PC)	MINIBRAVO2	60
MINI BRAVO 3 (1 PC)	MINIBRAVO3	60
MONOGEL	MONOGEL	17
MTN-10/3-1000/172	MTN1031000172	116
MTN-115/34-1000/172	MTN115341000172	116
MTN-16/5-1000/172	MTN1651000172	116
MTN-25/8-1000/172	MTN2581000172	116
MTN-35/12-1000/172	MTN35121000172	116
MTN-50/16-1000/172	MTN50161000172	116
MTN-63/19-1000/172	MTN63191000172	116
MTN-75/22-1000/172	MTN75221000172	116
MTN-85/25-1000/172	MTN85251000172	116
MTN-95/29-1000/172	MTN95291000172	116
MTR-10/3-1000-172	488809-000	116
MTR-10/3-1000/U	854745-000	116
MTR-10/3-A/U-4	283807-000	116
MTR-115/34-1000/172	827835-000	116
MTR-115/34-1000/U	036893-000	116
MTR-140/42-1000/172	891939-000	116
MTR-140/42-1000/U	149759-000	116
MTR-16/5-1000-172	925679-000	116
MTR-16/5-1000/U	411365-000	116
MTR-16/5-A/U	497587-000	116
MTR-160/55-1000/172	474381-000	116
MTR-180/60-1000/172	323497-000	116
MTR-180/60-1000/U	827643-000	116
MTR-25/8-1000-172	717783-000	116
MTR-25/8-1000/U	082743-000	116
MTR-25/8-A/U-4	651145-000	116
MTR-35/12-1000-172	064641-000	116
MTR-35/12-1000/U	089407-000	116
MTR-35/12-A/U-4	981425-000	116
MTR-50/16-1000-172	046911-000	116
MTR-50/16-1000/U	738765-000	116
MTR-50/16-A/U-4	035001-000	116
MTR-63/19-1000-172	223993-000	116
MTR-63/19-1000/U	644113-000	116
MTR-63/19-A/U-4	874903-000	116
MTR-75/22-1000/172	237137-000	116

Product	Item	Page
MTR-75/22-1000/U	605711-000	116
MTR-75/22-A/U-4	373921-000	116
MTR-85/25-1000/172	727282-000	116
MTR-85/25-1000/U	917867-000	116
MTR-95/29-1000/172	498559-000	116
MTR-95/29-1000/U	355919-000	116
MTR160/50-1000/U	938745-000	116
N NANO 3 (4 PCS)	NANO3	57
NANO 5 (2 PCS)	NANO5	57
NANO 6 (1 PC)	NANO6	57
NANO FOR-2.5 (1 PC)	NANOFOR-2.5	57
NANO FOR-4 (1 PC)	NANOFOR-4	57
NANO MAM-2.5 (2 PCS)	NANOMAM-2.5	57
NANO MAM-4 (1 PC)	NANOMAM-4	57
O OHM (1 PC)	OHM	76
OHM PACK 11 (11 PC)	OHMP11	76
OXSU-F-5131-IT01	365890-000	170
OXSU-F-5131-IT02	123020-000	170
OXSU-F-5131-IT03	124500-TEC	171
P PASCAL M2,5 12 PCS + 36 mammut 2,5 mm ²	PASCALM2.5	56
PASCAL 6 (2 PCS)	PASCAL6	54
PASCAL 6 MP (25 PCS)	PASCAL6MP	54
PASCAL 6 MP Orange (25 PCS)	PASCAL6-AMP	54
PASCAL 6 MP Blue (25 PCS)	PASCAL6-BMP	54
PASCAL 6 MP Yellow (25 PCS)	PASCAL6-GMP	54
PASCAL 6 MP Black (25 PCS)	PASCAL6-NMP	54
PASCAL 6 PACK 15 (15 PCS)	PASCAL6P15	54
POWER KIT 100	POWER-100	40
POWER KIT 120	POWER-120	40
POWER KIT 65	POWER-65	40
POWER KIT 80	POWER-80	40
R RAPID JOINT L1,5-IP68	RAPIDJL1.5-IP68	72
RAPID JOINT L10	301098-004	85
RAPID JOINT L10 RP	RAPIDJL10RP	87
RAPID JOINT L10-ARM	301098-10ARM	86
RAPID JOINT L10-IP68	RAPIDJL10-IP68	72
RAPID JOINT L10-S	301098-035	86
RAPID JOINT L25	301098-006	85
RAPID JOINT L25 RP	RAPIDJL25RP	87
RAPID JOINT L25-ARM	301098-25ARM	86
RAPID JOINT L25-IP68	RAPIDJL25-IP68	72
RAPID JOINT L25-S	301098-036	86
RAPID JOINT L6	301098-037	85
RAPID JOINT L6-IP68	RAPIDJL6-IP68	72
RAPID JOINT L95	301098-003	85
RAPID JOINT L95 RP	RAPIDJL95RP	87
RAPID JOINT L95-ARM	301098-016	86
RAPID JOINT L95-S	301098-012	86
RAPID JOINT-LS1	301098-018	86
RAPID JOINT-LS2	301098-019	86
RAPID JOINT-LS3	301098-020	86
RAPID JOINT-T101	301098-023	86
RAPID JOINT-T26	301098-021	86
RAPID JOINT-T61	301098-022	86
RAPID JOINT-TS101	301098-026	86
RAPID JOINT-TS26	301098-024	86

Product	Item	Page
RAPID JOINT-TS61	301098-025	86
RAPIDINO IP68 L2	RAPIDINOL2	70
RAPIDINO IP68 L3	RAPIDINOL3	70
RAPIDINO IP68 L4	RAPIDINOL4	70
RAPIDINO IP68 Y1	RAPIDINOY1	70
RAPIDINO IP68 Y3	RAPIDINOY3	70
RAY COPPER 1000	COPPER-100	125
RAY COPPER 2000	COPPER-200	125
RAY COPPER 3000	COPPER-300	125
RAY COPPER 5000	COPPER-500	125
RAY COPPER 6000	COPPER-600	125
RAY GEL 10 K-R	RAYGEL10K-R	12
RAY GEL 10 K-T	RAYGEL10K-T	12
RAY GEL 1000-R	RAYGEL1000-R	12
RAY GEL 1000-T	RAYGEL1000-T	12
RAY GEL 20 K-R	RAYGEL20K-R	12
RAY GEL 20 K-T	RAYGEL20K-T	12
RAY GEL 300-R	RAYGEL300-R	12
RAY GEL 300-T	RAYGEL300-T	12
RAY PRESS 16	RAYPRESS16	43
RAY PRESS 20	RAYPRESS20	43
RAY PRESS 25	RAYPRESS25	43
RAY PRESS 32	RAYPRESS32	43
RAY PRESS-PG11	RAYPRESSPG11	43
RAY PRESS-PG13.5	RAYPRESSPG13.5	43
RAY PRESS-PG16	RAYPRESSPG16	43
RAY PRESS-PG21	RAYPRESSPG21	43
RAY ROLL 1.6 Black	RAYROLL-1.6	112
RAY ROLL 12.7 Black	RAYROLL-12.7	112
RAY ROLL 19.0 Black	RAYROLL-19.0	112
RAY ROLL 2.4 Black	RAYROLL-2.4	112
RAY ROLL 25.4 Black	RAYROLL-25.4	112
RAY ROLL 3.2 Black	RAYROLL-3.2	112
RAY ROLL 4.8 Black	RAYROLL-4.8	112
RAY ROLL 6.4 Black	RAYROLL-6.4	112
RAY ROLL 9.5 Black	RAYROLL-9.5	112
RAY RTV 10K-N	RAYRTV10K-N	141
RAY RTV 20K-N	RAYRTV20K-N	141
RAY RTV 400K-N	RAYRTV400K-N	141
RAY-CSM-110/30-1000/172	934589-000	117
RAY-CSM-12/3-1000/172	672693-000	117
RAY-CSM-130/36-1000/172	833598-000	117
RAY-CSM-16/4-1000/172	542973-000	117
RAY-CSM-160/50-1000/172	430277-000	117
RAY-CSM-180/50-1000/172	237977-000	117
RAY-CSM-24/6-1000/172	050119-000	117
RAY-CSM-34/8-1000/172	453083-000	117
RAY-CSM-48/12-1000/172	582237-000	117
RAY-CSM-56/16-1000/172	898079-000	117
RAY-CSM-70/21-1000/172	862223-000	117
RAY-CSM-90/25-1000/172	862225-000	117
RAY-FASC B 22/75	700000-049	144
RAY-FASC B 25/135	700000-003	144
RAY-FASC B 25/98	700000-002	144
RAY-FASC B 26/160	700000-004	144
RAY-FASC B 26/200	700000-005	144
RAY-FASC B 36/140	700000-006	144

Product	Item	Page
RAY-FASC B 36/200	700000-007	144
RAY-FASC B 36/290	700000-008	145
RAY-FASC B 36/370	700000-009	145
RAY-FASC B 48/178	700000-011	145
RAY-FASC B 48/200	700000-012	145
RAY-FASC B 48/250	700000-013	145
RAY-FASC B 48/290	700000-014	145
RAY-FASC B 48/360	700000-015	145
RAY-FASC B 48/430	700000-017	145
RAY-FASC B 78/180	700000-052	145
RAY-FASC B 78/240	700000-019	145
RAY-FASC B 78/300	700000-020	145
RAY-FASC B 78/365	700000-021	145
RAY-FASC B 78/450	700000-022	145
RAY-FASC B 78/540	700000-023	145
RAY-FASC B 78/750	700000-024	145
RAY-FASC BBA 36	700002-000	145
RAY-FASC BBA 48	700004-000	145
RAY-FASC N 22/75	700000-050	144
RAY-FASC N 25/ 98	700000-026	144
RAY-FASC N 25/135	700000-027	144
RAY-FASC N 26/160	700000-028	144
RAY-FASC N 26/200	700000-029	144
RAY-FASC N 36/140	700000-030	144
RAY-FASC N 36/200	700000-031	144
RAY-FASC N 36/290	700000-032	144
RAY-FASC N 36/370	700000-033	144
RAY-FASC N 48/178	700000-035	144
RAY-FASC N 48/200	700000-036	144
RAY-FASC N 48/250	700000-037	144
RAY-FASC N 48/290	700000-038	144
RAY-FASC N 48/360	700000-039	144
RAY-FASC N 48/430	700000-041	144
RAY-FASC N 78/180	700000-051	144
RAY-FASC N 78/240	700000-043	144
RAY-FASC N 78/300	700000-044	144
RAY-FASC N 78/365	700000-045	144
RAY-FASC N 78/450	700000-046	144
RAY-FASC N 78/540	700000-047	144
RAY-FASC N 78/750	700000-048	144
RAY-FASC NBA 36	700003-000	145
RAY-FASC NBA 48	700005-000	145
RAY-FASC S	700001-000	145
RAY-FASC SI	700006-000	145
RAY-RSM-107/29-1000/232	395359-000	117
RAY-RSM-107/29-1500/232	546145-000	117
RAY-RSM-143/36-1000/232	002611-000	117
RAY-RSM-143/36-1500/232	091525-000	117
RAY-RSM-198/55-1000/232	318575-000	117
RAY-RSM-198/55-1500/232	247637-000	117
RAY-RSM-250/98-1000/232	595947-000	117
RAY-RSM-250/98-1500/232	247698-000	117
RAY-RSM-34/10-1000/232	406345-000	117
RAY-RSM-34/10-1500/232	240699-000	117
RAY-RSM-53/13-1000/232	279727-000	117
RAY-RSM-53/13-1500/232	505955-000	117
RAY-RSM-84/20-1000/232	953639-000	117

Product	Item	Page
RAY-RSM-84/20-1500/232	219483-000	117
RAY-TTF 1,5/16	RAY-TTF1.5/16	87
RAY-TTF 10/35	RAY-TTF10/35	87
RAY-TTF 25/50	RAY-TTF25/50	87
RAY-TTF 35/150	RAY-TTF35/150	87
RAY-TUM-12/3-0 (bars mt 1,2)	5634732003	115
RAY-TUM-12/4-0 (bars mt 1,2)	5509102048	115
RAY-TUM-16/4-0 (bars mt 1,2)	8014642003	115
RAY-TUM-19/6-0 (bars mt 1,2)	5067452035	115
RAY-TUM-24/6-0 (bars mt 1,2)	4177512003	115
RAY-TUM-24/8-0 (bars mt 1,2)	5509112040	115
RAY-TUM-3/1-0 (bars mt 1,2)	5504062059	115
RAY-TUM-32/8-0 (bars mt 1,2)	4951522003	115
RAY-TUM-4/1-0 (bars mt 1,2)	550406260	115
RAY-TUM-40/13-0 (bars mt 1,2)	5509122053	115
RAY-TUM-52/13-0 (bars mt 1,2)	7024702003	115
RAY-TUM-6/2-0 (bars mt 1,2)	5509092033	115
RAY-TUM-8/2-0 (bars mt 1,2)	5110554007	115
RAY-TUM-9/3-0 (bars mt 1,2)	5507832055	115
RAYBLOCK (50 PCS)	RAYBLOCK	46
RAYBLOCKB2 (40 PCS)	RAYBLOCKB2	46
RAYBLOCKB3 (30 PCS)	RAYBLOCKB3	46
RAYBLOCKB5 (18 PCS)	RAYBLOCKB5	46
RAYBLOCKUNO (20 PCS)	RAYBLOCKUNO	46
RAYCAST D 25-S	100017-005	100
RAYCAST D16-ARM	100016-001	101
RAYCAST D16-ARM-F	100016-002	101
RAYCAST D16/D25	100016-000	99
RAYCAST D6	100006-000	99
RAYCAST D6-ARM	100006-001	101
RAYCAST D6-ARM-F	100006-002	101
RAYCAST D6-S	100006-005	100
RAYCAST D95	100095-001	99
RAYCAST D95-ARM	100095-004	101
RAYCAST D95-ARM-F	100095-003	101
RAYCAST D95-S	100950-005	100
RAYCAST DPS25	100025-DPS	102
RAYCAST DPS6	100006-DPS	102
RAYCAST DPS95	100095-DPS	102
RAYCAST L 10-ARM	100001-001	101
RAYCAST L 25-ARM	100002-002	101
RAYCAST L 35-S	100035-005	100
RAYCAST L 50-ARM	100003-001	101
RAYCAST L 50-S	100050-005	100
RAYCAST L10	100001-000	99
RAYCAST L10-S	100001-005	100
RAYCAST L120	100120-000	99
RAYCAST L120-ARM	100120-002	101
RAYCAST L120-RP/120	RAYCASTL120RP120	103
RAYCAST L120-S	100120-005	100
RAYCAST L16/L25	100002-000	99
RAYCAST L240	100240-000	99
RAYCAST L240-ARM	100240-LARM	101
RAYCAST L240-RP/150	RAYCASTL240RP150	103
RAYCAST L240-S	100240-055	100
RAYCAST L25-S	100025-005	100
RAYCAST L35	100035-001	99

Product	Item	Page
RAYCAST L35 -ARM	100035-ARM	101
RAYCAST L35-RP/16	RAYCASTL35RP16	103
RAYCAST L35-RP/35	RAYCASTL35RP35	103
RAYCAST L50	100500-000	99
RAYCAST L50-RP/50	RAYCASTL50RP50	103
RAYCAST L95	100095-000	99
RAYCAST LPS10	100010-LPS	102
RAYCAST LPS240	100240-LPS	102
RAYCAST LPS25	100025-LPS	102
RAYCAST LPS95	100095-LPS	102
RAYCAST SD1	100001-OSD	102
RAYCAST SD2	100002-OSD	102
RAYCAST SD3	100003-OSD	102
RAYCAST SL11	100011-OSL	102
RAYCAST SL12	100012-OSL	102
RAYCAST SL13	100013-OSL	102
RAYCAST SL14	100014-OSL	102
RAYCAST SL15	100015-OSL	102
RAYCAST SL16	100016-OSL	102
RAYCAST SP D16	RAYCASTSPD16	103
RAYCAST SP D6	RAYCASTSPD6	103
RAYCAST SP L16	RAYCASTSPL16	103
RAYCAST SP L25	RAYCASTSPL25	103
RAYCAST SP L6	RAYCASTSPL6	103
RAYCAST SP T35	RAYCASTSPT35	103
RAYCAST TL16	100016-0TL	102
RAYCAST TL25	100025-0TL	102
RAYCAST TL35	100035-0TL	102
RAYCAST TL40	100040-0TL	102
RAYCAST TL500	100500-0TL	102
RAYCAST TL64	100064-0TL	102
RAYCAST TSL16	100016-TSL	102
RAYCAST TSL25	100025-TSL	102
RAYCAST TSL35	100035-TSL	102
RAYCAST TSL40	100040-TSL	102
RAYCAST TSL500	100500-TSL	102
RAYCAST TSL64	100064-TSL	102
RAYK016-53/42	119983-000	119
RAYK026-53/42	017847-000	119
RAYK033-53/42	645763-000	119
RAYK046-53/42	747267-000	119
RAYK224-53/42	522347-000	119
RAYK333-53/42	324253-000	119
RAYK466-53/42	556514-001	119
RAYL011-37/42	334969-000	119
RAYL022-37/42	821617-000	119
RAYL033/S	692333-000	119
RAYL044-37/42	547889-000	119
RAYL048-37/42	068743-000	119
RAYL055-37/42	190805-000	119
RAYL066-37/42	855203-000	119
RAYRESIN 170	100170-000	22
RAYRESIN 210	100210-000	22
RAYRESIN 420	100420-000	22
RAYTEAM 1510 White	021514-004	122
RAYTEAM 1510 Blue	021514-002	122
RAYTEAM 1510 Yellow/Green	021514-003	122

Product	Item	Page
RAYTEAM 1510 Grey	021514-006	122
RAYTEAM 1510 Brown	021514-007	122
RAYTEAM 1510 Black	021514-000	122
RAYTEAM 1510 Red	021514-001	122
RAYTEAM 1510/13 White	021513-009	122
RAYTEAM 1510/13 Blue	021513-006	122
RAYTEAM 1510/13 Yellow	021513-004	122
RAYTEAM 1510/13 Yellow/Green	021513-045	122
RAYTEAM 1510/13 Grey	021513-008	122
RAYTEAM 1510/13 Black	021513-000	122
RAYTEAM 1510/13 Red	021513-002	122
RAYTEAM 1510/13 Green	021513-005	122
RAYTEAM 1525 White	270999-009	122
RAYTEAM 1525 Blue	270999-006	122
RAYTEAM 1525 Yellow	270999-004	122
RAYTEAM 1525 Yellow/Green	270999-045	122
RAYTEAM 1525 Grey	270999-008	122
RAYTEAM 1525 Black	270999-000	122
RAYTEAM 1525 Red	270999-002	122
RAYTEAM 1525 Green	270999-005	122
RAYTEAM 1925 White	012141-007	122
RAYTEAM 1925 Blue	012141-002	122
RAYTEAM 1925 Yellow/Green	012141-003	122
RAYTEAM 1925 Grey	012141-004	122
RAYTEAM 1925 Brown	012141-005	122
RAYTEAM 1925 Black	012141-000	122
RAYTEAM 1925 Red	012141-001	122
RAYTEAM 1925/13 White	270913-005	122
RAYTEAM 1925/13 Blue	270913-006	122
RAYTEAM 1925/13 Yellow	270913-004	122
RAYTEAM 1925/13 Yellow/Green	270913-045	122
RAYTEAM 1925/13 Grey	270913-008	122
RAYTEAM 1925/13 Brown	270913-001	122
RAYTEAM 1925/13 Black	270913-000	122
RAYTEAM 1925/13 Red	270913-002	122
RAYTEAM 1925/13 Green	270913-050	122
RAYTEAM 2525 White	280998-000	122
RAYTEAM 2525 Grey	280997-000	122
RAYTEAM 2525 Black	280999-000	122
RAYTEAM-K	RAYTEAM-K20	122
	20 tapes 1925 + Flexometer 3m	
RAYTECH 2.3	3-2001-00-13	123
RAYTECH 23 BT	3-2002-96-13	123
RAYTECH 7-0	3-2042-00-13	124
RAYTECH SUPER 3.3 - Black	3-3061-00-13	123
RAYTEFILL	3-2140-00-13	124
RAYW248-53/42	102022-TEC	119
RAYW516-53/42	519411-000	119
RAYW526-53/42	395067-000	119
RAYW533-53/42	443425-000	119
RDCT-B 10/5	105004-BAR	114
RDCT-B 12/6	126040-BAR	114
RDCT-B 19/9	199550-BAR	114
RDCT-B 26/13	261345-BAR	114
RDCT-B 3/1.5	315002-BAR	114
RDCT-B 6/3	630045-BAR	114
READY BOX 120 IP68	READYBOX	32

Product	Item	Page
READY BOX 120 IP68 Black	READYBOX-N	32
READY BOX 90 IP68	READYBOX90	32
READY BOX 90 IP68 Black	READYBOX90-N	32
READY CAST L10	READYCASTL10	74
READY CAST L16/25	READYCASTL16/25	74
READY CAST L4	READYCASTL4	74
READY CAST Y16/25	READYCASTY16/25	74
READY CAST Y6	READYCASTY6	74
RGPO-B 12.7/6.4-0 Black	127640-BAR	114
RGPO-B 12.7/6.4-2 Red	127642-BAR	120
RGPO-B 12.7/6.4-6 Blue	127646-BAR	120
RGPO-B 12.7/6.4-X	127641-BAR	120
RGPO-B 19/9.5-0 Black	199500-BAR	114
RGPO-B 19/9.5-2 Red	199502-BAR	120
RGPO-B 19/9.5-6 Blue	199506-BAR	120
RGPO-B 19/9.5-X Transparent	199501-BAR	120
RGPO-B 2.4/1.2-2 Red	241202-BAR	120
RGPO-B 2.4/1.2-0 Black	241200-BAR	114
RGPO-B 2.4/1.2-6 Blue	241206-BAR	120
RGPO-B 2.4/1.2-9 White	241209-BAR	120
RGPO-B 25.4/12.7-0 Black	254120-BAR	114
RGPO-B 25.4/12.7-2 Red	254722-BAR	120
RGPO-B 25.4/12.7-6 Blue	254726-BAR	120
RGPO-B 25.4/12.7-X Transparent	254721-BAR	120
RGPO-B 3.2/1.6-0 Black	321600-BAR	114
RGPO-B 3.2/1.6-2 Red	321602-BAR	120
RGPO-B 3.2/1.6-6 Blue	321606-BAR	120
RGPO-B 3.2/1.6-9 White	321609-BAR	120
RGPO-B 3.2/1.6-X Transparent	321601-BAR	120
RGPO-B 38/19-0 Black	381900-BAR	114
RGPO-B 38/19-2 Red	381902-BAR	120
RGPO-B 38/19-6 Blue	381906-BAR	120
RGPO-B 38/19-X Transparent	381901-BAR	120
RGPO-B 4.8/2.4-0 Black	482400-BAR	114
RGPO-B 4.8/2.4-2 Red	482402-BAR	120
RGPO-B 4.8/2.4-6 Blue	482806-BAR	120
RGPO-B 4.8/2.4-9 White	482009-BAR	120
RGPO-B 4.8/2.4-X Transparent	482401-BAR	120
RGPO-B 51/26-0 Black	512600-BAR	114
RGPO-B 51/26-9 White	512609-BAR	120
RGPO-B 6.4/3.2-0 Black	643200-BAR	114
RGPO-B 6.4/3.2-2 Red	643202-BAR	120
RGPO-B 6.4/3.2-6 Blue	643206-BAR	120
RGPO-B 6.4/3.2-X Transparent	643201-BAR	120
RGPO-B 9.5/4.8-0 Black	954800-BAR	114
RGPO-B 9.5/4.8-2 Red	954802-BAR	120
RGPO-B 9.5/4.8-6 Blue	954806-BAR	120
RGPO-B 9.5/4.8-X Transparent	954801-BAR	120
RGPO-B 12.7/6.4-9 White	127649-BAR	120
RGPO-B 19/9.5-9 White	199509-BAR	120
RGPO-B 25.4/12.7-9 White	254129-BAR	120
RGPO-B 38/19-9 White	381909-BAR	120
RGPO-B 6.4/3.2-9 White	643209-BAR	120
RGPO-B 9.5/4.8 White	954809-BAR	120
RICEVITORE Receiver from 16 A.	RID-WL-R	218
RID Raytech Intelligent Display	RID	213

Product	Item	Page
RUBBER FLUID 200	RUBBERFLUID-200	21
RUBBER FLUID 350	RUBBERFLUID350	21
RUBBER JOINT 10	RUBBERJOINT10	97
RUBBER JOINT 120	RUBBERJOINT120	97
RUBBER JOINT 240	RUBBERJOINT240	97
RUBBER JOINT 25	RUBBERJOINT25	97
RUBBER JOINT 300	RUBBERJOINT300	97
RUBBER JOINT 35	RUBBERJOINT35	97
RUBBER JOINT 4	RUBBERJOINT4	93
RUBBER JOINT 50	RUBBERJOINT50	97
RUBBER JOINT 95	RUBBERJOINT95	97
RUBBER JOINT Y240	RUBBERJOINTY240	97
RUBBER JOINT Y25	RUBBERJOINTY25	97
RUBBER JOINT Y6	RUBBERJOINTY6	97
RUBBER JOINT Y95	RUBBERJOINTY95	97
S SHINY BRUSH 4 (SB4)	SHINYBRUSCH4	143
SHINY SOLAR	SHINYSOLAR	143
SHINY SOLAR 5	SHINYSOLAR5	143
SKY PLAST 250	SKYPLAST250	20
SKY PLAST 500	SKYPLAST	20
SOLARCOVER-4	SOLARCOVER-4	64
SOLARCOVER-6	SOLARCOVER-6	64
SPEEDY AF	7139-0053	131
SPEEDY AFS	7139-0055	131
SPEEDY AS	7139-0054	131
SPEEDY AT	7139-0048	131
SPEEDY BU	7139-0045	131
SPEEDY CA	7139-0049	131
SPEEDY GLASS 3/10	7139-0035	130
SPEEDY GLASS 3/15	7139-0036	130
SPEEDY GLASS 3/20	7139-0037	130
SPEEDY GLASS 3/25	7139-0060	130
SPEEDY GLASS 3/30	7139-0038	130
SPEEDY HELIX 4/10	7139-0031	129
SPEEDY HELIX 4/15	7139-0032	129
SPEEDY HELIX 4/20	7139-0033	129
SPEEDY HELIX 4/30	7139-0034	129
SPEEDY HELIX 5/10	7139-0025	129
SPEEDY HELIX 5/15	7139-0026	129
SPEEDY HELIX 5/20	7139-0027	129
SPEEDY HELIX 5/25	7139-0064	129
SPEEDY HELIX 5/30	7139-0028	129
SPEEDY HELIX 5/50	7139-0029	129
SPEEDY HELIX 5/60	7139-0030	129
SPEEDY MO	7139-0072	131
SPEEDY NYLON 3/10	SPEEDYNYLON3/10F	126
SPEEDY NYLON 3/15	SPEEDYNYLON3/15F	126
SPEEDY NYLON 3/20	SPEEDYNYLON3/20F	126
SPEEDY NYLON 3/25 S	SPEEDYNYLON3/25F	126
SPEEDY NYLON 3/5	SPEEDYNYLON3/5F	126
SPEEDY NYLON 4/10	SPEEDYNYLON4/10F	126
SPEEDY NYLON 4/15	SPEEDYNYLON4/15F	126
SPEEDY NYLON 4/20	SPEEDYNYLON4/20F	126
SPEEDY NYLON 4/25	SPEEDYNYLON4/25F	126
SPEEDY NYLON 4/5	SPEEDYNYLON4/5F	126
SPEEDY OL	7139-0071	131
SPEEDY OTC	7139-0044	131

Product	Item	Page
SPEEDY OTL	7139-0047	131
SPEEDY PN	7139-0050	131
SPEEDY PNG	7139-0046	131
SPEEDY PR GLASS	7139-0052	131
SPEEDY REP	7139-0051	131
SPEEDY RS	7139-0070	131
SPEEDY SONDA 3/10-F	7139-0002	128
SPEEDY SONDA 3/10-I	7139-0006	128
SPEEDY SONDA 3/15-F	7139-0003	128
SPEEDY SONDA 3/15-I	7139-0007	128
SPEEDY SONDA 3/20-F	7139-0004	128
SPEEDY SONDA 3/20-I	7139-0008	128
SPEEDY SONDA 3/5-F	7139-0001	128
SPEEDY SONDA 3/5-I	7139-0005	128
SPEEDY SONDA 4/10-F	7139-0010	128
SPEEDY SONDA 4/10-F-N	7139-0014	128
SPEEDY SONDA 4/10-I	7139-0018	128
SPEEDY SONDA 4/10-I-N	7139-0022	128
SPEEDY SONDA 4/15-F- N	7139-0011	128
SPEEDY SONDA 4/15-F	7139-0015	128
SPEEDY SONDA 4/15-I	7139-0019	128
SPEEDY SONDA 4/15-I-N	7139-0023	128
SPEEDY SONDA 4/20-F	7139-0012	128
SPEEDY SONDA 4/20-F-N	7139-0016	128
SPEEDY SONDA 4/20-I	7139-0020	128
SPEEDY SONDA 4/20-I-N	7139-0024	128
SPEEDY SONDA 4/25-F	7139-0059	128
SPEEDY SONDA 4/25-F-N	7139-0065	128
SPEEDY SONDA 4/25-I	7139-0058	128
SPEEDY SONDA 4/25-I-N	7139-0066	128
SPEEDY SONDA 4/5-F	7139-0009	128
SPEEDY SONDA 4/5-F-N	7139-0013	128
SPEEDY SONDA 4/5-I	7139-0017	128
SPEEDY SONDA 4/5-I-N	7139-0021	128
SPEEDY STEEL 6/20	7139-0039	128
SPEEDY STEEL 6/25	7139-0061	128
SPEEDY STEEL 6/30	7139-0040	128
SPEEDY STEEL 6/40	7139-0041	128
SPEEDY STEEL 6/50	7139-0062	128
SPEEDY STEEL 6/60	7139-0063	128
SPEEDY TFC	7139-0043	131
SPEEDY TFG	7139-0042	131
SPEEDY TS	7139-0069	131
SPEEDY WIRE GEL	900000-001	126
SPEEDY WIRE OIL	900000-003	126
SPEEDY WIRE SPRAY	SPEEDYWSPRAY	126
SUPER BLOCK 3	SUPERBLOCK3	48
SUPER BLOCK 3W	SUPERBLOCK3W	48
SUPER BLOCK 5	SUPERBLOCK5	48
SUPER BLOCK 5W	SUPERBLOCK5W	48
SUPER BLOCK IN-OUT	SUPERBLOCKINOUT	48
SUPER BLOCK IN-OUT M	SUPERBLOCKINOUTM	48
SUPER BLOCK IN-OUT W	SUPERBLOCKINOUTW	48
STOP ICE 10/12	STOPICE1012	200
STOP ICE 18/12	STOPICE1812	200
STOP ICE 2/12	STOPICE212	200
STOP ICE 5/12	STOPICE512	200

Product	Item	Page
STOP ICE PLUS 2	STOPICEPLUS2	201
STOP ICE PLUS 5	STOPICEPLUS5	201
SUPER CLIK 0	SUPERCLIK0	78
SUPER CLIK 1	SUPERCLIK1	78
SUPER CLIK 2	SUPERCLIK2	78
SUPER CLIK 3	SUPERCLIK3	78
SUPER CLIK MINI L	SUPERCLIKMINI-L	78
SUPER CLIK MINI Y	SUPERCLIKMINI-Y	78
T TECHNO GELGUM	TEGELGUM	18
TECHNO GELGUM 500	TEGELGUM500	18
THERMO MINIMIX-MC	THERMOMIN-MC	115
THERMO MINIMIX-N	THERMOMIN-N	115
THVE 15/300-E	206772-000	165
THVE 15/50-E	120036-TEC	165
THVE 15/800-E	125336-TEC	165
THVE 15/A-RC	906848-000	162
THVE 15/B-RC	500365-000	162
THVE 15/C-RC	068756-000	162
THVE 20/150-E/U	123021-000	170
THVE 20/150-I/U	364179-000	170
THVE 20/185-E/U	365891-000	170
THVE 20/185-I/U	618430-000	170
THVE 20/240-E	255098-TEC	165
THVE 20/240-I/U	521413-000	170
THVE 20/25-E	231047-TEC	165
THVE 20/630-E	792760-000	165
THVE 20/A-RC	507698-000	162
THVE 20/B-RC	190360-000	162
THVE 20/C-RC	485361-000	162
THVE 30/185-E	120057-TEC	165
THVE 30/500-E	372083-000	165
THVE 30/95-E	900926-000	165
THVE 30/A-RC	454523-000	162
THVE 30/B-RC	308359-000	162
THVE 30/C-RC	651264-000	162
THVE 30/D-RC	700320-000	163
THVE 45/A-E	THVE45/A-E	179
THVE 45/A-I	THVE45/A-I	179
THVE 6/120-E	THVE6/120-E	165
THVE 6/400-E	164000-000	165
THVE 6/630-E	606630-TEC	165
THVE 6/A-RC	369608-000	162
THVE 6/B-RC	034189-000	162
THVE 6/C-RC	882065-000	162
THVI 20/A-3	507698-003	168
THVI 20/A-3-ARM	507698-004	168
THVI 20/A-ARM	507698-002	164
THVI 20/B-3	190360-003	168
THVI 20/B-3-ARM	190360-004	168
THVI 20/B-ARM	190360-002	164
THVI 20/C-3	485361-003	168
THVI 20/C-3-ARM	485361-004	168
THVI 20/C-ARM	485361-002	164
THVI 30/A-3	507702-TTEC	168
THVI 30/A-3-ARM	THVI30/A-3-ARM	168
THVI 30/A-ARM	THVI30/A-ARM	164
THVI 30/B-3	507701-002	168

Product	Item	Page
THVI 30/B-3-ARM	507701-001	168
THVI 30/B-ARM	THVI30/B-ARM	164
THVI 30/C-3	THVI30/C-3	168
THVI 30/C-3-ARM	THVI30/C-3-ARM	168
THVI 30/C-ARM	THVI30/C-ARM	164
THVI 6/0-3	THVI6/0-3	168
THVI 6/0-3-ARM	THVI6/0-3-ARM	168
THVI 6/0-ARM	THVI6/0-ARM	164
THVI 6/A-3	THVI6/A-3	168
THVI 6/A-3-ARM	THVI6/A-3-ARM	168
THVI 6/A-ARM	THVI6/A-ARM	164
THVI 6/B-3	THVI6/B-3	168
THVI 6/B-3-ARM	THVI6/B-3-ARM	168
THVI 6/B-ARM	THVI6/B-ARM	164
THVI 6/C-3	THVI6/C-3	168
THVI 6/C-3-ARM	THVI6/C-3-ARM	168
THVI 6/C-ARM	THVI6/C-ARM	164
THVO 20/240-3	255101-TEC	169
THVO 20/240-3-ARM	255102-TEC	169
THVO 20/240-ARM	255100-TEC	167
THVO 20/25-3	231050-TEC	169
THVO 20/25-3-ARM	231051-TEC	169
THVO 20/25-ARM	231049-TEC	167
THVO 20/630-3	792763-000	169
THVO 20/630-3-ARM	792764-000	169
THVO 20/630-ARM	792762-000	167
THVO 30/185-3	THVO30/185-3	169
THVO 30/185-3-ARM	THVO30/185-3-ARM	169
THVO 30/185-ARM	THVO30/185-ARM	167
THVO 30/240-3	THVO30/240-3	169
THVO 30/240-3-ARM	THVO30/240-3-ARM	169
THVO 30/500-ARM	THVO30/500-ARM	167
THVO 30/95-3	231054-TEC	169
THVO 30/95-3-ARM	THVO30/95-3-ARM	169
THVO 30/95-ARM	THVO30/95-ARM	167
THVO 6/120-3	THVO6/120-3	169
THVO 6/120-3-ARM	THVO6/120-3-ARM	169
THVO 6/120-ARM	THVO6/120-ARM	167
THVO 6/35-3	THVO6/35-3	169
THVO 6/35-3-ARM	THVO6/35-3-ARM	169
THVO 6/400-3	THVO6/400-3	169
THVO 6/400-3-ARM	THVO6/400-3-ARM	169
THVO 6/400-ARM	THVO6/400-ARM	167
THVO 6/500-3	THVO6/500-3	169
THVO 6/500-3-ARM	THVO6/500-3-ARM	169
THVO 6/630-ARM	THVO6/630-ARM	167
THVO 6/70-ARM	THVO6/70-ARM	167
THVP 20/240-E/U-N1	145110-000	171
THVP 20/240-I/U	252214-000	171
TLV 0116-500	181198-000	109
TLV 0150-500	181198-002	109
TLV 0216	946613-000	109

Product	Item	Page
TLV 0216-500	181198-001	109
TLV 0216-AF	106391-000	109
TLV 0250	101526-000	109
TLV 0250-500	181198-003	109
TLV 0250-AF	024865-000	109
TLV 0316	496973-000	109
TLV 0316-500	816659-000	109
TLV 0316-AF	178316-000	109
TLV 0350	786134-000	109
TLV 0350-AF	179335-000	109
TLV 0416	288775-000	109
TLV 0416-AF	121775-000	109
TLV 0450	786200-000	109
TLV 0450-AF	868777-000	109
TLV 2150-500	179925-000	109
TLV 2300-500	181198-005	109
TLV 3150	786220-000	109
TLV 3150-500	181198-004	109
TLV 3150-AF	181196-000	109
TLV 3300	208159-000	109
TLV 3300-500	909765-000	109
TLV 3300-AF	181097-000	109
TLV 4150	597107-000	109
TLV 4150-AF	223409-000	109
TLV 4300	063097-000	109
TLV 4300-AF	803719-000	109
TLV 4500-AF	915556-000	109
TLV-0350-500	828617-000	109
TOM (1 PC)	TOM	68
TOM Black (1 PC)	TOM-N	68
W	WARM UP 1	216
	WARM UP 2	216
WATT	WATT	54
WATT + 1,5 10 PCS + 30 terminals from 1,5 mm ²	WATT-1.5	56
WATT + 2,5 10 PCS + 30 terminals from 2,5 mm ²	WATT-1.5	56
WATT MP Orange (25 PCS)	WATT-AMP	54
WATT MP Blue (25 PCS)	WATT-BMP	54
WATT MP Yellow (25 PCS)	WATT-GMP	54
WATT MP Black (25 PCS)	WATT-NMP	54
WATT Multipack (25 PCS)	WATT-MP	54
WATT PACK 15 (15 PCS)	WATTP15	54
WONDER FLUID 280	WONDER-F280	16
WONDER GEL	WONDER	14
WONDER GEL INVISIBLE	WONDER-INV	14
WPCT-IV-4X17	WPCTIV-4X17	118
WPCT-IV-4X24	WPCTIV-4X24	118
WPCT-IV-6X17	WPCTIV-6X17	118
WPCT-IV-6X24	WPCTIV-6X24	118
WPCT-17x100-RL	WPCT17X100-RL	118
WPCT-24x100-RL	WPCT24X100-RL	118



LOW VOLTAGE
MEDIUM VOLTAGE
HEATING CABLES

Ray
tech[®]

CABLE ACCESSORIES COMPANY